DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

	3A12
	Revision 89
	Textron Aviation
172	172I
172A	172K
172B	172L
172C	172M
172D	172N
172E	172P
172F (USAF T-41A)	172Q
172G	172R
172H (USAF T-41A)	172S
	September 15, 2026

WARNING: Use of alcohol-based fuels can cause serious performance degradation and fuel system component damage and is therefore prohibited on Cessna airplanes.

TYPE CERTIFICATE DATA SHEET NO. 3A12

This data sheet which is part of Type Certificate No. 3A12 prescribes conditions and limitations under which the product for which the type certificate was issued meets the airworthiness requirements of the Federal Aviation Regulations.

Type Certificate Holder	Textron Aviation Inc. One Cessna Boulevard Wichita, Kansas 67215
Type Certificate Holder Record	Cessna Aircraft Company transferred to Textron Aviation Inc. on July 29, 2015

I. Model 172, 4 PCLM (Normal Category), approved November 4, 1955; 2 PCLM (Utility Category), approved December 14, 1956

Engine	Continental O-300-A or O-300-B
*Fuel	80/87 minimum grade aviation gasoline
*Engine Limits	For all operations, 2700 rpm (145 hp)

Page No.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
Rev. No.	89	60	60	60	60	57	64	60	82	60	51	60	67	81	78	85	50	50	55	55
Page No.	21	22	23	24	25	26	27	28	29	30	31	32	33							
Rev. No.	50	72	59	83	81	80	76	86	77	80	87	89	89							

I. Model 172 (cont'd)

Propeller and Propeller Limits

1. McCauley Propeller
   Hub: 1A170/DM
   Static r.p.m. at maximum permissible throttle setting:
   Not over 2360, not under 2230.
   No additional tolerance permitted.
   Diameter: Not over 76 in., not under 74.5 in.
   Spinner: Dwg. 0550162
2. Sensenich Propeller
   Hub: M74DR or 74DR
   Static r.p.m. at maximum permissible throttle setting:
   Not over 2430, not under 2300
   No additional tolerance permitted
   Diameter: Not over 74 in., not under 72.0 in.
   Spinner: Dwg. 0550162
3. McCauley Propeller
   Hub: 1C172/MDM 7652, 53, or 55 30 lb. (-39.0)
   Static r.p.m. at maximum permissible throttle setting:
   Not over 2350, not under 2250.
   No additional tolerance permitted.
   Diameter: Not over 76 in., not under 74.5 in.
   Spinner: Dwg. 0550216

***Airspeed Limits (CAS)**

Maneuvering	115 mph (100 knots)
Maximum structural cruising	140 mph (122 knots)
Never exceed	160 mph (139 knots)
Flaps extended	100 mph (87 knots)

C.G. Range

Normal	(+40.8) to (+46.4) at 2200 lb.
	(+36.4) to (+46.4) at 1733 lb.
Utility category	(+38.4) to (+40.3) at 1950 lb.
	(+36.4) to (+40.3) at 1733 lb. or less

Straight line variation between points given.

Empty Weight C.G. Range

None

***Maximum Weight**

Normal category	2200 lb.
Utility category	1950 lb.

Number of Seats

4 (2 at +36, 2 at +70). For child's optional jump seat, refer to Equipment List.

Maximum Baggage

120 lb. (+95)

Fuel Capacity

42 gal. total, 37 gal. usable (two 21 gal. tanks in wings at +48).
(See NOTE 1 for weight of unusable fuel and oil).

Oil capacity

2 gal. (-20), includes 1 gal. unusable

Control Surface Movements

Wing Flaps	Takeoff		Retracted	0°
			1st notch	10°
	Landing		2nd notch	20°
			3rd notch	30°
			4th notch	40°
Ailerons	Up	20°	Down	14°
Elevator tab	Up	28°	Down	13°
Elevator	Up	28°	Down	26°
Rudder	Right	16°	Left	16°

Serial Numbers Eligible

610, 612, 615, 28000 thru 29999,
36000 thru 36999, 46001 thru 46754.

II. Model 172A, 4 PCL-SM (Normal Category), 2 PCLM (Utility Category), approved July 16, 1959; Model 172B, Skyhawk, 4 PCL-SM (Normal Category), 2 PCLM (Utility Category), approved June 14, 1960

Engine	Continental O-300-C or O-300-D
*Fuel	80/87 minimum grade aviation gasoline
*Engine Limits	For all operations, 2700 rpm (145 hp)
Propeller and Propeller Limits	1. McCauley Propeller Hub: 1C172/EM 7652, 53, or 55 Static rpm at maximum permissible throttle setting: Not over 2350, not under 2230. No additional tolerance permitted. Diameter: Not over 76 in., not under 74.5 in. Spinner: Dwg. 0550216, or 0550221 or 0550228 2. McCauley Propeller (seaplane) Hub: 1A175/SFC 8040 Static rpm at maximum permissible throttle setting: Not over 2480, not under 2380. No additional tolerance permitted. Diameter: Not over 80 in., not under 78.4 in. Spinner: Dwg. 0550216 or 0550221 3. Sensenich Propeller Hub: 74DC-0-56 Static rpm at maximum permissible throttle setting: Not over 2420, not under 2300. No additional tolerance permitted. Diameter: Not over 74 in., not under 72.5 in.
*Airspeed Limits (CAS)	Maneuvering 115 mph (100 knots) Maximum structural cruising 140 mph (122 knots) Never exceed 160 mph (139 knots) Flaps extended 100 mph (87 knots)
C.G. Range	Landplane (Model 172A): Normal category (+40.8) to (+46.4) at 2200 lb. (+36.4) to (+46.4) at 1733 lb. or less Utility category (+38.4) to (+40.3) at 1950 lb. (+36.4) to (+40.3) at 1733 lb. or less Straight line variation between points given. Landplane (Model 172B): Normal category (+40.4) to (+46.4) at 2200 lb. (+36.4) to (+46.4) at 1850 lb. or less Utility category (+37.4) to (+40.3) at 1950 lb. (+36.4) to (+40.3) at 1850 lb. or less Seaplane (Models 172A, 172B): Normal category (+39.8) to (+45.5) at 2220 lb. (+36.4) to (+45.5) at 1825 lb. or less Straight line variation between points given.
Empty Weight C.G. Range	None
*Maximum Weight	Landplane: Normal category 2200 lb. Utility category 1950 lb. Seaplane: Normal category 2220 lb.

II. Model 172A (cont'd)

Number of Seats	4 (2 at +36, 2 at +70). For child's optional jump seat, refer to Equipment List.
Maximum Baggage	120 lb. (+95)
Fuel Capacity	Model 172A: 42 gal. total, 37 gal. usable Model 172B: 39 gal. usable (two 21 gal. tanks in wings at +48) (See NOTE 1 for weight of unusable fuel and oil).
Oil Capacity	2 gal. (-20), 1 gal. usable

Control Surface Movements

Wing Flaps	Takeoff		Retracted	0°
			1st notch	10°
	Landing		2nd notch	20°
			3rd notch	30°
			4th notch	40°
Ailerons	Up	20°	Down	15°
Elevator tab	Up	28°	Down	13°
Elevator	Up	28°	Down	26°
Rudder (landplane)	Right	16°	Left	16°
(seaplane)	Right	19°	Left	15°

(Measured parallel to W.L.)

Serial Numbers Eligible	Model 172A: 622, 625, 46755 thru 47746 Model 172B: 630, 17247747 thru 17248734

III. Model 172C, 4 PCL-SM (Normal Category), 2 PCLM (Utility Category), approved July 18, 1961

Engine	Continental O-300-C or O-300-D
*Fuel	80/87 minimum grade aviation gasoline
*Engine Limits	For all operations, 2700 rpm (145 hp)

Propeller and Propeller Limits

1. McCauley Propeller
   Hub: 1C172/EM 7652, 53, or 55
   Static rpm, at maximum permissible throttle setting:
   Not over 2350, not under 2230.
   No additional tolerance permitted.
   Diameter: Not over 76 in., not under 74.5 in.
   Spinner: Dwg. 0550216, 0550221 or 0550228
2. McCauley Propeller (seaplane)
   Hub: 1A175/SFC 8040
   Static rpm, at maximum permissible throttle setting:
   Not over 2480, not under 2380.
   No additional tolerance permitted.
   Diameter: Not over 80 in., not under 78.4 in.
   Spinner: Dwg. 0550216 or 0550221
3. Sensenich Propeller
   Hub: 74DC-0-56
   Static rpm at maximum permissible throttle setting:
   Not over 2420, not under 2300.
   No additional tolerance permitted.
   Diameter: Not over 74 in., not under 72.5 in.

*Airspeed Limits (CAS)

Maneuvering	115 mph (100 knots)
Maximum structural cruising	140 mph (122 knots)
Never exceed	160 mph (139 knots)
Flaps extended	100 mph (87 knots)

III. Model 172C (cont'd)

C.G. Range	Landplane:	
	Normal category	(+40.5) to (+46.4) at 2250 lb.
		(+36.4) to (+46.4) at 1850 lb. or less
	Utility category	(+37.4) to (+40.3) at 1950 lb.
		(+36.4) to (+40.3) at 1850 lb. or less
	Seaplane:	
	Normal category	(+39.8) to (+45.5) at 2220 lb.
		(+36.4) to (+45.5) at 1825 lb. or less
	Straight line variation between points given.	
Empty Weight C.G. Range	None	
*Maximum Weight	Landplane:	
	Normal category	2250 lb.
	Utility category	1950 lb.
	Seaplane:	
	Normal category	2220 lb.
Number of Seats	4 (2 at +36, 2 at +70). For child's optional jump seat, refer to Equipment List.	
Maximum Baggage	120 lb. (+95)	
Fuel Capacity	39 gal. total, 36 gal. usable (two 19.5 gal. tanks in wings at +48). (See NOTE 1 for weight of unusable fuel and oil).	
Oil Capacity	2 gal. (-20), includes 1 gal. unusable	

Control Surface Movements

Wing Flaps	Takeoff		Retracted	0°
			1st notch	10°
	Landing		2nd notch	20°
			3rd notch	30°
			4th notch	40°
Ailerons	Up	20°	Down	15°
Elevator tab	Up	28°	Down	13°
Elevator	Up	28°	Down	26°
Rudder (Landplane)	Right	16°	Left	16°
(Seaplane)	Right	19°	Left	15°

(Measured parallel to W.L.)

Serial Numbers Eligible	17248735 thru 17249544

IV. Model 172D, 4 PCL-SM (Normal Category), 2 PCLM (Utility Category), approved June 19, 1962
Model 172E, 4 PCL-SM (Normal Category), 2 PCLM (Utility Category), approved June 27, 1963
Model 172F (USAF T-41A), 4 PCL-SM (Normal Category), 2 PCLM (Utility Category), approved April 21, 1964
Model 172G, 4 PCL-SM (Normal Category), 2 PCLM (Utility Category), approved June 15, 1965
Model 172H (USAF) T-41A), 4 PCL-SM (Normal Category), 2 PCLM (Utility Category), approved June7, 1966

Engine	Continental O-300-C or O-300-D
*Fuel	80/87 minimum octane aviation gasoline
*Engine Limits	For all operations, 2700 rpm (145 hp)

IV. Models 172D, 172E, 172F, 172G, 172H (cont'd)

Propeller and Propeller Limits

1. McCauley Propeller
   Hub: 1C172/EM 7652, 53
   Static rpm at maximum permissible throttle setting:
   Not over 2420, not under 2230.
   No additional tolerance permitted.
   Diameter: Not over 76 in., not under 74.5 in.
   Spinner: Model 172D/E/F: Dwg. 0550216, 0550221 or 0550228
   Model 172G/H: Dwg. 0550236
2. McCauley Propeller (seaplane)
   Hub: 1A175/SFC 8040
   Static rpm at maximum permissible throttle setting:
   Not over 2480, not under 2380.
   No additional tolerance permitted.
   Diameter: Not over 80 in., not under 78.4 in.
   Spinner: Model 172D/E/F: Dwg. 0550216, 0550221
   Model 172G/H: Dwg. 0550236

***Airspeed Limits (CAS)**

Maneuvering	122 mph (106 knots)
Maximum structural cruising	142 mph (122 knots)
Never exceed	174 mph (151 knots)
Flaps extended	100 mph (87 knots)

C.G. Range

Landplane
- Normal category: (+38.5) to (+47.3) at 2300 lb.; (+35.0) to (+47.3) at 1950 lb. or less
- Utility category: (+35.5) to (+40.5) at 2000 lb.; (+35.0) to (+40.5) at 1950 lb. or less

Seaplane
- Normal category: (+39.8) to (+45.5) at 2220 lb.; (+36.4) to (+45.5) at 1825 lb. or less

Straight line variation between points given.

Empty Weight C.G. Range

None

***Maximum Weight**

Landplane:	
Normal category	2300 lb.
Utility category	2000 lb.
Seaplane:	
Normal category	2220 lb.

Number of Seats

4 (2 at +36, 2 at +70). For child's optional jump seat, refer to Equipment List.

Maximum Baggage

120 lb. (+95)

Fuel Capacity

39 gal. total, 36 gal. usable (two 19.5 gal. tanks in wings at +48)
(See NOTE 1 for weight of unusable fuel and oil).

Oil Capacity

2 gal. (-20), 1 gal. usable

Control Surface Movements

Wing Flaps	Takeoff		Retracted	0°
			1st notch	10°
	Landing		0°	40°
Ailerons	Up	20°	Down	15°
Elevator tab	Up	28°	Down	13°
Elevator	Up	28°	Down	23°

(Neutral position is with bottom of balance area flush with bottom of stabilizer)

Rudder (landplane)	Right	16°	Left	16°
(seaplane)	Right	19°	Left	15°

IV. Models 172D, 172E, 172F, 172G, 172H (cont'd)

Serial Numbers Eligible	Model 172D:	17249545 thru 17250572
	Model 172E:	639, 17250573 thru 17251822
	Model 172F:	17251823 thru 17253392
	Model 172G:	17253393 thru 17254892
	Model 172H:	638, 17254893 thru 17256512 (except 17256493)

V. Model 172I, 4 PCL-SM (Normal Category), 2 PCLM (Utility Category), approved December 15, 1967
Model 172K, 4 PCL-SM (Normal Category), 2 PCLM (Utility Category), approved May 9, 1968

Engine: Lycoming O-320-E2D

*Fuel: 80/87 minimum grade aviation gasoline

*Engine Limits: For all operations, 2700 rpm (150 hp)

Propeller and Propeller Limits:

1. McCauley Propeller
   Hub: 1C172/MTM 7653
   Static rpm at maximum permissible throttle setting:
   Not over 2360, not under 2260.
   No additional tolerance permitted (see NOTE 3).
   Diameter: Not over 76 in., not under 74 in.
   Spinner: Dwg. 0550320
2. McCauley Propeller (seaplane)
   Hub: 1A175/ATM 8042
   Static rpm at maximum permissible throttle setting:
   Not over 2480, not under 2380.
   No additional tolerance permitted (see NOTE 3).
   Diameter: Not over 80 in., not under 78.4 in.
   Spinner: Dwg. 0550320
3. McCauley Propeller
   Hub: 1C160/CTM 7553
   Static rpm at maximum permissible throttle setting:
   Not over 2370, not under 2270.
   No additional tolerance permitted (see NOTE 3).
   Diameter: not over 75 in., not under 74 in.
   Spinner: Dwg. 0550320
4. McCauley Propeller (seaplane)
   Hub: 1A175/ETM 8042
   Static rpm at maximum permissible throttle setting:
   Not over 2480, not under 2380.
   No additional tolerance permitted (see NOTE 3).
   Diameter: Not over 80 in., not under 78.4 in.
   Spinner: Dwg. 0550321
5. McCauley Propeller
   Hub: 1C160/DTM 7553
   Static rpm at maximum permissible throttle setting:
   Not over 2370, not under 2270.
   No additional tolerance permitted (see NOTE 3).
   Diameter: Not over 75 in., not under 74 in.
   Spinner: Dwg. 0550320

*Airspeed Limits (CAS):

Maneuvering	122 mph (106 knots)
Maximum structural cruising	140 mph (122 knots)
Never exceed	174 mph (151 knots)
Flaps extended	100 mph (87 knots)

V. Model 172I, Model 172K (cont'd)

C.G. Range	Landplane:			
	Normal category	(+38.5) to (+47.3) at 2300 lb.		
		(+35.0) to (+47.3) at 1950 lb. or less		
	Utility category	(+35.5) to (+40.5) at 2000 lb.		
		(+35.0) to (+40.5) at 1950 lb. or less		
	Seaplane (Edo 89-2000 or 89A2000 floats):			
	Normal category	(+39.8) to (+45.5) at 2220 lb.		
		(+36.4) to (+45.5) at 1825 lb. or less		
	Straight line variation between points given.			
Empty Weight C.G. Range	None			
*Maximum Weight	Landplane:			
	Normal category	2300 lb.		
	Utility category	2000 lb.		
	Seaplane:			
	Normal category	2220 lb.		
Number of Seats	4 (2 at +34 to +46, 2 at +73). Occupant on child's optional jump seat at +93.			
Maximum Baggage	120 lb. at +95			
Fuel Capacity	42 gal. total, 38 gal. usable (two 21 gal. tanks in wings at +48) (See NOTE 1 for weight of unusable fuel and oil).			
Oil Capacity	2 gal. (-14.0), 1-1/2 gal. usable			
Control Surface Movements	Wing Flaps		Takeoff	0° - 10°
			Landing	0° - 40° ±2°
	Ailerons	Up	20° ±1°	Down 15° ±1°
	Elevator tab	Up	28° +1°, -0°	Down 13° +1°, -0°
	Elevator	Up	28° +1°, -0°	Down 23° +1°, -0°
	(Neutral position is with bottom of balance area flush with bottom of stabilizer.)			
	Rudder (landplane)	Right	16° ±1°	Left 16° ±1°
	(seaplane)	Right	19° ±1°	Left 15° ±1°
	(Measured parallel to W.L.)			
Serial Numbers Eligible	Model 172I: 17256513 thru 17257161			
	Model 172K			
	1969 model: 17257162 thru 17258486			
	1970 model: 17258487 thru 17259223			

VI. Model 172L, 4 PCL-SM (Normal Category), 2 PCLM (Utility Category), approved May 13, 1970

Engine	Lycoming O-320-E2D
*Fuel	80/87 minimum grade aviation gasoline
*Engine Limits	For all operations, 2700 rpm (150 hp)

VI. Model 172L (cont'd)

Propeller and Propeller Limits

1. McCauley Propeller
   Hub: 1C172/MTM 7653
   Static rpm at maximum permissible throttle setting:
   Not over 2360, not under 2260.
   No additional tolerance permitted (see NOTE 3).
   Diameter: Not over 76 in., not under 74 in.
   Spinner: Dwg. 0550320
2. McCauley Propeller (seaplane)
   Hub: 1A175/ATM 8042
   Static rpm at maximum permissible throttle setting:
   Not over 2480, not under 2380.
   No additional tolerance permitted (see NOTE 3).
   Diameter: Not over 80 in., not under 78.4 in.
   Spinner: Dwg. 0550320
3. McCauley Propeller
   Hub: 1C160/CTM 7553
   Static rpm at maximum permissible throttle setting:
   Not over 2370, not under 2270.
   No additional tolerance permitted (see NOTE 3).
   Diameter: Not over 75 in., not under 74 in.
   Spinner: Dwg. 0550320
4. McCauley Propeller
   Hub: 1C160/DTM 7553
   Static rpm at maximum permissible throttle setting:
   Not over 2370, not under 2270.
   No additional tolerance permitted (see NOTE 3).
   Diameter: Not over 75 in., not under 74 in.
   Spinner: Dwg. 0550320
5. McCauley Propeller (Seaplane only)
   Hub: 1A175/ETM 8042
   Static rpm at maximum permissible throttle setting:
   Not over 2480, not under 2380.
   No additional tolerance permitted (see NOTE 3).
   Diameter: Not over 80 in., not under 78.4 in.
   Spinner: Dwg. 0550321

*Airspeed Limits (CAS)

Maneuvering	122 mph (106 knots)
Maximum structural cruising	140 mph (122 knots)
Never exceed	174 mph (151 knots)
Flaps extended	100 mph (87 knots)

C.G. Range

Landplane

Normal category	(+38.5) to (+47.3) at 2300 lb.
	(+35.0) to (+47.3) at 1950 lb. or less
Utility category	(+35.5) to (+40.5) at 2000 lb.
	(+35.0) to (+40.5) at 1950 lb. or less

Straight line variation between points given.

Seaplane (Edo 89-2000 or 89A2000 floats):

Normal category	(+39.8) to (+45.5) at 2220 lb.
	(+36.4) to (+45.5) at 1825 lb. or less

Straight line variation between points given.

Empty Weight C.G. Range: None

*Maximum Weight

Landplane:	
Normal category	2300 lb.
Utility category	2000 lb.
Seaplane:	
Normal category	2220 lb.

VI. Model 172L (cont'd)

Number of Seats	4 (2 at +34 to +46, 2 at +73). Occupant on child's optional jump seat at +96.
Maximum Baggage	120 lb. at +95
Fuel Capacity	42 gal. total, 38 gal. usable (two 21 gal. tanks in wings at +48). (See NOTE 1 for weight of unusable fuel).
Oil Capacity	2 gal. (-14.0), 1-1/2 gal. usable. (See NOTE 1 for data on undrainable oil).

Control Surface Movements

Wing Flaps			Takeoff		0° - 10°
			Landing		0° - 40° ±2°
Ailerons		Up	20° ±1°	Down	15° ±1°
Elevator tab		Up	28° +1°, -0°	Down	13° +1°, -0°
Elevator		Up	28° +1°, -0°	Down	23° +1°, -0°

(Neutral position is with bottom of balance area flush with bottom of stabilizer)

Rudder (landplane)		Right	16° ±1°	Left	16° ±1°
	(seaplane)	Right	19° ±1°	Left	15° ±1°

(Measured parallel to W.L.)

Serial Numbers Eligible

1971 model: 17259224 thru 17259903
1972 model: 17259904 thru 17260758

VII. Model 172M, Skyhawk, 4 PCL-SM (Normal Category), 2 PCLM (Utility Category, approved May 12, 1972

Engine: Lycoming O-320-E2D

*Fuel: 80/87 minimum grade aviation gasoline

*Engine Limits: For all operations, 2700 rpm (150 hp)

Propeller and Propeller Limits

1. McCauley Propeller
   Hub: 1C160/CTM 7553
   Static rpm at maximum permissible throttle setting:
   Not over 2370, not under 2270.
   No additional tolerance permitted (see NOTE 3).
   Diameter: Not over 75 in., not under 74 in.
   Spinner: Dwg. 0550320
2. McCauley Propeller
   Hub: 1C160/DTM 7553
   Static rpm at maximum permissible throttle setting:
   Not over 2370, not under 2270.
   No additional tolerance permitted (see NOTE 3).
   Diameter: Not over 75 in., not under 74 in.
   Spinner: Dwg. 0550320
3. McCauley Propeller (seaplane)
   Hub: 1A175/ATM 8042
   Static rpm at maximum permissible throttle setting:
   Not over 2545, not under 2445.
   No additional tolerance permitted (see NOTE 3).
   Diameter: Not over 80 in., not under 78.4 in.
   Spinner: Dwg. 0550320
4. McCauley Propeller (seaplane)
   Hub: 1A175/ETM 8042
   Static rpm at maximum permissible throttle setting:
   Not over 2545, not under 2445.
   No additional tolerance permitted (see NOTE 3).
   Diameter: Not over 80 in., not under 78.4 in.
   Spinner: Dwg. 0550320

VII. Model 172M (cont'd)

*Airspeed Limits (CAS)	S/N 17256493, 17260759 thru 17265684:		
	Maneuvering	112 mph (97 knots)	
	Maximum structural cruising	145 mph (126 knots)	
	Never exceed	182 mph (158 knots)	
	Flaps extended	100 mph (87 knots)	
	S/N 17265685 thru 17267584:		
	Maneuvering	97 knots	
(See NOTE 4 on use of CAS)	Maximum structural cruising	128 knots	
	Never exceed	160 knots	
	Flaps extended	85 knots	
C.G. Range	Landplane:		
	Normal category	(+38.5) to (+47.3) at 2300 lb.	
		(+35.0) to (+47.3) at 1950 lb. or less	
	Utility category	(+35.5) to (+40.5) at 2000 lb.	
		(+35.0) to (+40.5) at 1950 lb. or less	
	Seaplane (Edo 89-2000 or 89A2000 floats):		
	Normal category	(+39.8) to (+45.5) at 2220 lb.	
		(+36.4) to (+45.5) at 1825 lb. or less	
	Straight line variation between points given.		
Empty Weight C.G. Range	None		
*Maximum Weight	Normal category: 2300 lb. (landplane); 2220 lb. (seaplane)		
	Utility category: 2000 lb. (landplane)		
Number of Seats	4 (2 at +34 to +46, 2 at +73). Occupant on child's optional jump seat at +96.		
Maximum Baggage	120 lb. at +95		
Fuel Capacity	42 gal. total, 38 gal. usable (two 21 gal. tanks in wings at +48)		
	(See NOTE 1 for data on unusable fuel).		
Oil Capacity	2 gal. (-14.0), 1-1/2 gal. usable		
	(See NOTE 1 for data on undrainable oil).		
Control Surface Movements	Wing Flaps	Takeoff 0° - 10°	(landplane/seaplane)
		Landing 0° - 40° +0° -2°	(landplane)
		0° - 30° ±2°	(seaplane)
	Ailerons	Up 20° ±1°	Down 15° ±1°
	Elevator tab	Up 28° +1°, -0°	Down 13° +1°, -0°
	Elevator	Up 28° +1°, -0°	Down 23° +1°, -0°
	(Neutral position is with bottom of balance area flush with bottom of stabilizer.)		
	Rudder (landplane)	Right 16° ±1°	Left 16° ±1°
	(seaplane)	Right 19° ±1°	Left 15° ±1°
	(Measured parallel to W.L.)		
Serial Numbers Eligible	1973 model: 17256493, 17260759 thru 17261898 (except 17261445 & 17261578)		
	1974 model: 17261899 thru 17263458		
	1975 model: 17263459 thru 17265684		
	1976 model: 17265685 thru 17267584		

VIII. Model 172N, Skyhawk, 4 PCL-SM (Normal Category), 2 PCLM (Utility Category), approved May 17, 1976

Engine

Lycoming O-320-H2AD

***Fuel**

100/130 minimum grade aviation gasoline
(S/N 17261445, 17267585 thru 17269309)

100LL/100 minimum grade aviation gasoline
(S/N 17261578, 17269310 thru 17274009)

***Engine Limits**

For all operations, 2700 rpm (160 hp)

Propeller and Propeller Limits

1. McCauley Propeller
   Hub: 1C160/DTM 7557
   Static rpm at maximum permissible throttle setting:
   Not over 2400, not under 2280.
   No additional tolerance permitted.
   Diameter: Not over 75 in., not under 74 in.
   Spinner: Dwg. 0550320
2. McCauley Propeller (seaplane)
   Hub: 1A175/ETM 8042
   Static rpm at maximum permissible throttle setting:
   Not over 2570, not under 2470.
   No additional tolerance permitted.
   Diameter: Not over 80 in., not under 78.5 in.
   Spinner: Dwg. 0550320

***Airspeed Limits (CAS)**
(see NOTE 4 on use of CAS)

Models: 1977, 1978, 1979

Maneuvering	97 knots
Maximum structural cruising	128 knots
Never exceed	160 knots
Flaps extended	85 knots

Model: 1980

Maneuvering	97 knots
Maximum structural cruising	127 knots
Never exceed	158 knots
Flaps extended	85 knots

C.G. Range

Landplane:

Normal category	(+38.5) to (+47.3) at 2300 lb.
	(+35.0) to (+47.3) at 1950 lb. or less
Utility category	(+35.5) to (+40.5) at 2000 lb.
	(+35.0) to (+40.5) at 1950 lb. or less

Seaplane (Edo 89-2000 or 89A2000 floats):

Normal category	(+39.8) to (+45.5) at 2220 lb.
	(+36.4) to (+45.5) at 1825 lb. or less

Straight line variation between points given.

Empty Weight C.G. Range

None

***Maximum Weight**

Normal category: 2300 lb. (landplane); 2220 lb. (seaplane)
Utility category: 2000 lb. (landplane)

Number of Seats

4 (2 at +34 to +46, 2 at +73). Occupant on child's optional jump seat at +96.

VIII. Model 172N (cont'd)

Maximum Baggage	120 lb. at +95					
Fuel Capacity	42 gal. total, 40 gal. usable (two 21.5 gal. tanks in wings at +48) (See NOTE 1 for data on unusable fuel).					
Oil Capacity	1.5 gal. (-14.0), 1.0 gal. usable					
Control Surface Movements	Wing Flaps	Takeoff	0° - 10°			(landplane/seaplane)
		Landing	0° - 40°	+0° -2°		(landplane)
			0° - 30°	±2°		(seaplane)
	Ailerons	Up	20° ±1°	Down	15° ±1°	
	Elevator tab	Up	28° +1°, -0°	Down	13° +1°, -0°	
	Elevator	Up	28° +1°, -0°	Down	23° +1°, -0°	
	(Neutral position is with bottom of balance area flush with bottom of stabilizer)					
	Rudder (landplane)	Right	16° ±1°	Left	16° ±1°	
	(seaplane)	Right	19° ±1°	Left	15° ±1°	
	(Measured parallel to W.L.)					
Serial Numbers Eligible	1977 model: 17261445, 17267585 thru 17269309 1978 model: 17261578, 17269310 thru 17271034 (except 17270050) 1979 model: 17271035 thru 17272884 1980 model: 17270050, 17272885 thru 17274009					

IX. Model 172P, Skyhawk, 4 PCL-SM (Normal Category), 2 PCLM (Utility Category), approved May 13, 1980

Engine	Lycoming O-320-D2J		
*Fuel	100LL/100 minimum grade aviation gasoline		
*Engine Limits	For all operations, 2700 rpm (160 hp)		
Propeller and Propeller Limits	1. McCauley Propeller Hub: 1C160/DTM 7557 Static rpm at maximum permissible throttle setting: Not over 2420, not under 2300 No additional tolerance permitted Diameter: Not over 75 in., not under 74 in. Spinner: Dwg. 0550320 2. McCauley Propeller (floatplane only) Hub: 1A175/ETM 8043 Static rpm at maximum permissible throttle setting: Not over 2570, not under 2470 No additional tolerance permitted Diameter: Not over 80 in., not under 78.5 in. Spinner: Dwg. 0550320		
*Airspeed Limits (CAS) (See NOTE 4 on use of CAS)	Maneuvering		99 knots (landplane) 96 knots (floatplane)
	Maximum structural cruising		127 knots
	Never exceed		158 knots
	Flaps extended		85 knots

IX. Model 172P (cont'd)

C.G. Range

Landplane:

Normal category	(+39.5) to (+47.3)	at 2400 lb.
	(+35.0) to (+47.3)	at 1950 lb. or less
Utility category	(+36.5) to (+40.5)	at 2100 lb.
	(+35.0) to (+40.5)	at 1950 lb. or less

Seaplane (Edo 89-2000 or 89A2000 floats):

Normal category	(+39.8) to (+45.5)	at 2220 lb.
	(+36.4) to (+45.5)	at 1825 lb. or less

Straight line variation between points given.

Empty Weight C.G. Range

None

*Maximum Weight

Normal category: 2400 lb. (landplane); 2220 lb. (seaplane)
Utility category: 2100 lb. (landplane)

Number of Seats

4 (2 at +34 to +46, 2 at +73). Occupant on child's optional jump seat at +96.

Maximum Baggage

120 lb. at +95

Fuel Capacity

42 gal. total, 40 gal. usable (two 21.5 gal. tanks in wings at +48)
(See NOTE 1 for data on unusable fuel).

Oil Capacity

2 gal. (-13.1), 1.5 gal. usable

Control Surface Movements

Wing Flaps		Takeoff	0° - 10°		
		Landing	0° - 30° +0°, -2°		
Ailerons		Up	20° ±1°	Down	15° ±1°
Elevator tab	(floatplane)	Up	28° +1°, -0°	Down	13° +1°, -0°
	(landplane)	Up	22° +1°, -0°	Down	19° +1°, -0°
Elevator		Up	28° +1°, -0°	Down	23° +1°, -0°

(Neutral position is with bottom of balance area flush with bottom of stabilizer)

Rudder	(landplane)	Right	16° ±1°	Left	16° ±1°
	(seaplane)	Right	19° ±1°	Left	15° ±1°

(Measured parallel to W.L.)

Serial Numbers Eligible

1981 model: 17274010 thru 17275034
1982 model: 17275035 thru 17275759
1983 model: 17275760 thru 17276079
1984 model: 17276080 thru 17276259
1985 model: 17276260 thru 17276516
1986 model: 17276517 thru 17276654

X. Model 172Q, Cutlass, 4 PCLM (Normal Category), approved October 15, 1982

Engine	Lycoming O-360-A4N
*Fuel	100LL/100 minimum grade aviation gasoline
*Engine Limits	For all operations, 2700 rpm (180 hp)
Propeller and Propeller Limits	1. McCauley Propeller Hub 1A170E/JFA 7658 Static rpm at maximum permissible throttle setting: Not over 2450, not under 2350. No additional tolerance permitted. Diameter: Not over 76 in., not under 74.5 in. Spinner: Dwg. 0509077
*Airspeed Limits	Maneuvering 105 knots Maximum structural cruising 127 knots Never exceed 158 knots Flaps extended 85 knots
C.G. Range	Normal category (+41.0) to (+47.3) at 2550 lb. (+35.0) to (+47.3) at 1950 lb. or less Straight line variation between points given.
Empty Weight C.G. Range	None
*Maximum Weight	Normal category: 2550 lb.
Number of Seats	4 (2 at +34 to +46, 2 at +73) (Occupant on optional child's seat at +96)
Maximum Baggage	120 lbs. at +95
Fuel Capacity	54 gal. total, 50 gal. usable (two 27 gal. tanks in wings at +48) (See NOTE 1 for data on unusable fuel).
Oil Capacity	9 qt. at -15.5, 2 qt. unusable
Control Surface Movements	Wing Flaps Takeoff 0° - 10° Landing 0° - 30° +0°, -2° Ailerons Up 20° ±1° Down 15° ±1° Elevator tab Up 22° +1°, -0° Down 19° +1°, -0° Elevator Up 28° +1°, -0° Down 23° +1°, -0° (Neutral position is with bottom of balance area flush with bottom of stabilizer) Rudder Right 16° ±1° Left 16° ±1° (Measured parallel to W.L.)
Serial Numbers Eligible	1983 model: 17275869 thru 17276054 1984 model: 17276101 thru 17276211

Data Pertinent to Models 172 thru 172Q

Datum	Front face of firewall (S/N 28000 thru 47746) Lower front face of firewall (S/N 17247747 thru 17276654)
Leveling Means	Upper doorsill

Certification Basis:

Models 172 thru 172P
Civil Air Regulations (CAR) Part 3 effective November 1, 1949, as amended by 3-1 through 3-12. In addition, effective at S/N 17271035 and On, 23.1559 effective March 1, 1978.
FAR 36 dated December 1, 1969, plus Amendments 36-1 through 36-5 for Model 172N.
FAR Part 36 dated December 1, 1969, plus Amendments 36-1 through 36-12 for Models 172P thru 172Q. In addition, effective at S/N 17276260 and On, 23.1545(a), Amendment 23-23 dated December 1, 1978.

Equivalent Safety Items	17261445, 17261578, 17265685
Airspeed Indicator	CAR 3.757 (see NOTE 4 on use of CAS) (S/N 17261445, 17261578, 17265685 thru 17276259)
Operating Limitations	CAR 3.778(a)

Model 172Q
Part 3 of CAR dated November 1, 1949, as amended by 3-1 through 3-12. In addition, 23.1559 effective March 1, 1978; 23.951(b)(2), Amendment 23-15 effective October 31, 1974; and 23.1545(a), Amendment 23-23 effective December 1, 1978.
FAR 36 dated December 1, 1969, plus amendments 36-1through 36-12.

Application for Type Certificate dated July 11, 1955. Type Certificate No. 3A12 issued November 4, 1955, obtained by the manufacturer under Delegation Option Procedures.

Production Basis:
Production Certificate No. 4. Delegation Option Manufacturer No. CE-1 authorized to issue airworthiness certificates under delegation option provisions of Part 21 of the FAR.

Equipment:
The basic required equipment as prescribed in the applicable airworthiness requirements (see Certification Basis) must be installed in the aircraft for certification. This equipment must include a current Airplane Flight Manual (AFM) effective S/N 17271035 and On.

1. Models 172 thru 172G: Stall warning indicator, Dwg. 0511062.
2. Model 172H and On: Stall warning indictor, Dwg. 0523112.

Cessna Publication TS1000-13 should be used for equipment references on all aircraft prior to the Model 172E. Refer to applicable equipment list for the Model 172E and subsequent models.

NOTE 1: Current weight and balance report including list of equipment included in certificated empty weight, and loading instructions, when necessary, must be provided for each aircraft at the time of original certification.

S/N 28000 thru 29999, 36000 thru 36999, 46001 thru 47746, 17247747 thru 17265684
The certificated empty weight and corresponding center of gravity location must include:
Unusable fuel of 30 lb. at (+46) on Models 172 and 172A, or
18 lb. at (+46) for Models 172B thru 172H, or
24 lb. at (+46) for Models 172I thru 172M (17265684), and
Undrainable oil of (0) lb. at -20) for Models 172 thru 172H, and
(0) lb. at (-14) for Models 172I thru 172M (17265684).

S/N 17261578, 17261445, 17265685 thru 17274009
The certificated empty weight and corresponding center of gravity location must include:
Unusable fuel of 24 lbs. at (+46) through Model 172M (17267584), or
18 lbs. at (+46) 17267585 and On, and
full oil of 11.3 lb. at (-14).

Data Pertinent to Models 172 thru 172Q (cont'd)
NOTE 1 (cont'd)

Model 172P, S/N 17274010 thru 17276654:
The certificated empty weight and corresponding center of gravity location must include:
Unusable fuel of 18 lb. at (+46) and full oil of 15 lb. at (-13.1).

Model 172Q, S/N 17275869 thru 17276211:
The certificated empty weight and corresponding center of gravity location must include:
Unusable fuel of 24 lb. at (+46) and full oil of 16.88 lb. at (-15.5).

NOTE 2. The following placards must be displayed as indicated:

A. In full view of the pilot:
(1) Models 172, 172A, 172B
"This airplane must be operated in compliance with the operating limitations stated in the form of placards, markings, and manuals.

NORMAL CATEGORY

Maximum design weight	2200 lb.		
Refer to weight and balance data for loading instructions.			
Flight maneuvering load factors	Flaps up	+3.8	-1.52
	Flaps down	+3.5	
No acrobatic maneuvers including spins approved.			

UTILITY CATEGORY

Maximum design weight	1950 lb.		
Baggage compartment and rear seat must not be occupied			
Flight maneuvering load factors	Flaps up	+4.4	-1.76
	Flaps down	+3.5	

No acrobatic maneuvers approved except those listed below.

Maneuver	Entry speed
Chandelles	115 mph (100 knots)
Lazy eights	115 mph (100 knots)
Steep turns	115 mph (100 knots)
Spins	Slow deceleration
Stalls (except whip stalls)	Slow deceleration"

(2) Model 172C
"This airplane must be operated in compliance with the operating limitations stated in the form of placards, markings, and manuals.

NORMAL CATEGORY

Maximum design weight	2250 lb.		
Refer to weight and balance data for loading instructions.			
Flight maneuvering load factors	Flaps up	+3.8	-1.52
	Flaps down	+3.5	
No acrobatic maneuvers including spins approved.			

UTILITY CATEGORY

Maximum design weight	1950 lb.		
Baggage compartment and rear seat must not be occupied.			
Flight maneuvering load factors	Flaps up	+4.4	-1.76
	Flaps down	+3.5	

No acrobatic maneuvers approved except those listed below.

Maneuver	Entry speed
Chandelles	115 mph (100 knots)
Lazy eights	115 mph (100 knots)
Steep turns	115 mph (100 knots)
Spins	Slow deceleration
Stalls (except whip stalls)	Slow deceleration"

Data Pertinent to Models 172 thru 172Q (cont'd)
NOTE 2 (cont'd)

(3) Models 172D, 172E, 172F, 172G, 172H, 172I, 172K
"This airplane must be operated in compliance with the operating limitations stated in the form of placards, markings, and manuals.

NORMAL CATEGORY

Maximum design weight	2300 lb.		
Refer to weight and balance data for loading instructions.			
Flight maneuvering load factors:			
	Flaps up	+3.8	-1.52
	Flaps down	+3.5	
No acrobatic maneuvers including spins approved.			

UTILITY CATEGORY

Maximum design weight	2000 lb.		
Baggage compartment and rear seat must not be occupied.			
Flight maneuvering load factors	Flaps up	+4.4	-1.76
	Flaps down	+3.5	

No acrobatic maneuvers except those listed below.

Maneuver	Max. Entry speed
Chandelles	122 mph (106 knots)
Lazy eights	122 mph (106 knots)
Steep turns	122 mph (106 knots)
Spins	Slow deceleration
Stalls (except whip stalls)	Slow deceleration"

(4) Model 172L (1971 model)
"This airplane must be operated in compliance with the operating limitations stated in the form of placards, markings, and manuals.

	MAXIMUMS			
	Normal Category		Utility Category	
Maneuvering speed (CAS)	122 mph (106 knots)		122 mph (106 knots)	
Gross weight	2300 lb.		2000 lb.	
Flight load factor				
Flaps up	+3.8	-1.52	+4.4	-1.76
Flaps down	+3.5		+3.5	

Normal category: No acrobatic maneuvers including spins approved.
Utility category: Baggage compartment and rear seat must not be occupied.

No acrobatic maneuvers approved except those listed below.

Maneuver	Entry speed
Chandelles	122 mph (106 knots)
Lazy eights	122 mph (106 knots)
Steep turns	122 mph (106 knots)
Spins	Slow deceleration
Stalls (except whip stalls)	Slow deceleration

Spin recovery: opposite rudder - forward elevator - neutralize controls

Known icing conditions to be avoided. This airplane is certified for the following flight operations as of date of original airworthiness certificate:

(DAY - NIGHT - VFR - IFR)" (as applicable)

Data Pertinent to Models 172 thru 172Q (cont'd)
NOTE 2 (cont'd)

(5) Model 172L (1972 model)
"This airplane must be operated in compliance with the operating limitations as stated in the form of placards, markings, and manuals:

	MAXIMUMS			
	Normal Category		Utility Category	
Maneuvering speed (CAS)	122 mph (106 knots)		122 mph (106 knots)	
Gross weight	2300 lb.		2000 lb.	
Flight load factor				
Flaps up	+3.8	-1.52	+4.4	-1.76
Flaps down	+3.5		+3.5	

Normal category: No acrobatic maneuvers including spins approved
Utility category: Baggage compartment and rear seat must not be occupied.

No acrobatic maneuvers approved except those listed below.

Maneuver	Max. Entry speed
Chandelles	122 mph (106 knots)
Lazy eights	122 mph (106 knots)
Steep turns	122 mph (106 knots)
Spins	Slow deceleration
Stalls (except whip stalls)	Slow deceleration

Spin recovery: opposite rudder - forward elevator - neutralize controls.

Intentional spins with flaps extended are prohibited. Known icing conditions to be avoided. This airplane is certified for the following flight operations as of date of original airworthiness certificate:

(DAY - NIGHT - VFR - IFR)" (as applicable)

(6) Model 172M (Landplane):
(S/N 17256493, 17260759 thru 17265684, except 17261445 and 17261578)
"This airplane must be operated in compliance with the operating limitations as stated in the form of placards, markings, and manuals.

	MAXIMUMS			
	Normal Category		Utility Category	
Maneuvering speed (CAS)	112 mph (97 knots)		112 mph (97 knots)	
Gross weight	2300 lb.		2000 lb.	
Flight load factor				
Flaps up	+3.8	-1.52	+4.4	-1.76
Flaps down	+3.0		+3.0	

Normal category: No acrobatic maneuvers including spins approved.
Utility category: Baggage compartment and rear seat must not be occupied.

No acrobatic maneuvers approved except those listed below.

Maneuver	Recommended Entry speed	Maneuver	Recommended Entry Speed
Chandelles	120 mph (104 knots)	Spins	Slow deceleration
Lazy eights	120 mph (104 knots)	Stalls (except whip stalls)	Slow deceleration
Steep turns	112 mph (97 knots)		

Altitude loss in stall recovery: 180 feet.
Abrupt use of the controls prohibited above 112 mph.

Data Pertinent to Models 172 thru 172Q (cont'd)
NOTE 2 (cont'd)

Spin recovery: opposite rudder - forward elevator - neutralize controls

Intentional spins with flaps extended are prohibited. Flight into known icing conditions prohibited. This airplane is certified for the following flight operations as of date of original airworthiness certificate:

(DAY - NIGHT - VFR - IFR)" (as applicable)

Model 172M (Floatplane):
(S/N 17256493, 17260759 thru 17265684, except 17261445 and 17261578)
"This airplane must be operated as a normal category airplane in compliance with the operating limitations as stated in the form of placards, markings, and manuals.

	MAXIMUMS	
Maneuvering speed	110 mph (96 knots) (CAS)	
Gross weight	2220 lbs.	
Flight load factor	Flaps up	+3.8, -1.52
	Flaps down	+3.0

WATER RUDDER: Extend for taxi; retract for takeoff, flight, and landing.
No acrobatic maneuvers, including spins approved.
Altitude loss in a stall recovery: 200 ft.
Flight into known icing conditions prohibited. This airplane is certified for the following flight operations as of date of original airworthiness certificate:

(DAY - NIGHT - VFR - IFR)" (as applicable)

(7) Models 172M, 172N (Landplane)
(S/N 17261445, 17261578, 17265685 thru 17271034, except 17270050)
"This airplane must be operated in compliance with the operating limitations stated in the form of placards, markings, and manuals.

	MAXIMUMS			
	Normal Category		Utility Category	
Maneuvering speed (CAS)	97 knots		97 knots	
Gross weight	2300 lb.		2000 lb.	
Flight load factor				
Flaps up	+3.8	-1.52	+4.4	-1.76
Flaps down	+3.0		+3.0	

Normal category: No acrobatic maneuvers including spins approved.
Utility category: Baggage compartment and rear seat must not be occupied.

NO ACROBATIC MANEUVERS EXCEPT THOSE LISTED BELOW:

Recommended		Recommended	
Maneuver	Entry speed	Maneuver	Entry Speed
Chandelles	105 knots	Spins	Slow deceleration
Lazy eights	105 knots	Stalls (except	Slow deceleration
Steep turns	95 knots)	whip stalls)	

Altitude loss in stall recovery: 180 feet.
Abrupt use of the controls prohibited above 97 knots

Data Pertinent to Models 172 thru 172Q (cont'd)
NOTE 2 (cont'd)

Spin recovery: opposite rudder - forward elevator - neutralize controls.

Intentional spins with flaps extended are prohibited. Flight into known icing conditions prohibited. This airplane is certified for the following flight operations as of date of original airworthiness certificate.

(DAY - NIGHT - VFR - IFR)" (as applicable)

Models 172M, 172N (Floatplane):
(S/N 17265685 thru 17271034)

FLOATPLANE
"This airplane must be operated as a normal category airplane in compliance with the operating limitations as stated in the form of placards, markings, and manuals.

		MAXIMUMS
Maneuvering speed (CAS)		96 knots
Gross weight		2220 lb.
Flight load factor	Flaps up	+3.8, -1.52
	Flaps down	+3.0

Water Rudder: Extend for taxi; retract for takeoff, flight, and landing.

No acrobatic maneuvers, including spins approved.
Altitude loss in a stall recovery: 200 ft.
Flight into known icing conditions prohibited. This airplane is certified for the following flight operations as of date of original airworthiness certificate:

(DAY - NIGHT - VFR - IFR)" (as applicable)

B. Forward of fuel selector valve (all models through S/N 17265684, except 17261445 and 17261578): "Both tanks on for takeoff and landing."

C. On the fuel selector valve (at appropriate location):

(1) Models 172, 172A

"Both:	37 gal.
Left:	18.5 gal.
Right:	18.5 gal.
Off"	

(2) Model 172B

"Both:	39 gal.
Left:	19.5 gal.
Right:	19.5 gal.
Off"	

(3) Models 172C, 172D, 172E, 172F, 172G, 172H

"Both:	36 gal.
Left:	18 gal.
Right:	18 gal.
Off"	

(4) Models 172I thru 172M (except S/N 17261445 and 17261578)

"Both:	38 gal. (all flight attitudes)
Left:	19 gal. (level flight only)
Right:	19 gal. (level flight only)
Off"	

Data pertinent to Models 172 thru 172Q (cont'd)
NOTE 2 (cont'd)

(5) Model 172N (S/N 17261445, 17261578, 17267585 thru 17271034, excluding 17270050)
"Both: 40 gal. (all flight altitudes) (takeoff - landing)
Left: 20 gal. (level flight only)
Right: 20 gal. (level flight only)
Off"

D. Models 172 thru 172E
On flap handle
(1) "Flaps - Pull to extend
Takeoff Retract 0°
1st notch 10°
Landing 0° - 40°
(2) "Avoid slips with flaps down."

E. Model 172F (electric flaps) thru S/N 17271034, excluding 17270050
Near flap indicator: "Avoid slips with flaps extended."

F. In baggage compartment:
(1) Models 172 thru 172B
"Maximum baggage 120 lb. For additional loading instructions, see weight and balance data."
(2) Models 172C thru 172M (1973 model)
"120 lb. maximum baggage and/or auxiliary seat passenger.
For additional loading instructions see weight and balance data."
(3) S/N 17261899 thru 17271034, excluding 17270050
"120 lb. maximum baggage and/or auxiliary passenger forward of baggage door latch."
"50 lb. maximum baggage aft of baggage door latch maximum 120 lb. combined.
For additional loading instructions see weight and balance data."

G. S/N 17258487 thru 17259903.
Near ammeter: "Do not turn off alternator in flight except in emergency."

H. Additional placards required in seaplane.
(1) Models 172A thru 172I, in full view of the pilot:
"Operate as normal category airplane except:
Maximum weight 2220 lb.
Maximum altitude loss in stall recovery 120 ft.
Flaps - takeoff - 1st notch -10°
Water rudder - pull to extract
Retract - takeoff, flight and landing
Extend - taxi."

(2) Model 172K, in full view of the pilot:
"THIS AIRPLANE MUST BE OPERATED IN COMPLIANCE WITH THE OPERATING LIMITATIONS AS STATED IN THE FORM OF PLACARDS, MARKINGS, AND MANUALS

NORMAL CATEGORY; FLOATPLANE
Maximum weight 2220 lb.
Refer to weight and balance data for loading instructions.

Flight maneuvering load factors Flaps up +3.8, -1.52
Flaps down +3.5

No acrobatic maneuvers including spins approved.
Maximum altitude loss in stall recovery: 120 ft.
Flaps: Takeoff - 10° . . . Water rudder: Pull to retract . . .
Retract: Takeoff, flight and landing . . . . Extend: Taxi."

Data Pertinent to Models 172 thru 172Q (cont'd)
NOTE 2 (cont'd)

(3) Model 172F thru S/N 17271034, excluding 17270050, in full view of the pilot. "Floatplane Max. Flaps - 30°."

(4) Model 172L, in full view of the pilot:

"FLOATPLANE
THIS AIRPLANE MUST BE OPERATED AS A NORMAL CATEGORY AIRPLANE IN COMPLIANCE WITH THE OPERATING LIMITATIONS AS STATED IN THE FORM OF PLACARDS, MARKINGS, AND MANUALS.

"MAXIMUMS

Maneuvering speed	122 mph CAS (106 knots)	
Gross weight	2220 lb.	
Flight load factor	Flaps up	+3.8, -1.52
	Flaps down	+3.5

WATER RUDDER: Extend for taxi; retract for takeoff, flight, and landing.

FLAPS: 10° for takeoff

No acrobatic maneuvers, including spins, approved.
Altitude loss in stall recovery: 120 ft.
Known icing conditions to be avoided. This airplane is certified for the following flight operations as of date of original airworthiness certificate:

(DAY - NIGHT - VFR - IFR)" (as applicable)

I. Models 172I, 172K, 172L (with IC172/MTM propeller)
Near tachometer: "Avoid continuous operation
1. Above 75 percent power in cruise
2. Above 2500 rpm in full throttle climb."

J. Model 172L (1972 model) thru Model 172N (1978 model)
Near ammeter and adjacent to overvoltage light: "High Voltage"

K. Models with S/N 28000 thru 17258855, except those with Cessna Kit No. SK-172-31B or SK-172-32 installed near fuel selector valve:

"SWITCH TO SINGLE TANK OPERATION IMMEDIATELY UPON REACHING CRUISE ALTITUDES ABOVE 5000 FEET."

L. Near fuel tank filler
(1) Models 172, 172A, 172B
"FUEL
80/87 min. grade aviation gasoline
Cap. 21 U.S. gal."

(2) Models 172C, 172D, 172E, 172F, 172G, 172H
"FUEL
80/87 min. grade aviation gasoline
Cap. 19.5 U.S. gal."

(3) Models 172I thru 172M (except S/N 17261445 and 17261578)
"FUEL
80/87 min. grade aviation gasoline
Cap. 21 US. gal."

Data pertinent to Models 172 thru 172Q (cont'd)
NOTE 2 (cont'd)

(4) Model 172N (S/N 17261445, 17267585 thru 17269309)
"FUEL
100/130 min. grade aviation gasoline
Cap. 21.5 US. gal."

(5) Model 172N (S/N 17261578, 17269310 thru 17271034, excluding 17270050)
"FUEL
100LL/100 min. grade aviation gasoline
Cap. 21.5 US. gal."

M. Effective at S/N 17270050, 17271035 thru 17276654
All placards required in the Pilot's Operating Handbook (POH) and FAA Approved AFM must be installed in the appropriate locations.

NOTE 3. Compliance with Service Letter SE74-16 (Carburetor Nozzle Replacement) allows rpm's as follows:
Landplane: not over 2420, not under 2300
Seaplane: not over 2570, not under 2445

NOTE 4. The marking of the airspeed indicator in CAS provides an Equivalent Level of Safety (ELOS) to CAR 3.757 when approved airspeed calibration data presented in Section V of the POH below is available to the pilot (TIAS is exactly equal to CAS):

MODELS	S/N's
172M, Cessna P/N D1057-13	17265685 thru 17267584
172N, Cessna P/N D1082-13	17261445, 17267585 thru 17269309
172N, Cessna P/N D1109-13	17261578, 17269310 thru 17271034, except 17270050
172N, Cessna P/N D1138-13PH	17271035 thru 17272884
172N, Cessna P/N D1172-13PH	17270050, 17272885 thru 17274009
172P, Cessna P/N D1192-13PH	17274010 thru 17275034
172P, Cessna P/N D1212-13PH	17275035 thru 17275759
172P, Cessna P/N D1231-13PH	17275760 thru 17276079
172P, Cessna P/N D1251-13PH	17276080 thru 17276259

NOTE 5. 14-volt electrical system
(Model 172 series thru S/N 17269309, except 17258105 thru 17258112, and 17261578)

28-volt electrical system
(S/N 17258105 thru 17258112, 17261578 and 17269310 thru 17276654)

NOTE 6. Special Ferry Flight Authorization. Flight Standards District Offices (FSDO) is authorized to issue Special overweight ferry flight authorizations. These airplanes are structurally satisfactory for ferry flight if maintained within the following limits:
1. Takeoff weight must not exceed 130% of the maximum weight for Normal Category.
2. The Never Exceed Airspeed (V_{NE}) and Maximum Structural Cruising Speed (V_C) must be reduced by 30%.
3. Forward and aft center of gravity limits may not be exceeded.
4. Structural load factors of +2.5 g. to -1.0 g. may not be exceeded.

Requirements for any additional oil should established in accordance with AC 23.1011-1. Increased stall speeds and reduced climb performance should be expected for the increased weights. Flight characteristics and performance at the increased weights have not been evaluated. Flight Permit for operations of overweight aircraft may be found in AC 21-4B.

In addition to the placards specified above, the prescribed operating limitations indicated by an asterisk (*) under Sections I through X of this data sheet must also be displayed by permanent markings.

XI. Model 172R, Skyhawk, 4 PCLM (Normal Category), 2 PCLM (Utility Category), Approved June 21, 1996

Engine

Lycoming IO-360-L2A, Rated 160 Horsepower

When modified by Cessna Modification Kit MK172-72-01 (See NOTE 4)
Lycoming IO-360-L2A, Rated 180 Horsepower

Fuel

100/100LL minimum grade aviation gasoline

Engine Limits

For all operations, 2,400 RPM

When modified by Cessna Modification Kit MK172-72-01 (See NOTE 4)
For all operations, 2,700 RPM

Propeller and Propeller Limits

1. McCauley Propeller
   Hub 1C235/LFA7570
   Static rpm at full throttle setting:
   Not over 2,165; not under 2,065.
   No additional tolerance permitted.
   Diameter: Not over 75 in., not under 74 in.
   Spinner: Dwg. 0550236

When modified by Cessna Modification Kit MK172-72-01 (See NOTE 4)

2. McCauley Propeller
   Hub 1A170E/JHA7660
   Static rpm at full throttle setting:
   Not over 2,400; not under 2,300.
   No additional tolerance permitted.
   Diameter: Not over 76 in., not under 75 in.
   Spinner: Dwg. 0550236

Airspeed Limits

Maneuvering	99 Knots IAS	(97 Knots CAS)
Max Structural Cruising	129 Knots IAS	(126 Knots CAS)
Never Exceed	163 Knots IAS	(160 Knots CAS)
Flaps Extended	85 Knots IAS	(84 Knots CAS)

When modified by Cessna Modification Kit MK172-72-01 (See NOTE 4)

Maneuvering	105 Knots IAS	(102 Knots CAS)
Max Structural Cruising	129 Knots IAS	(126 Knots CAS)
Never Exceed	163 Knots IAS	(160 Knots CAS)
Flaps Extended	85 Knots IAS	(84 Knots CAS)

C.G. Range

When using POH/AFM 172RPHUS-00, or later FAA approved revision, or POH/AFM 172RPHAUS-00 thru -03, or later FAA approved revision

Normal Category

(1) Aft Limits	47.3 inches aft of datum at 2,450 pounds or less.
(2) Forward Limits	Linear variation from 40.0 inches aft of datum at 2,450 lb. to 35.0 inches aft of datum at 1,950 lb.; 35.0 inches aft of datum at 1,950 lb. or less.

Utility Category

(1) Aft Limits	40.5 inches aft of datum at 2,100 lb. or less.
(2) Forward Limits	Linear variation from 36.5 inches aft of datum at 2,100 lb. to 35.0 inches aft of datum at 1,950 lb.; 35.0 inches aft of datum at 1,950 lb. or less.

XI. Model 172R (cont'd)

C.G. Range (cont'd)

When Using POH/AFM 172RPHAUS-04, or later FAA approved revision, or POH/AFM 172RPHBUS-00, or later FAA approved revision

Normal Category

(1) Aft Limits	47.3 inches aft of datum at 2,450 pounds or less.
(2) Forward Limits	Linear variation from 40.0 inches aft of datum at 2,450 lb. to 35.0 inches aft of datum at 1,950 lb.; 35.0 inches aft of datum at 1,950 lb. or less.

Utility Category

(1) Aft Limits	40.5 inches aft of datum at 2,200 pounds or less.
(2) Forward Limits	Linear variation from 37.5 inches aft of datum at 2,200 lb. to 35.0 inches aft of datum at 1,950 lb.; 35.0 inches aft of datum at 1,950 lb. or less.

When modified by Cessna Modification Kit MK172-72-01 (See NOTE 4)

Normal Category

(1) Aft Limits	47.3 inches aft of datum at 2,550 pounds or less.
(2) Forward Limits	Linear variation from 41.0 inches aft of datum at 2,550 lb. to 35.0 inches aft of datum at 1,950 lb.; 35.0 inches aft of datum at 1,950 lb. or less.

Utility Category

(1) Aft Limits	40.5 inches aft of datum at 2,200 pounds or less.
(2) Forward Limits	Linear variation from 37.5 inches aft of datum at 2,200 lb. to 35.0 inches aft of datum at 1,950 lb.; 35.0 inches aft of datum at 1,950 lb. or less.

Empty Wt. C.G. Range: None

Reference Datum: Lower portion of front face of firewall

MAC: 58.8 inches; Leading edge of MAC 25.9 inches aft of datum

Leveling Means: Left side of Tailcone at 108.0 inches and 142.0 inches aft of datum

Maximum Weights

When using POH/AFM 172RPHUS-00, or later FAA approved revision, or POH/AFM 172RPHAUS-00 thru -03 or later FAA approved revision

Normal Category

Maximum Ramp	2,457 lb.
Maximum Takeoff and Landing	2,450 lb.

Utility Category

Maximum Ramp	2,107 lb.
Maximum Takeoff and Landing	2,100 lb.

When using POH/AFM 172RPHAUS-04, or later FAA approved revision, or POH/AFM 172RPHBUS-00, or later FAA approved revision

Normal Category

Maximum Ramp	2,457 lb.
Maximum Takeoff and Landing	2,450 lb.

Utility Category

Maximum Ramp	2,207 lb.
Maximum Takeoff and Landing	2,200 lb.

XI. Model 172R (cont'd)

Maximum Weights (cont'd)

When modified by Cessna Modification Kit MK172-72-01 (See NOTE 4)

Normal Category

Maximum Ramp	2,558 lb.
Maximum Takeoff and Landing	2,550 lb.

Utility Category

Maximum Ramp	2,208 lb.
Maximum Takeoff and Landing	2,200 lb.

No. of Seats: 4 (2 at 34.0 to 46.0 inches aft of datum; 2 at 73.0 inches aft of datum)

Maximum Baggage: 120 lb. at 95.0 inches aft of datum

When modified by Cessna Modification Kit MK172-72-01 (See NOTE 4)
120 lb. at 82.0 to 108.0 inches aft of datum
50 lb. at 108.0 to 142.0 inches aft of datum
(Maximum combined weight capacity for baggage areas is 120 lb.)

Fuel Capacity (Gal.): 56 gallons total; 53 gallons usable
(Two 28-gallon tanks in wings at 48.0 inches aft of datum)
(See NOTE 1 for data on unusable fuel)

Oil Capacity (Gal.): 2.0 gallons at 13.1 inches forward of datum
3.5 quarts usable

When modified by Cessna Modification Kit MK172-72-01 (See NOTE 4)
2.0 gallons at 13.1 inches forward of datum
3.0 quarts usable

Control Surface Movements

Wing Flaps		Takeoff		0º - 10º
		Landing		0º - 30º + 0°/-2°
Ailerons	Up	20° ± 1°	Down	15° ± 1°
Elevator tab	Up	22° + 1°/-0°	Down	19° + 1°/-0°
Elevator	Up	28° + 1°/-0°	Down	23° + 1°/-0°

(Neutral position is with bottom of balance area flush with bottom of stabilizer)

Rudder (Measured parallel to W.L.): Right 16° 10'± 1° Left 16° 10' ± 1°
Rudder (Measured perpendicular to Hinge): Right 17° 44' ± 1° Left 17° 44' ± 1°

Serial Numbers Eligible: 17280001 and On

Data Pertinent to Model 172R:

Certification Basis:
FAR Part 23 effective February 1, 1965, as amended by 23-1 through 23-6, except as follows:
23.423, 23.611, 23.619, 23.623, 23.689, 23.775, 23.871, 23.1323, 23.1563 as amended by Amendment 23-7. 23.807, 23.1524 as amended by Amendment 23-10. 23.507, 23.771, 23.853(a)(b)(c), 23.1365 as amended by Amendment 23-14. 23.951 as amended by Amendment 23-15. 23.607, 23.675, 23.685, 23.733, 23.787, 23.1309, 23.1322 as amended by Amendment 23-17. 23.1301 as amended by Amendment 23-20. 23.1353, 23.1559 as amended by Amendment 23-21. 23.603, 23.605, 23.613, 23.1329, 23.1545 as amended by Amendment 23-23. 23.441, 23.1549 as amended by Amendment 23-28. 23.779, 23.781 as amended by Amendment 23-33. 23.1, 23.51, 23.561 as amended by Amendment 23-34. 23.301, 23.331, 23.351, 23.427, 23.677, 23.701, 23.735, 23.831 as amended by Amendment 23-42. 23.961, 23.1093; 23.1143(g), 23.1147(b), 23.1303, 23.1357, 23.1361, 23.1385 as amended by Amendment 23-43. 23.562(a), 23.562(b)(2), 23.562(c)(1), 23.562(c)(2), 23.562(c)(3), 23.562(c)(4) as amended by Amendment 23-44. 23.33, 23.53, 23.305, 23.321, 23.485, 23.621, 23.655, 23.731 as amended by Amendment 23-45.

FAR 36 dated December 1, 1969, as amended by Amendments 36-1 through 36-21.

Data Pertinent to Model 172R (cont'd)

Certification Basis (cont'd):

Additions for the Garmin G1000 Integrated Cockpit System (ICS) Only:
14 CFR 23.303, 23.307, 23.601, 23.1163(a), 23.1367, 23.1381 as amended by Amendment 23- N/C. 23.1589 as amended by Amendment 23-13. 23.771(a) as amended by Amendment 23-14. 23.607 and (Electrical System) 23.1309(a)(1)(2)(c) as amended by Amendment 23-17. 23.1301, 23.1327, 23.1547(e) as amended by Amendment 23-20. 23.1501, 23.1541(a)(1)(2)(b)(1)(2) as amended by Amendment 23-21. 23.603, 23.605 as amended by Amendment 23-23. 23.1529 as amended by Amendment 23-26. 23.561(e), 23.1523, 23.1581(a)(2), 23.1583(a)(c)(d)(f), 23.1585(a)(b)(d) as amended by Amendment 23-34. 23.301 as amended by Amendment 23-42. 23.1322, 23.1331, 23.1357(a)(b)(c)(d) as amended by Amendment 23-43. 23.305, 23.773(a)(1)(2), 23.1525, 23.1549 as amended by Amendment 23-45. 23.1303(a)(b)(c)(f), 23.1309(a)(1)(i)(ii)(2)(b)(1)(2)(i)(ii)(3)(4)(i)(ii)(iii)(iv)(c)(1)(2)(iii)(3)(d)(e)(f)(1), 23.1311, 23.1321(a)(c)(d)(e), 23.1323(a)(b)(1)(2)(c); 23.1329(g)(h), 23.1351(a)(1)(2)(i)(b)(1)(iii)(2)(3)(c)(4)(d)(1), 23.1353(a)(b)(c)(d)(e), 23.1359(c), 23.1361; 23.1365(a)(b)(d)(e)(f), 23.1431(a)(b)(d)(e) as amended by Amendment 23-49. 23.1325(a)(b)(1)(2)(i)(3)(c)(d)(e), 23.1543(b)(c), 23.1545(a)(b)(1)(2)(3)(4), 23.1553, 23.1555(a)(b), 23.1563(a), 23.1567(a) as amended by Amendment 23-50. 23.777(a)(b), 23.955(a)(2), 23.1337(a)(1)(2)(b)(1)(c) as amended by Amendment 23-51. 23.1305(a)(1)(2)(3)(b)(2)(3)(i)(4)(i)(5)(6)(i) as amended by Amendment 23-52. 23.901(a)(b) as amended by Amendment 23-53.

Additions for the Garmin GFC-700 Automatic Flight Control System (AFCS) only:
14 CFR 23.1335 as amended by Amendment 23-20, 23.1329(a)(c)(d)(e)(f) as amended by Amendment 23-49.

Equivalent Safety Items

1.	Induction System Icing Protection	23.1093, refer to FAA letter dated 5/3/1996
2.	Throttle Control	23.1143(g), refer to FAA letter dated 3/22/1996
3.	Mixture Control	23.1147(b), refer to FAA letter dated 3/22/1996
4.	Anti-Collision Light System	23.1401(d), refer to ACE-07-09, FAA letter dated 10/12/2007
5.	Aviation White Color Requirement	23.1397(c), refer to ACE-07-10, FAA letter dated 11/29/2007

Date of Application for Amended Type Certificate was September 25, 1995.
Type Certificate No. 3A12 was amended June 21, 1996.

Special Conditions as follows:
No. 23-159-SC, "Cessna Aircraft Company, Cessna Model 172R; Installation of Electronic Flight Instrument System and the Protection of the System from High Intensity Radiated Fields (HIRF)".

Production Basis
Production Certificate No. PC-4 issued March 28, 1997. Applies to S/N 17280014, 17280015, 17280017, 17280021 thru 17280029, 17280031 and On. Airplane serial numbers not listed were produced under Type Certificate only. Cessna is authorized to issue airworthiness certificates under the delegation provisions of Delegation Option Authorization No. CE-1 in accordance with Part 21 of the FAR.

Equipment
The basic required equipment as prescribed in the applicable airworthiness regulations (see Certification Basis) must be installed in the airplane for certification.

NOTE 1: Weight and Balance:

S/N 17280001 and On
The certificated empty weight and corresponding center of gravity location must include unusable fuel of 18 lb. at 46.0 inches aft of datum, and full oil of 15.0 lb. at 13.1 inches forward of datum.

Data Pertinent to Model 172R (cont'd)

NOTE 2: The airplane must be operated according to the appropriate Pilot's Operating Handbook and FAA Approved Airplane Flight Manual (POH/AFM). POH/AFM P/N 172RPHUS00, or later FAA approved revision, is applicable to Production Model 172R. POH/AFM P/N 172R180PH00, or later FAA approved revision, is applicable to Production Model 172R airplanes when modified by Cessna Modification Kit MK172-72-01. All POH/AFM Supplements approved for P/N number 172RPHUS00, are also applicable to P/N 172R180PH00, unless specifically noted otherwise in the Supplement. All FAA required placards are included in Section 2 of the applicable POH/AFM, the applicable operating rules, or the certification basis must be installed as specified via the parts list for 0500530, Airplane Assembly (useful placarding reference is the Textron Aviation Illustrated Parts Catalogue (IPC). Any discrepancies identified between the IPC and an aircraft under inspection need to be reconciled using the previously stated parts list).

FAA Approved AFM: P/N 172RPHAUS-00, or later FAA approved revision, is applicable to the Model 172R equipped with Garmin G1000 Integrated Cockpit System. The airplane must be operated according to the appropriate AFM. Required placards are included in the AFM, the applicable operating rules, or the certification basis must be installed as specified via the parts list for 0500530, Airplane Assembly (useful placarding reference is the Textron Aviation IPC. Any discrepancies identified between the IPC and an aircraft under inspection need to be reconciled using the previously stated parts list).

FAA Approved AFM: P/N 172RPHBUS-00, or later FAA approved revision, are applicable to the Model 172R equipped with Garmin G1000 Integrated Cockpit System and Garmin GFC-700 AFCS. The airplane must be operated according to the appropriate AFM. Required placards are included in the AFM, the applicable operating rules, or the certification basis must be installed as specified via the parts list for 0500530, Airplane Assembly (useful placarding reference is the Textron Aviation IPC. Any discrepancies identified between the IPC and an aircraft under inspection need to be reconciled using the previously stated parts list).

NOTE 3: Special Ferry Flight Authorization. FSDO is authorized to issue special overweight ferry flight authorizations. This airplane is structurally satisfactory for ferry flight if maintained within the following limits:

1. Takeoff weight must not exceed 130% of the maximum weight for Normal Category.
2. The Never Exceed Airspeed (V_{NE}) and Maximum Structural Cruising Speed (V_C) must be reduced by 30%.
3. Forward and aft center of gravity limits may not be exceeded.
4. Structural load factors of +2.5 g. to -1.0 g. may not be exceeded.

Requirements for any additional oil should be established in accordance with AC 23.1011-1. Increased stall speeds and reduced climb performance should be expected for the increased weights. Flight characteristics and performance at the increased weights have not been evaluated. Flight Permit for operations of overweight aircraft may be found in AC 21-4B.

NOTE 4: Only certain Model 172R airplane serial numbers are eligible for modification by Cessna Modification Kit MK172-72-01. Applicable serial numbers are as follows:

17280159	17280242	17280251	17280253	17280257
17280262	17280281	17280292	17280301	17280305
17280426	17280488	17280606	17280607	17280608
17280609	17280610	17280613	17280614	17280616
17280621	17280622	17280623	17280624	17280631
17280632	17280633	17280634	17280638	17280639
17280640	17280646	17280647	17280648	17280652
17280653	17280659	17280660	17280661	17280662
17280664	17280667	17280668	17280669	17280670
17280672	17280673	17280674	17280675	17280701
17280707				

NOTE 5: The following serial numbers are manufactured under the name Cessna Aircraft Company: 17280001 thru 17281622.

NOTE 6: Company name change effective 7/29/2015. The following serial numbers are manufactured under the name Textron Aviation Inc.: 17281623 and On.

XII. Model 172S, Skyhawk SP, 4 PCLM (Normal Category), 2 PCLM (Utility Category), Approved May 1, 1998

Engine	Lycoming IO-360-L2A, Rated 180 Horsepower
Fuel	100/100LL minimum grade aviation gasoline
Engine Limits	For all operations, 2,700 RPM
Propeller and Propeller Limits	1. McCauley Propeller Hub 1A170E/JHA7660 Static rpm at full throttle setting: Not over 2400; not under 2300. No additional tolerance permitted. Diameter: Not over 76 in., not under 75 in. Spinner: Dwg. 0550236
Airspeed Limits	Maneuvering 105 Knots IAS (102 Knots CAS) Max Structural Cruising 129 Knots IAS (126 Knots CAS) Never Exceed 163 Knots IAS (160 Knots CAS) Flaps Extended 85 Knots IAS (85 Knots CAS)
C.G. Range	Normal Category (1) Aft Limits — 47.3 inches aft of datum at 2,550 pounds or less. (2) Forward Limits — Linear variation from 41.0 inches aft of datum at 2,550 pounds to 35.0 inches aft of datum at 1,950 pounds. 35.0 inches aft of datum at 1,950 pounds or less. Utility Category (1) Aft Limits — 40.5 inches aft of datum at 2,200 pounds or less. (2) Forward Limits — Linear variation from 37.5 inches aft of datum at 2,200 pounds to 35.0 inches aft of datum at 1,950 pounds. 35.0 inches aft of datum at 1,950 pounds or less.
Empty Wt. C.G. Range	None
Reference Datum	Lower portion of front face of firewall
MAC	58.8 inches; Leading edge of MAC 25.9 inches aft of datum
Leveling Means	Left side of Tailcone at 108.0 inches and 142.0 inches aft of datum
Maximum Weights	Normal Category Maximum Ramp 2,558 lb. Maximum Takeoff and Landing 2,550 lb. Utility Category Maximum Ramp 2,208 lb. Maximum Takeoff and Landing 2,200 lb.
No. of Seats	4 (2 at 34.0 to 46.0 inches aft of datum; 2 at 73.0 inches aft of datum)
Maximum Baggage	120 lb. at 82.0 to 108.0 inches aft of datum 50 lb. at 108.0 to 142.0 inches aft of datum (Max. combined weight capacity for baggage areas is 120 pounds)
Fuel Capacity (Gal.)	56 gallons total; 53 gallons usable (two 28-gallon tanks in wings at 48.0 inches aft of datum). (See NOTE 1 for data on unusable fuel).
Oil Capacity (Gal.)	8.0 quarts at 13.1 inches forward of datum 3.0 quarts usable

XII. Model 172S (cont'd)

Control Surface Movements	Wing Flaps		Takeoff	0º - 10º	
			Landing	0º - 30º	+ 0°/-2°
	Ailerons	Up	20° ± 1°	Down	15° ± 1°
	Elevator tab	Up	22° + 1°/-0°	Down	19° + 1°/-0°
	Elevator	Up	28° + 1°/-0°	Down	23° + 1°/-0°
	(Neutral position is with bottom of balance area flush with bottom of stabilizer)				
	Rudder (Measured parallel to W.L.):			Right 16° 10'± 1°	Left 16° 10' ± 1°
	Rudder (Measured perpendicular to Hinge:			Right 17° 44' ± 1°	Left 17° 44' ± 1°
Serial Numbers Eligible	172S8001 and On				

Data Pertinent to Model 172S:

Certification Basis:
FAR Part 23 effective February 1, 1965, as amended by 23-1 through 23-6, except as follows:
23.423, 23.611, 23.619, 23.623, 23.689, 23.775, 23.871, 23.1323, 23.1563 as amended by Amendment 23-7. 23.807, 23.1524 as amended by Amendment 23-10. 23.507, 23.771, 23.853(a)(b)(c), 23.1365 as amended by Amendment 23-14. 23.951 as amended by Amendment 23-15. 23.607, 23.675, 23.685, 23.733, 23.787, 23.1309, 23.1322 as amended by Amendment 23-17. 23.1301 as amended by Amendment 23-20. 23.1353, 23.1559 as amended by Amendment 23-21. 23.603, 23.605, 23.613, 23.1329, 23.1545 as amended by Amendment 23-23. 23.441, 23.1549 as amended by Amendment 23-28. 23.779, 23.781 as amended by Amendment 23-33. 23.1, 23.51, 23.561 as amended by Amendment 23-34. 23.301, 23.331, 23.351, 23.427, 23.677; 23.701, 23.735, 23.831 as amended by Amendment 23-42. 23.961, 23.1093, 23.1143(g), 23.1147(b), 23.1303, 23.1357; 23.1361, 23.1385 as amended by Amendment 23-43. 23.562(a), 23.562(b)(2), 23.562(c)(1), 23.562(c)(2), 23.562(c)(3), 23.562(c)(4) as amended by Amendment 23-44. 23.33, 23.53, 23.305, 23.321; 23.485, 23.621, 23.655, 23.731 as amended by Amendment 23-45.

FAR 36 dated December 1, 1969, as amended by Amendments 36-1 through 36-21.

Additions for the Garmin G1000 Integrated Cockpit System (ICS) Only:
14 CFR 23.303, 23.307, 23.601, 23.1163(a), 23.1367, 23.1381 as amended by Amendment 23- N/C. 23.1589 as amended by Amendment 23-13. 23.771(a) as amended by Amendment 23-14. 23.607 and (Electrical System) 23.1309(a)(1)(2)(c) as amended by Amendment 23-17. 23.1301, 23.1327, 23.1547(e) as amended by Amendment 23-20. 23.1501, 23.1541(a)(1)(2)(b)(1)(2) as amended by Amendment 23-21. 23.603, 23.605 as amended by Amendment 23-23. 23.1529 as amended by Amendment 23-26. 23.561(e), 23.1523, 23.1581(a)(2), 23.1583(a)(c)(d)(f) and 23.1585(a)(b)(d) as amended by Amendment 23-34. 23.301 as amended by Amendment 23-42. 23.1322, 23.1331, 23.1357(a)(b)(c)(d) as amended by Amendment 23-43. 23.305, 23.773(a)(1)(2), 23.1525, 23.1549 as amended by Amendment 23-45. 23.1303(a)(b)(c)(f), 23.1309(a)(1)(i)(ii)(2)(b)(1)(2)(i)(ii)(3)(4)(i)(ii)(iii)(iv)(c)(1)(2)(iii)(c)(3)(d)(e)(f)(1), 23.1311, 23.1321(a)(c)(d)(e), 23.1323(a)(b)(1)(2)(c), 23.1329(g)(h), 23.1351(a)(1)(2)(i)(b)(1)(iii)(2)(3)(c)(4)(d)(1), 23.1353(a)(b)(c)(d)(e), 23.1359(c), 23.1361, 23.1365(a)(b)(d)(e)(f), 23.1431(a)(b)(d)(e) as amended by Amendment 23-49. 23.1325(a)(b)(1)(2)(i)(3)(c)(d)(e), 23.1543(b)(c), 23.1545(a)(b)(1)(2)(3)(4), 23.1553, 23.1555(a)(b), 23.1563(a), 23.1567(a) as amended by Amendment 23-50. 23.777(a)(b), 23.955(a)(2), 23.1337(a)(1)(2)(b)(1)(c) as amended by Amendment 23-51. 23.1305(a)(1)(2)(3)(b)(2)(3)(i)(b)(4)(i)(5)(6)(i) as amended by Amendment 23-52. 23.901(a)(b) as amended by Amendment 23-53.

Additions for the Garmin GFC-700 Automatic Flight Control System (AFCS) only:
14 CFR 23.1335 as amended by Amendment 23-20. 23.1329(a)(c)(d)(e)(f) as amended by Amendment 23-49.

Additions for the Garmin GI 275 Electronic Flight Instrument Only:
14 CFR 23.1327 as amended by Amendment 23-20. 23.1501 as amended by Amendment 23-21. 23.1529 as amended by Amendment 23-26. 23.1523(b), 23.1581(a)(1)(2) as amended by Amendment 23-34. 23.1322, 23.1331 as amended by Amendment 23-43. 23.1525 as amended by Amendment 23-45. 23.1303(a)(b)(f), 23.1309(a)(1)(2)(b)(c)(1)(2)(iii)(3)(d)(e)(f), 23.1311(a)(b), 23.1321(a)(c)(d)(e), 23.1323(a)(c), 23.1351(a)(1)(2)(i), 23.1359(c), 23.1365(a)(d)(e), 23.1431 (a)(b) as amended by Amendment 23-49. 23.1325(a)(b)(1)(i)(ii)(iii)(2)(i), 23.1543(b)(c), 23.1545(a)(b)(1)(2)(3)(4), 23.1555(a)(b) as amended by Amendment 23-50. 23.777(a)(b) as amended by Amendment 23-51. 23.1308(a)(b)(c) as amended by Amendment 23-57. 23.1306(a)(b) as amended by Amendment 23-61. 23.2010 and 23.2510 as amended by Amendment 23-64 (see NOTE 6). Effective at S/N 172S12701 and On.

Additions for 14 CFR Part 23 Amendment 64:
14 CFR 23.2000, 23.2005, 23.2010 as amended by Amendment 23-64 (see NOTE 7). Effective at S/N 172S12701 and On.

Data Pertinent to Model 172S: (cont'd)

Certification Basis (cont'd):

Additions for the Garmin G1000 NXi Integrated Cockpit System Only:
14 CFR 23.683, 23.867 as amended by Amendment 23-7. 23.613(a)(b) as amended by Amendment 23-45. 23.301(a), 23.337, 23.561(a)(b)(3)(e), 23.607(a)(b), 23.611 as amended by Amendment 23-48. 23.1329(b), 23.1351(g), 23.1353(h), 23.1359(a)(b), as amended by Amendment 23-49. 23.143(c), 23.1555(e)(2), 23.1581(a)(b)(1)(3)(c)(d)(f), 23.1583(h)(m), 23.1585(j) as amended by Amendment 23-50. 23.1337(b)(c) as amended by Amendment 23-51. 23.2515, 23.2520 as amended by Amendment 23-64 (see NOTE 8). Effective at S/N 172S13231 and On.

Additions for the Dual Electronic Ignition System Only:
14 CFR 23.1309(a)(1)(2), 23.1353(h), 23.1431(b) as amended by Amendment 23-49. 23.1581(a)(2) as amended by Amendment 23-50. 23.901(a)(1)(2)(b)(1)(2) as amended by Amendment 23-53. Effective at S/N 172S13375 and On.

Additions for new or changed non-rechargeable lithium battery installations:
14 CFR Part 23 regulations as amended by Amendment 23-64 (see NOTE 9): 14 CFR 23.2010 and 23.2325(g). Effective at S/N 172S13689 and On.

Additions for new or changed installations affecting aeronautical security (cybersecurity):
14 CFR Part 23 regulations as amended by Amendment 23-64 (see NOTE 10): 14 CFR 23.2010, 23.2500, 23.2505 and 23.2510. Effective at S/N 172S13689 and On.

Equivalent Safety Items

1. Induction System Icing Protection	23.1093, refer to FAA letter dated 5/1/1998
2. Throttle Control	23.1143(g), refer to FAA letter dated 5/1/1998
3. Mixture Control	23.1147(b), refer to FAA letter dated 5/1/1998
4. Anti-Collision Light System	23.1401(d), refer to ACE-07-09, FAA letter dated 10/12/2007
5. Aviation White Color Requirement	23.1397(c), refer to ACE-07-10, FAA letter dated 11/29/2007

Date of Application for Amended Type Certificate for Model 172S was November 13, 1997.
Type Certificate No. 3A12 was amended May 1, 1998, for Model 172S.

Special Conditions as follows:
No. 23-159-SC, "Cessna Aircraft Company, Cessna Model 172S. Installation of Electronic Flight Instrument System and the Protection of the System from High Intensity Radiated Fields (HIRF)."

Production Basis
Production Certificate No. PC-4 issued August 27, 1998. Applies to S/N 172S8003 and On. Airplane serial numbers not listed were produced under Type Certificate only. Cessna is authorized to issue airworthiness certificates under the delegation provisions of Delegation Option Authorization No. CE-1 in accordance with Part 21 of the FAR.

Equipment
The basic required equipment as prescribed in the applicable airworthiness regulations (see Certification Basis) must be installed in the airplane for certification.

NOTE 1. Weight and Balance:
S/N 172S8001 and On
The certificated empty weight and corresponding center of gravity location must include unusable fuel of 18 pounds at 46.0 inches aft of datum, and full oil of 15.0 pounds at 13.1 inches forward of datum.

NOTE 2. POH/AFM: P/N 172SPHUS-00 (or later FAA approved revision) is applicable to the Model 172S. The airplane must be operated according to the appropriate POH/AFM. All FAA required placards are included in Section 2 of the POH/AFM, the applicable operating rules, or the certification basis must be installed as specified via the parts list for 0500531, Airplane Assembly (useful placarding reference is the Textron Aviation IPC. Any discrepancies identified between the IPC and an aircraft under inspection need to be reconciled using the previously stated parts list).

FAA Approved AFM: P/N 172SPHAUS-00, or later FAA approved revision, is applicable to Model 172S equipped with Garmin G1000 Integrated Cockpit System. The airplane must be operated according to the appropriate AFM. Required placards are included in the AFM, the applicable operating rules, or the certification basis must be installed as specified via the parts list for 0500531, Airplane Assembly (A useful placarding reference is the Textron Aviation IPC. Any discrepancies identified between the IPC and an aircraft under inspection need to be reconciled using the previously stated parts list).

Data Pertinent to Model 172S: (cont'd)
NOTE 2. (cont'd)

FAA Approved AFM: P/N 172SPHBUS-00, or later FAA approved revision, are applicable to the Model 172S equipped with Garmin G1000 Integrated Cockpit System and Garmin GFC-700 AFCS. The airplane must be operated according to the appropriate AFM. Required placards are included in the AFM, the applicable operating rules, or the certification basis must be installed as specified via the parts list for 0500531, Airplane Assembly (useful placarding reference is the Textron Aviation IPC. Any discrepancies identified between the IPC and an aircraft under inspection need to be reconciled using the previously stated parts list).

FAA Approved AFM: P/N 172SPHCUS-00, or later FAA approved revision, are applicable to the Model 172S equipped with Garmin G1000 NXi Integrated Cockpit System. The airplane must be operated according to the appropriate AFM. Required placards are included in the AFM, the applicable operating rules, or the certification basis must be installed as specified via the parts list for 0500531, Airplane Assembly (useful placarding reference is the Textron Aviation IPC. Any discrepancies identified between the IPC and an aircraft under inspection need to be reconciled using the previously stated parts list).

NOTE 3. Special Ferry Flight Authorization. FSDO is authorized to issue Special overweight ferry flight authorizations. This airplane is structurally satisfactory for ferry flight if maintained within the following limits:

1. Takeoff weight must not exceed 130% of the maximum weight for Normal Category.
2. The Never Exceed Airspeed (V_{NE}) and Maximum Structural Cruising Speed (V_C) must be reduced by 30%.
3. Forward and aft center of gravity limits may not be exceeded.
4. Structural load factors of +2.5 g. to -1.0 g. may not be exceeded.

Requirements for any additional oil should be established in accordance with AC 23.1011-1. Increased stall speeds and reduced climb performance should be expected for the increased weights. Flight characteristics and performance at the increased weights have not been evaluated. Flight Permit for operations of overweight aircraft may be found in AC 21-4B.

NOTE 4. The following serials numbers are manufactured under the name Cessna Aircraft Company: 172S8001 thru 172S11614.

NOTE 5. Company name change effective 7/29/15. The following serials numbers are manufactured under the name Textron Aviation: 172S11615 and On.

NOTE 6. Means of Compliance for 23.2510 [23-64] is draft AC 20-184A.

NOTE 7. 14 CFR 23.2005 Certification Level and Performance Level: Level 2, Low Speed.

NOTE 8. Means of Compliance for 23.2515 [23-64] and 23.2520 [23-64] is FAA Policy PS-ACE-23-10.

NOTE 9. Means of Compliance for 23.2010 [23-64] and 23.2325(g) [23-64] is CPP-23.2525-1 (signed 2023.10.19).

NOTE 10. Means of Compliance for 23.2010, 23.2500, 23.2505, and 23.2510 as amended by Amendment 23-64 is ASTM F3532-22.

------- END ------