

1)

```
[D3_96469_Sazid> select * from orders where cnum=(select cnum from customers where cname='Cisneros');
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
+-----+-----+-----+-----+-----+
2 rows in set (0.01 sec)
```

7)

```
[D3_96469_Sazid> select * from orders o where o.snum=(select snum from salespeople where sname='Motika');
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
+-----+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

8)

```
[D3_96469_Sazid> select * from orders o where o.snum IN(select snum from customers where city='London');
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

6)

```
[D3_96469_Sazid> select * from orders o where o.amt>any(select o1.amt from customers c inner join orders o1 on c.cnum=o1.cnum where c.city='London');
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```

4)

```
[D3_96469_Sazid> select * from customers c where c.rating >= any(select c1.rating from customers c1 inner join salespeople s on c1.snum=s.snum where s.sname='Serres');
+-----+-----+-----+-----+-----+
| cnum | cname | city   | rating | snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome   | 200 | 1003 |
| 2003 | Liu      | San Jose | 200 | 1002 |
| 2004 | Grass    | Berlin  | 300 | 1002 |
| 2008 | Cisneros | San Jose | 300 | 1007 |
+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

11)

```
[D3_96469_Sazid> select * from customers c where c.rating>any(select rating from customers where city='Rome');
+-----+-----+-----+-----+-----+
| cnum | cname | city   | rating | snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome   | 200 | 1003 |
| 2003 | Liu      | San Jose | 200 | 1002 |
| 2004 | Grass    | Berlin  | 300 | 1002 |
| 2008 | Cisneros | San Jose | 300 | 1007 |
+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

12)

```
ERROR 1064 (12000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'select * from orders o where o.amt>any(select amt from orders where odate='1990-10-04');' at line 1
[D3_96469_Sazid> select * from orders o where o.amt>any(select amt from orders where odate='1990-10-04');
+-----+-----+-----+-----+-----+
| onum | amt   | odate | cnum | snum |
+-----+-----+-----+-----+-----+
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 | 309.95 | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
8 rows in set (0.01 sec)
```

13)

```
[D3_96469_Sazid> select * from orders where amt<any(select o.amt from orders o inner join customers c on o.cnum=c.cnum where c.city='San Jose');
+-----+-----+-----+-----+-----+
| onum | amt   | odate | cnum | snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 | 309.95 | 1990-10-04 | 2004 | 1002 |
+-----+-----+-----+-----+-----+
8 rows in set (0.00 sec)
```

2)

```
D3_96469_Sazid> SELECT o.amt, c.cname, c.rating
-> FROM customers c
-> INNER JOIN orders o ON c.cnum = o.cnum
-> WHERE o.amt > ALL (SELECT AVG(amt) FROM orders);
+-----+-----+-----+
| amt   | cname  | rating |
+-----+-----+-----+
| 5160.45 | Liu    | 200    |
| 9891.88 | Clemens | 100    |
| 4723.00 | Clemens | 100    |
+-----+-----+-----+
3 rows in set (0.00 sec)
```

5)

```
[D3_96469_Sazid> SELECT s1.snum,s1.sname,s1.city FROM salespeople s1 WHERE s1.snum NOT IN (SELECT s.snum FROM customers c INNER JOIN salespeople s ON s.snum = c.snum WHERE s.city = c.city );
+-----+-----+-----+
| snum | sname  | city   |
+-----+-----+-----+
| 1004 | Motika | London |
| 1007 | Rifkin | Barcelona |
| 1003 | Axelrod | New York |
+-----+-----+-----+
3 rows in set (0.00 sec)
```

9)

```
D3_96469_Sazid> SELECT s.sname, s.snum
-> FROM salespeople s
-> WHERE s.snum IN (
->     SELECT s1.snum
->     FROM salespeople s1
->     INNER JOIN customers c ON s1.snum = c.snum
->     GROUP BY s1.snum
->     HAVING COUNT(c.cnum) > 1
-> );
```

sname	snum
Peel	1001
Serres	1002

2 rows in set (0.01 sec)

10)

```
D3_96449_Sazid> SELECT s.snum, s.sname, s.city, count(cnum) FROM salespeople s INNER JOIN customers c1 ON s.snum = c1.snum WHERE s.snum = ANY (SELECT s1.snum FROM salespeople s1 INNER JOIN customers c ON s1.snum = c.snum GROUP BY s1.snum HAVING COUNT(c.cnum) > 1) GROUP BY s.sname, s.snum, s.city;
```

snum	sname	city	count(cnum)
1001	Peel	London	2
1002	Serres	San Jose	2

2 rows in set (0.00 sec)

3)

```
SELECT snum SUM(amt) FROM orders GROUP BY snum HAVING SUM(amt) >
(SELECT MAX(amt) FROM orders);
```

```
D3_96469_Sazid> SELECT snum, SUM(amt) FROM orders GROUP BY snum HAVING SUM(amt) > (SELECT MAX(amt) FROM orders);
```

snum	SUM(amt)
1001	15382.07

1 row in set (0.04 sec)