FOOD SERVICE & SOLUTION CO., LTD • บริษัท ฟูดเซอร์วิส แอนด์ โชลูชั่น จำกัด • フードサービス & ソリューション



29 S.Chalaemnimit, Bangkhlo, Bangkorlaem, Bangkok 10120, Thailand

 $T: +66(83)8392929, +66(81)6152621 \bullet F: +66(2)6885755$

M: contact@fsns-thailand.com • W: www.fsns-thailand.com • Line: fsns-thailand

PH-200: Waterproof pH Meter

FEATURES

- -Measures pH and Temperature
- -Auto-ranging three point calibration with digital fine tuning
- -Includes storage solution in a sponge embedded in a clear cap
- -Waterproof housing (IP-67 rating)
- -Simultaneous temperature display
- -Measurement Range: 0-14 pH
- -Digital automatic calibration (one point), with digital fine tuning
- -Automatic Temperature Compensation (ATC)
- -Auto-off function, data-hold function and low-battery indicator
- -Display: large and easy-to-read LCD screen includes simultaneous temperature reading
- -Replaceable Sensor (model SP-P2)
- -Factory Calibrated: The PH-200 meter is three-point checked and factory calibrated to pH 7.0. It can be recalibrated to any point in its range with digital calibration using the push buttons.
- -Includes a cap, batteries, lanyard, and pH 7.0 buffer

SPECIFICATIONS

pH Range: 0 - 14

Temperature Range: 0-80 °C; 32-176 °F

Resolution: 0.01 pH; Temperature resolution is 0.1 °C/F **Accuracy:** +/- 0.02 pH; Temperature accuracy is +/-2%

Calibration: Digital automatic calibration (one point) with digital fine tuning

Electrode: Replaceable glass sensor and reference tube electrodes

Housing: IP-67 Waterproof (submersible; floats)

Power source: 3 x 1.5V button cell batteries (LR44 or equivalent; included)

Dimensions: 18.5 x 3.4 x 3.4 cm (7.3 x 1.3 x 1.3 inches)

Weight: 96.4 g (3.4 oz)



