

- [CPSC 275: Introduction to Computer Systems](#)

[CPSC 275: Introduction to Computer Systems](#)

Fall 2025

- [Syllabus](#)
- [Schedule](#)
- [Resources](#)
- [Upload](#)
- [Solution](#)

Homework 31

NOTE: You are not required to hand in the following exercises, but you are strongly encouraged to complete them to strengthen your understanding of the concepts covered in class.

- Given a 32-bit virtual address space and a 24-bit physical address, determine the number of bits in the VPN, VPO, PPN, and PPO for the following page sizes P :

P	No. VPN bits	No. VPO bits	No. PPN bits	No. PPO bits
1K				
2K				
4K				
8K				

- Show how the example memory system in Lecture 30 translates a virtual address into a physical address and accesses the cache. For the given virtual address, indicate the TLB entry accessed, physical address, and cache byte value returned. Indicate whether the TLB misses, whether a page fault occurs, and whether a cache miss occurs. If there is a cache miss, enter “—” for “Cache byte returned.” If there is a page fault, enter “—” for “PPN” and leave parts C and D blank.

Virtual address: 0x03d7

A. Virtual address format

13	12	11	10	9	8	7	6	5	4	3	2	1	0

B. Address translation

Parameter	Value

VPN	
TLB index	
TLB tag	
TLB hit? (Y/N)	
Page fault? (Y/N)	
PPN	

C. Physical address format

11	10	9	8	7	6	5	4	3	2	1	0

D. Physical memory reference

Parameter	Value
Byte offset	
Cache index	
Cache tag	
Cache hit? (Y/N)	
Cache byte returned	

3. Repeat Exercise 2 for the virtual address 0x027c.

4. Repeat Exercise 2 for the virtual address 0x0040.

- **Welcome: Sean**

- [LogOut](#)

