Results

Own Python Summary Example

Summary

Input rows	N	Missing	Mean	Sample SD	Median	Minimum	Maximum
6	5	1	4.00	3.54	3.00	1.00	10.0

ClinicoPathPj launches its own Python subprocess. Both examples execute the same Python summary function. Missing cells are excluded; SD uses N minus 1. These are descriptive summaries, with no independence assumption or inferential test. Elapsed time includes the complete backend route and does not isolate process-launch performance.

Backend elapsed time

Route: processx; backend elapsed: 0.532 s.
Includes selected-data encoding, startup/imports, calculations, HTML and native mapping.
Excludes native image rendering and browser drawing. Pj resource preparation is included.
ClinicoPathPj processx runner; cooperative checkpoint and execution timeout.

Pj Service Summary Example

Summary

Input rows	N	Missing	Mean	Sample SD	Median	Minimum	Maximum
6	5	1	4.00	3.54	3.00	1.00	10.0

ClinicoPathPj calls the installed Pj public service using jamovi Python; no editor opens. Both examples execute the same Python summary function. Missing cells are excluded; SD uses N minus 1. These are descriptive summaries, with no independence assumption or inferential test. Elapsed time includes the complete backend route and does not isolate process-launch performance.

Backend elapsed time

Route: pj; backend elapsed: 2.681 s.
Includes selected-data encoding, startup/imports, calculations, HTML and native mapping.
Excludes native image rendering and browser drawing. Pj resource preparation is included.
Pj 1.5.0; runner: processx; checkpoint enabled; shared call timeout.

References

[1] R Core Team (2026). *R: A Language and environment for statistical computing*. (Version 4.6) [Computer software]. Retrieved from https://cran.r-project.org. (R packages retrieved from CRAN snapshot 2026-05-11).

[2] The jamovi project (2026). *jamovi*. (Version 28) [Computer Software]. Retrieved from https://www.jamovi.org.