




FCB: Component Count:				SBKBarMeter 28 V0 3
Item	Qty	Ref.	Value	Part
1	1	J1	Conn 01x11	2.54mm pin header
2	1	12	Conn_01x02	2.54mm pin header
3	1	J1	BAR	BL(Z)28-3005xxlinear displaytype






THIS PCB CAN BE USED WITH BOTH COMMON CATHODE (SK) OR COMMON ANODE (SA) BL28(Z)—3005xx BAR METER TYPE, IN COMBINAISON WITH THE RIGHT SBK BarDrive xx28 PCB DRIVER BACKPACK, OR WITH DIRECT WIRING WITH MAX7219/MAX7221.

SHOWING COMMON CATHODE (SK TYPE) CONNEXION WITH MAX7219/MAX7221 ICs



SHOWING COMMON ANODE (SA TYPE) CONNEXION WITH MAX7219/MAX7221 ICs



SBK BarMeter 28 V0 PCB

with BL(Z)28-3005xx linear led display type to use with SBK BarDrive xx28 backpack

or for direct wiring with MAX7219/MAX7221 ICs

Smart Builds & Kits

Sheet: /

File: SBK BarMeter 28 VO.kicad_sch

Title: SBK BarMerter 28 VO

 Size: USLetter
 Date: 2025-06-16
 Rev: 1

 KiCad E.D.A. kicad 7.0.9
 Id: 1/1