
Codility_

Candidate Report: trainingGRSJJQ-HHC

Check out Codility training tasks

Test Name:

Summary Review (0) Timeline





Tasks Details

1. CountFactorsTask ScoreCorrectnessPerformanceCount factors of given number n.100%100%100%

score: 100

7

8

Task description

A positive integer D is a *factor* of a positive integer N if there exists an integer M such that N = D * M.

For example, 6 is a factor of 24, because M = 4 satisfies the above condition (24 = 6 * 4).

Write a function:

class Solution { public int solution(int N); }

that, given a positive integer N, returns the number of its factors.

For example, given N = 24, the function should return 8, because 24 has 8 factors, namely 1, 2, 3, 4, 6, 8, 12, 24. There are no other factors of 24.

Write an efficient algorithm for the following assumptions:

N is an integer within the range [1..2,147,483,647].

Copyright 2009–2020 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

Solution Programming language used: Java 8 Total time used: 26 minutes Effective time used: 26 minutes Notes: not defined yet Task timeline 08:32:44 08:58:10 Code: 08:58:10 UTC, java, final, show code in pop-up

// you can also use imports, for example:

// you can write to stdout for debugging purposes, e.g.
// System.out.println("this is a debug message");

// import java.util.*;

import java.util.List;

class Solution {

import java.util.ArrayList;

public int solution(int N) {

```
List<Integer> list = new ArrayList<>();
11
             if(N<1)</pre>
12
                 return 0;
13
             for (int i = 1; i <= Math.sqrt(N); i++) {</pre>
                 if (N % i == 0) {
14
                      if (N / i == i) {
15
16
                         list.add(i);
17
18
19
                          list.add(i);
                          list.add(N/i);
20
21
                     }
22
23
             }
24
             return list.size();
25
         }
     }
26
```

Analysis summary

The solution obtained perfect score.

Analysis ?

Detected time complexity: O(sqrt(N))

xpar	nd all Exam	ple tests
•	example1 example test (N=24=4!)	√ OK
expar	nd all Correct	ness tests
•	squares N=16, N=36	√ OK
•	tiny N <= 10	√ OK
•	simple1 N=41(prime), N=42	√ OK
•	simple2 N=69, N=64, N=120=5!	√ OK
•	simple3 N=720=6!, N=1111	√ OK
•	simple4 N=5,040=7!, N=12,345	√ OK
•	simple5 N=34,879, N=40,320=8!	√ OK
•	extreme_one N=1	√ OK
expar	nd all Perform	nance tests
•	medium1 N=362,880=9!, N=1,948,102	√ OK
•	medium2 N=3,628,800=10!, N=5,621,892, N=	√ OK 4,999,696
•	big1 N=27,043,111, N=39,916,800=11!, 39,992,976	✓ OK N =
•	big2 N=97,093,212, N=2^28	√ OK
•	big3 N=479,001,600=12!, N=780291637 N=449,991,369	✓ OK 7(prime),
•	extreme_maxint N=1,000,000,000, N=MAX_INT, N=2147,395,600	√ OK

The PDF version of this report that may be downloaded on top of this site may contain sensitive data including personal information. For security purposes, we recommend you remove it from your system once reviewed.