
Codility_

Candidate Report: trainingSCED2G-SCB

Check out Codility training tasks

Test Name:

Summary Review (0) Timeline





Tasks Details

1. TapeEquilibrium Task Score Correctness Performance

Minimize the value |(A[0] + ... + A[P-1]) - (A[P] + ... + A[N-1])|.

100%

Task description

A non-empty array A consisting of N integers is given. Array A represents numbers on a tape.

Any integer P, such that 0 < P < N, splits this tape into two non-empty parts: A[0], A[1], ..., A[P - 1] and A[P], A[P + 1], ..., A[N - 1].

The difference between the two parts is the value of: |(A[0] + A[1] + ... + A[P-1]) - (A[P] + A[P+1] + ... + A[N-1])|

In other words, it is the absolute difference between the sum of the first part and the sum of the second part.

For example, consider array A such that:

- A[0] = 3
- A[1] = 1
- A[2] = 2
- A[3] = 4
- A[4] = 3

We can split this tape in four places:

- P = 1, difference = |3 10| = 7
- P = 2, difference = |4 9| = 5
- P = 3, difference = |6 7| = 1
- P = 4, difference = |10 3| = 7

Write a function:

```
class Solution { public int solution(int[] A); }
```

Solution

Programming language used: Java 8

Total time used: 1 minutes

Effective time used: 1 minutes

Notes: not defined yet

Task timeline



Code: 17:27:03 UTC, java, final, show code in pop-up score: 100

1 // you can also use imports, for example:
2 // import java.util.*;
3 // you can write to stdout for debugging purposes, e.g.
5 // System.out.println("this is a debug message");
6 class Solution {
8 public int solution(int[] A) {

25.10.2020

that, given a non-empty array A of N integers, returns the minimal difference that can be achieved.

For example, given:

A[0] = 3 A[1] = 1 A[2] = 2 A[3] = 4

A[4] = 3

the function should return 1, as explained above.

Write an efficient algorithm for the following assumptions:

- N is an integer within the range [2..100,000];
- each element of array A is an integer within the range [-1,000..1,000].

Copyright 2009–2020 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

Test results - Codility

```
// write your code in Java SE 8
             int len = A.length;
10
11
             if(len==1) {
                 return Math.abs(A[0]);
12
13
             } else if(len==2) {
14
                 return Math.abs((A[0]-A[1]));
15
             double sum = 0;
16
17
             for(int val : A) {
18
                 sum = sum+val;
19
20
             double leftSum = 0, difference = 0, minimum = Inte
21
22
             for(int i=0; i<len-1; i++) {</pre>
23
                 leftSum = leftSum + A[i];
                 difference = sum - 2*leftSum;
24
25
26
                 minimum = Math.min(Math.abs(difference), minim
27
             }
28
             return (int) minimum;
29
         }
30
     }
```

Analysis summary

The solution obtained perfect score.

Analysis 👩

Detected time complexity: **O(N)**

expand all	Example tests	3	
► exam	nple ole test	√	OK
expand all	Correctness tes	sts	
► doub two el	le ements	√	OK
	le_positive e test with positive numbers, length =	✓	OK
	le_negative e test with negative numbers, length =	√	OK
	le_boundary ne element on one of the sides	√	OK
	l_random m small, length = 100	√	OK
	I_range sequence, length = ~1,000	√	OK
► small	 elements	√	OK
expand all	Performance tes	sts	3
rando	um_random1 m medium, numbers from 0 to 100, = ~10,000	✓	OK
rando	um_random2 m medium, numbers from -1,000 to ngth = ~10,000	√	OK
large :	_ones sequence, numbers from -1 to 1, = ~100,000	✓	OK
•	_random m large, length = ~100,000	√	OK

•	large_sequence large sequence, length = ~100,000	✓	ОК
•	large_extreme		ок

The PDF version of this report that may be downloaded on top of this site may contain sensitive data including personal information. For security purposes, we recommend you remove it from your system once reviewed.