[Technical Data]

Selection of Transmission Timing Belts 5

-Transmission Capacity Table-

Selection is easy with Timing Pulleys and Belts automatic calculation tool available at:
http://fawos.misumi.jp/FA_WEB/pulley_sea/

Table 33. Reference Transmission Capacity of MXL Ps -Nominal Width of Belts 025 (6.4mm)- (W)

No. of Teeth of Small Pulley	12	14	15	16	18	20	22	24	25	26	28	30	32	36	40
Rotary Speed of Small Pulley(rpm) / Diameter of the Pitch Circle(mm)	7.76	9.06	9.70	10.35	11.64	12.94	14.23	15.52	16.17	16.82	18.11	19.40	20.70	23.29	25.97
950	9.0	10.5	11.3	12.0	13.5	15.0	16.5	18.0	18.8	19.6	21.1	22.6	24.1	27.1	30.1
1160	11.0	12.8	13.8	14.7	16.5	18.4	20.2	22.0	23.0	23.9	25.7	27.6	29.4	33.1	36.7
1425		15.8	16.9	18.0	20.3	22.6	24.8	27.1	28.2	29.3	31.6	33.9	36.1	40.6	45.1
1750		19.4	20.8	22.2	24.9	27.7	30.5	33.3	34.7	36.0	38.8	41.6	44.3	49.9	55.4
2850			33.9	36.1	40.6	45.1	49.6	54.1	56.4	58.6	63.1	67.6	72.1	81.0	90.0
3450			41.0	43.7	49.2	54.6	60.1	65.5	68.2	70.9	76.3	81.7	87.1	97.9	108.6
100	0.9	1.1	1.1	1.2	1.4	1.5	1.7	1.9	1.9	2.0	2.2	2.3	2.5	2.8	3.1
200	1.9	2.2	2.3	2.5	2.8	3.1	3.4	3.8	3.9	4.1	4.4	4.7	5.0	5.7	6.3
300	2.8	3.3	3.5	3.8	4.2	4.7	5.2	5.7	5.9	6.1	6.6	7.1	7.6	8.5	9.5
400	3.8	4.4	4.7	5.0	5.7	6.3	6.9	7.6	7.9	8.2	8.8	9.5	10.1	11.4	12.6
500	4.7	5.5	5.9	6.3	7.1	7.9	8.7	9.5	9.9	10.3	11.1	11.9	12.6	14.2	15.8
600	5.7	6.6	7.1	7.6	8.5	9.5	10.4	11.4	11.9	12.3	13.3	14.2	15.2	17.1	19.0
700	6.6	7.7	8.3	8.8	10.0	11.1	12.2	13.3	13.8	14.4	15.5	16.6	17.7	19.9	22.2
800	7.6	8.8	9.5	10.1	11.4	12.6	13.9	15.2	15.8	16.5	17.7	19.0	20.3	22.8	25.3
900	8.5	10.0	10.7	11.4	12.8	14.2	15.7	17.1	17.8	18.5	19.9	21.4	22.8	25.7	28.5
1000	9.5	11.1	11.9	12.6	14.2	15.8	17.4	19.0	19.8	20.6	22.2	23.8	25.3	28.5	31.7
1100	10.4	12.2	13.0	13.9	15.7	17.4	19.2	20.9	21.8	22.6	24.4	26.1	27.9	31.4	34.8
1200	11.4	13.3	14.2	15.2	17.1	19.0	20.9	22.8	23.8	24.7	26.6	28.5	30.4	34.2	38.0
1300		14.4	15.4	16.5	18.5	20.6	22.6	24.7	25.7	26.8	28.8	30.9	32.9	37.1	41.2
1400		15.5	16.6	17.7	19.9	22.2	24.4	26.6	27.7	28.8	31.0	33.3	35.5	39.9	44.3
1500		16.6	17.8	19.0	21.4	23.8	26.1	28.5	29.7	30.9	33.3	35.6	38.0	42.8	47.5
1600		17.7	19.0	20.3	22.8	25.3	27.9	30.4	31.7	32.9	35.5	38.0	40.5	45.6	50.7
1700		18.8	20.2	21.5	24.2	26.9	29.6	32.3	33.7	35.0	37.7	40.4	43.1	48.5	53.8
1800		19.9	21.4	22.8	25.7	28.5	31.4	34.2	35.6	37.1	39.9	42.8	45.6	51.3	57.0
2000			23.8	25.3	28.5	31.7	34.8	38.0	39.6	41.2	44.3	47.5	50.7	57.0	63.3
2200			26.1	27.9	31.4	34.8	38.3	41.8	43.6	45.3	48.8	52.2	55.7	62.7	69.6
2400			28.5	30.4	34.2	38.0	41.8	45.6	47.5	49.4	53.2	57.0	60.8	68.3	75.9
2600			30.9	32.9	37.1	41.2	45.3	49.4	51.5	53.5	57.6	61.7	65.8	74.0	82.1
2800				35.5	39.9	44.3	48.8	53.2	55.4	57.6	62.0	66.4	70.8	79.6	88.4
3000				38.0	42.8	47.5	52.2	57.0	59.3	61.7	66.4	71.2	75.9	85.3	94.6
3200				40.5	45.6	50.7	55.7	60.8	63.3	65.8	70.8	75.9	80.9	90.9	100.9
3400				43.1	48.5	53.8	59.2	64.5	67.2	69.9	75.2	80.6	85.9	96.5	107.1
3600				45.6	51.3	57.0	62.7	68.3	71.2	74.0	79.6	85.3	90.9	102.1	113.3
3800					54.1	60.1	66.1	72.1	75.1	78.1	84.0	90.0	95.9	107.7	119.5
4000					57.0	63.3	69.6	75.9	79.0	82.1	88.4	94.6	100.9	113.3	125.6
4200					59.8	66.4	73.0	79.6	82.9	86.2	92.8	99.3	105.8	118.8	131.8
4400					62.7	69.6	76.5	83.4	86.8	90.3	97.1	104.0	110.8	124.4	137.9
4600					65.5	72.7	79.9	87.1	90.7	94.3	101.5	108.6	115.8	129.9	144.0
4800					68.3	75.9	83.4	90.9	94.6	98.4	105.8	113.3	120.7	135.4	150.0

* Endurance time will be reduced in ⬚ marked area. Please avoid if possible.

* Values in the table above are for nominal belt width 025(6.4mm). For other belt widths, those values should be multiplied by the width correction coefficient, Kb, shown in Table 29.

Table 34. Reference Transmission Capacity of XL Ps -Nominal Width of Belts 100 (25.4mm)- (kW)

No. of Teeth of Small Pulley	10	11	12	14	15	16	18	19	20	21	22	24	25	26	28	30
Rotary Speed of Small Pulley(rpm) / Diameter of the Pitch Circle(mm)	16.17	17.79	19.40	22.64	24.26	25.87	29.11	30.72	32.34	33.96	35.57	38.81	40.43	42.04	45.28	48.51
950	0.14	0.16	0.17	0.20	0.21	0.23	0.26	0.27	0.29	0.30	0.32	0.35	0.36	0.38	0.41	0.43
1160	0.17	0.19	0.21	0.25	0.26	0.28	0.32	0.33	0.35	0.37	0.39	0.42	0.44	0.46	0.50	0.53
1425			0.26	0.30	0.32	0.35	0.39	0.41	0.43	0.46	0.48	0.52	0.54	0.57	0.61	0.65
1750			0.32	0.37	0.40	0.43	0.48	0.51	0.53	0.56	0.59	0.64	0.67	0.69	0.75	0.80
2850			0.52	0.61	0.65	0.07	0.78	0.82	0.87	0.91	0.95	1.04	1.08	1.12	1.21	1.29
3450			0.63	0.74	0.79	0.84	0.94	1.00	1.05	1.10	1.15	1.25	1.30	1.35	1.45	1.55
100	0.01	0.01	0.01	0.02	0.02	0.02	0.02	0.02	0.03	0.03	0.03	0.03	0.03	0.04	0.04	0.04
200	0.03	0.03	0.03	0.04	0.04	0.04	0.05	0.05	0.06	0.06	0.06	0.07	0.07	0.08	0.08	0.09
300	0.04	0.05	0.05	0.06	0.06	0.07	0.08	0.08	0.09	0.09	0.10	0.11	0.11	0.12	0.12	0.13
400	0.06	0.06	0.07	0.08	0.09	0.09	0.11	0.11	0.12	0.12	0.13	0.14	0.15	0.16	0.17	0.18
500	0.07	0.08	0.09	0.10	0.11	0.12	0.13	0.14	0.15	0.16	0.16	0.18	0.19	0.20	0.21	0.23
600	0.09	0.10	0.11	0.12	0.13	0.14	0.16	0.17	0.18	0.19	0.20	0.22	0.23	0.24	0.25	0.27
700	0.10	0.11	0.12	0.15	0.16	0.17	0.19	0.20	0.21	0.22	0.23	0.25	0.27	0.28	0.30	0.32
800	0.12	0.13	0.14	0.17	0.18	0.19	0.22	0.23	0.24	0.25	0.27	0.29	0.30	0.32	0.34	0.37
900	0.13	0.15	0.16	0.19	0.20	0.22	0.25	0.26	0.27	0.29	0.30	0.33	0.34	0.36	0.38	0.41
1000	0.15	0.16	0.18	0.21	0.23	0.24	0.27	0.29	0.30	0.32	0.33	0.37	0.38	0.40	0.43	0.46
1100	0.16	0.18	0.20	0.23	0.25	0.27	0.30	0.32	0.33	0.35	0.37	0.40	0.42	0.44	0.47	0.50
1200	0.18	0.20	0.22	0.25	0.27	0.29	0.33	0.35	0.37	0.38	0.40	0.44	0.46	0.48	0.51	0.55
1300			0.24	0.28	0.30	0.32	0.36	0.38	0.40	0.42	0.44	0.48	0.50	0.52	0.56	0.59
1400			0.25	0.30	0.32	0.34	0.38	0.41	0.43	0.45	0.47	0.51	0.53	0.56	0.60	0.64
1500			0.27	0.32	0.34	0.37	0.41	0.43	0.46	0.48	0.50	0.55	0.57	0.59	0.64	0.69
1600			0.29	0.34	0.37	0.39	0.44	0.46	0.49	0.51	0.54	0.59	0.61	0.63	0.68	0.73
1700			0.31	0.36	0.39	0.41	0.47	0.49	0.52	0.54	0.57	0.62	0.65	0.67	0.73	0.78
1800			0.33	0.38	0.41	0.44	0.49	0.52	0.55	0.58	0.60	0.66	0.69	0.71	0.77	0.82
2000			0.37	0.43	0.46	0.49	0.55	0.58	0.61	0.64	0.67	0.73	0.76	0.79	0.85	0.91
2200			0.40	0.47	0.50	0.54	0.60	0.64	0.67	0.70	0.74	0.80	0.84	0.87	0.94	1.00
2400			0.44	0.51	0.55	0.59	0.66	0.70	0.73	0.77	0.80	0.88	0.91	0.95	1.02	1.09
2600			0.48	0.56	0.59	0.63	0.71	0.75	0.79	0.83	0.87	0.95	0.99	1.03	1.10	1.18
2800			0.51	0.60	0.64	0.68	0.77	0.81	0.85	0.89	0.94	1.02	1.06	1.10	1.19	1.27
3000			0.55	0.64	0.69	0.73	0.82	0.87	0.91	0.96	1.00	1.09	1.14	1.18	1.27	1.35
3200			0.59	0.68	0.73	0.78	0.88	0.92	0.97	1.02	1.07	1.16	1.21	1.26	1.35	1.44
3400			0.62	0.73	0.78	0.83	0.93	0.98	1.03	1.08	1.13	1.23	1.28	1.33	1.43	1.53
3600			0.66	0.77	0.82	0.88	0.98	1.04	1.09	1.14	1.20	1.30	1.35	1.41	1.51	1.61
3800					0.87	0.92	1.04	1.09	1.15	1.21	1.26	1.37	1.43	1.48	1.59	1.69
4000					0.91	0.97	1.09	1.15	1.21	1.27	1.33	1.44	1.50	1.55	1.67	1.78
4200					0.96	1.02	1.14	1.21	1.27	1.33	1.39	1.51	1.57	1.63	1.74	1.86
4400					1.00	1.07	1.20	1.26	1.33	1.39	1.45	1.58	1.64	1.70	1.82	1.94
4600					1.05	1.12	1.25	1.32	1.38	1.45	1.52	1.64	1.71	1.77	1.90	2.02
4800					1.09	1.16	1.30	1.37	1.44	1.51	1.58	1.71	1.78	1.84	1.97	2.10

* Endurance time will be reduced in ⬚ marked area. Please avoid if possible.

* Values in the table above are for nominal belt width 100(25.4mm). For other belt widths, those values should be multiplied by the width correction coefficient, Kb, shown in Table 29.

Table 35. Reference Transmission Capacity of L Ps -Nominal Width of Belts 100 (25.4mm)- (kW)

No. of Teeth of Small Pulley	12	14	15	16	18	19	20	21	22	24	25	26	28	30	32	36	40	48
Rotary Speed of Small Pulley(rpm) / Diameter of the Pitch Circle(mm)	36.38	42.45	45.48	48.51	54.57	57.61	60.64	63.67	66.70	72.77	75.80	78.83	84.89	90.96	97.02	109.15	121.28	145.53
725	0.33	0.39	0.42	0.44	0.50	0.53	0.56	0.58	0.61	0.67	0.70	0.72	0.78	0.83	0.89	1.00	1.11	1.33
870	0.40	0.47	0.50	0.53	0.60	0.63	0.67	0.70	0.73	0.80	0.83	0.87	0.93	1.00	1.07	1.20	1.33	1.59
950	0.44	0.51	0.55	0.58	0.66	0.69	0.73	0.77	0.80	0.87	0.91	0.95	1.02	1.09	1.16	1.31	1.45	1.73
1160	0.53	0.62	0.67	0.71	0.80	0.85	0.89	0.93	0.98	1.07	1.11	1.15	1.24	1.33	1.41	1.59	1.76	2.09
1425		0.77	0.82	0.87	0.98	1.04	1.09	1.14	1.20	1.31	1.36	1.41	1.52	1.62	1.73	1.93	2.13	2.52
1750		0.94	1.01	1.07	1.20	1.27	1.34	1.40	1.47	1.59	1.66	1.72	1.85	1.97	2.10	2.34	2.58	3.02
2850				1.73	1.93	2.03	2.13	2.23	2.33	2.52	2.62	2.71	2.89	3.07	3.24	3.56	3.84	4.31
3450				2.07	2.31	2.43	2.54	2.66	2.77	2.99	3.09	3.19	3.39	3.58	3.76	4.07	4.33	4.67
100	0.04	0.05	0.05	0.06	0.06	0.07	0.07	0.08	0.08	0.09	0.09	0.10	0.10	0.11	0.12	0.13	0.15	0.18
200	0.09	0.10	0.11	0.12	0.13	0.14	0.15	0.16	0.17	0.18	0.19	0.20	0.21	0.23	0.24	0.27	0.30	0.37
300	0.13	0.16	0.17	0.18	0.20	0.22	0.23	0.24	0.25	0.27	0.29	0.30	0.32	0.34	0.37	0.41	0.46	0.55
400	0.18	0.21	0.23	0.24	0.27	0.29	0.30	0.32	0.34	0.37	0.38	0.40	0.43	0.46	0.49	0.55	0.61	0.74
500	0.23	0.27	0.29	0.30	0.34	0.36	0.38	0.40	0.42	0.46	0.48	0.50	0.54	0.58	0.61	0.69	0.77	0.92
600	0.27	0.32	0.34	0.37	0.41	0.44	0.46	0.48	0.51	0.55	0.58	0.60	0.64	0.69	0.74	0.83	0.92	1.10
700	0.32	0.37	0.40	0.43	0.48	0.51	0.54	0.56	0.59	0.64	0.67	0.70	0.75	0.81	0.86	0.97	1.07	1.28
800	0.37	0.43	0.46	0.49	0.55	0.58	0.61	0.64	0.68	0.74	0.77	0.80	0.86	0.92	0.98	1.10	1.22	1.46
900	0.41	0.48	0.52	0.55	0.62	0.66	0.69	0.73	0.76	0.83	0.86	0.90	0.97	1.03	1.10	1.24	1.37	1.64
1000	0.46	0.54	0.58	0.61	0.69	0.73	0.77	0.81	0.84	0.92	0.96	1.00	1.07	1.15	1.22	1.37	1.52	1.81
1100	0.51	0.59	0.63	0.68	0.76	0.80	0.84	0.89	0.93	1.01	1.05	1.09	1.18	1.26	1.34	1.51	1.67	1.99
1200	0.55	0.64	0.69	0.74	0.83	0.87	0.92	0.97	1.01	1.10	1.15	1.19	1.28	1.37	1.46	1.64	1.81	2.15
1300		0.70	0.75	0.80	0.90	0.95	1.00	1.05	1.09	1.19	1.24	1.29	1.39	1.48	1.58	1.77	1.96	2.32
1400		0.75	0.81	0.86	0.97	1.02	1.07	1.12	1.18	1.28	1.34	1.39	1.49	1.59	1.70	1.90	2.10	2.48
1500		0.81	0.86	0.92	1.03	1.09	1.15	1.20	1.26	1.37	1.43	1.48	1.59	1.70	1.81	2.03	2.24	2.64
1600		0.86	0.92	0.98	1.10	1.16	1.22	1.28	1.34	1.46	1.52	1.58	1.70	1.81	1.93	2.15	2.38	2.80
1700		0.91	0.98	1.04	1.17	1.23	1.30	1.36	1.42	1.55	1.61	1.68	1.80	1.92	2.04	2.28	2.51	2.95
1800		0.97	1.03	1.10	1.24	1.31	1.37	1.44	1.51	1.64	1.70	1.77	1.90	2.03	2.15	2.40	2.64	3.10
1900				1.16	1.31	1.38	1.45	1.52	1.59	1.73	1.80	1.86	2.00	2.13	2.27	2.52	2.77	3.24
2000				1.22	1.37	1.45	1.52	1.59	1.67	1.81	1.89	1.96	2.10	2.24	2.38	2.64	2.90	3.38
2200				1.34	1.51	1.59	1.67	1.75	1.83	1.99	2.06	2.14	2.29	2.44	2.59	2.87	3.14	3.64
2400				1.46	1.64	1.73	1.81	1.90	1.99	2.15	2.24	2.32	2.48	2.64	2.80	3.10	3.38	3.87
2500				1.52	1.70	1.80	1.89	1.97	2.06	2.24	2.32	2.41	2.58	2.74	2.90	3.20	3.49	3.98
2600				1.58	1.77	1.86	1.96	2.05	2.14	2.32	2.41	2.50	2.67	2.84	3.00	3.31	3.59	4.09
2800				1.70	1.90	2.00	2.10	2.20	2.29	2.48	2.58	2.67	2.85	3.02	3.19	3.51	3.80	4.27
3000				1.81	2.03	2.13	2.24	2.34	2.44	2.64	2.74	2.84	3.02	3.20	3.38	3.70	3.98	4.43
3200				1.93	2.15	2.27	2.38	2.48	2.59	2.80	2.90	3.00	3.19	3.38	3.55	3.87	4.15	4.56
3400				2.04	2.28	2.40	2.51	2.62	2.73	2.95	3.05	3.16	3.35	3.54	3.72	4.04	4.30	4.65
3600				2.15	2.40	2.52	2.64	2.76	2.87	3.10	3.20	3.31	3.51	3.70	3.87	4.18	4.43	4.71
3800					2.52	2.65	2.77	2.89	3.01	3.24	3.35	3.45	3.66	3.84	4.02	4.31	4.54	4.73
4000					2.64	2.77	2.90	3.02	3.14	3.38	3.49	3.59	3.80	3.98	4.15	4.43	4.62	4.72
4200					2.76	2.89	3.02	3.15	3.27	3.51	3.62	3.73	3.93	4.11	4.27	4.53	4.69	4.66
4400					2.87	3.01	3.14	3.27	3.40	3.64	3.75	3.85	4.05	4.23	4.38	4.61	4.72	4.56
4600					2.99	3.13	3.26	3.39	3.52	3.76	3.87	3.97	4.17	4.33	4.48	4.67	4.73	4.42
4800					3.10	3.24	3.38	3.51	3.64	3.87	3.98	4.09	4.27	4.43	4.56	4.71	4.72	4.23

* Endurance time will be reduced in ⬚ marked area. Please avoid if possible.

* ▭ The circumferential speed of pulley is 33(m/s)or more; a dynamic balance for the pulley is essential.

* Values in the table above are for nominal belt width 100(25.4mm). For other belt widths, those values should be multiplied by the width correction coefficient, Kb, shown in Table 29.

Table 36. Reference Transmission Capacity of H Ps -Nominal Width of Belts 100 (25.4mm)- (kW)

No. of Teeth of Small Pulley	14	15	16	18	19	20	21	22	24	25	26	28	30	32	36	40	48
Rotary Speed of Small Pulley(rpm) / Diameter of the Pitch Circle(mm)	56.60	60.64	64.68	72.77	76.81	80.85	84.89	88.94	97.02	101.06	105.1	113.19	121.28	129.36	145.53	161.70	194.04
725	1.33	1.43	1.52	1.71	1.81	1.90	2.00	2.09	2.28	2.38	2.47	2.66	2.85	3.04	3.41	3.79	4.53
870	1.60	1.71	1.83	2.05	2.17	2.28	2.40	2.51	2.74	2.85	2.96	3.19	3.41	3.64	4.08	4.53	5.41
950			1.99	2.24	2.37	2.49	2.61	2.74	2.99	3.11	3.23	3.48	3.72	3.97	4.45	4.93	5.89
1160			2.43	2.74	2.89	3.04	3.19	3.34	3.64	3.79	3.94	4.23	4.53	4.82	5.41	5.99	7.12
1425				3.35	3.54	3.72	3.91	4.09	4.45	4.63	4.81	5.17	5.53	5.89	6.59	7.27	8.61
1750				4.11	4.33	4.55	4.78	5.00	5.44	5.66	5.87	6.31	6.73	7.16	7.98	8.79	10.32
2850						7.27	7.61	7.95	8.61	8.93	9.25	9.87	10.48	11.06	12.16	13.15	14.80
3450						8.68	9.07	9.45	10.19	10.55	10.91	11.59	12.24	12.85	13.95	14.87	16.09
100	0.18	0.19	0.21	0.23	0.25	0.26	0.27	0.28	0.31	0.32	0.34	0.36	0.39	0.42	0.47	0.52	0.63
200	0.36	0.39	0.42	0.47	0.50	0.52	0.55	0.57	0.63	0.65	0.68	0.73	0.79	0.84	0.94	1.05	1.26
300	0.55	0.59	0.63	0.71	0.75	0.79	0.83	0.86	0.94	0.98	1.02	1.10	1.18	1.26	1.42	1.57	1.89
400	0.73	0.79	0.84	0.94	1.00	1.05	1.10	1.15	1.26	1.31	1.36	1.47	1.57	1.68	1.89	2.10	2.52
500	0.92	0.98	1.05	1.18	1.25	1.31	1.38	1.44	1.57	1.64	1.71	1.84	1.97	2.10	2.36	2.62	3.14
600	1.10	1.18	1.26	1.42	1.50	1.57	1.65	1.73	1.89	1.97	2.05	2.20	2.36	2.52	2.83	3.14	3.76
700	1.29	1.38	1.47	1.65	1.75	1.84	1.93	2.02	2.20	2.30	2.39	2.57	2.75	2.93	3.30	3.66	4.38
800	1.47	1.57	1.68	1.89	1.99	2.10	2.20	2.31	2.52	2.62	2.73	2.93	3.14	3.35	3.76	4.17	4.99
900	1.65	1.77	1.89	2.13	2.24	2.36	2.48	2.60	2.83	2.95	3.06	3.30	3.53	3.76	4.22	4.68	5.59
1000			2.10	2.36	2.49	2.62	2.75	2.88	3.14	3.27	3.40	3.66	3.92	4.17	4.68	5.19	6.18
1100			2.31	2.60	2.74	2.88	3.02	3.17	3.45	3.59	3.74	4.02	4.30	4.58	5.14	5.69	6.77
1200			2.52	2.83	2.99	3.14	3.30	3.45	3.76	3.92	4.07	4.38	4.68	4.99	5.59	6.18	7.35
1300				3.06	3.23	3.40	3.57	3.74	4.07	4.24	4.40	4.73	5.06	5.39	6.03	6.67	7.91
1400				3.30	3.48	3.66	3.84	4.02	4.38	4.55	4.73	5.09	5.44	5.79	6.48	7.16	8.47
1500				3.53	3.72	3.92	4.11	4.30	4.68	4.87	5.06	5.44	5,81	6.18	6.91	7.63	9.01
1600				3.76	3.97	4.17	4.38	4.58	4.99	5.19	5.39	5.79	6.18	6.57	7.35	8.10	9.55
1700				3.99	4.21	4.43	4.64	4.86	5.29	5.50	5.71	6.13	6.55	6.96	7.77	8.56	10.07
1800				4.22	4.45	4.68	4.91	5.14	5.59	5.81	6.03	6.48	6.91	7.35	8.19	9.01	10.57
1900						4.93	5.17	5.41	5.89	6.12	6.35	6.82	7.27	7.73	8.61	9.46	11.06
2000						5.19	5.44	5.69	6.18	6.43	6.67	7.16	7.63	8.10	9.01	9.89	11.53
2100						5.44	5.70	5.96	6.48	6.73	6.99	7.49	7.98	8.47	9.41	10.32	11.99
2200						5.69	5.96	6.23	6.77	7.03	7.30	7.82	8.33	8.83	9.81	10.73	12.43
2300						5.94	6.22	6.50	7.06	7.33	7.61	8.15	8.68	9.19	10.19	11.14	12.85
2400						6.18	6.48	6.77	7.35	7.63	7.91	8.47	9.01	9.55	10.57	11.53	13.25
2500						6.43	6.73	7.03	7.63	7.93	8.22	8.79	9.35	9.89	10.94	11.91	13.63
2600						6.67	6.99	7.30	7.91	8.22	8.52	9.10	9.68	10.24	11.30	12.28	13.99
2800						7.16	7.49	7.82	8.47	8.79	9.10	9.72	10.32	10.90	11.99	12.99	14.65
3000						7.63	7.98	8.33	9.01	9.35	9.68	10.32	10.94	11.53	12.64	13.63	15.21
3200						8.10	8.47	8.83	9.55	9.89	10.24	10.90	11.53	12.14	13.25	14.22	15.67
3400						8.56	8.95	9.33	10.07	10.42	10.78	11.45	12.10	12.71	13.81	14.75	16.02
3600						9.01	9.41	9.81	10.57	10.94	11.30	11.99	12.64	13.25	14.33	15.21	16.26
3800								10.28	11.06	11.44	11.80	12.50	13.15	13.75	14.80	15.60	16.38
4000								10.73	11.53	11.91	12.28	12.99	13.63	14.22	15.21	15.92	16.37
4200								11.18	11.99	12.37	12.75	13.44	14.08	14.65	15.56	16.16	16.23
4400								11.61	12.43	12.81	13.19	13.87	14.49	15.03	15.86	16.31	15.94
4600								12.03	12.85	13.23	13.60	14.28	14.87	15.37	16.09	16.39	15.51
4800								12.43	13.25	13.63	13.99	14.65	15.21	15.67	16.26	16.37	14.93

* Endurance time will be reduced in ⬚ marked area. Please avoid if possible.

* ▭ The circumferential speed of pulley is 33(m/s)or more; a dynamic balance for the pulley is essential.

* Values in the table above are for nominal belt width 100(25.4mm). For other belt widths, those values should be multiplied by the width correction coefficient, Kb, shown in Table 29.