[Technical Data]
Selection of Transmission Timing Belts 3

Selection is easy with Timing Pulleys and Belts automatic calculation tool available at:
http://fawos.misumi.jp/FA_WEB/pulley_sea/

[Step 3] Temporarily Selecting the Type of Belt from Selection Guide Table

Table 19. Selection Guide Table 1 (MXL,XL,L,H,T5,T10)




Table 20. Selection Guide Table 2 (S_M series)




Table 21. Selection Guide Table 3 (P_M series)




Table 22. Selection Guide Table 4 (MTS8M)




Table 23. Selection Guide Table 5 (UP_M series)




Table 24. Selection Guide Table (2GT·3GT series)





Table 25. Selection Guide Table (EV5GT·EV8YU series)



[Step 4] Determining Number of Teeth of Large and Small Pulley, Belt Length, Inter-Shaft Distance

(1) Select the number of teeth of large and small pulley from **P.2261~2271**, which can satisfy the predeterminated speed ratio.
(However, select the small pulley with number of teeth more than Min. Number of Teeth on Table 26.)

$$\text{Speed Ratio} = \frac{\text{Number of Teeth of Large Pulley}}{\text{Number of Teeth of Small Pulley}}$$

Table 26. Allowable min. number of teeth

Rotary Speed of Small Pulley (rpm)	Type of Belt, Minimum Number of Teeth																					
	MXL	XL	L	H	S2M	S3M	S5M	S8M	S14M	P2M	P3M	P5M	P8M	UP5M	UP8M	MTS8M	T5	T10	2GT	3GT	EV5GT	EV8YU
900 or Less	12	11	14	16	16	16	16	24	–	14	14	18	22	18	22	24	12	16	12	14	18	26
Over 900 1200 or Less	15	11	14	18	16	16	20	25	40	14	14	20	24	20	24	24	14	18	14	14	20	28
Over 1200 1800 or Less	15	12	16	20	18	18	24	28	48	14	14	24	26	24	26	26	16	20	16	16	24	32
Over 1800 3600 or Less	16	16	19	24	20	20	24	30	–	16	18	28	28	28	28	28	18	22	18	20	28	36
Over 3600 4800 or Less	–	16	20	24	20	20	24	32	–	18	20	30	30	30	30	28	18	22	20	20	30	–
Over 4800 10000 or Less	–	–	–	–	20	20	26	–	–	20	28	40	–	40	–	–	–	–	–	–	–	–

(2) Determine approx. belt circum. length (Lp') in terms of temporary inter-shaft distance (C'), diameter of large pulley (Dp) and diameter of small pulley (dp).
(Calculate pulley diameter with P.D. dimensions.)

$$Lp' = 2C' + \frac{\pi(Dp+dp)}{2} + \frac{(Dp-dp)^2}{4C'}$$

C' : Temporary Inter-shaft Distance
dp : Pitch Diameter of Small Pulley (mm)
Dp : Pitch Diameter of Large Pulley (mm)
Lp' : Approx. Belt Circum. Length (mm)

(3) Determine a belt circum. length (Lp') that is the nearest value to approx. belt circum. length referring to **P.1459~1470**, and then calculate the correct inter-shaft distance using the following formula.

$$C = \frac{b + \sqrt{b^2 - 8(Dp-dp)^2}}{8}$$

$$b = 2Lp - \pi(Dp+dp)$$

Dp : Pitch Diameter of Large Pulley (mm)
dp : Pitch Diameter of Small Pulley (mm)
Lp : Belt Circum. Length (mm)
C : Inter-shaft Distance

[Step 5] Determining Belt Width

(1)Calculate an approx. belt width using the following formula, and then select a belt width (Bw':mm) that is the nearest value to the approximated value.

$$Bw' = \frac{Pd}{Ps \cdot Km} \times Wp$$

Pd: Design Power
Ps: Reference Transmission Capacity……Use the Reference Transmission Capacity Table on **P.2261~2271.**
Km: Engagement Correction Coefficient (Table 27)
Wp: Reference Belt Width (Table 28)

Table 27. Engagement Correction Coefficient (Km)

No. of Teeth Engaged Zm	More than 6	5	4	3	2
Km	1.0	0.8	0.6	0.4	0.2
*Km	1.0	0.7	0.5	-	-

$$\text{No. of Teeth Engaged (Zm)} = \frac{Zd \cdot \theta}{360°}$$

$$\theta = 180° - \frac{57.3(Dp-dp)}{C}$$

Zd: No.of Teeth of Small Pulley
θ : Contact Angle (°)
Dp: Pitch Diameter of Large Pulley (mm)
dp: Pitch Diameter of Small Pulley (mm)
C:Inter-shaft Distance (mm)

Table 28. Reference Belt Width (Wp)

Type of Belt	MXL	XL	L	H	S2M	S3M	S5M	S8M	S14M	MTS8M
Reference Belt Width	6.4	25.4	25.4	25.4	4	6	10	60	120	60

Type of Belt	P2M	P3M	P5M	P8M	T5	T10
Reference Belt Width	4	6	10	15	10	10

(2)Check if Design Power (Pd) satisfies the following formula. (If not, select the belt width of one size larger again.)
For belt types P□M and UP□M, substitute *Km for meshing compensation factor

· Pd<Ps · Km · Kb
■2GT · 3GT · EV5GT · EV8YU
· Pd<Ps · Km · Kb · KL

Pd : Design Power
Ps : Reference Transmission Capacity
Km : Engagement Correction Coefficient
Kb : Width Correction Coefficient (Table 29)
KL : Length Correction Coefficient (Table 30)

Table 29. Width Correction Coefficient (Kb)

Type of Belt	Belt Width Nominal	Belt Width mm	Width Correction Coefficient Kb
MXL	019	4.8	0.72
	025	6.4	1.00
	037	9.5	1.57
	050	12.7	2.18
XL	025	6.4	0.15
	031	7.9	0.21
	037	9.5	0.28
	050	12.7	0.42
L	050	12.7	0.42
	075	19.1	0.71
	100	25.4	1.00
	150	38.1	1.56
H	075	19.1	0.71
	100	25.4	1.00
	150	38.1	1.56
	200	50.8	2.14

Type of Belt	Belt Width Nominal	Belt Width mm	Width Correction Coefficient Kb
S2M	040	4	1.00
	060	6	1.59
	100	10	2.84
S3M	060	6	1.00
	100	10	1.79
	150	15	2.84
S5M	100	10	1.00
	150	15	1.59
	250	25	2.84
S8M MTS8M	150	15	0.21
	250	25	0.37
	300	30	0.45
	400	40	0.63
S14M	400	40	0.29
	600	60	0.45

Type of Belt	Belt Width Nominal	Belt Width mm	Width Correction Coefficient Kb
P2M	040	4	1.00
	060	6	1.59
P3M	100	10	1.78
	150	15	2.84
P5M	100	10	1.00
	150	15	1.59
P8M	150	15	1.00
	250	25	1.79
T5	100	10	1.00
	150	15	1.60
	200	20	2.30
	250	25	2.90
T10	150	15	1.60
	200	20	2.30
	250	25	2.90
	300	30	3.50
	400	40	4.60
	500	50	5.80

Type of Belt	Belt Width Nominal	Belt Width mm	Width Correction Coefficient Kb
2GT	4	4	1.00
	6	6	1.67
	9	9	2.67
3GT	6	6	1.00
	9	9	1.66
	15	15	2.97
EV5GT	9	9	0.53
	12	12	0.76
	15	15	1.00
EV8YU	15	15	0.71
	20	20	1.00
	25	25	1.29

Table 30. Length Correction Coefficient(KL)

Length Correction Coefficient(KL)	0.80	0.90	1.00	1.10	1.20
2GT Belt Length(mm)	130 or less	131~182	183~280	281~419	420 or less
3GT Belt Length(mm)	190 or less	191~260	261~400	401~599	600 or less
EV5GT Belt Length(mm)	440 or less	441~550	551~800	801~1100	1001 or less
EV8YU Belt Length(mm)	600 or less	601~900	901~1250	1251~1799	1800 or less