

Master on Artificial Intelligence

Natural
Language
Research
Group

Constituency
parsing with
NLTK

Dependency
parsing with
NLTK

Introduction to Human Language Technologies 8. Parsing

Natural Language Research Group



UNIVERSITAT POLITÈCNICA DE CATALUNYA
BARCELONATECH

Facultat d'Informàtica de Barcelona



Course 2018/19

Outline

Natural
Language
Research
Group

Constituency
parsing with
NLTK

Dependency
parsing with
NLTK

1 Constituency parsing with NLTK

- Non-probabilistic parsers
- Mandatory Exercise
- Probabilistic parsers

2 Dependency parsing with NLTK

- CoreNLP
- Paraphrases

Constituency parsing with NLTK

Non-probabilistic parsers:

- ChartParser (default parser is BottomUpLeftCornerChartParser)
- BottomUpChartParser, LeftCornerChartParser
- TopDownChartParser, EarleyChartParser
- ...

Probabilistic parsers:

- InsideChartParser, RandomChartParser, LongestChartParser (they are bottom-up parsers)
- ViterbiParser
- CoreNLPParser (third-party's parser)
- ...

Non-probabilistic parsers: Charts

Example:

```
In [1]: 1 import nltk
        2 from nltk import CFG, ChartParser
        3
        4 grammar = CFG.fromstring('''
        5     NP -> NNS | JJ NNS | NP CC NP
        6     NNS -> "cats" | "dogs" | "mice" | NNS CC NNS
        7     JJ -> "big" | "small"
        8     CC -> "and" | "or"
        9     ''')
       10
       11 sent = ['small', 'cats', 'and', 'mice']
       12
       13 parser = ChartParser(grammar)
       14 parse = parser.parse(sent)
```

```
In [2]: 1 ts = []
        2 for t in parse:
        3     ts.append(t)
        4 print('number of trees:', len(ts))
```

number of trees: 2


Non-probabilistic parsers: Charts

Output 1:

```
In [3]: print(ts[0])  
ts[0]
```

```
(NP (JJ small) (NNS (NNS cats) (CC and) (NNS mice)))
```


Out[3]:



```
In [4]: print(ts[1])  
ts[1]
```

```
(NP (NP (JJ small) (NNS cats)) (CC and) (NP (NNS mice)))
```

Out[4]:



Non-probabilistic parsers: Charts

Output II:

```
In [5]: # achieve the list of applied edges
parse = parser.chart_parse(['small', 'cats', 'and', 'mice'])
print("TD num edges = ", parse.num_edges())
```

TD num edges = 28

```
In [6]: parse.edges()
```

```
Out[6]: [[Edge: [0:1] 'small'],
[Edge: [1:2] 'cats'],
[Edge: [2:3] 'and'],
[Edge: [3:4] 'mice'],
[Edge: [0:1] JJ -> 'small' *],
[Edge: [0:1] NP -> JJ * NNS],
[Edge: [1:2] NNS -> 'cats' *],
[Edge: [1:2] NP -> NNS *],
[Edge: [1:2] NNS -> NNS * CC NNS],
[Edge: [0:2] NP -> JJ NNS *],
[Edge: [0:2] NP -> NP * CC NP],
[Edge: [1:2] NP -> NP * CC NP],
[Edge: [2:3] CC -> 'and' *],
[Edge: [1:3] NNS -> NNS CC * NNS],
[Edge: [0:3] NP -> NP CC * NP],
[Edge: [1:3] NP -> NP CC * NP],
[Edge: [3:4] NNS -> 'mice' *],
[Edge: [3:4] NP -> NNS *],
[Edge: [3:4] NNS -> NNS * CC NNS]]
```

Non-probabilistic parsers: Charts

Main differences of non-probabilistic chart parsers:

- BottomUpChartParser: bottom-up strategy
- BottomUpLeftCornerChartParser (ChartParser): bottom-up strategy filtering out edges without any word subsumtion (e.g., [0,0]: $X \rightarrow \cdot Y Z$)
- LeftCornerChartParser: bottom-up strategy filtering out edges without new word subsumptions (e.g., if we already got [0,1] $Y \rightarrow y.$ and [1,2] $Z \rightarrow z.$ then [0,1] $A \rightarrow Y.Z$ is filtered out whereas [0,2] $A \rightarrow Y Z.$ is fired)
- TopDownChartParser: top-down strategy
- EarleyChartParser: incremental top-down strategy (more efficient)

```
In [7]: 1 from nltk import TopDownChartParser
        2
        3 parser = nltk.TopDownChartParser(grammar)
        4 parse = parser.parse(sent)
```

Mandatory Exercise

Statement:

- Consider the following sentence: *Lazy cats play with mice.*
- Expand the grammar of the example related to non-probabilistic chart parsers in order to subsume this new sentence.
- Perform the constituency parsing using a BottomUpChartParser, a BottomUpLeftCornerChartParser and a LeftCornerChartParser.
- For each one of them, provide the resulting tree, the number of edges and the list of explored edges.
- Which parser is the most efficient for parsing the sentence?
- Which edges are filtered out by each parser and why?

Probabilistic parsers: Charts

Natural
Language
Research
Group

Constituency
parsing with
NLTK

Probabilistic
parsers

Dependency
parsing with
NLTK

Example: inside chart parser

```
In [1]: 1 import nltk
2 from nltk.parse.pchart import PCFG, InsideChartParser
3
4 grammar = PCFG.fromstring('''
5     NP -> NNS [0.5] | JJ NNS [0.3] | NP CC NP [0.2]
6     NNS -> "cats" [0.1] | "dogs" [0.2] | "mice" [0.3] | NNS CC NNS [0.4]
7     JJ -> "big" [0.4] | "small" [0.6]
8     CC -> "and" [0.9] | "or" [0.1]
9     ''')
10
11 sent = ['small', 'cats', 'and', 'mice']
12
13 parser = InsideChartParser(grammar)
14 parse = parser.parse(sent)
```

```
In [2]: 1 ts = []
2 for t in parse:
3     ts.append(t)
4 print('number of trees:', len(ts))
```

number of trees: 2


Probabilistic parsers: Charts

Output:

```
In [3]: 1 print(ts[0])  
        2 ts[0]
```

(NP (JJ small) (NNS (NNS cats) (CC and) (NNS mice))) (p=0.001944)


Out[3]:



```
In [4]: 1 print(ts[1])  
        2 ts[1]
```

(NP (NP (JJ small) (NNS cats)) (CC and) (NP (NNS mice))) (p=0.000486)

Out[4]:



Probabilistic parsers: Charts

Natural
Language
Research
Group

Constituency
parsing with
NLTK

Probabilistic
parsers

Dependency
parsing with
NLTK

Main differences of probabilistic chart parsers:

- They use the bottom-up strategy
- InsideChartParser: select edges in decreasing order of their trees' inside probs. $p \rightarrow A, B \Rightarrow \text{Prob} = P(p)P(A)P(B)$
- RandomChartParser: select edges in random order.
- LongestChartParser: select longer edges before shorter ones.

Probabilistic parsers: Viterbi

Example: Probabilistic Viterbi parser


```
In [1]: 1 import nltk
        2 from nltk import PCFG, ViterbiParser
        3
        4 grammar = PCFG.fromstring('''
        5     NP -> NNS [0.5] | JJ NNS [0.3] | NP CC NP [0.2]
        6     NNS -> "cats" [0.1] | "dogs" [0.2] | "mice" [0.3] | NNS CC NNS [0.4]
        7     JJ -> "big" [0.4] | "small" [0.6]
        8     CC -> "and" [0.9] | "or" [0.1]
        9     ''')
       10
       11 sent = ['small', 'cats', 'and', 'mice']
       12
       13 parser = ViterbiParser(grammar)
       14 parse = parser.parse(sent)
```

Output:

```
In [2]: 1 tree = next(parse)
        2 print(tree)
        3 tree
```

(NP (JJ small) (NNS (NNS cats) (CC and) (NNS mice))) (p=0.001944)

Out[2]:



Probabilistic parsers: Viterbi

Trace:

```
In [3]: 1 parser = ViterbiParser(grammar)
        2 parser.trace(3)
        3 parse = parser.parse(sent)
        4 next(parse)
```

Inserting tokens into the most likely constituents table...

Insert: |=...| small

Insert: |.=...| cats

Insert: |..=...| and

Insert: |...=...| mice

Finding the most likely constituents spanning 1 text elements...

Insert: |=...| JJ -> 'small' [0.6] 0.6000000000

Insert: |.=...| NNS -> 'cats' [0.1] 0.1000000000

Insert: |.=...| NP -> NNS [0.5] 0.0500000000

Insert: |..=...| CC -> 'and' [0.9] 0.9000000000

Insert: |...=...| NNS -> 'mice' [0.3] 0.3000000000

Insert: |...=...| NP -> NNS [0.5] 0.1500000000

Finding the most likely constituents spanning 2 text elements...

Insert: |=...| NP -> JJ NNS [0.3] 0.0180000000

Finding the most likely constituents spanning 3 text elements...

Insert: |.===...| NP -> NP CC NP [0.2] 0.0013500000

Insert: |.===...| NNS -> NNS CC NNS [0.4] 0.0108000000

Insert: |.===...| NP -> NNS [0.5] 0.0054000000

Discard: |.===...| NP -> NP CC NP [0.2] 0.0013500000

Discard: |.===...| NP -> NP CC NP [0.2] 0.0013500000

Finding the most likely constituents spanning 4 text elements...

Insert: |====...| NP -> JJ NNS [0.3] 0.0019440000

Discard: |====...| NP -> NP CC NP [0.2] 0.0004860000

Discard: |====...| NP -> NP CC NP [0.2] 0.0004860000

Probabilistic parsers: learn a PCFG

Natural
Language
Research
Group

Example: learn a treebank grammar

```
In [4]: 1 import nltk
        2 from nltk.corpus import treebank
        3 productions = []
        4 S = nltk.Nonterminal('S')
        5 for f in treebank.fileids():
        6     for tree in treebank.parsed_sents(f):
        7         productions += tree.productions()
        8 grammar = nltk.induce_pcfg(S, productions)
        9 grammar.productions()[10:15]
```

```
Out[4]: [NN -> 'evil' [7.59532e-05],
         NN -> 'powder' [7.59532e-05],
         SBAR -> WHNP-167 S [0.000424628],
         VBN -> 'drawn' [0.00140581],
         NN -> 'senior' [0.000151906]]
```

Constituency
parsing with
NLTK

Probabilistic
parsers

Dependency
parsing with
NLTK


Probabilistic parsers: learn a PCFG

Example: apply the learnt PCFG to Viterbi parser

```
In [5]: sent = ['it', 'is', 'a', 'small', 'group', 'of', 'workers', 'and', 'researchers']
parser = ViterbiParser(grammar)
parse = parser.parse(sent)
tree = next(parse)
print(tree)
tree
```

```
(S
 (NP-SBJ (PRP it))
 (VP
  (VBZ is)
  (NP-PRD
   (NP (DT a) (JJ small) (NN group))
   (PP
    (IN of)
    (NP (NNS workers) (CC and) (NNS researchers)))))) (p=2.64379e-21)
```

Out[5]:




Probabilistic parsers: CoreNLP parser

Example:

```
In [6]: # run in a shell:
# java -mx4g -cp "*" edu.stanford.nlp.pipeline.StanfordCoreNLPServer -port 9000 -timeout 15000
import nltk
from nltk.parse.corenlp import CoreNLPParser
parser = CoreNLPParser(url='http://localhost:9000')
parse = parser.raw_parse('Smith jumps over lazy dogs')
tree = next(parse)
print(tree)
tree
```

```
(ROOT
 (S
  (NP (NNP Smith))
  (VP (VBZ jumps) (PP (IN over) (NP (JJ lazy) (NNS dogs))))))
```

Out[6]:



Outline

Natural
Language
Research
Group

Constituency
parsing with
NLTK

Dependency
parsing with
NLTK

1 Constituency parsing with NLTK

- Non-probabilistic parsers
- Mandatory Exercise
- Probabilistic parsers

2 Dependency parsing with NLTK

- CoreNLP
- Paraphrases

Dependency parsing: CoreNLP dependency parser

Natural
Language
Research
Group

Constituency
parsing with
NLTK

Dependency
parsing with
NLTK

CoreNLP

Example:

```
In [1]: 1 import nltk
        2 from nltk.parse.corenlp import CoreNLPDependencyParser
        3
        4 parser = CoreNLPDependencyParser(url='http://localhost:9000')
        5 parse = parser.raw_parse('Smith jumps over the lazy dog')
```

```
In [2]: 1 tree = next(parse)
        2 for t in tree.triples():
        3     print(t)


(('jumps', 'VBZ'), 'nsubj', ('Smith', 'NNP'))
(('jumps', 'VBZ'), 'nmod', ('dog', 'NN'))
(('dog', 'NN'), 'case', ('over', 'IN'))
(('dog', 'NN'), 'det', ('the', 'DT'))
(('dog', 'NN'), 'amod', ('lazy', 'JJ'))
```

Dependency parsing: CoreNLP dependency parser

Showing the graph:

```
In [3]: 1 # Graphviz is needed  
2 # sudo pip3 install graphviz  
3 tree
```

Out[3]:



Mandatory exercise

Natural
Language
Research
Group

Constituency
parsing with
NLTK

Dependency
parsing with
NLTK
Paraphrases

Statement:

- 1 Read all pairs of sentences of the trial set within the evaluation framework of the project.
- 2 Compute the Jaccard similarity of each pair using the dependency triples from *CoreNLPPependencyParser*.
- 3 Show the results. Do you think it could be relevant to use NEs to compute the similarity between two sentences? Justify the answer.