



# Map-making strategies for next generation CMB polarization experiments

Simon Biquard<sup>1</sup>

<sup>1</sup>AstroParticule et Cosmologie, Paris, France



## Introduction

*Map-making* is the reconstruction of the observed sky from the time-ordered data (TOD) collected by a telescope. It compresses the volume of data by many orders of magnitude, while trying to preserve cosmological information.

In the quest for B-mode polarization of the CMB, modern experiments are lining up tens, even hundreds of thousands of detectors to extract the primordial signal. As a result, the size of the TOD is increasing to an unprecedented volume, challenging our ability to analyze it correctly and efficiently.

	Polarbear	SO	CMB-S4
Data volume	100 TB	2 PB	50 PB
CPU hours	20 k	35 M	500 M

Table 1. Data volume and current CPU time needed to produce *one* sky map.

## Quick review of map-making flavors

### Data model and estimators

$$\mathbf{d} = \mathbf{P}\mathbf{s} + \mathbf{n} \quad (1)$$

This is the usual assumed data model for the map-making problem.

- $\mathbf{d}$  = TOD (calibrated)
- $\mathbf{P}$  = pointing matrix, encodes scanning and orientation of the telescope
- $\mathbf{s}$  = true sky map
- $\mathbf{n}$  = noise vector

Map-making is just a *linear operation*,  $\mathbf{m} = \mathbf{L}\mathbf{d}$ , mapping the TOD to an estimator  $\mathbf{m}$  of the true sky map.

Method	Operator $\mathbf{L}$	Pros	Cons
Binning	$\left(\mathbf{P}^T \mathbf{\Lambda} \mathbf{P}\right)^{-1} \mathbf{P}^T \mathbf{\Lambda}$	unbiased, cheap	complex noise
GLS	$\left(\mathbf{P}^T \mathbf{C}_n^{-1} \mathbf{P}\right)^{-1} \mathbf{P}^T \mathbf{C}_n^{-1}$	unbiased, min. variance	expensive
Filter-and-bin	$\left(\mathbf{P}^T \mathbf{\Lambda} \mathbf{P}\right)^{-1} \mathbf{P}^T \mathbf{F}$	easy to compute	biased
Templates	$\left(\mathbf{P}^T \mathbf{F} \mathbf{P}\right)^{-1} \mathbf{P}^T \mathbf{F}$	unbiased filtering	iterative

Table 2. Comparison of different map-making approaches. Legend:  $\mathbf{\Lambda}$  = diagonal noise weights;  $\mathbf{C}_n^{-1}$  = noise covariance matrix;  $\mathbf{F}$  = filtering and weighting operator.

### Observing from the ground

Ground-based experiments have to deal with two specific contaminants which are very bright compared to the CMB:

- *atmospheric signal*, a major source of noise correlations
- *ground pickup*, typically due to the far side-lobes of the beam

Those contaminants are largely unpolarized, which motivates the **pair differencing** approach, where the timestreams of two orthogonal detectors are subtracted in order to eliminate non polarized signals.

## Evaluation of the pair differencing approach

I use the map-making library **mappraiser**[1] to process simulations produced with the **TOAST** software:

- instrument: SO-SAT @ 90 GHz
- schedule: one day per month during one year
- sky: CMB lensed scalar anisotropies (from Planck FFP10 simulations)
- high-resolution atmosphere simulation
- instrumental noise
- gain errors in detector pairs
- in the future: elliptical beams

Figure of merit ?

## Results: gain errors

### Numerical advantages of pair differencing

Reduce noise correlations...

### Conclusion / Discussion ?

In what conditions is pair differencing reasonable to use ? What do we lose ? What do we gain ?

## References

[1] Hamza El Bouhargani, Aygul Jamal, Dominic Beck, Josquin Errard, Laura Grigori, and Radek Stompork. MAPPRaiser: A massively parallel map-making framework for multi-kilo pixel CMB experiments. *Astronomy and Computing*, 39:100576, April 2022.