

BPHO ROUND 0 · MARKSCHEME

Drill bank section 2

25 questions · 60 minutes · single answer, 5 options · **no calculator** · no negative marking*Original questions written for this course, in the Round 0 format. Not BPhO material.*

Quick key

Q1 C	Q2 A	Q3 E	Q4 B	Q5 D
Q6 E	Q7 A	Q8 A	Q9 C	Q10 B
Q11 C	Q12 B	Q13 B	Q14 E	Q15 D
Q16 B	Q17 C	Q18 C	Q19 A	Q20 C
Q21 D	Q22 B	Q23 B	Q24 C	Q25 D

Worked solutions

Q1 · Dimensional analysis: the speed of a capillary ripple — **Answer C**

What is being tested. Whether you can turn a physical statement into three simultaneous equations and solve them, without knowing or remembering any formula for a ripple. Everything needed is in the question.

Step 1 — write down the dimensions. Read them off the units rather than trying to recall them:

$$\begin{aligned}
 [v] &= L \, T^{-1} \\
 [\gamma] &= N \, m^{-1} = M \, T^{-2} \\
 [\rho] &= M \, L^{-3} \\
 [\lambda] &= L
 \end{aligned}$$

The surface tension is the only awkward one. A newton is $kg \, m \, s^{-2}$, so a newton per metre is $kg \, m \, s^{-2} / m = kg \, s^{-2}$: mass to the first power, time to the minus two, and no length at all.

Step 2 — propose the form and match. Assume the answer is a product of powers, $v = k \, \gamma^a \, \rho^b \, \lambda^c$, with k a dimensionless number that dimensional analysis cannot find. Match each base dimension in turn:

$$\begin{aligned}
 \text{mass:} & \quad a + b = 0 \\
 \text{length:} & \quad -3b + c = 1 \\
 \text{time:} & \quad -2a = -1
 \end{aligned}$$

Step 3 — the time equation alone fixes a. $-2a = -1$ gives $a = 1/2$. That is the whole reason a square root appears, and it is forced by the time dimension: only surface tension carries time, and it carries it as T^{-2} .

Step 4 — mass, then length. From $a + b = 0$, $b = -1/2$: the speed goes *down* as the water gets denser, which is what a heavy liquid ought to do. Substituting into the length equation, $-3(-1/2) + c = 1$, so $c = 1 - 3/2 = -1/2$. The exponent on wavelength is negative.

Step 5 — assemble.

$$\begin{aligned} v &= k \gamma^{1/2} \rho^{-1/2} \lambda^{-1/2} \\ &= k \sqrt{\gamma / (\rho \lambda)} \end{aligned}$$

So **Answer: C**. The $1/2$ powers are not decoration: they are what the three equations produce, and a solution without a square root is already suspicious.

The distractors.

- $\sqrt{(\gamma\rho/\lambda)}$ divides by the density where it should multiply, i.e. takes $b = +1/2$. That contradicts the mass equation, which is $a + b = 0$ and not $a - b = 0$.
- $\sqrt{(\gamma\lambda/\rho)}$ is right on mass and time but takes $c = +1/2$, the wrong sign on the wavelength. It is the most tempting wrong answer because it has the right shape — a root, and λ on top.
- $v/(\rho\lambda)$ has all three exponents right and no square root. It fails on inspection: surface tension is kg s^{-2} and density times wavelength is kg m^{-2} , so this combination is $\text{m}^2 \text{s}^{-2}$ — a squared speed, not a speed.
- $\sqrt{(\gamma\rho)}/\lambda$ takes the root and then divides by the wavelength as well, which makes the length exponent $-3/2$ instead of $-1/2$.

The trap. Reaching for a remembered formula. There is no need to know anything about ripples: the three equations are forced by the dimensions, and the only freedom left over is the dimensionless constant k , which is exactly the part dimensional analysis is allowed not to know.

Relevant topics: base and derived units; the dimensions of mechanical quantities; simultaneous equations in three unknowns; the limits of dimensional analysis.

The trap. Hunting for a remembered ripple formula. The exponents are forced by the dimensions, so the only thing you cannot derive is the dimensionless constant in front.

Q2 · An endless resistor ladder: resistance between the input terminals — **Answer A**

What is being tested. Whether you spot that an endless network is unchanged when you add a section to it. Once you see that, the problem is one equation; without it, there is nothing to write down at all.

Step 1 — the self-similarity. Call the resistance of the whole endless ladder R_{eq} . Now look at what the ladder is made of: a resistor R in series with a branch that has a resistor R in parallel with *the rest of the ladder*. But the rest of the ladder is the same endless ladder, so its resistance is also R_{eq} . The network contains itself.

Step 2 — write the fixed-point relation.

$$R_{\text{eq}} = R + (R \times R_{\text{eq}})/(R + R_{\text{eq}})$$

The first term is the series resistor. The second is R in parallel with R_{eq} , which is **product over sum**.

Step 3 — clear the fraction. Multiply through by $R + R_{eq}$:

$$\begin{aligned} R_{eq}(R + R_{eq}) &= R(R + R_{eq}) + R R_{eq} \\ R R_{eq} + R_{eq}^2 &= R^2 + R R_{eq} + R R_{eq} \\ R_{eq}^2 - R R_{eq} - R^2 &= 0 \end{aligned}$$

The $R R_{eq}$ terms do not cancel on the right — there are two of them, and only one on the left.

Step 4 — solve and choose the root.

$$\begin{aligned} R_{eq} &= (R \pm \sqrt{R^2 + 4R^2})/2 \\ &= R(1 \pm \sqrt{5})/2 \end{aligned}$$

So **Answer: A**, $R(1 + \sqrt{5})/2$, which is about $1.618R$. The minus root is $-0.618R$, a negative resistance, which no passive network can have; that is the physics choosing between the two roots for you.

Step 5 — check the size of the answer. It must exceed R (there is a resistor in series) and must be less than $2R$ (the parallel branch is smaller than the R in it). $1.618R$ sits between the two, and $\sqrt{5}$ is about 2.24 , so 1.618 is right. This one sanity check removes three of the five options.

The distractors.

- $R(1 + \sqrt{3})$ comes from $R_{eq}^2 - 2R R_{eq} - 2R^2 = 0$, i.e. doubling the linear term. It appears if you treat the parallel branch as R in parallel with $2R_{eq}$.
- $2R$ assumes an endless chain has endless resistance. It does not: each added section is in parallel with everything after it, so the total is pulled back down. The answer is finite, and less than $2R$.
- $R\sqrt{2}$ is the geometric mean of R and $2R$. It looks plausible and is about $1.414R$, which is inside the allowed range, so the range check alone does not kill it — the algebra does.
- $R(3 + \sqrt{5})/2$ is $2.618R$, the larger root of the *other* quadratic. It is greater than $2R$, so the range check rejects it immediately.

The trap. Trying to add up infinitely many sections. The sum does not converge term by term in any convenient way; the fixed-point argument is what makes the problem finite. Whenever a structure repeats endlessly, ask what stays the same when you add one more copy.

Relevant topics: series and parallel combinations; self-similar networks; quadratic equations; choosing the root with physical meaning.

The trap. Trying to sum the sections one at a time. The endless ladder is a fixed point of the relation 'one more section', and that is the only route to a finite equation.

Q3 · Photoelectric effect: kinetic energy from a threshold wavelength — **Answer E**

What is being tested. Whether you know what a threshold wavelength *is*, rather than treating it as another number to plug into a subtraction.

Step 1 — turn both wavelengths into energies. For photons, $E = hc/\lambda$. The product hc is the one worth remembering, because it is the same for every photon problem. For the record, and never as a step you have to perform:

$$\begin{aligned}
 hc &= 6.63 \times 10^{-34} \times 3.0 \times 10^8 \\
 &= 1.99 \times 10^{-25} \text{ J m} \\
 &= 1240 \text{ eV nm}
 \end{aligned}$$

The last form is the useful one: it lets you work in electron volts and nanometres with no unit conversion at all. Both numbers in the question are already in those units.

Step 2 — the work function. The threshold wavelength is the *longest* wavelength that still ejects an electron. At that wavelength the electron comes off with no kinetic energy at all, so the photon energy equals the work function exactly:

$$W = hc/620 \text{ nm} = 1240/620 = 2.0 \text{ eV}$$

Step 3 — Einstein's equation. Energy is conserved: the photon gives up its energy, part goes to escape the surface and the rest becomes kinetic energy.

$$\begin{aligned}
 K_{\text{max}} &= hc/310 \text{ nm} - W \\
 &= 1240/310 - 2.0 \\
 &= 4.0 - 2.0 \\
 &= 2.0 \text{ eV}
 \end{aligned}$$

So **Answer: E.**

Step 4 — check the sign and the size. The incident wavelength, **310 nm**, is shorter than the threshold, so photoemission happens and K_{max} must be positive. It must also be less than the incident photon energy, **4.0 eV**, because the electron has to pay the work function. **2.0 eV** satisfies both.

The distractors.

- **1.0 eV** comes from treating the work function as $1240/1240$, i.e. halving it. The threshold is **620 nm**, not **1240 nm**.
- **4.0 eV** is the incident photon energy with nothing taken off. It is the most common error in this question: it ignores the work function entirely.
- **6.0 eV** adds instead of subtracts. That would mean the electron gains energy from escaping the metal, which is the opposite of what a work function means.
- **0.5 eV** comes from an inverse-square law in the wavelength, $2.0 \times (310/620)^2$. Photon energy goes as $1/\lambda$, not $1/\lambda^2$.

The trap. The word "threshold" invites you to subtract two wavelengths. What you subtract is two *energies*. Converting first costs one line and removes the whole class of mistake.

Relevant topics: the photon model; work function and threshold frequency; the electron volt; conservation of energy in the photoelectric effect.

The trap. Subtracting one wavelength from the other. A threshold wavelength has to be turned into an energy before it can be subtracted from anything.

Q4 · A bouncing ball: total time before the bouncing dies away — **Answer B**

What is being tested. Whether you can build a series out of the physics and then sum it, rather than trying to add bounce after bounce by hand.

Step 1 — the first drop. The ball falls from rest through h under gravity:

$$h = 0.5 g t_0^2$$

$$t_0 = \sqrt{2h/g}$$

Step 2 — how long one bounce takes. After a bounce the ball rises to a height h_n and falls back. The time to rise to h_n from rest is $\sqrt{2h_n/g}$, and the fall back takes exactly the same time, because the motion is the same reversed. So one complete bounce lasts

$$t_n = 2 \sqrt{2 h_n / g}$$

This factor of two is the single most common place to go wrong: a bounce is up *and* down.

Step 3 — the heights fall by a factor of four. The first rebound reaches $h/4$, the next $h/16$, and so on. But time goes as the square root of height, so

$$t_1 = 2 \sqrt{2(h/4)/g} = 2 \sqrt{2h/g} \times (1/2) = t_0$$

$$t_2 = t_0 \times (1/2)$$

$$t_3 = t_0 \times (1/4)$$

The heights fall by four, so the times fall by two. The times form a geometric series with common ratio $1/2$.

Step 4 — sum to infinity.

$$T = t_0 + t_1 + t_2 + \dots$$

$$= t_0 + t_0(1/2) + t_0(1/4) + \dots$$

$$= t_0 [1 + (1/2 + 1/4 + 1/8 + \dots)]$$

$$= t_0 [1 + 1]$$

$$= 3 t_0$$

The bracket in the second line is $a/(1 - r)$ with $a = 1/2$ and $r = 1/2$, which is 1 . So

$$T = 3 \sqrt{2h/g}$$

So **Answer: B.**

Step 5 — check it is sensible. The total must be finite (the heights die away fast) and must be bigger than t_0 . It is three times t_0 : one drop, plus a first bounce that takes as long as the drop, plus the rest. Both conditions hold.

The distractors.

- $2\sqrt{2h/g}$ counts the drop and the first bounce and stops. It leaves out the whole infinite tail, which adds exactly one more t_0 .
- $4\sqrt{2h/g}$ uses a ratio of $1/2$ on the *heights* rather than on the times. That would be right if the height fell by a factor of two each time, which would mean a ratio of $1/\sqrt{2}$ in the times, and a sum of $1 + 2/(1 - 1/\sqrt{2})$ — much larger than 4.
- $(1 + \sqrt{2})\sqrt{2h/g}$ takes each bounce as a single traversal. It is about 2.4 times t_0 , which is the right order of magnitude, so only the algebra separates it from the correct answer.

· $(5/2)\sqrt{(2h/g)}$ adds three terms and stops. The tail is not negligible: it contributes $t_0/2$, which is exactly what this option is missing.

The trap. Bouncing balls invite you to add up bounces. Almost every such question is really a geometric series question, and the physics only has to supply the ratio. Here the ratio comes from **time proportional to the square root of height**, which is why it is $1/2$ and not $1/4$.

Relevant topics: free fall from rest; the symmetry of rise and fall; geometric series and their sums; the square-root relation between time and height.

The trap. Using the ratio of the heights as the ratio of the times. Time goes as the square root of height, so a factor of four in height is a factor of two in time.

Q5 · Conical pendulum: the period as a function of the cone angle — **Answer D**

What is being tested. Whether you can resolve a force into two directions that do different jobs — one of which is not accelerating at all — and then eliminate the force between them.

Step 1 — set up the two directions. The bob moves in a horizontal circle at constant speed. That tells you two things at once:

vertically: no acceleration at all
 horizontally: accelerating towards the centre, $a = \omega^2 r$

Only two forces act: the weight mg downwards and the tension T along the string. Resolve the tension into a vertical component $T \cos\theta$ and a horizontal component $T \sin\theta$.

Step 2 — vertical. Nothing accelerates vertically, so the vertical forces balance:

$$T \cos(\theta) = mg$$

Step 3 — horizontal. The horizontal component of the tension is the entire centripetal force. The radius of the circle is $r = L \sin\theta$, the horizontal distance from the pivot to the bob:

$$T \sin(\theta) = m \omega^2 r = m \omega^2 L \sin(\theta)$$

Step 4 — divide to kill the tension. Both equations contain T , and dividing one by the other removes it. The $\sin\theta$ also cancels, which is the pleasant surprise of this problem:

$$\begin{aligned} (T \sin(\theta))/(T \cos(\theta)) &= (m \omega^2 L \sin(\theta))/(mg) \\ \tan(\theta) &= \omega^2 L \sin(\theta)/g \\ 1/\cos(\theta) &= \omega^2 L/g \\ \omega^2 &= g/(L \cos(\theta)) \end{aligned}$$

The radius has vanished. The bob could be going round a circle of any size; what fixes the period is only how far the string is tilted.

Step 5 — convert to a period.

$$\begin{aligned} \omega &= \sqrt{g/(L \cos(\theta))} \\ \text{Period} &= 2\pi / \omega = 2\pi \sqrt{L \cos(\theta)/g} \end{aligned}$$

So **Answer: D.**

Step 6 — test the limit. As θ tends to zero the string hangs vertically, $\cos\theta$ tends to 1, and the period tends to $2\pi\sqrt{L/g}$ — exactly the small-swing period of an ordinary pendulum. That is a strong check, because a conical pendulum with a very narrow cone really is almost an ordinary pendulum. As θ approaches 90 degrees the period falls towards zero, which is also right: a nearly horizontal string needs an enormous speed to hold the bob up.

The distractors.

- $2\pi\sqrt{L/g}$ is the limit answer, not the general one. It is what you get by ignoring θ altogether.
- $2\pi\sqrt{L \sin\theta/g}$ uses the radius as though it were the pendulum length. The radius does appear in the force equation, but it cancels.
- $2\pi\sqrt{L/(g \cos\theta)}$ inverts the cosine. That would make the period grow without limit as the string approached horizontal, when in fact the bob must go round faster and faster. The limit check rejects it.
- $2\pi\sqrt{g/(L \cos\theta)}$ inverts the whole expression. Its dimensions are the reciprocal of a time, so it cannot be a period at all.

The trap. Treating $\sin\theta$ and $\cos\theta$ as interchangeable because both are "just the angle". They are attached to different jobs: the cosine carries the weight, the sine carries the centripetal force. Mixing them up is the whole difficulty of this question.

Relevant topics: resolving forces; centripetal acceleration; motion in a horizontal circle; the small-angle limit of the simple pendulum.

The trap. Swapping sin and cos. The cosine component of the tension holds the weight up; the sine component turns the bob. They are not interchangeable.

Q6 · A water jet striking a wall: the force from a rate of momentum loss — **Answer E**

What is being tested. Whether you can use $F = dp/dt$ directly, without inventing an acceleration. A stream of fluid has no single mass and no single acceleration, and trying to find either is the wrong road.

Step 1 — how much water arrives each second. In one second the water travels a distance v , so the volume that reaches the wall is a cylinder of length v and cross-section A :

$$\begin{aligned}\text{volume per second} &= A v \\ \text{mass per second} &= \rho A v\end{aligned}$$

Step 2 — how much momentum that water carries. Momentum is mass times velocity, so the momentum arriving each second is

$$\text{momentum per second} = (\rho A v) \times v = \rho A v^2$$

Step 3 — the water stops, so all of it goes. The water does not bounce and does not splash back in this model: it comes to rest against the wall. So every kilogram-metre-per-second that arrives is destroyed. The rate at which momentum is destroyed is $\rho A v^2$.

Step 4 — read off the force. Newton's second law in its momentum form says the force equals the rate of change of momentum, so

$$F = dp/dt = \rho A v^2$$

So **Answer: E.**

Step 5 — a dimensional check. The units of $\rho A v^2$ are $(\text{kg m}^{-3})(\text{m}^2)(\text{m}^2 \text{s}^{-2}) = \text{kg m s}^{-2}$, which is a newton. The units of the runner-up option, $\rho A v$, are kg s^{-1} — a mass per second, which is not a force at all. The dimensions settle it without any physics.

The distractors.

- $\rho A v$ stops one step early. It is the mass flow rate, and it is the right quantity to start from — but it still has to be multiplied by the speed to become a momentum flow.
- $2\rho A v^2$ is right for a jet that rebounds elastically at the same speed, because then the momentum change is $mv - (-mv) = 2mv$. The question says the water comes to rest, so the factor of two does not belong.
- $\rho A v^2/2$ is $\frac{1}{2}mv^2$ in disguise, i.e. the kinetic energy arriving per second. Energy per second is a power, in watts, not a force.
- $\rho A^2 v$ squares the area instead of the speed. It is dimensionally a force as well, which is what makes it dangerous: the dimensions alone cannot separate it from the right answer, only the physics can.

The trap. Reaching for $F = ma$ and hunting for the mass. In a continuous flow the natural quantity is the *rate*, and the rate of momentum change is already a force. Writing $F = dp/dt$ at the start turns this into a two-line question.

Relevant topics: Newton's second law in momentum form; mass flow rate; impulse; dimensional checking as a way to eliminate options.

The trap. Searching for a mass and an acceleration. In a steady flow the momentum is destroyed at a constant rate, and that rate is the force.

Q7 · Extension of a wire when both the length and the diameter are changed — **Answer A**

What is being tested. Whether you can track two changes at once and remember which way each one pushes the answer. The arithmetic is trivial; the bookkeeping is the question.

Step 1 — write the relation once. Young's modulus is stress over strain, and rearranging it for the extension gives the working form:

$$E = (F/A)/(e/L) \quad \text{so} \quad e = FL/(AE)$$

The extension grows with the load and with the length, and shrinks as the area grows. All three dependences are worth saying out loud, because they are what the question is really about.

Step 2 — the new area. The cross-section is a circle, so $A = \pi d^2/4$. The diameter enters **squared**. The new wire has diameter $d/2$, so

$$A_{\text{new}} = \pi (d/2)^2/4 = (1/4) A$$

The area is a quarter of the original, not a half. This is the step the question is built around.

Step 3 — put both changes in. The same extension e is wanted from the new wire, so solve for the new load:

$$\begin{aligned} e &= F_{\text{new}} (2L) / ((A/4) E) \\ &= F_{\text{new}} \times 8L / (A E) \end{aligned}$$

For the original wire, $e = F L / (A E)$. Setting the two equal:

$$\begin{aligned} F L / (A E) &= F_{\text{new}} \times 8L / (A E) \\ F &= 8 F_{\text{new}} \\ F_{\text{new}} &= F/8 \end{aligned}$$

So **Answer: A.**

Step 4 — check the direction. The new wire is twice as long, which makes it stretch more easily, and four times thinner in area, which makes it stretch much more easily. Both changes make it more compliant, so it must need a *smaller* load for the same extension. Any answer above F is therefore wrong on sight, which removes two of the five options before any algebra.

The distractors.

- **F/4** accounts for the area alone and ignores the doubled length.
- **F/2** treats the halved diameter as a halved area. That is the error of forgetting to square, and it is the most common one in this question.
- **2F** reverses one of the two effects: it takes the doubled length as making the wire stiffer, which is backwards.
- **F** assumes the geometry cannot matter. A wire is not a rigid body: its dimensions are exactly what sets how far it stretches.

The trap. Halving the diameter and halving the area feel like the same statement, and they are not. Every time a diameter, a radius or a side appears in a formula, ask whether it is squared.

Relevant topics: Young's modulus; stress and strain; the area of a circle; scaling arguments and their direction.

The trap. Treating a halved diameter as a halved area. The area goes as the square of the diameter, so it falls to a quarter.

Q8 · Doppler shift: the frequency heard from a source closing at $v/5$ — **Answer A**

What is being tested. Whether you know which way the shift goes and which quantity sits in the denominator. Both mistakes are caught by one question asked at the start: should the answer be bigger than 1 or smaller?

Step 1 — decide the direction before writing anything. The car is closing on the observer. Each successive wave crest is emitted from a point slightly nearer than the last, so the crests are crowded together. Crowded crests mean a shorter wavelength, and with the wave speed unchanged a shorter wavelength means a higher frequency. So f'/f must be **greater than 1**.

Step 2 — write the relation. For a source moving at speed u towards a stationary observer, with sound speed v :

$$f' = f \, v / (v - u)$$

The $v - u$ is in the denominator precisely because the crowding makes the apparent wavelength *shorter*, and a shorter wavelength means a larger frequency.

Step 3 — substitute and simplify. With $u = v/5$:

$$\begin{aligned} f' / f &= v / (v - v/5) \\ &= v / ((4/5)v) \\ &= 5/4 \end{aligned}$$

The common factor of v cancels, which is why the answer does not depend on the speed of sound at all. So **Answer: A**.

Step 4 — the check from step 1. $5/4 = 1.25$, which is greater than 1. The direction check passes. It also rules out $4/5$, $5/6$ and any other value below 1 in one stroke.

The distractors.

- $4/5$ is the receding answer, $v / (v + u)$. It is exactly what the observer hears *after* the car has passed, and it is the single most common wrong answer here.
- $6/5$ comes from $1 + u/v = 1 + 1/5$. It adds the ratio to one instead of forming $v / (v - u)$. Numerically it is close to the right answer, which is what makes it dangerous.
- $25/16$ is $(5/4)^2$, the shift applied twice. That is the answer for a source whose sound reflects back from a moving observer, not for a single journey.
- $5/6$ inverts the fraction, putting $v - u$ on top. The ratio would then be below 1, contradicting the direction check.

The trap. Trying to remember whether the source speed goes on the top or the bottom. Do not remember: decide the direction first. Closing means higher, so the answer must exceed 1, and only one arrangement of v and $v - u$ gives that.

Relevant topics: the Doppler effect for a moving source; wavelength and frequency at fixed wave speed; ratio simplification; limiting and direction checks.

The trap. Reciting the Doppler formula without deciding which way the shift goes. Closing means higher, and that one fact fixes where $v - u$ belongs.

Q9 · A prism at minimum deviation: finding the deviation from the refractive index — **Answer C**

What is being tested. Whether you know the minimum-deviation relation and, more importantly, whether you can undo it in the right order. The physics is one line; the algebra is where marks are lost.

Step 1 — what "minimum deviation" buys you. In general a ray is refracted at two faces and the deviation depends on the angle of incidence. But there is one incidence angle at which the deviation is least, and at that angle the ray passes through the prism **symmetrically**: it makes the same angle with

both faces. That symmetry is what makes the problem solvable, because it means the ray inside makes an angle $A/2$ with each normal, and Snell's law only has to be applied once.

$$n \sin(A/2) = \sin((A + D)/2)$$

Step 2 — substitute the numbers. With $A = 60^\circ$ and $n = \sqrt{2}$:

$$\begin{aligned}\sqrt{2} \sin(30 \text{ deg}) &= \sin((60 \text{ deg} + D)/2) \\ \sqrt{2} \times 1/2 &= \sin((60 \text{ deg} + D)/2) \\ 1/\sqrt{2} &= \sin((60 \text{ deg} + D)/2)\end{aligned}$$

Step 3 — undo the sine. The angle whose sine is $1/\sqrt{2}$ is 45° :

$$\begin{aligned}(60 \text{ deg} + D)/2 &= 45 \text{ deg} \\ 60 \text{ deg} + D &= 90 \text{ deg} \\ D &= 30 \text{ deg}\end{aligned}$$

So **Answer: C**.

Step 4 — check the answer is possible. A deviation of 30° is positive, which it must be for a ray passing through a prism, and it is smaller than the prism angle, which is typical for a moderately refracting glass. A negative or absurdly large answer would mean an arithmetic slip.

The distractors.

- 45° is the value of $(A + D)/2$. It is the right number at the wrong stage: the half-angle has been found and then reported as though it were the deviation.
- 60° assumes $D = A$. That is true only for the one glass whose index makes it so, and this is not that glass. It is a tempting answer because the prism angle is the only other angle in the question.
- 15° subtracts $A/2$ a second time, so it removes 30 degrees twice from the 60.
- 22.5° divides $(A + D)$ by four instead of two, which halves the half-angle.

The trap. Treating $\sin\theta$ as if it were θ . The sine of 30 degrees is a half, and the angle whose sine is a half is 30 degrees — but the angle whose sine is $1/\sqrt{2}$ is **45** degrees, not **0.707** degrees and not 30. Writing the inverse sine explicitly, and keeping the degree signs attached, prevents the whole family of slips.

Relevant topics: refraction at a plane surface; the prism relation; minimum deviation; inverse trigonometric functions.

The trap. Treating $\sin(\theta)$ as though it were θ . The angle whose sine is $1/\sqrt{2}$ is 45 degrees, and that is the step the question is really testing.

Q10 · Parallel resistors: which one takes the larger share of the power — **Answer B**

What is being tested. Whether you know which quantity is shared. That single decision sets the direction of the answer before any arithmetic is done.

Step 1 — what is common, and therefore which form of the power to use. Resistors in parallel have the **same potential difference** across them. So the useful form of the power is the one containing V :

$$P = V^2/R$$

The other form, $P = I^2R$, would be the wrong choice here, because the currents are not equal.

Step 2 — the two powers. With a common V :

$$P_3 = V^2/3 \quad P_6 = V^2/6$$

The $3\ \Omega$ resistor dissipates twice the power of the $6\ \Omega$ one, because V^2 is divided by a smaller number.

Step 3 — the fraction.

$$P_{\text{total}} = V^2/3 + V^2/6 = V^2(2/6 + 1/6) = V^2/2$$

$$\text{fraction} = P_3/P_{\text{total}} = (V^2/3)/(V^2/2) = 2/3$$

The V^2 cancels, which is why the answer does not depend on the battery voltage. So **Answer: B**.

Step 4 — check the direction. The $3\ \Omega$ resistor is the smaller one, so in parallel it must take the larger share. $2/3$ is more than a half, which is consistent. Any answer below $1/2$ is wrong on sight, and that removes $1/3$ and $4/9$ immediately.

The distractors.

- $1/3$ divides the power in proportion to the resistances, giving the smaller resistor the smaller share. That is the rule for resistors in *series*, where the current is common and $P = I^2R$. Here it is exactly backwards.
- $1/2$ splits the power equally, which would need the two resistances to be equal.
- $4/9$ is $(2/3)^2$, the resistance ratio squared. There is no squared ratio in this problem.
- $5/6$ is $1/3 + 1/2$, adding two fractions that were never shares of the same total.

The trap. The direction question — "does the smaller resistor take more or less?" — is worth answering before touching the algebra, because in parallel the answer is "more" and in series it is "less". Getting that right converts a five-option guess into a two-option calculation.

Relevant topics: parallel circuits; the two forms of the power equation; choosing the form that matches the shared quantity; simplifying algebraic fractions.

The trap. Dividing power in proportion to resistance. That is the series rule. In parallel the voltage is common, so power goes as $1/R$ and the smaller resistor takes more.

Q11 • Half-life from a decay curve plotted with a logarithmic activity axis — **Answer C**

What is being tested. Whether you know what a logarithmic axis is *for*. On a log axis equal ratios occupy equal distances, so an exponential decay plots as a straight line and its halvings become equal steps that can simply be counted.

Step 1 — why the straight line matters. A straight line on a log plot means the activity is multiplied by the same factor in every equal interval of time. That is exactly what exponential decay does:

$$A = A_0 (1/2)^{(t/T)}$$

Take logarithms of both sides and the right-hand side becomes linear in t , with slope fixed by T . So the straightness of the graph is not a coincidence to be noted — it is the statement that the decay is exponential, and it licenses the method that follows.

Step 2 — read a ratio, not a difference. The activity does not fall by 700 kBq. It falls by a *factor*:

$$800/100 = 8$$

On a linear axis the difference would be the useful quantity. Here it is not: the gap between 100 and 200 is the same size as the gap between 400 and 800, so a fall of 50 kBq and a fall of 400 kBq are drawn identically.

Step 3 — turn the factor into a number of halvings. One halving divides by two, two halvings divide by four, three divide by eight:

$$8 = 2^3$$

So three halvings carry the activity from 800 kBq down to 100 kBq.

Step 4 — divide. Those three halvings occupy the twelve minutes between the two stated points:

$$T = 12/3 = 4 \text{ min}$$

So **Answer: C**.

Step 5 — check it against the graph. Start at 800 kBq. After one half-life, 400 kBq; after two, 200 kBq; after three, 100 kBq — which is the stated point at twelve minutes. So four minutes per halving lands exactly on both labelled points, and it is the only value that does.

The distractors.

- **1.5 min** divides twelve by the factor eight, treating a ratio as though it were a count. Eight is how much the activity is divided by, not how many times.
- **3 min** counts four halvings where there are three. The chain $800 \rightarrow 400 \rightarrow 200 \rightarrow 100$ has three steps, not four, because the number of steps is one fewer than the number of values in the chain.
- **6 min** takes the whole twelve minutes as two halvings, which would be right only if the activity had fallen by a factor of four, to 200 kBq.
- **12 min** takes the time to reach the last plotted point as the half-life itself. After one half-life the activity must have halved, and it has not.

The trap. Reading a logarithmic axis as though it were linear. Everything about the drawing looks like an ordinary graph, and the natural instinct is to measure the fall in kBq. On a log axis that measurement is meaningless; the only quantity with a physical meaning is the ratio of the two values, and the only way to use it is as a power of two.

Relevant topics: exponential decay; half-life; logarithmic scales and the reading of graphs; powers of two.

The trap. Reading the logarithmic axis as linear and measuring the fall in kBq. On a log axis a fall of 700 kBq and a fall of 50 kBq can be the same vertical distance, so only the ratio is meaningful.

Q12 · Power in one resistor of a network driven by a cell with internal resistance — **Answer B**

What is being tested. Two habits at once: reducing a network from the inside out, and refusing to forget that the source has resistance of its own. The second habit is what separates the correct answer from the most popular wrong one.

Step 1 — reduce the parallel pair. The two $6\ \Omega$ resistors carry the same potential difference, and they are equal, so the combination is half of one of them:

$$\begin{aligned} 1/R_p &= 1/6 + 1/6 = 2/6 \\ R_p &= 3\ \Omega \end{aligned}$$

Step 2 — add the series resistor. The parallel combination and the $3\ \Omega$ resistor carry the same current, so their resistances add:

$$R_{\text{ext}} = 3 + 3 = 6\ \Omega$$

Step 3 — the internal resistance is in the loop too. The current flows through the source as well as through the external circuit, so the $2\ \Omega$ is in series with everything else:

$$R_{\text{total}} = 6 + 2 = 8\ \Omega$$

This is the step that most candidates skip, and it is worth pausing on. The electromotive force is the energy per unit charge supplied by the source *including* what it spends on its own resistance. Only the terminal potential difference is available to the external circuit, and the terminal p.d. is not 12 V.

Step 4 — the current.

$$I = E/R_{\text{total}} = 12/8 = 1.5\ \text{A}$$

Step 5 — the power in the $3\ \Omega$ resistor. The current is known and the resistance is known, so the form of the power equation to use is the one without a voltage in it:

$$P = I^2 R = (1.5)^2 \times 3 = 2.25 \times 3 = 6.75\ \text{W}$$

So **Answer: B.**

Step 6 — check the potential differences round the loop. The terminal p.d. is $12 - 1.5 \times 2 = 9\ \text{V}$. Across the $3\ \Omega$ resistor the drop is $1.5 \times 3 = 4.5\ \text{V}$. That leaves $9 - 4.5 = 4.5\ \text{V}$ across the parallel pair, and $1.5\ \text{A}$ through $3\ \Omega$ gives $4.5\ \text{V}$. The two agree, so the reduction was consistent. As a second check, the total power supplied is $12 \times 1.5 = 18\ \text{W}$, of which $1.5^2 \times 2 = 4.5\ \text{W}$ is wasted internally and $13.5\ \text{W}$ reaches the external circuit — and $13.5 = 6.75 + 6.75$, the two halves of the external circuit splitting the power equally because both are $3\ \Omega$.

The distractors.

· **4.5 W** is the power dissipated inside the source, $I^2 r$. It is a real and relevant quantity — it is the whole reason the terminal p.d. is not 12 V — but it is not the power in the $3\ \Omega$ resistor.

· **12 W** comes from leaving the internal resistance out, so that $I = 12/6 = 2\ \text{A}$ and $P = 2^2 \times 3 = 12\ \text{W}$. This is the most common error: the source is treated as ideal. A current of 2 A would also imply a terminal p.d. of 12 V, which cannot be right when 2 A is flowing through a $2\ \Omega$ internal resistance.

- **13.5 W** is the total power delivered to the external circuit. It is right about the current and wrong about the location: the external circuit contains the parallel pair as well as the series resistor.
- **18 W** is the total power supplied by the cell, internal loss included.

The trap. Every one of the four wrong options is a genuine power in this circuit. Nothing is arithmetically wrong with any of them; they are answers to four different questions. The work is therefore not the calculation but the identification — decide which quantity the question asks for, and say so in words, before touching a formula.

Relevant topics: resistors in series and in parallel; electromotive force and internal resistance; the terminal potential difference; the two forms of the power equation.

The trap. Treating the cell as ideal and using 12 V across the external circuit. The internal resistance carries the same current, so it belongs in the denominator: $12/8$, not $12/6$.

Q13 · The common speed after a perfectly inelastic collision between equal masses — **Answer B**

What is being tested. Whether you reach for momentum rather than energy when the collision is inelastic. The word "stick" tells you the collision is perfectly inelastic, and that single word decides which conservation law is usable.

Step 1 — which quantity is conserved. The track is smooth, so there is no external horizontal force on the pair. Momentum is therefore conserved. Kinetic energy is *not*: the trolleys stick, and the energy that disappears goes into deformation, sound and heating at the coupling. A solution that starts from $\frac{1}{2}mu^2 = \frac{1}{2}(m+M)v^2$ is answering a different question.

Step 2 — the momentum before. Only the first trolley is moving:

$$p_{\text{before}} = m u + M \times 0 = 2.0 \times 3.0 = 6.0 \text{ kg m s}^{-1}$$

The stationary trolley has no momentum, and forgetting that — or accidentally giving it speed u — is what produces the option 4.5 m s^{-1} .

Step 3 — the momentum after. The two trolleys move as one body of mass 4.0 kg at the unknown common speed:

$$p_{\text{after}} = (2.0 + 2.0) v = 4.0 v$$

Step 4 — equate and solve.

$$\begin{aligned} 4.0 v &= 6.0 \\ v &= 1.5 \text{ m s}^{-1} \end{aligned}$$

So **Answer: B**.

Step 5 — check it is sensible. Two checks, both of which the answer passes. First, the common speed must lie between the two initial speeds: 0 and 3.0 , and 1.5 does. A collision that made the pair move faster than the incoming trolley would create momentum from nothing. Second, the kinetic energy must fall. Before, $\frac{1}{2} \times 2.0 \times 3.0^2 = 9.0 \text{ J}$; after, $\frac{1}{2} \times 4.0 \times 1.5^2 = 4.5 \text{ J}$. Half the kinetic energy has gone, which is what "sticking" means. Note that the momentum check and the energy check give opposite instructions — one says conserved, the other says reduced — and both are satisfied.

The distractors.

- 0.75 m s^{-1} is half of the correct answer: the mass ratio has been applied twice, once to get 1.5 and again to halve it.
- 3.0 m s^{-1} assumes the moving trolley keeps its speed and simply carries the other along. That would conserve neither momentum nor energy.
- 4.5 m s^{-1} adds the two speeds and halves: $(3.0 + 6.0)/2$, or equivalently treats the stationary trolley as moving at -3.0 and then takes the magnitude.
- 6.0 m s^{-1} is the total momentum, 6.0 kg m s^{-1} , reported as a speed. The units do not match, which is the giveaway.

The trap. Reaching for kinetic energy because the question mentions speed. Energy is the right tool for a smooth slide and the wrong tool for a collision that sticks. The test is one question: is anything permanently deformed? If yes, energy is not conserved and momentum is the only route.

Relevant topics: conservation of linear momentum; perfectly inelastic collisions; the difference between conserved and non-conserved quantities; checking an answer against limiting values.

The trap. Starting from conservation of kinetic energy. A collision in which the bodies stick is perfectly inelastic, so energy is lost; only momentum is conserved.

Q14 · The fraction of stored energy lost when a charged capacitor is joined to an uncharged one — **Answer E**

What is being tested. Whether you can identify which quantity is conserved before doing any algebra. Charge is conserved here and energy is not, and that single decision fixes the whole solution.

Step 1 — what is conserved. The supply has been removed before the connection is made, so the plates are isolated. No charge can leave them and none can arrive: the total charge is fixed.

$$Q = C V$$

Energy is *not* conserved. When the connection is made, charge flows through the wire, which has resistance; the current heats the wire and radiates. The final state is therefore not the one that conserves energy, and any solution that assumes it is will be wrong.

Step 2 — what the connection does. Joining the upper plates to each other and the lower plates to each other puts the two capacitors in parallel, so they must end at the same potential difference V_{new} , and the total charge is shared between them:

$$C_{\text{total}} = C + 2C = 3C$$

Step 3 — the new potential difference. The same charge now sits on a larger capacitance:

$$V_{\text{new}} = Q/C_{\text{total}} = CV/(3C) = V/3$$

The potential difference has fallen to a third. It had to fall: the same charge on three times the capacitance means one third of the potential difference.

Step 4 — the energy before. Working in terms of Q and C avoids carrying the factor of a half through the ratio, but either form will do:

$$E_{\text{before}} = Q^2/(2C)$$

Step 5 — the energy after, and the fraction lost.

$$E_{\text{after}} = Q^2/(2 \times 3C) = Q^2/(6C)$$

$$E_{\text{after}}/E_{\text{before}} = (1/6)/(1/2) = 1/3$$

One third of the energy remains, so two thirds has been dissipated:

$$\text{fraction lost} = 1 - 1/3 = 2/3$$

So **Answer: E.**

Step 6 — check it is sensible. The fraction lost must lie between zero and one. It cannot be zero, because the potential difference fell and energy goes as the square of the potential difference. It cannot be one, because charge is still stored and the capacitors are still charged to $V/3$. Two thirds sits comfortably inside those bounds. A second check: the result does not contain the resistance of the wire. That is right — the wire only decides how *fast* the energy is lost, not how much. A thicker wire loses the same two thirds, just more quickly.

The distractors.

- **0** conserves energy as well as charge. That would require the potential difference to be unchanged, which is impossible when the same charge now occupies three times the capacitance.
- **1/4** comes from taking the new potential difference as $V/2$, which is what you get by treating the second capacitor as having capacitance C rather than $2C$. With $V_{\text{new}} = V/2$ the final energy would be three eighths of the initial and the loss one quarter.
- **1/3** is the fraction that *remains*. It is the ratio $E_{\text{after}}/E_{\text{before}}$, reported without the final subtraction.
- **1/2** is the folk belief that exactly half the energy is always lost when capacitors are joined. It happens to be true for two equal capacitors, and it is the reason the belief exists — but here the capacitances are in the ratio one to two, so it does not apply.

The trap. Assuming that energy is conserved because the problem says nothing about friction or resistance. Something always dissipates the difference when isolated conductors at different potentials are joined, and the amount does not depend on what that something is. The energy is genuinely gone from the circuit, and the only way to find the answer is to conserve the quantity that *is* conserved.

Relevant topics: capacitance and charge; capacitors in parallel; energy stored in a capacitor; conservation of charge in an isolated system.

The trap. Conserving energy as well as charge. When isolated plates at different potentials are joined, charge is conserved but the potential difference must fall, and the difference in energy is always dissipated.

What is being tested. Whether you can set up the floating condition once and then reuse it, instead of treating the two liquids as two separate problems. The block does not change, and that is the thread that joins the two cases.

Step 1 — the floating condition. The block is in equilibrium, so the upward force from the liquid exactly balances its weight:

$$\text{upthrust} = \text{weight of the block}$$

Step 2 — write both sides in full. The upthrust is the weight of the liquid pushed aside, and the weight of the block is the weight of its whole volume:

$$\rho_L V_{\text{sub}} g = \rho_b V g$$

Here V_{sub} is the submerged volume, V is the block's total volume, ρ_L is the density of the liquid and ρ_b that of the block.

Step 3 — cancel. The gravitational field strength appears on both sides and goes. The volume of the block also appears on both sides, so only the *fraction* of it that is submerged survives:

$$V_{\text{sub}}/V = \rho_b/\rho_L$$

This is the whole physics of the problem in one line, and it is worth reading in words: **the submerged fraction equals the ratio of the two densities**. Nothing else matters — not the shape of the block, not its size, not the value of g .

Step 4 — find the density of the block from the water. With three quarters submerged in water:

$$\begin{aligned} 3/4 &= \rho_b/1000 \\ \rho_b &= 750 \text{ kg m}^{-3} \end{aligned}$$

Step 5 — find the density of the unknown liquid. The block is the same, so ρ_b is still 750. Now half the volume is submerged:

$$\begin{aligned} 1/2 &= 750/\rho_L \\ \rho_L &= 750/(1/2) = 1500 \text{ kg m}^{-3} \end{aligned}$$

So **Answer: D**.

Step 6 — check the direction. The unknown liquid is denser than water, so it should hold the block higher, and it does: half submerged against three quarters. If the answer had come out below 1000 the block would have had to sink deeper, contradicting the given fraction. That direction check costs nothing and catches the inversion error immediately.

The distractors.

- **500 kg m⁻³** takes the submerged fraction, one half, and reads it directly as a density in hundreds. The fraction is a pure number and carries no units of its own.
- **750 kg m⁻³** is the density of the block. It is the right number at the wrong stage: the water gives it, and the question asks about the liquid.
- **1000 kg m⁻³** assumes that because the block still floats the liquid must be water. It floats in both, but at different depths, and that difference is the entire information content of the second sentence.

· 2000 kg m^{-3} inverts the ratio: $750/(3/4)$ instead of $750/(1/2)$, which puts the denser liquid on the wrong side of the comparison.

The trap. Treating the two floats as unrelated. The temptation is to write the floating condition twice from scratch, and in doing so to introduce a second unknown. The block's density is common to both cases, so the first case is not a separate question — it is the step that supplies the number the second case needs.

Relevant topics: Archimedes' principle; the floating condition; density and relative density; cancelling common factors in a physical relation.

The trap. Treating the submerged fraction as a density. It is a pure number, and it equals the ratio of the block's density to the liquid's — so the liquid's density is found by dividing, not by reading the fraction off.

Q16 · Two-source interference: the lowest frequency for which a given point is a minimum — **Answer B**

What is being tested. Whether you can handle a whole family of answers and pick the right member of it. Any number of frequencies make **P** a minimum; the question asks for the lowest, and that is a separate decision from the physics.

Step 1 — the path difference. The two waves travel different distances to reach **P**, and only the difference matters:

$$\Delta = 3.5 - 2.5 = 1.0 \text{ m}$$

The two distances themselves are never used again. What matters is how much further one wave has travelled than the other.

Step 2 — the condition for a minimum. A minimum needs the two waves to arrive in antiphase, which happens when one has travelled an odd number of half-wavelengths further than the other:

$$\Delta = (n + 1/2) \lambda, \quad n = 0, 1, 2, \dots$$

With a whole number of wavelengths the waves arrive in step and the point is a maximum. With an odd number of *half*-wavelengths they arrive exactly out of step.

Step 3 — the lowest frequency is the longest wavelength. Since $f = v/\lambda$ at fixed v , asking for the lowest frequency is the same as asking for the longest wavelength. Rearranging the condition:

$$\lambda = \Delta / (n + 1/2)$$

The right-hand side is largest when the denominator is smallest, and the smallest allowed denominator is $1/2$, at $n = 0$. So the longest wavelength that gives a minimum is

$$\lambda = 1.0 / (1/2) = 2.0 \text{ m}$$

Step 4 — the frequency.

$$f = v/\lambda = 340/2.0 = 170 \text{ Hz}$$

So **Answer: B**.

Step 5 — confirm it is the lowest. The next member of the family has $n = 1$, giving $\lambda = 1.0 / (3/2) = 0.67 \text{ m}$ and $f = 510 \text{ Hz}$. Every later member is shorter still, so 170 Hz is the lowest and there is nothing below it that works.

Step 6 — check against the condition. At 170 Hz the wavelength is 2.0 m and the path difference is 1.0 m , which is exactly $\lambda/2$. That is the $n = 0$ member of the family, and it does give a minimum. As a second check, at 85 Hz the wavelength would be 4.0 m and the path difference would be only $\lambda/4$ — not a minimum at all, which is why the answer cannot be below 170 Hz .

The distractors.

- **85 Hz** takes the minimum condition as a quarter of a wavelength. Half a wavelength is what puts two waves out of step, because a half-wavelength shift is a phase shift of 180° .
- **340 Hz** uses the constructive condition: at this frequency the wavelength is 1.0 m , exactly the path difference, so the two waves arrive in step and **P** is a maximum.
- **510 Hz** is a genuine minimum — the wavelength is 0.67 m and the path difference is one and a half wavelengths — but it is the *second* member of the family, not the lowest. This is the most dangerous option, because it satisfies the physics and fails only the word "lowest".
- **680 Hz** gives a wavelength of 0.5 m , so the path difference is two wavelengths and the point is again a maximum.

The trap. Answering the physics and stopping. The condition $\Delta = (n + 1/2)\lambda$ has infinitely many solutions, and every one of them is a minimum. Reading the question as "find a frequency" rather than "find the lowest frequency" is what makes 510 Hz look right. The extremal word in the question is doing as much work as the formula.

Relevant topics: the wave equation; path difference; constructive and destructive superposition; selecting the extremal member of a family of solutions.

The trap. Finding any frequency that gives a minimum rather than the lowest one. The condition has infinitely many solutions; the word 'lowest' selects the $n = 0$ member, which is the longest wavelength.

Q17 · The Young modulus from a force-extension graph and the dimensions of the wire — **Answer C**

What is being tested. Whether you can move between the three quantities that all describe the same wire — stiffness, stress and strain — and the Young modulus, which is the only one of them that belongs to the *material* rather than to the particular wire.

Step 1 — read the gradient. The graph is a straight line through the origin, so the wire obeys Hooke's law over the range shown. The gradient is the stiffness:

$$k = F/x = 40 / (2.0 \times 10^{-3}) = 2.0 \times 10^4 \text{ N m}^{-1}$$

The extension must be converted to metres here. Dividing 40 by 2.0 without converting would give a stiffness a thousand times too large, and that error survives all the way to the final answer.

Step 2 — stress. Stress is the force per unit area of cross-section:

$$\text{stress} = F/A = 40 / (1.0 \times 10^{-7}) = 4.0 \times 10^8 \text{ Pa}$$

Step 3 — strain. Strain is the fractional extension, and it is a ratio of two lengths, so it has no units:

$$\text{strain} = x/L = (2.0 \times 10^{-3})/2.0 = 1.0 \times 10^{-3}$$

Step 4 — the Young modulus.

$$E = \text{stress/strain} = (4.0 \times 10^8)/(1.0 \times 10^{-3}) = 4.0 \times 10^{11} \text{ Pa}$$

So **Answer: C.**

It is worth seeing the same calculation in one line, because the single line is where the direction of **L** becomes visible:

$$E = (F/A)(L/x) = (F/x)(L/A) = 2.0 \times 10^4 \times (2.0/(1.0 \times 10^{-7})) = 4.0 \times 10^{11} \text{ Pa}$$

Step 6 — check the units and the magnitude. The units of $(F/x)(L/A)$ are $(\text{N m}^{-1})(\text{m}/\text{m}^2) = \text{N m}^{-2}$, which is the pascal. So the arithmetic cannot be out by a unit. And $4.0 \times 10^{11} \text{ Pa}$ is **400 GPa**, which is the right order for a metal — steel is around **200 GPa** and this material is stiffer, which is unremarkable. An answer of 4.0×10^8 or 4.0×10^{14} would have to be wrong on sight.

The distractors. All four are the correct formula with one quantity misplaced, which is why they are close enough to be tempting.

- **$1.0 \times 10^{11} \text{ Pa}$** takes the strain as xL , multiplying by the length instead of dividing. The strain is a *fraction*, so it must be smaller than the extension, not larger.
- **$2.0 \times 10^{11} \text{ Pa}$** takes the strain as x alone. The length of the wire then never enters the calculation, which cannot be right: two wires of the same material and area but different lengths stretch by different amounts under the same force.
- **$8.0 \times 10^{11} \text{ Pa}$** uses a length of **1.0 m** rather than **2.0 m**, so the strain comes out twice as large and the modulus twice as small.
- **$1.6 \times 10^{12} \text{ Pa}$** uses **0.5 m**, which halves the strain and doubles the modulus relative to the correct value.

The trap. Reading the gradient and stopping. The gradient gives the stiffness of *this wire*; the Young modulus is a property of *the material*, and the two are related only through the length and the area. A second wire of the same material, twice as long and with the same area, would have half the stiffness and exactly the same Young modulus — which is the clearest statement of why the extra step is needed.

Relevant topics: Hooke's law and the force-extension graph; stress, strain and the Young modulus; the gradient of a straight-line graph; unit consistency in a compound formula.

The trap. Reporting the gradient as the answer. The gradient is the stiffness of this wire, which depends on its length and area; the Young modulus is a property of the material alone.

Q18 · How the number of photons emitted per second depends on power and wavelength — **Answer C**

What is being tested. Whether you can reduce a physical situation to a proportionality before putting any numbers in. No value of the power, the wavelength or Planck's constant is needed, and none is given.

Step 1 — the energy of one photon.

$$E = hc/\lambda$$

A shorter wavelength means a more energetic photon. Halving the wavelength therefore *doubles* the energy each photon carries.

Step 2 — the number of photons per second. A beam of power P delivers P joules each second, and each photon takes E of those joules:

$$N = P/E = P \lambda / (hc)$$

Step 3 — the proportionality. The constants h and c do not change, so they can be dropped when only a ratio is wanted:

$$N \text{ proportional to } P \lambda$$

This is the whole question in one line. The photon rate is proportional to the *product* of the power and the wavelength — not to either one alone.

Step 4 — apply the two changes. Doubling P doubles N . Halving λ halves N , because a more energetic photon means fewer of them are needed to carry the same energy.

Step 5 — combine.

$$\text{factor} = 2 \times (1/2) = 1$$

The two changes cancel exactly, and the photon rate is unchanged. So **Answer: C**.

It is worth seeing the cancellation in one line, because it shows the answer does not depend on either number:

$$N_{\text{new}}/N_{\text{old}} = (2P)(\lambda/2)/(P \lambda) = 1$$

The distractors.

- **1/4** multiplies the two factors together as $2 \times (1/2)$ read as though both were divisions. The power change increases the rate and the wavelength change decreases it, so the factors act in opposite directions.
- **1/2** applies only the wavelength change. It is the right reasoning with half the question missing.
- **2** applies only the power change. Same omission, opposite half.
- **4** adds the two factors instead of multiplying them: $2 + 2$, treating the halving as another doubling.

The trap. Handling the two changes one at a time and then reporting the first one. The question states two changes, and both have to be carried through. The safe habit is to write the proportionality down before touching the factors: once $N \text{ proportional to } P\lambda$ is on the page, the cancellation is mechanical and the partial answers stop being tempting.

Relevant topics: photon energy; the wave equation applied to light; power as energy per unit time; proportionality and the combination of factors.

The trap. Applying only one of the two changes. The photon rate is proportional to the power times the wavelength, so both changes act, and here they cancel exactly.

Q19 · The first-order approximation to a series combination when one term dominates — **Answer A**

What is being tested. Whether you can turn an expression into the standard small-parameter form, and then use the expansion the data sheet provides. Both halves are needed: the data sheet gives $(1 + x)^n \approx 1 + nx$, but it does not tell you what x is.

Step 1 — what the limit should look like. Before any algebra, ask what the physics demands. Two springs end to end are always *softer* than either one alone, because each contributes its own stretch. If one spring is very stiff and the other is soft, the stiff one barely stretches at all, so the pair behaves like the soft one alone — but still a little softer. So the answer must start with k and be slightly less than it.

Step 2 — divide by the large quantity. This is the step that decides the question. Dividing numerator and denominator by K :

$$k_{\text{combined}} = kK/(k + K) = k/(1 + k/K)$$

Dividing by k instead would give $K/(1 + K/k)$, in which the small parameter appears upside down as a large one, and the expansion would be useless.

Step 3 — recognise the form. The result is k multiplied by $(1 + x)^{-1}$ with $x = k/K$, which is small by the statement of the question.

Step 4 — expand. The data sheet supplies the result for a small parameter, with $n = -1$:

$$\begin{aligned} (1 + x)^n &= 1 + nx \\ (1 + k/K)^{-1} &= 1 - k/K \end{aligned}$$

So

$$k_{\text{combined}} = k(1 - k/K) = k - k^2/K$$

So **Answer: A**.

Step 5 — check the limits. Let K grow without bound. The correction term k^2/K goes to zero and the expression reduces to exactly k , which is the physically required answer and confirms the leading term. Now let K fall towards k : the correction is then of order one, the expansion is no longer valid, and the answer correctly becomes unreliable — as it should, since the approximation was only ever claimed for small k/K . Two limits, both correct, and neither needed any arithmetic beyond reading the expression.

The distractors.

- $k(1 + k/K)$ gets the sign of the correction wrong, making the combination *stiffer* than the softer spring. Step 1 rules this out on physical grounds without any algebra: joining springs end to end cannot stiffen the pair.

- $k(1 - K/k)$ inverts the small ratio. The correction is then huge, and the expression is not an approximation at all.

- $K(1 - k/K)$ keeps the stiffer spring as the leading term. It reduces to K in the limit, which would mean the very stiff spring is doing all the stretching.
- k gives the leading term only. It is the correct limit, and it is not what the question asks for: "to first order" means the leading term *plus* the first correction.

The trap. Expanding in the wrong variable. The small parameter has to be the ratio of the smaller quantity to the larger one, and which of the two you divide by decides whether the small parameter even appears. A useful habit is to write down what the small parameter is going to be *before* starting the algebra — here k/K , because the question says so — and then to divide by whatever makes it appear.

Relevant topics: the small-parameter approximations supplied on the data sheet; combining springs in series; reducing an expression to standard form by dividing through; checking an approximation against its limiting cases.

The trap. Dividing by the smaller quantity, which puts the small parameter upside down and makes the expansion meaningless. Divide by the larger one so that the ratio is small.

Q20 · The number of images of a point object between two plane mirrors at an angle — **Answer C**

What is being tested. Whether you realise that a plane mirror does not stop after one reflection. Each image is a perfectly good object as far as the other mirror is concerned, so the reflections go round and round until the geometry closes them off.

Step 1 — one mirror on its own. A plane mirror forms an image as far behind the reflecting surface as the object is in front of it, on the perpendicular through the object. With one mirror the bead would have exactly one image.

Step 2 — the second mirror reflects the first image. That image is now an object for the second mirror, which forms its own image of it. That second image is in turn an object for the first mirror, and so on. The chain does not stop after two steps.

Step 3 — what closes the chain. The reflections are all mirror images in one of the two mirror planes, and the two planes meet along the edge at 60° . Reflecting repeatedly in two planes that meet at an angle is the same as rotating the original bead about the edge in steps of that angle. So the images and the bead itself lie at equal angular intervals all the way round the edge:

$$\text{angular step} = 60^\circ$$

Step 4 — how many positions are there? A full turn contains

$$360/60 = 6$$

equal steps, so there are six positions in the ring.

Step 5 — remove the bead itself. One of those six positions is the bead, not an image of it. The number of images is therefore

$$\text{images} = 6 - 1 = 5$$

So **Answer: C**.

Step 6 — check that the ring closes. The division is exact: six steps of 60° come back to the start with nothing left over. That matters. If the angle had been, say, 50° , then $360/50 = 7.2$, the ring would not close, and one of the reflections would fall outside the region between the mirrors and not be seen at all. The question's 60° is chosen precisely so that this ambiguity does not arise, and a candidate who checks the division has confirmed that the simple count is the right one to use.

The distractors.

- 3 divides 180° by 60° . That would be right if the two mirrors formed a single flat surface — that is, if the angle between them were 180° rather than 60° .
- 4 counts the reflections one short, as though the chain stopped after each mirror had been used twice.
- 6 is $360/60$ without the subtraction: the bead itself has been counted as one of its own images. There are six *positions* in the ring and five *images*.
- 11 is $2 \times 6 - 1$, the form that belongs to two separate parallel mirrors, where each mirror images the other's images independently. With the mirrors at an angle the two chains are not independent — they are the same chain.

The trap. Assuming each mirror contributes exactly one image. The reflections multiply rather than add, because an image can be reflected again. The reliable way to think about it is to stop counting mirrors and start counting positions in the ring: the geometry of the wedge, not the number of mirrors, decides how many there are.

Relevant topics: reflection at a plane surface; the position of an image in a plane mirror; multiple reflections between inclined mirrors; rotational symmetry about an axis.

The trap. Counting one image per mirror. Each image is an object for the other mirror, so the reflections continue until the geometry closes the chain round the edge.

Q21 · The number of distinct gamma photon energies from a set of nuclear energy levels — **Answer D**

What is being tested. Whether you see that a transition is possible between *any* two levels, not just between neighbours. Once that is clear the physics is over and the question becomes a counting one.

Step 1 — what a gamma photon carries. When the nucleus drops from one level to another it loses energy, and that energy leaves as one photon:

$$E_{\text{gamma}} = E_{\text{upper}} - E_{\text{lower}}$$

So every observable photon energy is a difference between two of the four levels.

Step 2 — which pairs are available. The nucleus in the 7.0 MeV level has three possible destinations: 3.0, 1.0 and 0. If it goes to 3.0 MeV it is then in the 3.0 MeV level, from which it can go to 1.0 or to 0. And from 1.0 MeV it can go to 0. So every pair of levels is reachable, directly or by stages.

Step 3 — the count. Counting the destinations level by level:

from 7.0 MeV: 3 destinations
 from 3.0 MeV: 2 destinations
 from 1.0 MeV: 1 destination
 total = 3 + 2 + 1 = 6

So Answer: D.

Step 4 — the six energies, written out. This is the step that turns a count into an answer, because the question asks for different *energies*, not for different transitions:

$$\begin{array}{ll} 7.0 - 0 = 7.0 \text{ MeV} & 7.0 - 1.0 = 6.0 \text{ MeV} \\ 7.0 - 3.0 = 4.0 \text{ MeV} & 3.0 - 0 = 3.0 \text{ MeV} \\ 3.0 - 1.0 = 2.0 \text{ MeV} & 1.0 - 0 = 1.0 \text{ MeV} \end{array}$$

Step 5 — check that no two coincide. The six values are 1.0, 2.0, 3.0, 4.0, 6.0 and 7.0 MeV — all different. So six transitions give six distinct photon energies, and the count of transitions and the count of energies agree. That agreement is not automatic, and the next paragraph is about why.

Step 6 — the point of the check. Suppose the levels had been at 0, 1.0, 2.5 and 4.0 MeV. There would still be six transitions, but two of them would both give 1.5 MeV, so only five distinct photon energies would be observed. The number of *transitions* and the number of *energies* are different questions, and the question asked for energies. Working the six differences out is the only way to be sure they are distinct, and it costs one line.

The distractors.

- **3** counts only the transitions leaving the top level, which is the first line of the count rather than the whole of it.
- **4** counts only the transitions arriving at the ground state, one from each level. That is the other half of the same mistake: it counts by destination instead of by pair, and each way of counting on its own misses the others.
- **5** is the count you get by assuming two of the six differences coincide. It is the right method with an unjustified subtraction — and the explicit list in Step 4 shows there is nothing to subtract.
- **12** counts each pair in both directions, as though dropping from 7.0 to 1.0 and rising from 1.0 to 7.0 were two different emissions. A rising transition absorbs a photon; it does not emit one.

The trap. Assuming the nucleus must cascade one level at a time. It does not — a single photon can carry away the whole difference between any two levels — and equally, it is not restricted to the four differences between neighbouring levels. Both the "only neighbours" picture and the "one per level" picture give four or fewer, and both are wrong.

Relevant topics: nuclear energy levels; gamma emission; photon energy as a level difference; counting the pairs in a set.

The trap. Counting only transitions between neighbouring levels. A single gamma photon can carry the difference between any two levels, so every pair contributes a possible energy.

Q22 · How the separation of two balls released in succession changes while both fall — **Answer B**

What is being tested. Whether you can reason about a difference of two motions rather than about each motion separately. Both balls are accelerating, and that is what makes the question feel harder than it is.

Step 1 — the speeds. At any instant after the second ball is released, both balls have been falling for different lengths of time. With t measured from the release of the second ball:

$$v_1 = g(t + \Delta t) \quad v_2 = g t$$

Both speeds are growing, and they are growing at the same rate.

Step 2 — subtract. The difference between them does not grow at all:

$$v_1 - v_2 = g(t + \Delta t) - g t = g \Delta t$$

Every term in t has cancelled. The speed difference is fixed, and it equals the speed the first ball had already gained during the delay. This is the whole question: equal accelerations cancel in the difference.

Step 3 — what a constant speed difference means. If the first ball is always moving $g\Delta t$ faster than the second, then the gap between them opens at that rate and at no other rate. The separation is therefore *increasing at a constant rate*.

Step 4 — write the separation down. The first ball has been falling for $t + \Delta t$ and the second for t , so

$$\begin{aligned} \text{separation} &= (1/2) g (t + \Delta t)^2 - (1/2) g t^2 \\ &= (1/2) g (2 t \Delta t + \Delta t^2) \\ &= g \Delta t t + (1/2) g \Delta t^2 \end{aligned}$$

The t^2 terms have cancelled, leaving something linear in t . A linear function of time grows at a constant rate, which confirms Step 3 by a second route.

Step 5 — check the two limits. At $t = 0$, the instant the second ball is released, the separation is $\frac{1}{2}g\Delta t^2$ — the head start, and not zero. As t grows, the separation grows without limit at the steady rate $g\Delta t$. Both of those are what the physical picture demands: the balls are already apart when the second is released, and they never come back together. So **Answer: B**.

The distractors.

- **Constant separation** is the most common answer, and it comes from a real confusion: equal accelerations do not mean equal speeds. They mean the speeds stay *equally different*. The balls are at different points of the same journey, and the journey is getting longer for both of them at the same rate.
- **Increasing at an increasing rate** transfers the shape of the distance fallen — which does grow as the square of the time — onto the separation. The squared terms cancel when the two motions are subtracted, so the separation is linear, not quadratic.
- **Decreasing at a constant rate** has the second ball closing the gap. That would require the second ball to be the faster one, which cannot happen when it was released later and both accelerate identically.
- **Decreasing at an increasing rate** gets both the direction and the shape wrong.

The trap. Reasoning about one ball and then the other instead of about the difference. Each ball on its own is genuinely accelerating, and every statement you can make about either one is about a quantity that grows as the square of the time. The only way to see the linear behaviour is to subtract first and look at what survives.

Relevant topics: free fall from rest; relative velocity; the difference between acceleration and velocity; combining two motions with the same acceleration.

The trap. Assuming equal accelerations mean equal speeds. They mean the speed DIFFERENCE is constant, so the gap opens at a steady rate rather than accelerating.

Q23 · The displacement of mercury in a U-tube when an oil column is added to one arm — **Answer B**

What is being tested. Whether you set the pressure balance up at the right place, and whether you remember that the mercury has to go somewhere. The first is physics, the second is bookkeeping, and both have to be right.

Step 1 — where to compare pressures. Take the level of the mercury surface in the arm that has risen, and extend that level across to the other arm. The mercury below that level is a single connected body of liquid at rest, so the pressure must be the same at that level on both sides.

Step 2 — the left-hand side. Above that level in the oil-filled arm there is the oil column, of depth h , plus the mercury. The oil adds

$$p_{\text{oil}} = \rho_{\text{oil}} g h$$

Everything above the oil, the air, presses on both arms equally, so it cancels and can be ignored.

Step 3 — the right-hand side. On the other side the only liquid above the chosen level is mercury, and its depth is the difference between the two mercury surfaces. Call the distance the surface in the oil-filled arm fell x . The mercury has not been lost: the volume that left one arm arrived in the other, and the arms have the same cross-section, so the other surface rose by x as well. The difference in levels is therefore

$$\text{difference in levels} = 2x$$

and the pressure it provides is

$$p_{\text{Hg}} = \rho_{\text{Hg}} g (2x)$$

This factor of two is the whole of the bookkeeping, and leaving it out gives an answer twice as large as it should be.

Step 4 — equate and cancel. The pressures at the chosen level are equal:

$$\rho_{\text{oil}} g h = \rho_{\text{Hg}} g (2x)$$

The gravitational field strength appears on both sides and goes. Nothing in the problem needed a value for g , and that is a sign the setup is right.

Step 5 — solve. Rearranging, and working in centimetres so that $h = 16$ and x comes out in centimetres:

$$\begin{aligned} x &= \rho_{\text{oil}} h / (2 \rho_{\text{Hg}}) = (850 \times 16) / (2 \times 13600) \\ &= 13600 / 27200 = 0.5 \text{ cm} = 5.0 \text{ mm} \end{aligned}$$

So **Answer: B**.

Step 6 — check the size. The oil column is 16 cm deep and the mercury moves only 0.5 cm . Mercury is about sixteen times as dense as this oil, and the level difference is twice the displacement, so a

displacement of exactly one thirty-second of the oil column is what the densities demand. That is 0.5 cm , and it is what came out. If the answer had been of the same order as 16 cm the balance would have been set up wrongly.

The distractors.

- **2.5 mm** is half the correct answer: the factor of two has been applied twice, once in the equation and again in the arithmetic.
- **10 mm** comes from forgetting that the other arm moves. Using $\rho_{\text{oil}} h = \rho_{\text{Hg}} x$ gives $13600/13600 = 1.0 \text{ cm}$. It is the most likely error and it is out by exactly a factor of two.
- **20 mm** multiplies by two instead of dividing, which is the same as taking the level difference to be half the displacement — the geometry upside down.
- **40 mm** has the factor of two inverted and the arithmetic wrong as well, being four times the correct answer.

The trap. Treating the mercury surface as though it were held still on the other side. It is not: the two arms are connected, so any mercury that leaves one arrives in the other. The same reasoning appears wherever a liquid is displaced in a tube of uniform bore, and the factor of two is always twice the movement of a single surface, never the movement itself.

Relevant topics: pressure in a liquid; the pressure balance in a U-tube; the manometer; why the gravitational field strength cancels in a ratio of columns.

The trap. Forgetting that the other arm rises. The difference in mercury levels is TWICE the displacement of one surface, so leaving out the factor of two doubles the answer.

Q24 · An order-of-magnitude estimate of the mass of air in a room — **Answer C**

What is being tested. Whether you can produce a defensible number for a quantity nobody has measured, and then say whether it is sensible. An estimate is not a guess: it is a calculation from rounded inputs, and its value lies in the check at the end.

Step 1 — what the answer is made of. The air fills the room, so its mass is the density multiplied by the volume:

$$m = \rho V$$

Step 2 — the volume. The room is a box, so the volume is the product of its three dimensions:

$$V = 10 \times 8 \times 3 = 240 \text{ m}^3$$

Step 3 — the density of air. This is the one fact the question requires you to have. Air is about 1.2 kg m^{-3} , and for an estimate it is worth rounding to 1 kg m^{-3} straight away, because the dimensions are themselves only known to one figure.

Step 4 — multiply.

$$m = 1 \times 240 = 240 \text{ kg}$$

So the answer is a few hundred kilograms. So **Answer: C**.

Step 5 — check it against something known. This is the step that makes the estimate worth anything. If the room were filled with water instead, the mass would be 240 m^3 times 1000 kg m^{-3} , which is 240000 kg — about two hundred and forty tonnes. Air is roughly a thousandth as dense as water, so a few hundred kilograms is the right kind of answer, and the option 3000 kg is an order of magnitude too big. A second check: a few hundred kilograms is the mass of a small car. A classroom's air weighing about as much as a car is surprising, but it is not absurd, and that is exactly the sort of reaction a good estimate should provoke.

The distractors. Every wrong option is a factor of ten from the answer, which is what makes the question a test of estimation rather than of arithmetic — the digits are all correct, and only the position of the decimal point differs.

- **3 kg** reads the density of air as about one *gram* per cubic metre rather than one kilogram. The density of air is 1.2 kg m^{-3} , which is 1200 g m^{-3} .

- **30 kg** drops one of the three dimensions, so the volume comes out as 24 m^3 instead of 240 m^3 . The room has three dimensions and all three must be used.

- **3000 kg** takes the density of air to be around 10 kg m^{-3} , which is nearer the density of a dense gas under pressure than of the air in a room.

- **30000 kg** compounds the density error with a volume error, so the estimate is too large on two counts at once.

The trap. Treating the estimate as finished once the multiplication is done. The multiplication is the easy part; the check against a known mass is what tells you whether the decimal point is in the right place, and it is the only defence against being out by a factor of ten — which, on a five-option question whose options are all powers of ten apart, is the difference between the right answer and every wrong one.

Relevant topics: density and mass; order-of-magnitude estimation; checking an answer against a familiar quantity; significant figures in an estimate.

The trap. Stopping at the multiplication. An estimate is only worth something once it has been compared with a known mass; without that check, a factor of ten is invisible.

Q25 · The maximum kinetic energy of photoelectrons when the wavelength is halved — **Answer D**

What is being tested. Whether you treat the work function as a fixed subtraction or as something that scales with the light. It does not scale: it is a property of the metal, and the same toll is paid whatever arrives.

Step 1 — the photoelectric equation. One photon is absorbed by one electron. The energy has to do two things: get the electron out of the metal, and give it whatever is left as kinetic energy:

$$hf = \phi + E_k$$

where ϕ is the work function and E_k is the maximum kinetic energy.

Step 2 — the original photon energy. This is the step that makes the rest possible. The question gives the kinetic energy and the work function, but not the photon energy, so it has to be found:

$$hf = 2.0 + 1.0 = 3.0 \text{ eV}$$

Step 3 — what halving the wavelength does. Photon energy is hc/λ , so it is inversely proportional to the wavelength. Halving λ doubles hf :

$$hf_{\text{new}} = 2 \times 3.0 = 6.0 \text{ eV}$$

Step 4 — the work function does not change. This is the crux. The work function is the energy needed to remove an electron from that particular metal. It depends on the metal and not on the light, so the same 2.0 eV is subtracted as before.

Step 5 — subtract.

$$E_{k,\text{new}} = 6.0 - 2.0 = 4.0 \text{ eV}$$

So Answer: D.

Step 6 — check that the increase is more than proportional. The photon energy doubled, from 3.0 to 6.0 eV , but the kinetic energy went from 1.0 to 4.0 eV — a factor of four, not two. That is not an error: it is what a fixed subtraction does. The work function took one third of the original photon energy and takes only one third of the new one... in fact it takes 2.0 of 6.0 , which is one third, so the share it takes has fallen, and the share left for the electron has risen. Whenever a fixed amount is subtracted from a quantity that has grown, the remainder grows by more than the original factor. The direction of the answer is therefore right, and so is its size.

The distractors.

- **1.0 eV** assumes the kinetic energy is unchanged. That would require the photon energy to be unchanged, which contradicts halving the wavelength.
- **2.0 eV** doubles the kinetic energy in step with the photon energy. It treats the work function as though it too had doubled, or as though it did not exist.
- **3.0 eV** is the original photon energy. It is a real quantity and a useful intermediate step, which is exactly why it is offered — but the question asks for the kinetic energy, not for the photon energy.
- **6.0 eV** is the new photon energy with the work function never subtracted. The electron cannot leave with all of it; getting out of the metal costs energy, and that cost is the whole content of the work function.

The trap. Scaling everything in proportion. A candidate who notices that halving the wavelength doubles the photon energy may double the kinetic energy as well, and the answer looks reasonable. It is wrong because the photoelectric equation is not a proportion — it is a proportion with a constant taken away, and a constant taken away breaks proportionality.

Relevant topics: the photoelectric effect; the work function; photon energy and wavelength; the threshold frequency; why a fixed subtraction destroys proportionality.

The trap. Doubling the kinetic energy because the photon energy doubled. The work function is a fixed subtraction, so the remainder grows by MORE than the factor the photon energy grew by.