

DEPLOYMENT.md — Sentinel

Table of Contents

- [DEPLOYMENT.md — Sentinel](#)
- [Prerequisites - Required Software - Required Accounts & Access - System Dependencies](#)
 - [Ubuntu/Debian](#)
 - [macOS](#)
- [Environment Variables - Creating .env File - Local Development - Step 1: Clone and Install - Step 2: Create Data Directory - Step 3: Configure SSH Access](#)
 - [Ensure SSH key has correct permissions](#)
 - [Test SSH access to a monitored VM](#)
- [Step 4: Initialize Database - Step 5: Start Development Server](#)
 - [With auto-reload \(Node 18+ required\)](#)
 - [Or standard start](#)
- [Step 6: Verify Health](#)
 - [Expected: {"status":"ok","uptime":}](#)
- [Development Workflow](#)
 - [Run with custom port](#)
 - [Run with debug logging](#)
 - [Monitor logs in real-time](#)
- [Build - Production Dependencies Only - Verification](#)
 - [Verify all dependencies are installed](#)
 - [Check for vulnerabilities](#)
 - [Test the application starts](#)
- [Output Structure - Deployment Options - Recommended: Bare Metal / VM Deployment \(Primary\)](#)
 - [1. Create application user](#)
 - [2. Deploy application](#)
 - [3. Install dependencies as sentinel user](#)
 - [4. Create data directory](#)
 - [Enable and start service](#)
 - [Check status](#)
 - [View logs](#)
- [Alternative: Docker Deployment](#)
 - [Build image](#)
 - [Run container](#)
- [Alternative: Railway / Render \(Not Recommended\) - Alternative: PM2 Process Manager](#)
 - [Install PM2 globally](#)
 - [Start application](#)
 - [Save PM2 configuration](#)
 - [Setup PM2 to start on boot](#)
 - [Run the command it outputs](#)
 - [Monitor](#)
- [Docker - Dockerfile](#)

- [Install build dependencies for better-sqlite3](#)
- [Create app directory](#)
- [Copy package files](#)
- [Install dependencies](#)
- [Copy application source](#)
- [Create data directory](#)
- [Expose port](#)
- [Set environment variables](#)
- [Health check](#)
- [Run as non-root user](#)
- [.dockerignore - Docker Compose \(Optional\)](#)
 - [Start with docker-compose](#)
 - [View logs](#)
 - [Stop](#)
- [CI/CD - GitHub Actions Workflow - Required GitHub Secrets - Manual Deployment Script](#)
 - [Create deployment package](#)
 - [Upload to server](#)
 - [Deploy on server](#)
 - [Cleanup](#)
- [Monitoring - Application Health Monitoring](#)
 - [Simple health check](#)
 - [Detailed status](#)
- [System Resource Monitoring](#)
 - [View real-time logs](#)
 - [View logs from last hour](#)
 - [View errors only](#)
 - [Export logs](#)
 - [Real-time logs](#)
 - [Monitor CPU/Memory](#)
 - [View detailed info](#)
- [Database Monitoring](#)
 - [Check database size](#)
 - [SQLite statistics](#)
 - [Check for database locks](#)
- [Performance Monitoring - Alert Configuration - Log Rotation - Backup Strategy](#)
 - [Daily database backup script](#)
 - [Backup with timestamp](#)
 - [Keep only last 7 days](#)
- [Recommended Monitoring Stack](#)
 - [Install node_exporter for system metrics](#)
 - [Create systemd service for node_exporter](#)
- [Related Documentation](#)

Prerequisites

Required Software

- **Node.js:** v18.x or higher (v20.x recommended)
- **npm:** v9.x or higher
- **SQLite3:** System libraries for better-sqlite3 compilation
- **SSH Access:** Required for VM monitoring functionality
- **Operating System:** Linux (Ubuntu recommended) or macOS

Required Accounts & Access

- SSH keys configured for all VMs being monitored
- Access to TheForge infrastructure network
- Port 3000 available on host machine (Claudinator)

System Dependencies

```
# Ubuntu/Debian
sudo apt-get update

sudo apt-get install -y build-essential python3 sqlite3 libsqlite3-dev
```

macOS

```
brew install sqlite3
```

Environment Variables

The following environment variables should be configured:

Variable	Description	Required	Default	Example
-----	-----	-----	-----	-----
<code>PORT</code>	Server listening port	No	3000	<code>3000</code>
<code>NODE_ENV</code>	Environment mode	No	development	production
<code>DB_PATH</code>	SQLite database file path	No	<code>./data/sentinel.db</code>	<code>/var/sentinel/sentinel.db</code>
<code>LOG_LEVEL</code>	Application log level	No	info	debug , info , warn , error
<code>SSH_KEY_PATH</code>	Path to SSH private key for VM access	Yes	-	<code>/home/user/.ssh/id_rsa</code>
<code>ALERT_CHECK_INTERVAL</code>	Cron schedule for alert checks	No	<code>/5</code>	<code>/2</code>
<code>BACKUP_CHECK_INTERVAL</code>	Cron schedule for	No	<code>0 /6</code>	<code>0 /4</code>

	backup checks			
METRICS_RETENTION_DAYS	Days to retain metrics history	No	30	90

Creating .env File

```
cat > .env << EOF
PORT=3000

NODE_ENV=production

DB_PATH=/var/sentinel/sentinel.db

SSH_KEY_PATH=/home/forge/.ssh/id_rsa

LOG_LEVEL=info

ALERT_CHECK_INTERVAL=/5      *

BACKUP_CHECK_INTERVAL=0 /6

METRICS_RETENTION_DAYS=30

EOF
```

Local Development

Step 1: Clone and Install

```
git clone <repository-url> sentinel
cd sentinel

npm install
```

Step 2: Create Data Directory

```
mkdir -p data
chmod 755 data
```

Step 3: Configure SSH Access

```
# Ensure SSH key has correct permissions
chmod 600 ~/.ssh/id_rsa
```

Test SSH access to a monitored VM

```
ssh -i ~/.ssh/id_rsa user@monitored-vm.local
```

Step 4: Initialize Database

The database will auto-initialize on first run, but you can verify:

```
sqlite3 data/sentinel.db ".tables"
```

Step 5: Start Development Server

```
# With auto-reload (Node 18+ required)
npm run dev
```

Or standard start

```
npm start
```

The server will start on `http://localhost:3000`

Step 6: Verify Health

```
curl http://localhost:3000/health
```

Expected: `{"status": "ok", "uptime": <seconds`

Development Workflow

```
# Run with custom port
PORT=3001 npm run dev
```

Run with debug logging

```
LOG_LEVEL=debug npm run dev
```

Monitor logs in real-time

```
tail -f logs/sentinel.log # if logging to file
```

Build

This is a Node.js Express application that does not require a build step.

Production Dependencies Only

```
npm install --production
```

Verification

```
# Verify all dependencies are installed
npm list --depth=0
```

Check for vulnerabilities

```
npm audit
```

Test the application starts

```
node src/server.js
```

Output Structure

```
sentinel/
├── src/           # Application source code
├── data/         # SQLite database (runtime generated)
├── node_modules/ # Dependencies
├── package.json  # Project manifest
└── .env          # Environment configuration
```

Deployment Options

Recommended: Bare Metal / VM Deployment (Primary)

Best for: Infrastructure monitoring tools that need host-level access

This application is designed to run directly on **Claudinator** (Ubuntu host) to monitor TheForge infrastructure. Deploy as a systemd service for production reliability.

Setup Process:

```
# 1. Create application user
sudo useradd -r -s /bin/bash -m -d /opt/sentinel sentinel
```

2. Deploy application

```
sudo mkdir -p /opt/sentinel

sudo cp -r ./* /opt/sentinel/

sudo chown -R sentinel:sentinel /opt/sentinel
```

3. Install dependencies as sentinel user

```
sudo -u sentinel bash -c 'cd /opt/sentinel && npm install --production'
```

4. Create data directory

```
sudo mkdir -p /var/sentinel

sudo chown sentinel:sentinel /var/sentinel
```

Systemd Service Configuration:

```
sudo nano /etc/systemd/system/sentinel.service
```

```
[Unit]
Description=Sentinel Infrastructure Monitor

After=network.target

Wants=network-online.target

[Service]

Type=simple

User=sentinel
```

```
Group=sentinel

WorkingDirectory=/opt/sentinel

Environment="NODE_ENV=production"

Environment="PORT=3000"

Environment="DB_PATH=/var/sentinel/sentinel.db"

Environment="SSH_KEY_PATH=/home/sentinel/.ssh/id_rsa"

ExecStart=/usr/bin/node /opt/sentinel/src/server.js

Restart=always

RestartSec=10

StandardOutput=journal

StandardError=journal

SyslogIdentifier=sentinel

[Install]

WantedBy=multi-user.target
```

```
# Enable and start service
sudo systemctl daemon-reload

sudo systemctl enable sentinel

sudo systemctl start sentinel
```

Check status

```
sudo systemctl status sentinel
```

View logs

```
sudo journalctl -u sentinel -f
```

Alternative: Docker Deployment

Best for: Containerized environments, development, or isolated deployments

```
# Build image
docker build -t sentinel:latest .
```

Run container

```
docker run -d \

  --name sentinel \
  -p 3000:3000 \
  -v /var/sentinel:/data \
  -v ~/.ssh:/root/.ssh:ro \
  -e NODE_ENV=production \
  -e DB_PATH=/data/sentinel.db \
  -e SSH_KEY_PATH=/root/.ssh/id_rsa \
  --restart unless-stopped \
  sentinel:latest
```

Alternative: Railway / Render (Not Recommended)

Note: These platforms are not ideal for this application because:

- Requires SSH access to external VMs
- Needs persistent SQLite database storage
- Better suited for traditional VPS deployment

If you must use Railway/Render, use PostgreSQL instead of SQLite and configure SSH keys via secrets.

Alternative: PM2 Process Manager

Best for: Simpler deployment without systemd

```
# Install PM2 globally
npm install -g pm2
```

Start application

```
cd /opt/sentinel

pm2 start src/server.js --name sentinel
```

Save PM2 configuration

```
pm2 save
```

Setup PM2 to start on boot

```
pm2 startup
```

Run the command it outputs

Monitor

```
pm2 monit
```

```
pm2 logs sentinel
```

Docker

Dockerfile

```
FROM node:20-alpine
```

Install build dependencies for better-sqlite3

```
RUN apk add --no-cache \
```

```
python3 \
make \
g++ \
sqlite \
openssh-client
```

Create app directory

```
WORKDIR /app
```

Copy package files

```
COPY package*.json ./
```

Install dependencies

```
RUN npm ci --production
```

Copy application source

```
COPY src/ ./src/
```

Create data directory

```
RUN mkdir -p /data
```

Expose port

```
EXPOSE 3000
```

Set environment variables

```
ENV NODE_ENV=production \  
  
    PORT=3000 \  
    DB_PATH=/data/sentinel.db
```

Health check

```
HEALTHCHECK --interval=30s --timeout=3s --start-period=40s --retries=3 \  
  
    CMD node -e "require('http').get('http://localhost:3000/health', (r) => {process.exit(r.statusCode)})"
```

Run as non-root user

```
USER node
```

```
CMD ["node", "src/server.js"]
```

.dockerignore

```
node_modules  
npm-debug.log
```

```
.env

.git

.gitignore

data/

*.md

.DS_Store
```

Docker Compose (Optional)

```
version: '3.8'

services:

  sentinel:
    build: .
    container_name: sentinel
    ports:
      - "3000:3000"
    volumes:
      - sentinel-data:/data
      - ~/.ssh:/home/node/.ssh:ro
    environment:
      - NODE_ENV=production
      - DB_PATH=/data/sentinel.db
      - SSH_KEY_PATH=/home/node/.ssh/id_rsa
      - LOG_LEVEL=info
    restart: unless-stopped
    healthcheck:
      test: ["CMD", "node", "-e", "require('http').get('http://localhost:3000/health', (r) => {proc
      interval: 30s
      timeout: 3s
      retries: 3
      start_period: 40s

volumes:

  sentinel-data:
    driver: local
```

```
# Start with docker-compose
docker-compose up -d
```

View logs

```
docker-compose logs -f
```

Stop

```
docker-compose down
```

CI/CD

GitHub Actions Workflow

Create `.github/workflows/deploy.yml`:

```
name: Deploy Sentinel

on:
  push:
    branches: [main, production]
  workflow_dispatch:

jobs:
  test:
    runs-on: ubuntu-latest
    steps:
      - uses: actions/checkout@v4

      - name: Setup Node.js
        uses: actions/setup-node@v4
        with:
          node-version: '20'
          cache: 'npm'

      - name: Install dependencies
        run: npm ci

      - name: Run security audit
        run: npm audit --audit-level=high

      - name: Check for syntax errors
        run: node --check src/server.js

  deploy:
    needs: test
    runs-on: ubuntu-latest
    if: github.ref == 'refs/heads/production'
    steps:
      - uses: actions/checkout@v4

      - name: Deploy to Claudinator
        uses: appleboy/ssh-action@master
        with:
          host: ${ secrets.DEPLOY_HOST }
          username: ${ secrets.DEPLOY_USER }
          key: ${ secrets.DEPLOY_SSH_KEY }
          script: |
            cd /opt/sentinel
            git pull origin production
            npm install --production
            sudo systemctl restart sentinel
            sleep 5
            curl -f http://localhost:3000/health || exit 1

  docker:
    needs: test
    runs-on: ubuntu-latest
    if: github.ref == 'refs/heads/main'
    steps:
      - uses: actions/checkout@v4

      - name: Set up Docker Buildx
        uses: docker/setup-buildx-action@v3

      - name: Login to Docker Hub
```

```

uses: docker/login-action@v3
with:
  username: ${ secrets.DOCKERHUB_USERNAME }
  password: ${ secrets.DOCKERHUB_TOKEN }

- name: Build and push
  uses: docker/build-push-action@v5
  with:
    context: .
    push: true
    tags: |
      ${ secrets.DOCKERHUB_USERNAME }/sentinel:latest
      ${ secrets.DOCKERHUB_USERNAME }/sentinel:${ github.sha }
    cache-from: type=registry,ref=${ secrets.DOCKERHUB_USERNAME }/sentinel:buildcache
    cache-to: type=registry,ref=${ secrets.DOCKERHUB_USERNAME }/sentinel:buildcache,mode=max

```

Required GitHub Secrets

Configure these in your repository settings (Settings → Secrets → Actions):

- `DEPLOY_HOST` : Claudinator hostname/IP
- `DEPLOY_USER` : SSH user (e.g., `sentinel`)
- `DEPLOY_SSH_KEY` : Private SSH key for deployment
- `DOCKERHUB_USERNAME` : Docker Hub username (if using Docker)
- `DOCKERHUB_TOKEN` : Docker Hub access token (if using Docker)

Manual Deployment Script

Create `scripts/deploy.sh` :

```

#!/bin/bash
set -e

REMOTE_USER="sentinel"

REMOTE_HOST="claudinator.local"

REMOTE_PATH="/opt/sentinel"

echo "🚀 Deploying Sentinel to $REMOTE_HOST..."

```

Create deployment package

```

echo "📦 Creating deployment package..."

tar --exclude='node_modules' \

  --exclude='.git' \
  --exclude='data' \
  --exclude='.env' \
  -czf sentinel-deploy.tar.gz .

```

Upload to server

```
echo "📦 Uploading to server..."
```

```
scp sentinel-deploy.tar.gz $REMOTE_USER@$REMOTE_HOST:/tmp/
```

Deploy on server

```
echo "🔧 Installing on server..."
```

```
ssh $REMOTE_USER@$REMOTE_HOST << 'ENDSSH'
```

```
cd /opt/sentinel
tar -xzf /tmp/sentinel-deploy.tar.gz
npm install --production
sudo systemctl restart sentinel
sleep 5
curl -f http://localhost:3000/health && echo "✅ Deployment successful!"
```

```
ENDSSH
```

Cleanup

```
rm sentinel-deploy.tar.gz
```

```
echo "🌟 Deployment complete!"
```

```
chmod +x scripts/deploy.sh
./scripts/deploy.sh
```

Monitoring

Application Health Monitoring

Built-in Health Endpoint

```
# Simple health check
curl http://localhost:3000/health
```

Detailed status

```
curl http://localhost:3000/status
```

Uptime Monitoring Services

Configure external monitoring with:

- **UptimeRobot**: <https://uptimerobot.com> (free tier available)
- **Pingdom**: <https://www.pingdom.com>
- **StatusCake**: <https://www.statuscake.com>

Monitor: `http://claudinator:3000/health` every 5 minutes

System Resource Monitoring

With Systemd Journal

```
# View real-time logs
sudo journalctl -u sentinel -f
```

View logs from last hour

```
sudo journalctl -u sentinel --since "1 hour ago"
```

View errors only

```
sudo journalctl -u sentinel -p err
```

Export logs

```
sudo journalctl -u sentinel --since "2024-01-01" > sentinel-logs.txt
```

With PM2

```
# Real-time logs
pm2 logs sentinel
```

Monitor CPU/Memory

```
pm2 monit
```

View detailed info

```
pm2 show sentinel
```


Database Monitoring

```
# Check database size
ls -lh /var/sentinel/sentinel.db
```

SQLite statistics

```
sqlite3 /var/sentinel/sentinel.db "

SELECT

    name,
    (SELECT COUNT(*) FROM sqlite_master WHERE type='table' AND name=t.name) as row_count
FROM sqlite_master t WHERE type='table';

"
```

Check for database locks

```
fuser /var/sentinel/sentinel.db
```

Performance Monitoring

Node.js Built-in Profiling

Add to your application for production profiling:

```
// In src/server.js - add at startup
if (process.env.NODE_ENV === 'production') {

    const v8 = require('v8');
    const fs = require('fs');

    setInterval(() => {
        const stats = {
            memory: process.memoryUsage(),
            cpu: process.cpuUsage(),
            uptime: process.uptime()
        };
        fs.appendFileSync('/var/log/sentinel-stats.log', JSON.stringify(stats) + '\n');
    }, 60000); // Every minute
}
```

Prometheus Metrics (Suggested)

Install `prom-client` for Prometheus-compatible metrics:

```
npm install prom-client
```

Alert Configuration

Create alerting rules for:

- **Service Down:** Health check fails for 2+ minutes
- **High Memory:** Memory usage > 512MB

- **Database Issues:** Database size > 1GB or lock detected
- **SSH Failures:** Cannot connect to monitored VMs

Log Rotation

Configure logrotate for systemd journals:

```
sudo nano /etc/systemd/journald.conf
```

```
[Journal]
SystemMaxUse=500M

SystemMaxFileSize=50M

MaxRetentionSec=2week
```

```
sudo systemctl restart systemd-journald
```

Backup Strategy

```
# Daily database backup script
#!/bin/bash

BACKUP_DIR="/var/backups/sentinel"

mkdir -p $BACKUP_DIR
```

Backup with timestamp

```
sqlite3 /var/sentinel/sentinel.db ".backup $BACKUP_DIR/sentinel-$(date +%Y%m%d-%H%M%S).db"
```

Keep only last 7 days

```
find $BACKUP_DIR -name "sentinel-*.db" -mtime +7 -delete
```

Add to crontab:

```
sudo crontab -e
0 2 * * /opt/sentinel/scripts/backup.sh
```

Recommended Monitoring Stack

For Production:

1. **Grafana + Prometheus:** Full metrics dashboard

2. **Loki**: Log aggregation
3. **Alertmanager**: Alert routing and notifications
4. **Node Exporter**: System metrics

Quick Setup:

```
# Install node_exporter for system metrics
wget https://github.com/prometheus/node_exporter/releases/download/v1.7.0/node_exporter-1.7.0.linux-  

tar xvfz node_exporter-1.7.0.linux-amd64.tar.gz
sudo cp node_exporter-1.7.0.linux-amd64/node_exporter /usr/local/bin/
sudo useradd -rs /bin/false node_exporter
```

Create systemd service for node_exporter

```
sudo nano /etc/systemd/system/node_exporter.service
```

This gives you infrastructure-wide visibility including Sentinel's health.

Related Documentation

- [Readme](#)
- [Architecture](#)
- [Api](#)
- [Contributing](#)

Generated by Athena — © 2026 TheForge, LLC