

mcp-okn: redesign of mcp-proto-okn

Cleaner multi-graph querying, automated registry/schema handling, deterministic diagrams, and reproducible transcripts

mcp-proto-okn (current)	Change area	mcp-okn (new)
Single-graph queries; multi-graph answers merged outside the endpoint.	Query model	Native multi-graph & cross-graph bridge queries with explicit named-graph scoping (<code>purl.org/okn/frink/kg/{shortname}</code>).
Subset of 35 KGs plus Ubergraph.	KG coverage	All FRINK-loaded KGs, except semopenalex.
Registry built semi-automatically from GitHub metadata; curated repo schemas.	Registry + schema	Auto-built from the FRINK registry, cached at startup; curated schemas with endpoint-probing fallback.
LLM-generated Mermaid schema diagrams, so output may vary.	Schema diagrams	Server-generated Mermaid diagrams from the schema — deterministic and reproducible.
Ontology subtree traversal in Ubergraph is iterative.	Ontology expansion	Full-subtree expansion using precomputed Ubergraph closures.
Each graph queried separately; results merged server-side.	Cross-graph joins	Precomputed, verified join recipes: <code>list_crosswalks</code> / <code>find_crosswalks</code> and <code>get_join_strategy</code> (shared key, predicates, runnable skeleton query).
No spatial helpers.	Geospatial	<code>point_to_s2</code> maps a lat/long to its S2 cell IRI for geospatial joins.
No explicit query logging; transcripts summarize work, not verbatim.	Reproducibility	Explicit query-log controls; transcripts include executable queries for replay.