


Neural Machine Translation by Jointly Learning to Align and Translate

Muhammad Tasnim Mohiuddin

School of Computer Science and Engineering
Nanyang Technological University

March 21, 2018

Encoder-Decoder Model in NMT



- Encoder reads and encodes a source sentence into a fixed-length vector (**Thought Vector / Context Vector**).
- Decoder then outputs a translation from the encoded vector.

Problems with Basic Encoder-Decoder Model

Encoder needs to be able to **compress all the necessary information** of a source sentence **into a fixed-length vector**.

Problematic while dealing with long sentences.

Performance of a basic encoder-decoder model deteriorates rapidly as the length of an input sentence increases.

Problems with Basic Encoder-Decoder Model

Encoder needs to be able to **compress all the necessary information** of a source sentence **into a fixed-length vector**.

Problematic while dealing with long sentences.

Performance of a basic encoder-decoder model deteriorates rapidly as the length of an input sentence increases.

What is the solution?


Attention Mechanism

- The most important distinguishing feature of this approach from the basic encoderdecoder is that **it does not attempt to encode a whole input sentence into a single fixed-length vector.**

Attention Mechanism

- The most important distinguishing feature of this approach from the basic encoderdecoder is that **it does not attempt to encode a whole input sentence into a single fixed-length vector.**
- Each time the proposed model generates a word in a translation, **it searches for a set of positions in a source sentence where the most relevant information is concentrated.**
- This frees a neural translation model from having to squash all the information of a source sentence, regardless of its length, into a fixed-length vector.

Proposed Model



- Context vector

$$c_i = \sum_{j=1}^{T_x} \alpha_{ij} h_j$$

- Weight α_{ij} is computed by


$$\alpha_{ij} = \text{softmax}(e_{ij}) = \frac{\exp(e_{ij})}{\sum_{k=1}^{T_x} \exp(e_{ik})}$$

- Alignment model score

$$e_{ij} = v_a^T \tanh(W_a s_{i-1} + U_a h_j)$$

It is a **feedforward neural network** jointly trained with others.

Visualize the effect of weight α_{ij}



Result

