

Second-Order Discretization in Space and Time for Grey S_2 -Radiation Hydrodynamics

Simon R. Bolding, Joshua E. Hansel, & Jim E. Morel

16 October 2015

CLASS seminar



Outline


- 1 Overview
- 2 Low-Order Solver
- 3 High-Order Solver
- 4 HOLO Algorithm
- 5 Test Problems
- 6 Conclusions

Outline

- 1 Overview
- 2 Low-Order Solver
- 3 High-Order Solver
- 4 HOLO Algorithm
- 5 Test Problems
- 6 Conclusions

What is radiation hydrodynamics?

- Thermal radiative transfer coupled to material motion
 - Useful for inertial confinement fusion and astrophysics calculations



Example of a 1D Radiative Shock Solution

Goal of this project

- Extended work by Edwards and Morel for a method that is second-order in [space](#) and [time](#). to be applied to S_2 equations, preserving

The governing equations

Real EQUATIONS HOW WE WILL WRITE THEM TO MAKE
THIS PRESENTATION EASIER TO FOLLOW

The MUSCL Hancock method

A PREDICTOR CORRECTOR METHOD

Linear Discontinuous Galerkin Spatial Discretization for TRT

Operator splitting and general approach

Development of Algorithm

Non-linear iteration scheme for implicit solve

Extra stuff

Code implemented in python

Energy slope stuff

Other things

Future Work

Coupling to a high-order system using hybrid-“ S_2 -like” equations.

A High-Order Low-Order Solution to a Transport Problem

Basic Idea

Build a low-order (LO) system that can be efficiently solved, such that it preserves a high-order (HO) solution from MC simulations

A High-Order Low-Order Solution to a Transport Problem

Basic Idea

Build a low-order (LO) system that can be efficiently solved, such that it preserves a high-order (HO) solution from MC simulations

A High-Order Low-Order Solution to a Transport Problem

Basic Idea

Build a low-order (LO) system that can be efficiently solved, such that it preserves a high-order (HO) solution from MC simulations

- **LO system** is lower-dimensional, “ S_2 -like” equations
 - Handles scattering and fission source iterations
 - Useful for coupled physics and non-linear systems
 - Produces **FE representation of sources** for HO system

A High-Order Low-Order Solution to a Transport Problem

Basic Idea

Build a low-order (LO) system that can be efficiently solved, such that it preserves a high-order (HO) solution from MC simulations

- **LO system** is lower-dimensional, “S₂-like” equations
 - Handles scattering and fission source iterations
 - Useful for coupled physics and non-linear systems
 - Produces **FE representation of sources** for HO system
- **HO system** is a fixed-source, pure absorber transport problem
 - MC does not directly determine k_{eff} or fission source, only used to **evaluate consistency terms**
 - We will solve the HO system with ECMC


Overview of Exponentially Convergent Monte Carlo

- Iterative form of Residual Monte Carlo
 - Each batch tallies the **error** in current estimate of solution, which is a transport problem with a reduced source
 - Can reduce statistical error **globally** $\propto e^{-\alpha N}$
 - Does not make difficult problems easier

Overview of Exponentially Convergent Monte Carlo

- Iterative form of Residual Monte Carlo
 - Each batch tallies the **error** in current estimate of solution, which is a transport problem with a reduced source
 - Can reduce statistical error **globally** $\propto e^{-\alpha N}$
 - Does not make difficult problems easier
- Requires a **discretized** form of the angular flux
 - Use **projection** onto space-angle FE mesh
 - Adaptive mesh refinement mitigates truncation error, allowing convergence to be maintained

High-Order Low-Order Algorithm





Outline

- 1 Overview
- 2 Low-Order Solver
- 3 High-Order Solver
- 4 HOLO Algorithm
- 5 Test Problems
- 6 Conclusions



LO Discretization & Space-Angle Moments

- Linear discontinuous (LD) FE in space and half range angular averages



LO Discretization & Space-Angle Moments

- Linear discontinuous (LD) FE in space and half range angular averages



- Examples of moments:

Spatial: left basis

$$\langle \cdot \rangle_{L,i} = \frac{2}{h_i} \int_{x_{i-1/2}}^{x_{i+1/2}} b_{L,i}(x)(\cdot) dx$$

Angular: positive flow

$$\phi^+(x) = 2\pi \int_0^1 \psi(x, \mu) d\mu$$

Forming LO Equations Over an Element

- Taking moments of TE yields **4 equations**, per cell i , e.g.

$$\begin{aligned}
 & -2\mu_{i-1/2}^+ \phi_{i-1/2}^+ + \langle \mu \rangle_{L,i}^+ \langle \phi \rangle_{L,i}^+ + \langle \mu \rangle_{R,i}^+ \langle \phi \rangle_{R,i}^+ + \Sigma_t h_i \langle \phi \rangle_{L,i}^+ \\
 & - \frac{\Sigma_s h_i}{4\pi} \left(\langle \phi \rangle_{L,i}^+ + \langle \phi \rangle_{L,i}^- \right) = \frac{1}{k_{\text{eff}}} \frac{\nu \Sigma_f h_i}{4\pi} \left(\langle \phi \rangle_{L,i}^+ + \langle \phi \rangle_{L,i}^- \right)
 \end{aligned}$$

- Cell unknowns are **moments**: $\langle \phi \rangle_{L,i}^+$, $\langle \phi \rangle_{R,i}^+$, $\langle \phi \rangle_{L,i}^-$, $\langle \phi \rangle_{R,i}^-$

Forming LO Equations Over an Element

- Taking moments of TE yields **4 equations**, per cell i , e.g.

$$\begin{aligned}
 & -2\mu_{i-1/2}^+ \phi_{i-1/2}^+ + \langle \mu \rangle_{L,i}^+ \langle \phi \rangle_{L,i}^+ + \langle \mu \rangle_{R,i}^+ \langle \phi \rangle_{R,i}^+ + \Sigma_t h_i \langle \phi \rangle_{L,i}^+ \\
 & - \frac{\Sigma_s h_i}{4\pi} \left(\langle \phi \rangle_{L,i}^+ + \langle \phi \rangle_{L,i}^- \right) = \frac{1}{k_{\text{eff}}} \frac{\nu \Sigma_f h_i}{4\pi} \left(\langle \phi \rangle_{L,i}^+ + \langle \phi \rangle_{L,i}^- \right)
 \end{aligned}$$

- Cell unknowns are **moments**: $\langle \phi \rangle_{L,i}^+$, $\langle \phi \rangle_{R,i}^+$, $\langle \phi \rangle_{L,i}^-$, $\langle \phi \rangle_{R,i}^-$
- To close system, need angular consistency terms and spatial closure
 - Estimate *average* μ terms from HO solution
 - Use the LD spatial closure, consistent with our HO solver

Computing LO Consistency terms from HO Solution

- For $\mu > 0$, L moment

$$\langle \mu \rangle_{L,i}^+ \simeq \frac{\int_0^1 \int_{x_{i-1/2}}^{x_{i+1/2}} \mu b_{L,i}(x) \tilde{\psi}^{HO}(x, \mu) dx d\mu}{\int_0^1 \int_{x_{i-1/2}}^{x_{i+1/2}} b_{L,i}(x) \tilde{\psi}^{HO}(x, \mu) dx d\mu}$$

Computing LO Consistency terms from HO Solution

- For $\mu > 0$, L moment

$$\langle \mu \rangle_{L,i}^+ \simeq \frac{\int_0^1 \int_{x_{i-1/2}}^{x_{i+1/2}} \mu b_{L,i}(x) \tilde{\psi}^{HO}(x, \mu) dx d\mu}{\int_0^1 \int_{x_{i-1/2}}^{x_{i+1/2}} b_{L,i}(x) \tilde{\psi}^{HO}(x, \mu) dx d\mu}$$

- ECMC gives LDfE representation of $\tilde{\psi}^{HO}(x, \mu)$
 - Evaluate consistency terms directly
 - For initial solve, use S_2 : $\langle \mu \rangle^\pm = \pm \frac{1}{\sqrt{3}}$

Solving LO System with Power Iteration

- Global System:

$$\mathbf{D}(\mu^{HO})\Phi = \frac{1}{k_{\text{eff}}}\mathbf{F}\Phi$$

Solving LO System with Power Iteration

- Global System:

$$\mathbf{D}(\mu^{HO})\Phi = \frac{1}{k_{\text{eff}}}\mathbf{F}\Phi$$

Algorithm

- 1 Guess $\Phi^{(0)}$ and $k_{\text{eff}}^{(0)}$

$$\Phi^{(l+1)} = \frac{1}{k_{\text{eff}}^{(l)}}\mathbf{D}^{-1}\mathbf{F}\Phi^{(l)}$$

$$k_{\text{eff}}^{(l+1)} = k_{\text{eff}}^{(l)} \frac{\int \nu \Sigma_f \phi^{(l+1)} dx}{\int \nu \Sigma_f \phi^{(l)} dx}.$$

Solving LO System with Power Iteration

- Global System: $\mathbf{D}(\mu^{HO})\Phi = \frac{1}{k_{\text{eff}}} \mathbf{F}\Phi$

Algorithm

- 1 Guess $\Phi^{(0)}$ and $k_{\text{eff}}^{(0)}$

$$\Phi^{(l+1)} = \frac{1}{k_{\text{eff}}^{(l)}} \mathbf{D}^{-1} \mathbf{F} \Phi^{(l)}$$


$$k_{\text{eff}}^{(l+1)} = k_{\text{eff}}^{(l)} \frac{\int \nu \Sigma_f \phi^{(l+1)} dx}{\int \nu \Sigma_f \phi^{(l)} dx}.$$

- 2 Accelerate $\Phi^{(l+1)}$ and $k_{\text{eff}}^{(l+1)}$ after each power iteration with Nonlinear Krylov Acceleration (NKA)
- 3 Converge $\Delta\Phi^{(l)}$ and $\Delta k_{\text{eff}}^{(l)}$

Outline

- 1 Overview
- 2 Low-Order Solver
- 3 High-Order Solver**
- 4 HOLO Algorithm
- 5 Test Problems
- 6 Conclusions


Space-Angle LDFE Mesh



- $\tilde{\psi}(x, \mu)$ is linear over each cell, **preserving** 0th and 1st moment in x and μ
- Use path-length estimators of flux to approximate moments e.g.

$$\langle \psi \rangle_{\mu, ij} = \frac{6}{h_{\mu}^2 h_x} \iint_{\mathcal{D}} (\mu - \mu_i) \psi(x, \mu) dx d\mu$$

Space-Angle LDFE Mesh



- $\tilde{\psi}(x, \mu)$ is linear over each cell, preserving 0th and 1st moment in x and μ
- Use path-length estimators of flux to approximate moments e.g.

$$\langle \psi \rangle_{\mu, ij} = \frac{6}{h_\mu^2 h_x} \iint_{\mathcal{D}} (\mu - \mu_i) \psi(x, \mu) dx d\mu$$

- Use standard LD and upwinding to get face terms

High Order System and ECMC Algorithm

- Pure absorber transport problem

$$\left[\mu \frac{\partial}{\partial x} + \Sigma_t \right] \psi(x, \mu) = \frac{1}{4\pi} \left(\Sigma_s + \frac{\nu \Sigma_f}{k_{\text{eff}}^{LO}} \right) \phi^{LO}(x)$$

$$\mathbf{L}\psi = q^{LO}$$

High Order System and ECMC Algorithm

- Pure absorber transport problem

$$\left[\mu \frac{\partial}{\partial x} + \Sigma_t \right] \psi(x, \mu) = \frac{1}{4\pi} \left(\Sigma_s + \frac{\nu \Sigma_f}{k_{\text{eff}}^{\text{LO}}} \right) \phi^{\text{LO}}(x)$$

$$\mathbf{L}\psi = q^{\text{LO}}$$

ECMC Algorithm

- Residual Equation: $\mathbf{L}(\psi - \tilde{\psi}^{(m)}) = q^{\text{LO}} - \mathbf{L}\tilde{\psi}^{(m)}$
 $\mathbf{L}\tilde{\epsilon}^{(m)} = \tilde{r}^{(m)}$

High Order System and ECMC Algorithm

- Pure absorber transport problem

$$\left[\mu \frac{\partial}{\partial x} + \Sigma_t \right] \psi(x, \mu) = \frac{1}{4\pi} \left(\Sigma_s + \frac{\nu \Sigma_f}{k_{\text{eff}}^{\text{LO}}} \right) \phi^{\text{LO}}(x)$$

$$\mathbf{L}\psi = q^{\text{LO}}$$

ECMC Algorithm

- Residual Equation: $\mathbf{L}(\psi - \tilde{\psi}^{(m)}) = q^{\text{LO}} - \mathbf{L}\tilde{\psi}^{(m)}$
 $\mathbf{L}\tilde{\epsilon}^{(m)} = \tilde{r}^{(m)}$
- Compute $\tilde{\epsilon}^{(m)} = \mathbf{L}^{-1}\tilde{r}^{(m)}$ with MC, projecting the solution
- Update: $\tilde{\psi}^{(m+1)} = \tilde{\psi}^{(m)} + \tilde{\epsilon}^{(m)}$

High Order System and ECMC Algorithm

- Pure absorber transport problem

$$\left[\mu \frac{\partial}{\partial x} + \Sigma_t \right] \psi(x, \mu) = \frac{1}{4\pi} \left(\Sigma_s + \frac{\nu \Sigma_f}{k_{\text{eff}}^{\text{LO}}} \right) \phi^{\text{LO}}(x)$$

$$\mathbf{L}\psi = q^{\text{LO}}$$

ECMC Algorithm

- Residual Equation: $\mathbf{L}(\psi - \tilde{\psi}^{(m)}) = q^{\text{LO}} - \mathbf{L}\tilde{\psi}^{(m)}$
 $\mathbf{L}\tilde{\epsilon}^{(m)} = \tilde{r}^{(m)}$
- Compute $\tilde{\epsilon}^{(m)} = \mathbf{L}^{-1}\tilde{r}^{(m)}$ with MC, projecting the solution
- Update: $\tilde{\psi}^{(m+1)} = \tilde{\psi}^{(m)} + \tilde{\epsilon}^{(m)}$
 - If $\tilde{\epsilon}$ is reduced each batch, exponential convergence achieved
 - h -refine when $\epsilon(x, \mu)$ not represented sufficiently
- Repeat until $\|\tilde{\epsilon}\|_2 < \text{tol} \times \|\psi\|_2$

Other MC Details

Improving Statistics and Efficiency

- Particles **only stream**: $w(s) = w_0 e^{-\Sigma_t s}$

Other MC Details

Improving Statistics and Efficiency

- Particles **only stream**: $w(s) = w_0 e^{-\Sigma_t s}$
- Cell-wise, global representation accommodates **stratified** sampling
 - $N_{ij} \propto |r_{ij}(x, \mu)|$
 - Force $N_{ij} \geq N_{\min}$

Other MC Details


Improving Statistics and Efficiency

- Particles **only stream**: $w(s) = w_0 e^{-\Sigma_t s}$
- Cell-wise, global representation accommodates **stratified** sampling
 - $N_{ij} \propto |r_{ij}(x, \mu)|$
 - Force $N_{ij} \geq N_{\min}$
- Initialize $\tilde{\psi}(x, \mu)$ to latest HO solution for first batch

Outline

- 1 Overview
- 2 Low-Order Solver
- 3 High-Order Solver
- 4 HOLO Algorithm**
- 5 Test Problems
- 6 Conclusions

High-Order Low-Order Algorithm



Outline

- 1 Overview
- 2 Low-Order Solver
- 3 High-Order Solver
- 4 HOLO Algorithm
- 5 Test Problems**
- 6 Conclusions

Critical slab benchmark


Problem Parameters

- $k_{\infty} = 2.29$, $\Sigma_t = 0.326 \text{ cm}^{-1}$
- Initially $100 \times$ & 20μ cells
- Adaptive HO convergence

Critical slab benchmark

Problem Parameters

- $k_{\infty} = 2.29$, $\Sigma_t = 0.326 \text{ cm}^{-1}$
- Initially $100 \times 20 \mu$ cells
- Adaptive HO convergence



- $|\Delta\Phi|_{\text{rel}} < 10^{-4}$ in 4 outer iterations, using $\sim 2.4 \times 10^7$ histories

- For 10 independent simulations:

$\overline{k_{\text{eff}}}$	0.999998
$\sigma(k_{\text{eff}})$	0.4 pcm
$\Delta k_{\text{eff}}^{\text{max}}$	1.1 pcm
$\sigma_{\text{rel}}(\phi_i)$	1.4 pcm

Optically thick, near-critical slab


Problem Parameters

- $k_{\infty} = 1$, $\Sigma_t = 5.0 \text{ cm}^{-1}$, $\Sigma_s = 4.5 \text{ cm}^{-1}$, $\text{DR} \simeq \mathbf{0.984}$
- Relative Tolerance of $1.0\text{E-}05$ for HO and LO solvers, $1.0\text{E-}04$ outer

Optically thick, near-critical slab

Problem Parameters

- $k_{\infty} = 1$, $\Sigma_t = 5.0 \text{ cm}^{-1}$, $\Sigma_s = 4.5 \text{ cm}^{-1}$, $\text{DR} \approx 0.984$
- Relative Tolerance of $1.0\text{E-}05$ for HO and LO solvers, $1.0\text{E-}04$ outer




- LO fission source convergence:
 - PI: **389** iterations
 - NKA: **27** iterations
- 3 outer iterations, 4.4×10^6 total histories
- $k_{\text{eff}} = 0.99793$

Comparison of statistical noise for standard and ECMC HO solvers

One HOLO solve, with a fixed 1.5×10^5 histories. Comparison of **ECMC** with 5 batches and standard MC (**SMC**)


Comparison of statistical noise for standard and ECMC HO solvers

One HOLO solve, with a fixed 1.5×10^5 histories. Comparison of **ECMC** with 5 batches and standard MC (**SMC**)



Comparison of statistical noise for standard and ECMC HO solvers

One HOLO solve, with a fixed 1.5×10^5 histories. Comparison of **ECMC** with 5 batches and standard MC (**SMC**)



$$\frac{\|\sigma(\psi^{SMC})\|}{\|\tilde{\epsilon}^{ECMC}\| + \|\sigma(\epsilon^{ECMC})\|} = 16$$

Outline

- 1 Overview
- 2 Low-Order Solver
- 3 High-Order Solver
- 4 HOLO Algorithm
- 5 Test Problems
- 6 Conclusions

Observations & Future Work

- Able to solve for k_{eff} and fission source with HOLO method
 - Pure absorber histories are more efficient than standard MC simulations
 - ECMC works well in HOLO context

Observations & Future Work

- Able to solve for k_{eff} and fission source with HOLO method
 - Pure absorber histories are more efficient than standard MC simulations
 - ECMC works well in HOLO context
- Stratified source sampling produces less variance than a constant number of histories per cell


Observations & Future Work

- Able to solve for k_{eff} and fission source with HOLO method
 - Pure absorber histories are more efficient than standard MC simulations
 - ECMC works well in HOLO context
- Stratified source sampling produces less variance than a constant number of histories per cell
- Need to use the estimated statistical error in tallies for $\tilde{\epsilon}(x, \mu)$
 - Run more particles on refined meshes, monitoring local error
 - Source biasing

Observations & Future Work

- Able to solve for k_{eff} and fission source with HOLO method
 - Pure absorber histories are more efficient than standard MC simulations
 - ECMC works well in HOLO context
- Stratified source sampling produces less variance than a constant number of histories per cell
- Need to use the estimated statistical error in tallies for $\tilde{\epsilon}(x, \mu)$
 - Run more particles on refined meshes, monitoring local error
 - Source biasing
- Working on application to [thermal radiative transfer](#) problems

Marshak Wave Problem, Radiation Temperature Profile



- **IMC**: 100,000 particles per time step
- **HOLO-ECMC**: 15,000 particles per time step

Questions?

Second-Order Discretization in Space and Time for Grey S_2 -Radiation Hydrodynamics

Simon R. Bolding, Joshua E. Hansel, & Jim E. Morel

21 November 2014




Algorithm

- ❶ $\tilde{\psi}^{(0)} = \tilde{\psi}$ or from last batch this time step
- ❷ Using Monte Carlo, $\epsilon^{(m)} = \mathbf{L}^{-1} \tilde{r}^{(m)}$
 - Use volumetric tallies, weighted with x and μ basis moments time ψ to construct LD $\tilde{\epsilon}^{(m)}(x, \mu)$ over the current space-angle mesh
- ❸ $\tilde{\psi}^{(j+1)} = \tilde{\psi}^{(m)} + \tilde{\epsilon}^{(m)}$
- ❹ **IF** error stagnation:
 - Refine mesh based on relative jump error in $\tilde{\psi}(x, \mu)$
- ❺ Repeat 2-4 until $\|\tilde{\epsilon}\|_2 < \text{tol} \times \|\psi\|_2$

Algorithm

- ➊ Initialize $\langle \mu \rangle^\pm$ parameters to S_2
- ➋ Solve LO system using power iteration
- ➌ Build q^{LD} for HO solver, and set $\tilde{\psi}$ to latest HO estimate on coarsest $x-\mu$ mesh
- ➍ Solve $\tilde{\psi}(x, \mu) = \mathbf{L}^{-1} q^{LO}$ using ECMC
- ➎ Compute new $\langle \mu \rangle^\pm$ parameters using $\tilde{\psi}^{HO}$ over LO mesh
- ➏ Repeat 2-5 until $\underline{\Phi}^{LO}$ is converged
- Use adaptive convergence criteria

Space-Angle Mesh and MC Implementation Details



- $\tilde{\psi}(x, \mu) = \psi_{a,i} + \psi_{x,i} \frac{2}{h_x}(x - x_i) + \psi_{\mu,i} \frac{2}{h_\mu}(\mu - \mu_i)$

- Path-length estimators of moments, e.g.

$$\psi_{x,i} = \frac{6}{h_x^2 h_\mu} \iint_{\mathcal{D}} (x_{c,j} - x_i) \psi(x, \mu) dx d\mu$$

- Particles **only stream** $w(s) = w_0 e^{-\Sigma_t s}$
- LDFE and upwinding **eliminates** surface tallies
- Cell-wise, global representation allows for **stratified** sampling
 - $N_{i,j} \propto |r_i(x, \mu)|$
 - Force $N_i \geq N_{\min}$ and adjust particle weights

Overview of Exponentially Convergent Monte Carlo

- We will use ECMC to solve HO transport problem

Overview of Exponentially Convergent Monte Carlo

- We will use ECMC to solve HO transport problem
- An iterative form of residual Monte Carlo, performed in batches
 - Use information about current estimate of solution to solve transport problem with a reduced source
- Can reduce statistical error **globally** $\propto e^{-\alpha N}$
 - Does not make difficult problems easier, but reduces variance

Overview of Exponentially Convergent Monte Carlo

- We will use ECMC to solve HO transport problem
- An iterative form of residual Monte Carlo, performed in batches
 - Use information about current estimate of solution to solve transport problem with a reduced source
- Can reduce statistical error **globally** $\propto e^{-\alpha N}$
 - Does not make difficult problems easier, but reduces variance
- Requires a **discretized** form of the angular flux
 - Use finite element representation
 - Adaptive mesh refinement allows the error to continue to be reduced