# A High-Order Low-Order Algorithm with Exponentially-Convergent Monte Carlo for Thermal Radiative Transfer

Simon Bolding and Jim Morel

4 August 2016

NE UP Nuclear Energy University Programs
U.S. Department of Energy

CERT
Center for Exascale Radiation Transport

We are interested in modeling thermal radiation transport in the high energy density physics regime

Materials under extreme conditions
Temperatures $\mathcal{O}(10^6)$ K or more

Photon radiation transports through a material
Significant energy may be exchanged

We want to improve efficiency of calculations
e.g., inertial confinement fusion, supernovae, et. al.

Our method has been applied to a simplified model: the 1D grey radiative transfer equations

Energy balance equations for radiation and material.

Radiation intensity $I(x, \mu, t)$, material temperature $T(x, t)$

$$\frac{1}{c}\frac{\partial I}{\partial t} + \mu\frac{\partial I}{\partial x} + \sigma_t I(x, \mu, t) = \frac{1}{4\pi}\left(\sigma_a ac T^4 + \sigma_s \phi\right),$$

$$C_v\frac{\partial T(x, t)}{\partial t} = \sigma_a \phi(x, t) - \sigma_a ac T^4$$

Equations are nonlinear and may be tightly coupled

Absorption opacity (σ_a) can be a strong function of T

Implicit Monte Carlo (IMC) is the standard Monte Carlo transport method for TRT problems

The system is *linearized* over a time step $t \in [t^n, t^{n+1}]$
Opacities are evaluated with $T(t^n)$

- Produces a linear MC transport problem
  with effective emission and scattering terms

- Emission source is **not** fully implicit.
  Monte Carlo integration over Δt for intensity

Our high-order low-order (HOLO) method improves on several drawbacks of IMC

Standard IMC	HOLO Method
Large statistical noise possible	ECMC is very efficient for TRT problems
Effective scattering can make MC very expensive	MC solution has no scattering
Linearization can cause non-physical results (maximum principle violations)	Fully implicit time-discretization and LO solution resolves nonlinearities
Reconstruction of linear emission shape limits artificial energy propagation	Linear-discontinuous FE for $T(x)$ preserving equilibrium diffusion limit

A HOLO Algorithm for Thermal Radiative Transfer

Overview of algorithm

Derivation of the LO equations

Exponentially Convergent MC High-Order Solver

Computational Results

Ongoing Research

A HOLO Algorithm for Thermal Radiative Transfer

Overview of algorithm

Derivation of the LO equations

Exponentially Convergent MC High-Order Solver

Computational Results

Ongoing Research

Solve a non-linear low-order system with high-order angular correction from efficient MC simulations

The **LO system** is space-angle moment equations, on a fixed finite-element (FE) spatial mesh

- ▶ Reduced dimensionality in angle
  allows for solution with Newton's method

- ▶ **Output:** linear-discontinuous $\phi(x)$ and $T(x)$
  Construct LDFE scattering and emission source

The **HO system** is a pure-absorber transport problem

- ▶ Solved with exponentially-convergent MC (ECMC)
  for *efficient* reduction of statistical noise

- ▶ **Output:** consistency terms

Iterations between the HO and LO systems are performed each time step

Initialize LO system using $\tilde{I}^n$ → LO Newton solve, fully converged ← Consistency terms

LO Newton solve, fully converged → $T_{LO}^{n+1}(x)$, $\phi_{LO}^{n+1}(x)$ → Outers Complete?

Outers Complete? — yes → Move to next time step

Outers Complete? — no → Construct LDFE emission source → HO ECMC solve for $\tilde{I}^{n+1}(x, \mu)$ → Consistency terms

Move to next time step ⤍ Initialize LO system using $\tilde{I}^n$

A HOLO Algorithm for Thermal Radiative Transfer

Overview of algorithm

Derivation of the LO equations

Exponentially Convergent MC High-Order Solver

Computational Results

Ongoing Research

The LO equations are formed as *consistently* as possible with spatial and angular moments of TRT equations

The time discretization is backward Euler
for both the HO and LO equations

FE basis functions weight spatial moments:

$$\langle\cdot\rangle_{L,i} = \frac{2}{h_i} \int_{x_{i-1/2}}^{x_{i+1/2}} b_{L,i}(x)(\cdot)\mathrm{d}x$$

Half-range integrals reduce angular dimensionality

$$\phi^+(x) = 2\pi \int_0^1 I(x,\mu)\mathrm{d}\mu$$

Apply moments to the TRT equations and manipulate to form angular consistency terms

Ultimately, we get 4 radiation and 2 material equations
for each spatial element i

The streaming terms are algebraically manipulated
to form consistency terms (no approximation here)

For example, apply $\langle \cdot \rangle_{L,i}^+$ to a streaming term:

$$\left\langle \mu \frac{\partial I}{\partial x} \right\rangle_L^+ = -\frac{2}{h_i} \{\mu I\}_{i-1/2}^+ + \langle \mu I \rangle_{L,i}^+ + \langle \mu I \rangle_{R,i}^+$$

$$= -\frac{2}{h_i} \frac{\{\mu I\}_{i-1/2}^+}{\phi_{i-1/2}^+} \phi_{i-1/2}^+ + \frac{\langle \mu I \rangle_{L,i}^+}{\langle \phi \rangle_{L,i}^+} \langle \phi \rangle_{L,i}^+ + \frac{\langle \mu I \rangle_{R,i}^+}{\langle \phi \rangle_{R,i}^+} \langle \phi \rangle_{R,i}^+$$

We can close equations with HO angular information and a linear-discontinuous (LD) spatial discretization

1. Assume $T(x)$ and $T^4(x)$ are LD

2. A lagged $\tilde{I}_{HO}^{n+1}$ is used to evaluate consistency terms

3. Eliminate $\phi_{i+1/2}^{\pm}$ with LD closure preserving equi. diff. limit

$$\phi_{i+1/2}^{+} = 2\langle\phi\rangle_{R,i}^{+} - \langle\phi\rangle_{L,i}^{+}$$

4. Global system solved with Newton's method and lagged **implicit opacities** Energy is always conserved

Use source-iteration with diffusion-synthetic acceleration (DSA) to solve LO equations

In higher dimensions, the scattering terms cannot be directly inverted easily

Use source iteration with WLA-DSA
for (effective) scattering source of each Newton step

1. Sweep for a new $\phi^\pm$
   with a lagged scattering source

2. Solve approximate spatially continuous diffusion equation for error in scattering iterations

3. Update with local balance equations over elements

Recast iterations as DSA-preconditioned Krylov method
to resolve convergence difficulties with inconsistencies

A HOLO Algorithm for Thermal Radiative Transfer

Exponentially Convergent Monte Carlo can efficiently reduce noise globally

Each MC batch tallies the error in the solution

- ▸ standard MC particle transport, but a **complex** source

- ▸ ECMC requires a **functional** representation of $I(x, \mu)$

Can reduce solution error globally $\propto e^{-\alpha N}$
Adaptive h-refinement can help represent error

### $I^n(x, \mu)$ often provides an *excellent* estimate of $I^{n+1}(x, \mu)$
No MC sampling for equilibrium regions

We use a projection $\tilde{I}(x, \mu)$ of the angular intensity onto a LDFE space-angle mesh

local volumetric tallies

$$\tilde{I}_{ij}(x, \mu) = I_a + \frac{2}{h_x}I_x(x - x_i) + \frac{2}{h_\mu}I_\mu(\mu - \mu_i)$$

Each x-μ cell

We apply the ECMC algorithm to
the pure-absorber HO transport equation

$$\left[\mu \frac{\partial}{\partial x} + \left(\sigma_t + \frac{1}{c\Delta t} \right) \right] I^{n+1} = \frac{1}{4\pi} \left[\boxed{\sigma_a ac \left(T_{LO}^{n+1} \right)^4 + \sigma_s \phi_{LO}^{n+1}} \right] + \frac{\tilde{I}^n}{c\Delta t}$$

$$\mathbf{L} I^{n+1} = q$$

For each batch m:

- Evaluate residual source: $r^{(m)} = q - \mathbf{L}\tilde{I}^{n+1,(m)}$

- Estimate $\epsilon^{(m)} = \mathbf{L}^{-1} r^{(m)}$ via Monte Carlo simulation

- Update solution:
$$\tilde{I}^{n+1,(m+1)} = \tilde{I}^{n+1,(m)} + \tilde{\epsilon}^{(m)}$$
$$= \tilde{I}^{n+1,(m)} + \mathbf{L}^{-1} q - \mathbf{L}^{-1} \mathbf{L} \tilde{I}^{n+1,(m)}$$

Our HO system allows for simple variance reduction methods

Histories stream without collision

along path s, weight reduces as $w(s) = w_0 e^{-\sigma_t s}$

Use cell-wise systematic sampling for $|r^{(m)}|$ source

Particularly effective in thick cells

- ▶ Particles in each x-μ cell $\propto |r^{(m)}|$ in cell

- ▶ Set minimum n for cells

  except for cells in thermal equilibrium

A HOLO Algorithm for Thermal Radiative Transfer

Overview of algorithm

Derivation of the LO equations

Exponentially Convergent MC High-Order Solver

Computational Results

Ongoing Research

We will test our method with several standard **Marshak Wave** problems

Results show radiation temperature $T_r = \sqrt[4]{\phi/ac}$

# The HOLO method produces significantly less noise than IMC in a Marshak Wave test problem

- $\sigma_a \propto T^{-3}$

- Transient solution after 5 shakes
 200 x cells and 4 μ cells (for ECMC)

The LDFE representation has higher spatial accuracy than IMC source tilting for two-material problem

Left half is optically thin ($\sigma = 0.2$ cm^{-1}) and right half is thick ($\sigma_a = 2000$ cm^{-1}). ECMC uses 8 μ cells

$t = 5$ (sh)

Legend:
- HOLO-ECMC $N_c = 20$
- HOLO-ECMC $N_c = 200$
- IMC $N_c = 20$
- IMC $N_c = 200$

T (keV) vs x (cm)

ECMC is more efficient than standard MC (SMC) as a HO solver

Different HO solvers: ECMC with 3 batches, standard MC (SMC), and an S_2 solution

# The LDFE discretization for the LO equations preserves the equilibrium diffusion limit

Large constant σ_a and small c_v

Our HOLO method preserves the maximum principle with sufficient nonlinear convergence

- ▶ **Material temperatures** plotted; all simulations end at $t = 0.1$ sh
  $\sigma_a \propto T^{-3}$, c_v is small, $T_{r,inc} = 1$ keV

- ▶ LO Newton iterations required damping

DSA improves convergence of source iteration solution to LO equations

Exponential convergence can be maintained if the LDFE mesh resolves the solution reasonably

A HOLO Algorithm for Thermal Radiative Transfer

Overview of algorithm

Derivation of the LO equations

Exponentially Convergent MC High-Order Solver

Computational Results

Ongoing Research

We need a way to resolve issues when the LDFE representation of the intensity is negative

Negative intensities can occur in optically thick cells
Mesh refinement is of minimal use

$\tilde{I}_{HO}(x, \mu)$ must be positive for consistency terms
to produce a physical, stable LO solution

Independent fix up for LO solution
E.g., lumping or preserving balance with floored $\phi(x)$

Can add source δ to produce a positive projection $\tilde{l}_{pos}$ such that $\tilde{l}_{pos}$ satisfies the latest residual equation

Produce $\tilde{l}_{\mathsf{pos}}$ by scaling $x - \mu$ moments equally,
to estimate source for the next iteration

$$\mathsf{L}\tilde{l}^{(m)} = q - r^{(m)}$$
$$\mathsf{L}\tilde{l}^{(m)}_{\mathsf{pos}} = q - r^{(m)} + \delta^{(m+1)}$$

$$\delta^{(m+1)} = \mathsf{L}\left(\tilde{l}^{(m)} - \tilde{l}^{(m)}_{\mathsf{pos}}\right)$$
$$q \to q + \delta^{(m+1)}$$

We can delay error stagnation
Investigating alternative positive projection of l

A doubly-discontinuous trial space in time allows for a MC temporal closure

Include $\frac{1}{c}\frac{\partial}{\partial t}(\cdot)$ in transport operator **L**
with $T(x)$ still implicit

Sample and track in time
Tally $\tilde{\epsilon}(x, \mu)$ at t^{n+1}

In LO equations parameterize ϕ_{LO}^{n+1}
in terms of **time-averaged** unknowns,
e.g.,

$$\langle\phi\rangle_{L,i}^{n+1} = 2\,\gamma_{L,i}^{HO}\,\overline{\langle\phi\rangle}_{L,i} - \langle\phi\rangle_{L,i}^{n}$$

Discuss briefly resolving issues with negativities, probably in smooth slide

TRY TO GET PARTICLE HISTORY COUNTS FOR SMOOTH PROBLEM

The time-closure parameters preserve the accuracy of MC time-treatment

- ▶ Problem is near void, so temperature uncouples

- ▶ 3 large time steps

Backup slide with timing results

There are short term and long term goals left to investigate

1. Resolving issues with negative intensities
   - Accuracy of added source method

   - Consistency with LO solution

2. Using HO solution to estimate spatial closure

3. Source iterations with DSA for LO system

4. Implement damped Newton method to demonstrate maximum principle preservation in extreme problems

5. (Stretch goal) MC integration in time with consistent LO equations

Backup Slides

Simon Bolding and Jim Morel

Implementation specifics for results in the computational results section

- ▶ The LD representation of $I(x, \mu)$ is negative near the wave-front
    - ▶ Here, no correction is applied to the HO solution, and the LO solution uses lumped LD and S_2 equivalent terms in negative elements

- ▶ For all results
    1. Initial Δt of 0.001 sh (0.01 ns), linearly increased to 0.01 sh by 15% per step

    2. One HO solve per time step (predictor-corrector)
        - ▶ *each HO* solve has 3 ECMC batches

    3. $\sigma_s = 0$

    4. No mesh refinement in ECMC

Solving LO System with Newton's Method

- Linearization:
$$\underline{B}(T^{n+1}) = \underline{B}(T^*) + \left(T^{n+1} - T^*\right) \left.\frac{\partial \underline{B}}{\partial t}\right|_{t^*}$$

- Modified system

$$\left[\mathbf{D}(\mu^{\pm}) - \sigma_a^*(1 - f^*)\right] \underline{\Phi}^{n+1} = f^*\underline{B}(T^*) + \frac{\Phi^n}{c\Delta t}$$

$$\boxed{\hat{\mathbf{D}}\Phi^{n+1} = \underline{Q}}$$

$$f = \left(1 + \sigma_a^* c\Delta t \frac{4aT^{*3}}{\rho c_v}\right)^{-1} \qquad T_i^* = \frac{T_{L,i}^* + T_{R,i}^*}{2}$$

- Equation for T^{n+1} based on linearization that is conservative

- Converge T^{n+1} and $\langle \phi \rangle$ with Newton Iterations

We will use a linear doubly-discontinuous (LDD) trial space to allow for a HO spatial closure


- $\tilde{I}_{HO}(x, \mu)$ will be linear in μ along face
  Error estimated with MC face tallies

- In LO equations use LDD for $\phi^{\pm}$
  The linear interior preserves the EDL

- Parameterize LO spatial closure to eliminate outflow:

$$\phi_{i+1/2}^+ = \frac{3 + \gamma_{i,HO}^+}{2} \langle\phi\rangle_{R,i}^+ + \frac{\gamma_{i,HO}^+ - 3}{2} \langle\phi\rangle_{L,i}^+$$

The angular flux for the two material problem is difficult to resolve near $\mu = 0$

Two Material Problem, comparison in optically thin region

▶ Plot of radiation temperature after 10 time steps

Derivation of LO System

▸ Taking moments of TE yields 4 equations, per cell i, e.g.

$$-2\mu_{i-1/2}^{n+1,+}\phi_{i-1/2}^{n+1,+} + \{\mu\}_{L,i}^{n+1,+}\langle\phi\rangle_{L,i}^{n+1,+} + \{\mu\}_{R,i}^{n+1,+}\langle\phi\rangle_{R,i}^{n+1,+} +$$

$$\left(\sigma_t^{n+1} + \frac{1}{c\Delta t}\right)h_i\langle\phi\rangle_{L,i}^{n+1,+} - \frac{\sigma_s h_i}{2}\left(\langle\phi\rangle_{L,i}^{n+1,+} + \langle\phi\rangle_{L,i}^{n+1,-}\right)$$

$$= \frac{h_i}{2}\langle\sigma_a^{n+1}acT^{n+1,4}\rangle_{L,i} + \frac{h_i}{c\Delta t}\langle\phi\rangle_{L,i}^{n,+}, \quad (1)$$

▸ Cell unknowns: $\langle\phi\rangle_{L,i}^+$, $\langle\phi\rangle_{R,i}^+$, $\langle\phi\rangle_{L,i}^-$, $\langle\phi\rangle_{R,i}^-$, T_L, T_R

▸ Need angular consistency terms and spatial closure (LD)