

Python Notes

Basics

Keywords are words which has special meaning and predefined functionality. Thus, these words cannot be used for any other purpose, such as variable or function names. In the code below, some important keywords (and, def, if, elif, else, for) are demonstrated. The full list of keywords is also provided.

```
import keyword
def my_function():
    for x in range(1, 6):
        if x > 1 and x < 5:
            print("middle")
        elif x == 1:
            print("beginning")
        else:
            print("end")
my_function()
print(keyword.kwlist)

beginning
middle
middle
middle
end
['False', 'None', 'True', 'and', 'as', 'assert', 'async', 'await',
'break', 'class', 'continue', 'def', 'del', 'elif', 'else', 'except',
'finally', 'for', 'from', 'global', 'if', 'import', 'in', 'is',
'lambda', 'nonlocal', 'not', 'or', 'pass', 'raise', 'return', 'try',
'while', 'with', 'yield']
```

An **identifier** is a user-created name given to a variable, function, class, or module in order to identify and use it, as shown below. The function is given the identifier 'sum' and we define its parameter variables as 'x' and 'y'. By giving these objects names, we can use them when calling the function and printing the sum value.

```
def sum(x, y):
    print(x + y)
sum(10, 7)

17
```

In Python, **comments** are written using hashtags or three single/double quotes. Comments are often used to make the code more readable and explain difficult sections. Hashtags are used for short, single line notes, while three quotes are for multi-line explanations. Since the function name 'new_function' below does not explain its purpose, a comment can do so instead. In the rest of the code, single line comments explain the purpose of a certain line

```
'''The function below finds the square of the sum of two numbers x and
In other words, it prints (x+y)^2'''
def new_function(x, y):
    sum = x + y
    print(sum*sum)
new_function(-1, 1) # this function call will print the result 0
# new function(2, 5) this function call will not print anything

0
```

Statements are basic instructions which the interpreter can execute that we write to complete a task. Examples of statements include imports, printing, assignment, conditionals, loops. Statements are usually a single line, but can be extended using the character '\l'.

```
# an import statement
import keyword
# assignment stament continued to two lines
x = 1 + 2 + \
2 + 4 + 5 + 6
# conditional statement
if(x == 20):
    print("yay!") # print statement
# looping statementfor x in range(1, 2):
    print("no!") # print statement

yay!
no!
```

In Python, **indentation** is used to define blocks of code. This is how the interpreter knows that code belongs in the body of an if-statement, within a function definition, or in a loop. Failing to indent will cause an indentation error.

```
x = 4
while x > 1:
    x = x - 1
    print(x) # since the loop was indented correctly, "3 2 1" will be pr

y = 4
while y > 1:
    y = y - 1
print(y) # since the loop is not indented, the same code will print ju.

3
2
1
1
```

A **docstring** is the first line(s) of a function, class, or module and documents the usage and purpose in three quotes. Unlike a regular comment, docstrings are stored as an attribute of their associated object and can be accessed.

```
def mult(x, y):
    """
    Multiplies two numbers and returns the product.

    Args:
        x: first number
        y: second number

    Returns:
        The product the the two parameters
    """
    return x*y
prod = mult(5, 2)
print(prod)
print(mult.__doc__) # we can access the docstring with this call

10

    Multiplies two numbers and returns the product.

    Args:
        x: first number
        y: second number

    Returns:
        The product the the two parameters
```

Strings in Python are indicated through single or double quotes. For multi-line strings, three quotes can be used.

We can find the length of a string using the len() function and search for certain characters within it using the keyword 'in'.

Strings have both **forward** and **backward indexing**. In forward indexing the first character is in position 0 and can be accessed with str[o], the second character is in position 1, and so on. For backward indexing, the last char character is in position -1, the second to last is in -2, and this continues in decreasing values.

Using **string slicing**, we can get a range of characters within a string. For the first 5 characters,we can use str[:5]. str[5:], however, will get the characters from position 5 to the end of the string. To retrieve the characters from position 1 to position 5, we use str[1,6], since the end of the range is not inclusive. Splicing can also be done with backward indexing.

To modify a string, the replace(str1, str2) method can be used to replace all occurences of str1 in the string with str2. The string can also be divided around a certain phrase using the split(str) method. Furthermore, the upper() and lower() functions are used to convert the entire string to uppercase or lowercase, respectively. The strip() function is used to remove all whitespace from the beginning and end of a string. To conjoin two strings together, we simply use to addition operatir '+'.

```
str = " hello, world ".title()
print(str)
str1 = "Say" + str[:7]
# this will print "Say Hello," the first five characters with "Say" c
print(str1)
str2 = str[-7:-1]
# since we used backward indexing, this will print "world"
print(str2)
str = str.replace("world", "Everyone")
# due to the replace function, " Hello, Everyone " will be printed
print(str)
str = str.lower()
# the lowercase version " hello, everyone " will be printed
print(str)
str = str.strip()
# without whitespaces, "hello, everyone" will be printed
print(str)
split_str = str.split(",")
# the string has been split around the comma and stripped, so the seco
print(split_str[1].strip())

Hello, world
Say Hello
world
Hello, Everyone
hello, everyone
hello, everyone
everyone
```