

Mini-project 1

Design of a 2d bridge

Project organization:


- Groups: 3 to 5 students
- 20% of final grade
- Pdf report: maximum 10 pages
- Programming language: **MATLAB**
- Submission: November 13, 2026
- Total workload: 32h (approx. 8h per student)

You are tasked with designing and analyzing a 2d bridge using four fixed anchor points. The bridge must span a 20 meter gap and support a vertical point load applied at the center of the span.

Anchor points and load configuration

The bridge connects the following four supports on a horizontal plane:

- Left outer: $(-1, 0)$
- Left inner: $(0, 0)$
- Right inner: $(20, 0)$
- Right outer: $(21, 0)$



Truss design requirements

The bridge must be modeled as both a planar truss and a planar frame. A vertical point load of 50 kN is applied at node 5, located at a defined height a , that can be chosen freely, and should represent a lower chord joints.

You are required both to perform both a static and a dynamic analysis for each of the three materials listed below, treating each case as a distinct full-bridge design. Compare the results obtains for each material and discuss the differences in terms of the modeling assumptions, planar truss vs planar frame.

Material	E (GPa)	Density (kg/m ³)	Cross-sectional area	Volume cap
Structural steel	200	7850	15–50 cm ²	1 m ³
Reinforced concrete	30	2500	300–600 cm ²	4 m ³
Engineered wood	12	600	30–100 cm ²	1.7 m ³

Static analysis

Each bridge design must strictly adhere to realistic structural behavior by ensuring static performance under load. This means the following two requirements must be satisfied:

1. The entire structure must remain fully within the elastic range of the chosen material—no yielding or permanent deformation is allowed. Additionally, the displacement at any node must not exceed **40 mm**, in accordance with the L/500 criterion.
2. Your designs should aim to optimize the total material volume. The total volume of the structure must not exceed the specified volume cap for each material.

Dynamic analysis

A separate modal analysis must be performed for each of the three trusses corresponding to the different materials. The following requirement must be satisfied:

3. For each design, compute the first three natural frequencies and the corresponding mode shapes. The first natural frequency must *not* fall within the range of **1.5 to 10 Hz**.

Bonus 1: To ensure dynamic stability and avoid resonance with common excitation sources, you should aim for a first natural frequency **above 50 Hz**, where feasible.

Bonus 2: Reproduce one of your MATLAB models (either the planar truss or the 2D beam, for one selected material) in ANSYS. Perform static and modal analyses, then compare with your MATLAB results. Briefly explain any differences.

Deliverables

1. MATLAB:

- Nodes and elements definitions
- Stiffness and mass matrices assembly
- Static and modal analysis
- Plots and visualizations

2. Report:

- Truss layouts with labeled pins and bars,
- Summary of MATLAB results (displacements, stresses, frequencies and mode shapes),
- Discussion of your findings.