

My Class Teacher Guide

This folder contains the Windows version of My Class.

Run The App

Double-click:

```
demo.bat
```

This starts the app with class code **demo**, opens the teacher computer browser, and uses port **5555**.

You may need to run **demo.bat** as an administrator from **cmd**, especially if the teacher's computer has Windows 11.

Replace **demo** with your class code if needed.

Teacher login:

```
Username: t
Password: t
```

The launcher opens the correct teacher computer URL automatically.

The app home page shows the URL and QR code students can use to open the app on their devices.

Students must be on the same Wi-Fi/LAN and use the displayed URL.

Create A New Class

1. Start the app.
2. Sign in as the teacher.
3. Open the **School/Class** page from the app menu.
4. In the **Schools** section, click **Add** and create a school.
5. In the **Classes** section, select the school.
6. Click **Add** and create a class.
7. Enter a class name and a unique class code, for example **S-A-2025**.

Class codes are normalized to uppercase. Use a short, unique code that is easy for students to type. Adding a school or year prefix can help, for example **S-A-2025**.

Give students this link:

```
http://<teacher-computer-ip>:5555/?c=<class-code>
```

Example:

```
http://192.168.1.165:5555/?c=S-A-2025
```

You can also copy `demo.bat`, rename it to something like `S-A-2025.bat`, and change this line:

```
call run.bat demo %*
```

to:

```
call run.bat S-A-2025 %*
```

Then double-click `S-A-2025.bat` to start that class.

To run a class on a different port, pass the port as the second value:

```
.\scripts\run.bat S-A-2025 3333
```

Students can register or sign in using the same class code.

Create A Quiz

Quizzes are stored here:

```
assets\quizzes
```

Create one folder for each quiz:

```
assets\quizzes\my-quiz\  
  quiz.json  
  01\  
    q.json  
    q.jpg  
    a.jpg  
  02\  
    q.json  
    q.jpg  
    a.jpg
```

Use numbered folders such as `01`, `02`, `03` for question order.

quiz.json

Create **quiz.json** in the quiz folder:

```
{
  "name": "My Quiz",
  "title": "My Classroom Quiz",
  "timeLimitSeconds": 30,
  "answerCount": 4
}
```

Values:

- **name**: quiz name shown in the teacher quiz selector.
- **title**: title shown on teacher and student screens.
- **timeLimitSeconds**: default timer for each question, in seconds.
- **answerCount**: optional default number of answer buttons. Use 1, 2, 3, or 4. If omitted, the app uses 4.

q.json

Create **q.json** inside each question folder:

```
{
  "question": "Which planet is known as the Red Planet?",
  "correctAnswer": "2",
  "timeLimitSeconds": 10,
  "answerCount": 4
}
```

Values:

- **question**: question title shown in the app.
- **correctAnswer**: correct answer button number as text, such as "1", "2", "3", or "4".
- **timeLimitSeconds**: optional timer for this question only. If omitted, the app uses **quiz.json timeLimitSeconds**.
- **answerCount**: optional number of answer buttons for this question only. If omitted, the app uses the quiz default.

Images

Each question folder needs:

- **q.jpg**: question image shown while students answer.
- **a.jpg**: answer image shown after the teacher clicks **Show Answer**.

q.jpeg also works for question images, but answer images should be named **a.jpg**.

After Adding Quizzes

Restart the app after adding or changing quiz files. The new quiz should appear in the teacher quiz selector.

If students cannot open the link, check:

- They are on the same Wi-Fi/LAN as the teacher computer.
- Windows Firewall allows the app or port 5555.
- The school or guest Wi-Fi is not blocking device-to-device connections.