## Compiler Top-Down Parse Exercise Summer - 2018

```
Given this Top-Down parse grammar:
  1. <stmt-list> ::= <stmt> { ; <stmt> }
  2. <stmt>
              ::= <assign> | <read> | <write> | <for>
  3. <assign>
              ::= id := <exp>
  4. <exp> ::= <term> { + <term> | - <term> }
  5. <term> ::= <factor> { * <factor> | DIV <factor> }
  6. <factor> ::= id | int | ( <exp> )
  7. <read>
           ::= READ ( <id-list> )
  8. <id-list> ::= id { , id }
  9. <write> ::= WRITE ( <id-list> )
  10. <for> ::= FOR <index-exp> DO <body>
  11. <index-exp> ::= id := <exp> TO <exp>
  12. <body> ::= <stmt> | BEGIN <stmt-list> END
Draw the Top-Down parse tree for this <stmt>
FOR N := 1 TO 20 DO
         BEGIN
              READ ( value );
              sumSQ := sumSQ + value * value;
                   := sum + value
          END
```

· See attached For tree

## Bottom-Up Parse Workshop - Spring 2018

Draw the Parse tree for this **<statement-list>** using the Compiler Precedence Matrix, and the Top - Down Parse Grammar.

The tree should grow up toward the top of the page.

Insert the left / center / right parse precedence markers as you draw the tree. / <  $\bullet$ The parsing is left to right.

· See attached for tree · See below for precedence Markers

mean := sum DIV 20 ; variance := sumSQ DIV 20 - mean \* mean ; WRITE ( mean , variance ) <. > L.

	VAR	DEGIN	END	END	INTER	FOR SCER	READ	WRITE	70 TO	000	/	/	/.	//!	1/+		/*	DIE		/	10	the tree
PROGRAM																				1	<	
VAR	<b>=</b>										⋖	<	V								⋖	
BEGIN			<u> </u>	<b>±</b>		⋖	<	♦			<										<	
END			>_	>							>											
INTEGER	>										>											
FOR READ										÷									<u></u>		<	
WRITE	dies.																		<u></u>			
TO										>					< <	< <	⋖	<	<		<	~
DO			>	$\triangleright$		<	<	<			>										<	
	>		>	>		<	<	<			$\triangleright$	⋖	<b>V</b>	0							<	
	≥	•			<						>											
																					÷	
:=			⊳	⊳					÷		$\triangleright$				<-	⋖	<	<	<		<	<
+			>	$\triangleright$					>	$\triangleright$	$\triangleright$				$\triangleright$	$\triangleright$	<	<	<	$\triangleright$	<	<
Zerly was			➣	>					⊳	>	>				>	$\triangleright$	<	<	< -	>	<	<
*			⊳	>					>	$\triangleright$	$\triangleright$				$\triangleright$	D	$\triangleright$	D	⋖	$\triangleright$	<	⋖
DIA			>	>					>	$\triangleright$	$\triangleright$					>	>	>	V .	>	~	< /
1			7	$\triangleright$					2	1	>		V			∨ ∧				<b>≐</b> ∧	<	<
int	>																			A A		
THE	1											20 300 0174			_	_	1					

## Top-Down <for> @author Sean Connor @date 24 July 2018 FOR DO <body> <index-exp> TO **BEGIN** <stmt-list> END = <exp> <exp> $\{N\}$ <term> <term> <stmt> <stmt> <stmt> <factor> <factor> <read> <assign> <assign> \_\_\_\_\_ int {1} {20} id <exp> <exp> := {sumSQ} {sum} <term> <term> <term> <term> <id-list> READ <factor> <factor> <factor> <factor> <factor> id id {sumSQ} {value} {value} {value} {sum} {value}

