



McDOWELL & ASSOCIATES  
Geotechnical, Environmental, & Hydrogeologic Services  
21355 Hatcher Avenue • Ferndale, MI 48220  
Phone: (248) 399-2066 • Fax: (248) 399-2157

JOB NO. 20-324

SURFACE ELEV. DATE 12-3-20

LOG OF SOIL  
BORING NO. 1

PROJECT Soils Investigation

LOCATION Proposed Houses  
505 Glendale Circle  
Ann Arbor, Michigan

Sample & Type	Depth	Legend	SOIL DESCRIPTION	Penetration Blows for 6"	Moisture %	Natural Wt. P.C.F.	Dry Den Wt. P.C.F.	Unc. Comp. Strength PSF.	Str. %
			0'6" Moist dark brown clayey TOPSOIL with vegetation						
	1								
A	2		Extremely stiff moist brown silty CLAY with sand and pebbles	10					
UL	3			10	15.3				
	4		4'0"	16/3"		*		(9000+)	
B	5								
UL	6								
C	7		Extremely stiff moist brown silty CLAY with sand and pebbles and moist brown silty fine sand seams	30					
UL	8			15/3"					
	9		9'0"	---					
D	10								
UL	11		Very stiff moist variegated silty CLAY with sand and pebbles and moist brown fine to medium sand seams	15					
	12		12'0"	23					
	13			10/2"					
	14		Very stiff moist blue silty CLAY with traces of sand and pebbles						
E	15								
UL	16		15'6"	8					
	17			10					
	18			15					
	19								
	20								
	21								
	22								
	23								
	24								
	25								

TYPE OF SAMPLE

- D. - DISTURBED
- U.L. - UNDIST. LINER
- S.T. - SHELBY TUBE
- S.S. - SPLIT SPOON
- R.C. - ROCK CORE
- ( ) - PENETROMETER

REMARKS: \*Calibrated Penetrometer

GROUND WATER OBSERVATIONS

G.W. ENCOUNTERED AT	FT.	INS.
G.W. ENCOUNTERED AT	FT.	INS.
G.W. AFTER COMPLETION	FT.	INS.
G.W. AFTER	HRS.	FT.
G.W. VOLUMES		INS.
		None

Standard Penetration Test - Driving 2" OD Sampler 1' With  
140# Hammer Falling 30": Count Made at 6" Intervals