

MST03 Broadcast Frame Format

Minew Info Broadcast Frame Data Format

Offset	Length	Type	Data	Details
0	1	Data Length	0x02	Length of AD Structure Data
1	1	Flag Data Type	0x01	AD Type is Flags
2	1	Flag Data	0x06	Flags for 'LE General Discoverable Mode' and 'BR/EDR Not Supported'
3	1	Data Length	/	Length of AD Structure Data
4	1	AD Type	0xFF	AD Type for Manufacturer Specific Data
5	2	Company ID	0x3906	
7	1	Frame Type	0xCA	
8	1	Frame Version	0x00	
9	6	Mac Address	-	LE 0x0165332211AC = AC:11:22:33:65:01
15	1	Battery Level	-	Battery Level Percentage 0x64 = 100%
16	2	Firmware Version	-	
18	8	Peripheral Support	-	
26	1	TBD	0x00	To Be Defined
27	2	Salt	-	
29	2	Digital Signature	-	

Combination Frame Data Format

Offset	Length	Type	Data	Details
0	1	Data Length	0x02	Length of AD Structure Data
1	1	Flag Data Type	0x01	AD Type is Flags
2	1	Flag Data	0x06	Flags for 'LE General Discoverable Mode' and 'BR/EDR Not Supported'
3	1	Data Length	/	Length of AD Structure Data
4	1	AD Type	0xFF	AD Type for Manufacturer Specific Data
5	2	Company ID	0x3906	
7	1	Frame Type	0xCA	
8	1	Frame Version	0x03	
9	1	Block ID	0x20	
10	2	Temperature	-	8.8 Fixed Point 1973 => 25.44°C
12	1	Block ID	0x03	
13	2	X-axis	-	8.8 Fixed Point 0000 => 0.00g
15	2	Y-axis	-	8.8 Fixed Point FF80 => -0.50g
17	2	Z-axis	-	8.8 Fixed Point 013B => 1.23g
19	2	Salt	-	
21	2	Digital Signature	-	