Practice Set 2 — AIP-C01 (Days 1–5 + gap lesson)

Monday 26 Oct 2026 · 45 questions · ~60% hard, ~40% medium · Official formats: multiple choice (4 options) and multiple response

Instructions
Time limit: **105 minutes** (~2.3 minutes per question, the real exam's pace). No notes, no searching. Multiple response questions are graded all-or-nothing. **(Select ALL that apply.)** questions are an extra-hard practice format — the real exam always states how many to select. Answer every question (no penalty for guessing) and mark guesses with **(G)**. Reply as **1-B 2-A,D 3-C …**

Question 1

A retailer must write short alt-text descriptions for 40,000 product photos every night. Testing showed a small model gives acceptable descriptions. Results are needed by the next morning, and cost is the top priority. Which approach should the team use?

A. Submit the photos to a small multimodal model as one batch inference job each evening

B. Send each image's file name and product title to a small text-only model through on-demand inference

C. Call a large multimodal model on demand with response streaming for each photo as it is uploaded

D. Use an image-generation model to regenerate each photo and keep the prompt it used as the description

Question 2

A company's application runs in eu-central-1. Customer data must never be processed outside the European Union. The model the team selected is not offered in eu-central-1, but is offered in other EU Regions. What should the team do?

A. Use Custom Model Import to bring the selected model's weights into eu-central-1

B. Call the model through an EU-geography cross-Region inference profile

C. Move the application to us-east-1, where the model and the most capacity are available

D. Call the model through a global cross-Region inference profile so that capacity is always available

Question 3

Thirty microservices owned by different teams call Amazon Bedrock. The security team must be able to change the approved model used by all services within an hour, without any team redeploying, and any change must be checked against a list of allowed models before it reaches the services. What should the platform team build?

A. Ask each service to read the model ID from an environment variable that the central team updates through pull requests

B. A service control policy that denies every model except the approved one in all accounts

C. A central AWS AppConfig configuration profile with a JSON Schema validator of allowed models, read by every service at runtime

D. Bedrock Intelligent Prompt Routing configured separately in each of the thirty services

Question 4

Version 5 of a fine-tuned model must replace version 4 on an Amazon SageMaker AI endpoint. Version 5 should first receive 10% of traffic for 30 minutes and must revert automatically if the endpoint's p99 latency alarm fires; otherwise it should take all traffic. What should the team do?

A. Update the endpoint with a blue/green deployment that uses canary traffic shifting and CloudWatch alarm auto-rollback

B. Create a separate endpoint for version 5 and adjust weighted Amazon Route 53 records by hand during the window

C. Replace the model artefact in the endpoint's existing S3 location and restart the endpoint

D. Mark version 5 as Approved in SageMaker Model Registry so that it becomes the active version

Question 5

A Bedrock model used by a production assistant reaches end-of-life in 60 days. The company wants to move to a successor with the least risk to users. Which combination of steps should it take? (Select TWO.)

A. Fine-tune the current model now so that the custom copy remains callable after the base model retires

B. Compare candidate successors with a model evaluation job on production-like prompts

C. Switch to the chosen successor through runtime configuration with a gradual rollout and alarm-based rollback

D. Keep the current model ID, because Bedrock forwards calls to the successor model after end-of-life

E. Purchase Provisioned Throughput for the current model so that it stays available after end-of-life

Question 6

A team self-hosts a 34-billion-parameter model at 16-bit precision on SageMaker AI. Its instance has four GPUs with 24 GB of memory each, so the model does not fit on a single GPU. Precision must not be reduced. How should the team serve the model?

A. Lower the maximum output tokens so that the model needs less memory to load

B. Run the model on one GPU and let the container spill the remaining weights to the instance's CPU memory

C. Quantise the model to 4-bit so that it fits on one GPU

D. Use a Large Model Inference container with tensor parallelism across the four GPUs

Question 7

A fine-tuned Bedrock model serves an internal fraud-review tool with a constant, predictable load around the clock. The business cannot accept throttled requests. Which deployment option fits best?

A. Provisioned Throughput with a commitment term sized to the steady load

B. Batch inference jobs submitted every hour

C. A cross-Region inference profile for the custom model

D. On-demand inference with SDK retries and exponential backoff

Question 8

In a support assistant, about 80% of questions are routine (order status, opening hours) and 20% are complex disputes. The company wants to cut model costs without lowering answer quality on the complex disputes. Which approach fits best?

A. Buy Provisioned Throughput for the large model so that each request costs less

B. Answer with a small model first and pass the question to a larger model only when the answer fails validation

C. Distil one small model from the large model and use it for every question

D. Send every question to a small model and instruct it to reply that a human will follow up when unsure

Question 9

Legal questions should reach a large model paired with the legal knowledge base, coding questions should reach a code-specialised model, and everything else should go to a small model. Compliance wants a reviewable record of why each request went where it did. Which combination should the team implement? (Select TWO.)

A. A weighted Lambda alias that sends one third of the traffic to each model

B. Bedrock Intelligent Prompt Routing configured across the three different providers

C. An AWS Step Functions Choice state that branches to the matching model call, with execution history retained

D. A first step that labels each request's category using a small, inexpensive model

E. API Gateway mapping templates that select the model from the request path

Question 10

A Lambda function behind an API Gateway REST API generates detailed reports that take about three minutes. Clients receive gateway timeout errors. Users are happy to wait a few minutes for the report. What should the developer do?

A. Send each report request as its own Bedrock batch inference job

B. Accept the request, queue the job in Amazon SQS, generate the report in a worker, store it in S3, and let clients check its status

C. Switch to a much smaller model so that every report is generated within the timeout

D. Raise the Lambda function's timeout to 15 minutes

Question 11

In an interactive writing assistant, answers must appear word by word, and users can send corrections and follow-up messages while an answer is still arriving, all within the same open session. What should the team use between the browser and the backend?

A. The browser polling an S3 object for partial results every second

B. An Amazon SQS FIFO queue per user that the browser reads from

C. An API Gateway WebSocket API, with Lambda posting each generated chunk to the client's connection

D. An API Gateway REST API with Lambda response streaming

Question 12

Requests pass through API Gateway, a Lambda function, a knowledge base lookup and a Bedrock model call. After a release, p95 latency rose from 3 to 9 seconds. The team needs a timing breakdown for individual requests across every step. What should it use?

A. AWS CloudTrail events for the Bedrock API calls

B. AWS X-Ray tracing on API Gateway and Lambda, with the SDK calls instrumented

C. The Lambda Duration metric in Amazon CloudWatch

D. Bedrock model invocation logging to Amazon S3

Question 13

During daily peaks, users of a chat assistant see errors because Bedrock returns ThrottlingException. About half of the traffic is non-urgent summarisation that can finish within an hour. The team wants fewer user-visible failures without buying dedicated capacity. Which actions should it take? (Select THREE.)

A. Increase the Lambda function's memory allocation

B. Also retry ValidationException errors with backoff

C. Switch the model ID to a geographic cross-Region inference profile

D. Enable SDK retries with exponential backoff and jitter

E. Raise the Lambda function's reserved concurrency so that more requests run in parallel

F. Send the non-urgent summarisation requests to an SQS queue processed at a steady rate

Question 14

A knowledge base uses a Confluence data source. Pages change throughout the day, and answers must reflect edits within about 15 minutes. The team wants a serverless solution with minimal effort. What should it do?

A. Delete and re-create the knowledge base every night

B. Run StartIngestionJob for the Confluence data source every 15 minutes from Amazon EventBridge Scheduler

C. Increase the number of retrieved results so that newer pages are included

D. Export Confluence pages to S3 by hand each week and sync that bucket instead

Question 15

Employees in twelve countries use an HR assistant. Policies differ by country, and answers sometimes mix rules from several countries. Each user's country is available in their sign-in token. What should the team do?

A. Create one guardrail per country with denied topics for every other country's policies

B. Increase the chunk size so that each chunk contains a full country policy

C. Add an instruction to the system prompt telling the model to answer using the user's country

D. Record each document's country as a metadata attribute and filter retrieval using the country from the token

Question 16

A team already runs an Amazon OpenSearch Service cluster with custom analysers and scoring for product search. It wants to add semantic search using an Amazon Titan embedding model, without writing an embedding pipeline in its application code. What should it do?

A. Migrate the catalogue to Aurora PostgreSQL with pgvector and query it with SQL

B. Configure neural search in the existing cluster with an ML connector to Amazon Bedrock

C. Create a Bedrock knowledge base with a quick-create OpenSearch Serverless vector store

D. Write a Lambda function that embeds every product and writes the vectors into the cluster

Question 17

A single vector index holds 400 million vectors for five business units. Each query only ever needs one business unit's data, the units have different freshness requirements, and search latency is too high. What should the team do?

A. Enable hybrid search on the existing index

B. Add replica shards to the existing index

C. Increase the embedding dimensions to make matches more precise

D. Create one index per business unit and send each query to its unit's index

Question 18

Which statements about scaling an Amazon OpenSearch Service vector index are correct? (Select ALL that apply.) [extra-hard practice format — the real exam states the number]

A. Replica shards can answer search requests, which increases read throughput

B. Adding replicas reduces the amount of data each primary shard holds

C. Replicas let the index keep serving when a node holding a primary shard fails

D. A query runs on the relevant shards in parallel, and their results are merged

E. Approximate nearest-neighbour settings trade search recall against latency

F. A search stops at the first shard that returns a matching vector

Question 19

A single file contains 2,000 independent question-and-answer pairs of roughly 100 tokens each. After ingestion with default chunking, retrieved chunks often contain the end of one answer and the start of an unrelated one. What should the team do?

A. Use a custom Lambda chunking function that splits the file at each question boundary

B. Increase the fixed-size chunk overlap to 50%

C. Enable hybrid search so that exact question wording is matched

D. Switch to hierarchical chunking with large parent chunks

Question 20

Users ask questions in Spanish and Portuguese. Documents are in English and Spanish. Retrieval is poor for Portuguese questions, and the current embedding model was trained mostly on English. What should the team do?

A. Choose an embedding model with strong multilingual support, re-embed the documents, and evaluate retrieval for each language

B. Increase the current model's embedding dimensions to 1024

C. Add a rerank model on top of the current retrieval results

D. Translate every document into Portuguese with Lambda and keep the current embedding model

Question 21

Analysts ask questions such as "How did revenue and headcount change in EMEA and APAC compared with last year?". The knowledge base returns chunks covering only one region or one metric. The team wants the least development effort. What should it do?

A. Pass the sessionId from the previous RetrieveAndGenerate call

B. Increase the chunk size so that each chunk covers more regions

C. Enable query decomposition on the RetrieveAndGenerate call

D. Lower the generation model's temperature

Question 22

Searches for "cheap flights to Bombay" miss documents that say "low-cost fares to Mumbai". Hybrid search is already enabled. The team is willing to add a custom step before retrieval. What should it do?

A. Re-embed the documents with more embedding dimensions

B. Enable implicit metadata filtering on the destination attribute

C. Split the question into separate sub-questions for flights and destinations

D. Have an FM generate alternative phrasings of the question, retrieve for each, and merge the results

Question 23

Three agent teams use different frameworks. All of them must query the same vector store with consistent authentication and a consistent response format. What should the platform team provide?

A. Direct OpenSearch REST access, with each team managing its own credentials and parsing

B. A retrieval tool exposed through an MCP server that each team's MCP client calls

C. Instructions in each agent's system prompt describing how to search the store

D. A separate copy of the index for each team

Question 24

A team with no existing database wants managed retrieval-augmented generation over documents in S3, with vectors stored and managed automatically and the least operational effort. What should it use?

A. Amazon RDS for PostgreSQL with pgvector and custom ingestion Lambda functions

B. A self-managed OpenSearch cluster on Amazon EC2

C. An Amazon DynamoDB table storing vectors as item attributes

D. A Bedrock knowledge base with a quick-create vector store

Question 25

A chatbot uses the Converse API. Each call sends only the user's latest message, and the model keeps losing track of earlier parts of the conversation. What should the developer change?

A. Send the full alternating user and assistant message history on each call

B. Switch to a model with a larger context window

C. Raise the temperature so that the model infers missing context

D. Copy the previous answers into the system prompt on every call

Question 26

An agent must remember each customer's preferred language and seat type across conversations weeks apart. Raw conversation records must be deleted after 7 days. What should the developer implement?

A. The preferences written into the agent's system prompt

B. A DynamoDB table of transcripts with a 7-day time to live, loaded at the start of each session

C. AgentCore Memory with a 7-day expiry for short-term events and a long-term user-preference strategy per user

D. A knowledge base that ingests all transcripts nightly

Question 27

A retailer has twelve specialist agents. Each customer message should reach the single most suitable specialist, and follow-up messages should keep their conversational context, with minimal custom routing code. What should the team use?

A. A swarm in which specialists hand messages to each other until one accepts

B. A supervisor agent that sends every message to all twelve specialists and merges the replies

C. One agent that holds all twelve specialists' tools

D. AWS Agent Squad with its classifier-based routing

Question 28

A team needs an agent loop in which every reasoning step, tool call and tool result is recorded and can be inspected visually afterwards. The tools are Lambda functions. What should the team build?

A. A single Lambda function with a while loop that prints each step to its logs

B. A prompt flow with fixed nodes for three tool calls

C. An AWS Step Functions state machine that loops through a model call, a choice of tool, and a Lambda task

D. A Bedrock batch inference job that processes the steps in order

Question 29

An internal agent can call tools that modify HR records. It must never run longer than 5 minutes, never make more than 20 tool calls per request, and, even if manipulated by a crafted prompt, must not change records outside the requester's department. Which combination of controls meets these requirements? (Select THREE.)

A. A workflow-level TimeoutSeconds of 300 on the Step Functions state machine

B. Response streaming so that users can stop long-running answers

C. Storing every tool result in DynamoDB for later review

D. A loop counter checked by a Choice state that ends the loop after 20 tool calls

E. AWS X-Ray tracing on every tool call

F. Least-privilege roles for the tool functions plus department-scoped authorisation checks in the tool code

G. A higher temperature so that the agent explores fewer repeated tool calls

Question 30

Three different models sometimes return different labels for the same content-moderation item. The company wants a final decision rule that improves accuracy and surfaces uncertain items. Which rule fits best?

A. Always use the label from the model with the highest public benchmark score, and log the others

B. Use whichever label arrives first to keep latency low

C. Ask a fourth model to rewrite the three labels as one combined sentence

D. Take the label most models agree on, and send items without a majority to human review

Question 31

A team wants users to rate each answer with thumbs up or down, and later analyse ratings by prompt and model version. What should it build?

A. Bedrock model invocation logging alone

B. A support email address where users send feedback

C. An API Gateway endpoint and Lambda function that store request ID, prompt, answer, model version and rating in DynamoDB

D. AWS CloudTrail logging of the Bedrock API calls

Question 32

A create_ticket tool receives priority values like "urgent!!" and requests with no customer ID. Which combination makes the tool reliable? (Select TWO.)

A. Quietly replace any invalid priority with low without telling the model

B. Restrict priority to an enum in the tool's input schema and mark customer_id as required

C. Validate inputs in the tool's Lambda function and return a descriptive error result the model can act on

D. Remove the priority parameter so that it can never be wrong

E. Increase the model's max tokens so it writes complete parameters

Question 33

A document-conversion tool needs 2 GB of libraries, keeps frequently used templates cached in memory, and some jobs run for 25 minutes. It must be exposed to agents through MCP. Where should the MCP server run?

A. Amazon ECS on AWS Fargate

B. AWS Lambda behind API Gateway

C. An AWS Step Functions Express workflow

D. An API Gateway mock integration

Question 34

An existing Bedrock agent (Agents Classic) sometimes invents missing values such as order numbers instead of asking the customer. What should the developer configure?

A. Configure return of control for every action group

B. Attach a knowledge base that contains example order numbers

C. Enable the agent's built-in User input capability

D. Mark every action parameter as optional so that the agent can proceed without them

Question 35

A developer's Converse tool loop fails with a validation error after the model requests a tool. The developer sends the tool's output back as a new message with role assistant containing plain text. What is the correct way to return tool output?

A. A message with role user containing toolResult blocks, each referencing the matching toolUseId

B. Add the tool output to the system prompt and resend the original messages

C. Keep role assistant but wrap the output in a toolUse block

D. Start a new conversation that contains only the tool output

Question 36

Lambda functions in private subnets with no NAT gateway must call a Bedrock knowledge base and invoke models. Security requires that any Bedrock call not arriving through the company's private connections is refused. What should the team configure?

A. A gateway endpoint for Amazon S3 and a security group allowing HTTPS

B. A NAT gateway with a security group restricted to AWS IP ranges

C. Interface endpoints for bedrock-runtime and bedrock-agent-runtime, plus an IAM deny when aws:SourceVpce is not one of them

D. An interface endpoint for the bedrock control-plane service only

Question 37

Analysts must test prompts on real support transcripts. Names and phone numbers must be replaced with consistent placeholders so that conversations remain readable. What should the team do?

A. Apply a guardrail that blocks any prompt containing PII

B. Detect PII with Amazon Comprehend and replace each entity with a type placeholder such as [NAME] before use

C. Encrypt the transcripts with a customer managed KMS key

D. Add an S3 Lifecycle rule that deletes transcripts after 30 days

Question 38

An analytics agent queries a data lake through Amazon Athena. It must never see the salary column of the employees table, while HR analysts can. What should the team use?

A. An S3 bucket policy denying the agent access to the employees prefix

B. AWS Lake Formation column-level permissions for the agent's role

C. A guardrail word filter for the word salary

D. A system prompt instruction telling the agent to ignore salaries

Question 39

Which statements about data privacy in Amazon Bedrock are correct? (Select ALL that apply.) [extra-hard practice format — the real exam states the number]

A. Prompts and responses are not used to train the base models

B. A global cross-Region inference profile can process requests outside your geography

C. Requests are always processed in the Region you call, even when using inference profiles

D. Prompts are shared with the model provider to improve future versions

E. Prompts and outputs are stored only if you enable model invocation logging

Question 40

The security team wants an alert within minutes whenever any principal other than an approved application role invokes Bedrock models in a production account. What should it implement?

A. Attach a guardrail to every model call

B. Enable AWS X-Ray sampling on the application

C. Enable model invocation logging to S3 and review the logs monthly

D. Capture Bedrock API activity with AWS CloudTrail and alert through an EventBridge rule or metric filter on unapproved principals

Question 41

A policy assistant sometimes states facts that aren't in the retrieved documents and sometimes answers a different question than the user asked. Both kinds of response must be blocked automatically, with minimal custom code. What should the team configure?

A. A guardrail contextual grounding check with both grounding and relevance thresholds

B. Temperature 0 and top-p 0.1 on the generation model

C. A rerank model with twice as many retrieved results

D. A metadata filter that limits retrieval to policy documents

Question 42

An extraction feature returns slightly different invoice numbers for the same email on repeated runs, although the number is clearly present in the text. What should the developer change first?

A. Switch to a model with a larger context window

B. Add a stop sequence after the invoice number

C. Lower the temperature

D. Increase the maximum output tokens

Question 43

Generated summaries regularly end mid-sentence. The response metadata shows the model stopped because of a length limit. What should the developer do?

A. Add a stop sequence at the end of each paragraph

B. Retry the request with exponential backoff

C. Lower the temperature to make answers shorter

D. Increase the maximum output tokens for the request

Question 44

Before rolling out a new chunking strategy, a team must show that retrieved passages are more relevant and that final answers stay faithful to the sources, using managed tooling. Which combination should it run? (Select TWO.)

A. A guardrail word filter on the generated answers

B. A Bedrock Evaluations retrieve-only RAG evaluation that scores context relevance and coverage

C. A Bedrock Evaluations retrieve-and-generate RAG evaluation that scores faithfulness and correctness

D. A CloudWatch dashboard of model invocation latency

E. AWS X-Ray traces of the retrieval calls

Question 45

A client calls Bedrock and receives various errors. Which of these errors should the client fix in the request or configuration rather than retry with backoff? (Select ALL that apply.) [extra-hard practice format — the real exam states the number]

A. ServiceUnavailableException during a brief service disruption

B. AccessDeniedException because the role lacks bedrock:InvokeModel

C. ThrottlingException during a traffic peak

D. ValidationException because the input is longer than the model's context window

E. ModelNotReadyException while capacity is being prepared

Answer sheet

Q	Answer	Q	Answer	Q	Answer
1		16		31	
2		17		32	
3		18		33	
4		19		34	
5		20		35	
6		21		36	
7		22		37	
8		23		38	
9		24		39	
10		25		40	
11		26		41	
12		27		42	
13		28		43	
14		29		44	
15		30		45	