



EcoGuard Primer

Product Overview

EcoGuard Primer is a water-based, eco-friendly primer suitable for both interior and exterior surfaces. Designed to promote excellent adhesion and superior coverage, it is ideal for use before applying a variety of water-based or latex paints. EcoGuard Primer is low-odor and formulated to minimize environmental impact, making it perfect for residential and commercial applications.

Ideal For:

- Drywall
- Plaster
- Masonry
- Wood

EcoGuard Primer effectively seals porous substrates, evens out absorption rates, and prepares surfaces for a flawless finish.

Surface Preparation

Proper preparation is vital to achieve the best performance and durability from EcoGuard Primer. Follow these steps carefully:

1. Cleaning:
 - Remove all dust, dirt, oil, grease, and any traces of mildew using a damp cloth, mild detergent, or mildew remover.
 - Allow surfaces to dry thoroughly before proceeding.
2. Sanding:
 - Lightly sand glossy, painted, or uneven surfaces to dull the sheen and promote better primer adhesion.
 - Use fine-grit sandpaper (150–220 grit) and wipe off any dust after sanding.
3. Patching:
 - Fill holes, cracks, or imperfections with an appropriate patching compound or filler.



EcoGuard Primer

- Allow to dry, then sand smooth and clean off dust.

Tip: Always ensure that patched and sanded areas are completely clean and dry before priming.

Application Instructions

Tools Required:

- Synthetic or nylon-bristle brush
- High-quality roller (3/8" nap recommended)
- HVLP (High Volume, Low Pressure) sprayer

Preparation:

- Stir EcoGuard Primer thoroughly with a clean stir stick prior to application and occasionally during extended use.

Technique:

1. Apply a consistent, generous but controlled coat to the prepared surface.
2. Avoid over-application, which may cause streaks, runs, or extended dry times.
3. For best results, complete one wall or area at a time, maintaining a wet edge.
4. Use a brush for cut-in work (edges and corners), and a roller or sprayer for larger expanses.

Coverage:

- 300–350 sq. ft. per gallon, depending on surface texture and porosity.
- Highly absorbent or rough surfaces may reduce coverage.

Recommended Conditions:

- Apply when ambient and surface temperatures are between 50°F and 90°F (10°C–32°C).
- Avoid priming in excessively humid (above 80%) or below-grade, unventilated spaces unless proper airflow is provided.



EcoGuard Primer

Page 2

Drying & Recoating

- Touch Dry: 30 minutes under ideal conditions (70°F, 50% relative humidity).
- Ready to Recoat: 2 hours.
- Dry times may be extended in cooler temperatures or higher humidity.
- Ensure primer is fully dry before applying topcoat for best results.

Cleanup & Disposal

- Clean brushes, rollers, sprayers, and pans promptly with warm soapy water.
- Rinse all equipment thoroughly before the primer dries.
- For skin contact, wash with warm water and soap.
- Do not pour leftover primer or rinse water down drains; dispose of according to local waste regulations.

Product Compatibility

- EcoGuard Primer is compatible with most water-based and latex paints.
- Highly recommended as a base coat for NatureTint and UltraCover product lines.
- For specialty topcoats (e.g., solvent- or oil-based), spot test for adhesion or consult manufacturer guidelines.

Storage & Handling

- Store EcoGuard Primer in a cool, dry location.
- Keep container tightly sealed when not in use.
- Do not freeze. Protect from temperatures below 32°F (0°C).
- Keep away from direct sunlight and excessive heat.

Application Tips



EcoGuard Primer

- Always stir well before and during application for consistency.
- Test the primer in an inconspicuous area if unsure about surface compatibility.
- Maintain good airflow during application and drying.
- Do not apply in damp or rainy weather on exterior surfaces.
- For best finish, lightly sand and dust wipe after priming and before top coating, especially on wood.

Frequently Asked Questions

Q: Do I always need primer?

A: Not for previously painted, sound, non-glossy or stain-free surfaces, but it's highly recommended for new, bare, porous, patched or stained surfaces.

Q: Can I tint EcoGuard Primer?

A: Yes, it may be lightly tinted with universal colorants to closely match your topcoat for easier coverage.

Q: What if my primer freezes?

A: If frozen, do not use; freezing damages product integrity.

For additional support or detailed application videos, visit our website or contact our technical support team.