



Rain Shield Exterior

Product Overview

All-Weather Acrylic-Latex Exterior Paint is a high-performance, water-based coating designed for outstanding durability across a variety of exterior surfaces. Engineered for longstanding color retention, mildew resistance, and superior adhesion, it is ideal for residential and commercial exterior applications.

Ideal For Use On:

- Concrete
- Brick
- Fiber cement
- Stucco
- Wood siding

Features & Benefits:

- Durable all-weather formula
- UV and mildew resistant
- Provides up to 10 years of surface protection

Surface Preparation

Proper surface preparation is critical for maximizing paint adhesion and durability.

Please follow all steps for best results:

1. Cleaning:

- Remove loose dirt, debris, chalk, mildew, or peeling paint using a pressure washer.
 - Set the washer to a safe pressure setting to avoid surface damage.
 - Use a cleaning solution suitable for exteriors if necessary.

2. Rinse and Dry:

- Rinse thoroughly to remove all cleaning agents and residue.
- Allow surface to dry completely before painting—typically, this requires 24 hours



Rain Shield Exterior

of good drying conditions.

- Inspect for and repair cracks, chips, or holes with appropriate sealant or filler, then allow repairs to cure and sand smooth if necessary.

NOTE: Painting over damp or dirty substrates can result in poor adhesion and premature paint failure.

Application Instructions

Tools:

- 3/8" nap roller for textured, masonry, or rough surfaces
- Airless sprayer for larger or hard-to-reach areas (see sprayer instructions for proper tip size and pressure)
- Quality nylon or polyester brush for cutting in at edges and trim

Before You Start:

- Stir paint thoroughly with a paddle or mechanical shaker to ensure color uniformity and consistency. Repeat stirring every couple hours during use.

How to Apply:

1. Plan Your Timing: Avoid painting in direct sunlight or when rain is expected within 6 hours for optimal results.
2. Start with Edges: Use a brush to cut in edges, corners, and trim.
3. Large Surfaces: Apply paint using a 3/8" nap roller or properly equipped airless sprayer.
4. Finish One Wall at a Time: For multi-surface projects, complete one area or elevation at a time to maintain a wet edge and avoid visible lap marks.
5. Apply Evenly: Roll or spray in straight, overlapping strokes to ensure uniform coverage. Do not overwork the paint.

Environmental Conditions:

- Apply when air and surface temperatures are between 55°F and 95°F (13–35°C).
- Optimal humidity level is below 80%. Avoid application in high humidity, extreme heat, or cold.

Coverage:



Rain Shield Exterior

- 250–300 sq. ft. per gallon on rough surfaces (expect higher coverage on smoother, less porous substrates).
- Coverage may vary depending on texture, porosity, and application method.

Dry Time & Recoat

- Touch Dry: 1 hour (at 77°F/25°C and 50% relative humidity)
- Rain-Ready: 6 hours—do not expose freshly painted surfaces to rain or heavy moisture during this period
- Recoat: After 4 hours, if additional coats are needed

NOTE: Allow extra drying time in cool, damp, or humid conditions, or for very thick applications.

Cleanup & Storage

Tools:

- Clean all brushes, rollers, and sprayers with soap and water immediately after use, before paint dries.

Leftover Paint:

- Do not pour left-over paint or rinse water into drains or sewers. Dispose of according to local regulations.

Storage:

- Keep paint containers tightly closed when not in use
- Store indoors, off the floor, and away from heat, sparks, open flames, and freezing temperatures.
- Do not let paint freeze.

Durability & Maintenance

- UV Resistant: Resists fading and chalking from sunlight
- Mildew Resistant: Protective finish guards against mold and mildew growth
- Longevity: Provides up to 10 years of protection with proper application and



Rain Shield Exterior

maintenance

Care Tips:

- Inspect painted surfaces annually for damage and clean gently with a hose and soft brush
- Touch up chips or worn areas promptly to maintain protection

Professional Tips

- *Apply between 55°F–95°F for best results.*
- *Work top-down on each wall to manage drips and runs.*
- *Always maintain a wet edge to avoid lap marks, particularly in hot or breezy conditions.*
- *Start early in the day to avoid afternoon sun and rapid drying.*
- *Wear appropriate safety equipment when pressure washing or spraying.*

Frequently Asked Questions

What kind of primer should I use?

- For unpainted and highly porous surfaces, a high-quality exterior masonry or wood primer is recommended.

Can I paint over chalky or peeling surfaces?

- All loose or chalky material must be removed. Repair and prime as needed before painting.

How long does it really last?

- With proper preparation and application, the finish can last up to 10 years.

Questions or support needed? Contact our technical support team or visit our website for more detailed guides and video demonstrations.