



Rust Block Enamel

Product Overview

RustBlock Enamel is a high-performance, direct-to-metal enamel formulated specifically to protect rust-prone outdoor surfaces. It delivers long-lasting protection and an attractive finish in a single step, blocking corrosion and sealing out moisture and contaminants.

Ideal For

- Metal fences
- Railings
- Outdoor furniture
- Tools
- Gates

RustBlock Enamel is suitable for use on most ferrous metal surfaces commonly exposed to weather and moisture.

Surface Preparation

Proper surface preparation is critical to achieve maximum protection and adhesion. Inadequate prep may result in peeling, insufficient coverage, or continued rusting.

1. Remove Rust and Loose Material

- Use a wire brush or abrasive wheel to remove loose rust, previous coatings, and all flaking material.
- For heavily corroded surfaces, consider using a rust converter on deep pitting.

2. Degreasing

- Clean thoroughly with mineral spirits to remove grease, oil, wax, fingerprints, or other contaminants.
- Wipe surface with a clean, lint-free cloth soaked in mineral spirits; repeat if necessary until wipe comes away clean.

3. Final Preparation

- Ensure the metal is completely dry and free of dust before painting.
- Use compressed air or a dry cloth to remove any sanding dust or debris



Rust Block Enamel

immediately before coating.

Tip:

For best results, complete all preparation steps immediately before applying RustBlock Enamel to prevent flash rusting.

Application Method

Recommended Equipment:

- Natural-bristle brush for precision and even coating
- Filtered sprayer for large or irregular surfaces (use appropriate filter size to avoid clogging)

Instructions:

1. Do Not Thin:
Apply RustBlock Enamel at full strength; thinning may compromise coverage and rust protection.
2. Stir Thoroughly:
Vigorously stir the paint with a paint paddle or mechanical stirrer before and during use to ensure uniform color and performance.
3. Application:
 - Apply an even coat, avoiding drips or runs.
 - For best protection, ensure full coverage, including weld points, seams, and corners.
 - Seal edges and inaccessible spots with a small brush.
 - For sprayer use, filter paint before filling to prevent tip clogging.

Environmental Conditions:

- Apply only in dry weather with moderate temperatures.
- Surface and air temperatures must be above 50°F (10°C) throughout the application and drying period.
- Avoid painting in high humidity (over 80%) or if rain is expected within 24 hours.

Coverage



Rust Block Enamel

- Coverage Rate: 300 sq. ft. per gallon on smooth, properly prepared metal.
- Note: Coverage will decrease on rough or irregular surfaces.

Page 2

Dry Time

- Tack-Free: 1 hour (at 70°F/50% RH)
- Hard Dry/Cure: 8 hours (ideal conditions)
- Full Cure: For heavy use or recoating, allow at least 24 hours.

Tip: Cooler temperatures or higher humidity will extend drying time.

Cleanup

Tools and Equipment:

- Clean all brushes, sprayers, and other applicators immediately after use with mineral spirits.
- Wipe spills with mineral spirits before the product dries.
- Keep containers tightly sealed when not in use.

Safety Precautions:

- Work in a well-ventilated area or outdoors.
- Avoid inhaling vapors; use approved respiratory protection if ventilation is limited.
- Dispose of solvent-soaked materials in accordance with local regulations due to combustion risk.

Rust Protection

- RustBlock Enamel creates a durable, corrosion-resistant film that seals out moisture and air.
- Provides up to 5 years of rust protection when applied on properly prepared surfaces.
- Inspect coated items annually and touch up worn or damaged areas as needed



Rust Block Enamel

for continuous protection.

Application Tips

- Best results are achieved in dry, mild conditions (50°F–85°F).
- Stir product at intervals while working for optimum results.
- Avoid applying thick coats—multiple thin coats offer better protection.
- For previously painted or bare steel, ensure removal of all surface rust and old, loose paint.
- Do not apply if dew or rain is expected within 24 hours.

Frequently Asked Questions

Can I apply RustBlock Enamel directly over rust?

- Remove all loose and flaky rust. Product will seal minor, tight rust but is not a substitute for thorough surface prep.

Should I apply a primer?

- RustBlock Enamel is formulated for direct-to-metal use; primer is not required unless recommended for severe or marine environments.

How do I store unused paint?

- Store in a cool, dry location. Keep container closed tightly and away from heat or flame.

Questions or need assistance?

Contact our technical support team or visit our website for tips, safety data sheets, and troubleshooting guides.