Commands

Knowing the framework lets you:
1. Target specific vulnerabilities
2. Reduce guessing
3. Faster recon (VERY important)

cat /var/log/auth.log.1 | grep COMMAND this worke[illegible]

Meaning:

File	Meaning
auth.log	Current / newest log entries
auth.log.1	Previous log file
auth.log.2.gz	Older compressed logs
	↓
auth.log.3.gz	Even older logs

Linux

pwd	# show current directory
ls	# list files
ls -la	# list hidden files
cd folder	# enter directory
cd ..	# go back
history	# show command history
mkdir name	# create folder
touch file.txt	# create file
rm file	# delete file
rm -rf folder	# delete folder
cp file a/b	# copy file
mv file a/b	# move/rename file
clear	# clear terminal
find / -name file	# locate file
grep "text" file	# Searches for the word "text" inside a specific file
grep -r "password"	# Searches recursively through folders for the word password

-Privilege Escalation

whoami	current user
id	user + group info
sudo -l	sudo permission
sudo -i	This opens a root login shell
sudo su	use sudo to run su
su root	switch user to root

-Networking

ip a
ifconfig
ping <ip>
netstat -tulpn
ss -tulpn
curl http://site
wget http://file

-Enumeration

uname -a
hostname
ps aux
top
env
printenv

-File Reading

cat file
less file
more file
head file
tail file
strings file

Note: grep = search tool, -r = recursive (search all folders), "text" word to search, . = current directory
grep -i "password" file, -i = ignore upper/lowercase

Gobuster

	gobuster dir -u http://IP -w /usr/share/wordlists/dirb/common.txt
	• **gobuster** = tool to perform web content discovery • **dir** = specifies the directory & file enumeration mode, which attempts to discover hidden directories and files on a web server • **--url http://site** = sets the target website that gobuster will scan • **-w /usr/share/wordlists/dirbuster/directory-list.txt** = specifies the wordlist Gobuster will use to guess directory and file names
	gobuster dir -u http://target -w wordlist.txt

ssh

ssh user@ip
ssh -i key user@ip
scp file user@ip:/home/user

Nikto

nikto -h http://IP -o scan.txt

Nmap

nmap <IP> = Basic scan
nmap -sV <IP> = Service + version detection
nmap -A <IP> = Aggressive scan
nmap -p- <IP> = Scan all ports
nmap -F <IP> = Fast scan

Nmap -sC -sV -p-

-sC	default scripts
-sV	service versions
-p-	scan all ports

= full enumeration

curl

curl	download something from the internet using the terminal Prints it directly in the terminal Doesn't save it as a file
curl -O	Downloads AND: Saves it as a file Uses the original filename
curl IP -v	Verbose mode shows headers + request details

md5sum file.txt = creates a hash of a file using the MD5 algorithm
nano valid_usernames.txt = make a file
-i = case insensitive

ffuf -u http://target/FUZZ -w common.txt