

PREVIEW

Key	Function
→ _l	[mpv] play this line (guessing start pos at cursor), stop at end
⇧→ _l	[mpv] play this line from start (no guessing)
\ → _l	[mpv] play this line (from cursor), don't stop
\ _	[mpv] play line by line from this one till EOF

TIMECODE EDITING

J	Join (timecode) with the next line; If on the first of two http lines with timestamp, will made an EDL line.
	[split] this line into two, guessing a new timecode
mm	mark/unmark word break point, then l. [split] will use this and cursor together. useful when cut time not predicted well.
⇧← ⇧→	Roll timecode with the previous line for 1 sec
g0	go to the start of subtitle
g8	go to record_out timecode in prev line
g9	go to record_in timecode
gO	append a gap for 5 secs below current line
gN	append a line for 10 minutes below current line, place cursor to input clipname
gB gb	toggle a line between '[B]' or not.
\ c	toggle conceallevel=0, 1

EDITORIAL DECISION / BBC Paper Edit

\ p	Enter cherry-pick mode. tabnew on the left, map ⇧
⇧	pick this line to Vim tab 1, then mark used ---
\ P	Enter cherry-pick mode (split horizontally), map ⇧
⇧	pick this line to next window, then mark used ---
⊗	reject this line, mark xxx , then go to next line
⊗ (fn⊗)	toggle between EDL and xxx ; toggle --- to EDL
V _	render those highlighted lines with tsv2roughcut
V x	export those highlighted lines with tsv2fcpxml

MPV IPC CONTROL MODE

\\	init.mpv --input-ipc-server=/tmp/mpvsocket --pause clipname.mp4 and enter IPC Control mode. s ← → ↑ ↓ _ ⇧ is redefined, and restored at quit
\\	send quit signal via ipc socket to mpv
_	[mpv ipc] toggle play
← →	move, then [mpv ipc] seek to cursor
↑ ↓	move, then [mpv ipc] seek; reload when clip changed
\ _	[mpv ipc] play from this line till EOF
⇧, s	[mpv ipc] seek to cursor
ns	[mpv ipc] search next (n), and seek
S	[mpv ipc] sync playhead: seek vim cursor to nearest of mpv timecode, wrap end
\ S	backwards of sync playhead
gS	playhead sync periodically, every 1s. call again to dismiss. _ will pause and restore status
→ _l	seek to cursor, [mpv ipc] always play. if in comment region, jump to next 'EDL'
⇧→ _l	seek to line head, then → _l
gi	[mpv ipc] get current timecode, write record_in. overwrite existing.
go	[mpv ipc] get current timecode, write record_out & clipname. overwrite existing

Org mode/Markdown Folding

→ _l	When not on a EDL/---/xxx line. do za on ## Header or * Org head
⇧ → _l	cycle foldlevel=0,1,2
	if on a EDL line, you have to use za zm zr zo zO zM zR
]]	go to next heading
[[go to previous heading
g]	go to next comment line (not start with EDL)
g[previous.

Syntax

```
*Section 1
Any line starts without EDL is note.
** SubSection
EDL→00:00:01,000→00:00:05,000→|_image_|→subtitles...
EDL→00:00:01,000→00:10:01,422→|_clipname_|→[B]this is B-Roll
EDL→00:00:01,000→00:10:01,422→|_clipname_|→subtitles...

## Subsection
Sharp, asterisk are both recognized as header, and can be
folded with TAB key.
```