


This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may be applied only at the location of the Party Authorized To Apply Mark.

Applicant:	Guangdong Siber Electric Mfg Ltd	Manufacturer:	Guangdong Siber Electric Mfg Ltd
Address:	304&303, Building 9, Wanyang Wanzhong Park, No.2 Huabao East Road, Longjiang Town, Shunde District, Foshan City, Guangdong Province	Address:	304&303, Building 9, Wanyang Wanzhong Park, No.2 Huabao East Road, Longjiang Town, Shunde District, Foshan City, Guangdong Province
Country:	China	Country:	China
Party Authorized To Apply Mark:	Same as Manufacturer		
Report Issuing Office:	Intertek Testing Services Shenzhen Limited Guangzhou Branch		
Control Number:	<u>5005258</u>	Authorized by:	 for L. Matthew Snyder, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.
545 East Algonquin Road, Arlington Heights, IL 60005
Telephone 800-345-3851 or 847-439-5667 Fax 312-283-1672

Standard(s):	Switches For Appliances - Part 1: General Requirements [UL 61058-1:2017 Ed.5]
	Switches For Appliances – Part 1-1: Requirements For Mechanical Switches [UL 61058-1-1:2017 Ed.1]
	Switches for Appliances Part 1: General Requirements [CSA C22.2#61058-1:2017 Ed.3]
	Switches For Appliances - Part 1-1: Requirements For Mechanical Switches [CSA C22.2#61058-1-1:2017 Ed.1]
Product:	Appliance switches
Brand Name:	 施霸 (siber) SIBER
Models:	HERO-3, HERO-3-1.

2.0 Product Description	
Product	Appliance switches
Brand name	 施霸 (siber) S I B E R
Description	The products covered by this report are push-button switches for appliances.
Models	HERO-3, HERO-3-1.
Model Similarity	HERO-3 is identical with HERO-3-1 except HERO-3-1 used transparent button, HERO-3 used opaque button. HERO-3 and HERO-3-1 had an alternative overall shell. Detail refer to Sec.7.0
Ratings	0-16(4)A 125/250VAC, T125, 50/60HZ 1E4 0-10A 125/250VAC, T125, 50/60HZ 1E4 0-6A 125/250VAC, T125, 50/60HZ 1E4
Other Ratings	NA
Conditions of Acceptability	The products covered in this Report are incomplete in construction features or limited in performance capabilities and are intended for use and evaluation in other products. Consideration should be given to the following when the component is used in or with another product. 1. The switch terminals have been investigated for use with copper alloy solder terminal. 2. The spacing between any connections when installed on the switch terminals and the adjacent mounting surface shall be judged using the spacing requirements contained in the end-product standard. 3. The switches have been subjected to a minimum of 6000 cycles endurance test. 4. The switch has openings in the housing adjacent to arcing parts. Caution is needed if the end-use application involves combustible dust or adjacent combustible materials that could be ignited by switch arcing. 5. Type of disconnection: Full Disconnection 6. Glow wire test temperature for switch body: 850°C. 7. Ball pressure test temperature for switch body: 145°C