



Product Service

CERTIFICATE

No. B 093102 0006 Rev. 01

Holder of Certificate: **Siber(China) Electric Mfg. Limited**
A on 5/F., Wah Hen
Commercial Centre, Nos.381-383 Hennessy Road
Wanchai
HONG KONG

Certification Mark:



Product: **Appliance switch**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 6810020017503

Valid until: 2028-09-24

Date, 2023-09-25


(Michael Xu)

CERTIFICATE

No. B 093102 0006 Rev. 01

Model(s):

KCD1, KCD2, KCD2(P), XN-14B, DSE-2210,
 DSE-2310, DSE-2410, DSE-S-2210, DSE-S-2310,
 DSE-S-2410, SB5-1, SB5-2, FM1-1115, FM1-1115A,
 FM1-1115S, KA6, KA6F, KA7, KA7F, KAN-J2, KAN-J5

Parameters:

Parameter concerns	Specification for components	
Rated voltage/frequency:	125/250VAC; 50/60Hz	
Rated current/ambient temperature:	KCD1	16(6)A or 16A or 10A, T125
	KCD2, KCD2(P):	12(8)A or 12(4)A or 23A or 16A, T105/55
	XN-14B:	10(2)A or 8(2)A or 5A, T85 or T105
	DSE-2210, DSE-2310, DSE-2410, DSE-S-2210, DSE-S-2310, DSE-S-2410:	10(2)A or 8A or 6A, T85
	SB5-1, SB5-2:	2A or 1A, T85
	FM1-1115, FM1-1115A, FM1-1115S:	10A or 6A, T105
	KA6, KA6F, KA7, KA7F:	3A or 1A, T85
	KAN-J2:	10(3)A or 6A or 3A, T85
	KAN-J5:	1A or 0.5A, 25T85
Overvoltage category:	II	
Rated impulse withstand voltage:	2500V	
Degree of protection:	IP20 (KCD2, KA6, KA6F, KA7, KA7F, KAN-J2) IP65 (KCD2(P): IP65 for actuating member, IP00 for other parts) IP00 (KCD1, XN-14B, DSE-2210, DSE-2310, DSE-2410, DSE-S-2210, DSE-S-2310, DSE-S-2410, SB5-1, SB5-2, FM1-1115, FM1-1115A, FM1-1115S, KAN-J5)	
Number of cycles:	1E4 2E4 only for KCD2, KCD2(P): 12(8)A	

CERTIFICATE

No. B 093102 0006 Rev. 01

Disconnection:	XN-14B, SB5-1, SB5-2, FM1-1115, FM1-1115A, FM1-1115S, KA6, KA6F, KA7, KA7F, KAN-J2, KAN-J5	Micro- disconnection
	KCD1, KCD2, KCD2(P), DSE-2210, DSE-2310, DSE-2410, DSE-S-2210, DSE-S-2310, DSE-S-2410	Full disconnection
Supply connection:	XN-14B, DSE-2210, DSE-2310, DSE-2410, DSE-S-2210, DSE-S-2310, DSE-S-2410, SB5-1, SB5-2, FM1-1115, FM1-1115A, FM1-1115S, KA6, KA6F, KA7, KA7F, KAN-J2, KAN-J5	Solder terminal
	KCD1, KCD2, KCD2(P)	Tab terminal
Type of switch:	KCD1, KCD2, KCD2(P)	Rocker switch
	FM1-1115, FM1-1115A, FM1-1115S, KA6, KA6F, KA7, KA7F, KAN-J2, KAN-J5	Push-button switch
	XN-14B, DSE-2210, DSE-2310, DSE-2410, DSE-S-2210, DSE-S-2310, DSE-S-2410, SB5-1, SB5-2	Push-pull switch
Degree of pollution:	1(SB5-1, SB5-2) 2 (KCD1, KCD2, KCD2(P), XN-14B, DSE-2210, DSE-2310, DSE-2410, DSE-S-2210, DSE-S-2310, DSE-S-2410, FM1-1115, FM1-1115A, FM1-1115S, KA6, KA6F, KA7, KA7F, KAN-J2, KAN-J5)	
Duty type:	Continuous	
Glow wire temperature:	850°C	

Tested according to: EN IEC 61058-1:2018
 EN 61058-1-1:2016