



Product Service

CERTIFICATE

No. B 093102 0004 Rev. 02

**Holder of
Certificate:**

SIBER (CHINA) ELECTRIC MFG. LIMITED
FLAT/RM A & B, 15/F., Neich Tower, 128 Gloucester Road
Wanchai
HONG KONG

Certification Mark:



Product:

**Appliance switch
(Appliance Switch)**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 6810020005303

Valid until: 2030-02-11

Date, 2025-02-12


(Michael Xu)

CERTIFICATE

No. B 093102 0004 Rev. 02

Model(s):

CO, COG, COP, SB1-16, KW3A, KCD3-1, KCD3, KCD3-11N, KCD3-5, KCD3-6, KW4A(S), SB1-05, HERO-1, HERO-2, SL-401, SL-401-1, XN-14, XN-14A, XN-14BX, XN-14B, XN-14B-S, XN-14B-6, XN-14BX-4, Facai-1, Facai-2

Parameters:

Parameter concerns	Specification for components	
Rated voltage/frequency:	125/250VAC; 50/60Hz	
Rated current/ambient temperature:	CO, COG, COP	16A, T85
	SB1-16, KW3A	16(4)A, T105
	KCD3-1	3A, T105/55
	KCD3, KCD3-11N, KCD3-5, KCD3-6	13(4)A, 6(3)A, T105/55
	KW4A(S), SB1-05	10.1(3)A, 5(2)A, T105
	HERO-1, HERO-2	10.1(3)A, 6(3)A, T105
	SL-401, SL-401-1	12(3)A, 10A, 6A, T85
	XN-14, XN-14A, XN-14B, XN-14B-S, XN-14B-6, Facai-1	15(2)A, 10(2)A, 8(2)A, 5A, T85, T105
	XN-14BX	15(2)A, 13(2)A, 10(2)A, 8(2)A, 5A, T85, T105
	XN-14BX-4, Facai-2	15(2)A, T125
Overvoltage category:	II	
Rated impulse withstand voltage:	2500V	
Degree of protection:	IP00 (except for rocker switch) IP20 (after mounted for rocker switch)	
Number of cycles:	1E4	
Disconnection:	SB1-16, KW3A, KW4A(S), SB1-05, SL-401, SL-401-1, XN-14, XN-14A, XN-14BX, KCD3-6, XN-14B, XN-14B-S, XN-14B-6, XN-14BX-4, Facai-1, Facai-2	Micro- disconnection
	CO, COG, COP, KCD3-1, KCD3, KCD3-11N, KCD3-5, HERO-1, HERO-2	Full disconnection

CERTIFICATE

No. B 093102 0004 Rev. 02

Supply connection:	CO, COG, COP, KW4A(S), SB1-05, SL-401, SL-401-1, XN-14, XN-14A, XN-14BX, XN-14B, XN-14B-S, XN-14B- 6, XN-14BX-4, Facai-1, Facai- 2	Solder terminal
	SB1-16, KW3A, KCD3-1, KCD3, KCD3-11N, KCD3-5, KCD3-6	Tab terminal
	HERO-1, HERO-2	Screwless terminal
Type of switch:	CO, COG, COP, KCD3-1, KCD3, KCD3-11N, KCD3-5, KCD3-6, HERO-1, HERO-2	Rocker switch
	SB1-16, KW3A, KW4A(S), SB1-05	Push-button switch
	SL-401, SL-401-1, XN-14, XN- 14A, XN-14BX, XN-14B, XN- 14B-S, XN-14B-6, XN-14BX-4, Facai-1, Facai-2	Push-pull switch
Degree of pollution:	2	
Duty type:	Continuous	
Glow wire temperature:	850°C	

Tested according to: EN IEC 61058-1:2018
EN 61058-1-1:2016