MUSTANG
MOTORCYCLE SEATS

MOUNTING SUGGESTIONS

Harley-Davidson® FL Touring 2008-2018
One-piece Seat

Hardware: stock 1/4"-20 x 1/2" rear fender screw

Tools needed: Phillips screwdriver

Removal of stock seat:

Two-piece stock seat:

1. Remove the rear 1/4"-20 fender screw with a Phillips screwdriver and set it aside. The stock rear fender screw will be used to attach your new Mustang seat.

2. Slide the rear seat back and up.

3. Remove the two nuts holding the solo in place.

4. Carefully lift the back of the driver's seat up and back to disengage the front bracket and remove the seat.

One-piece stock seat

1. Remove the rear 1/4"-20 fender screw with a Phillips screwdriver and set it aside. The stock rear fender screw will be used to attach your new Mustang seat.

2. Remove the hand strap that is secured to the motorcycle on each side where the front saddlebag mount is located.

3. Slide the seat up and back to disengage the front bracket and remove the seat.

Installation of Mustang seat:

1. Remove any seat supports from the frame rails and be sure wiring is routed along the inside of the frame rails. CVO models: remove any plastic trim from the fender so the Mustang seat installs on the bare fender.

2. If the seat is heated, connect the cable to the accessory port. Be sure the port is free of dirt and debris. If the accessory port is already in use, use Harley part 70264-94A or 70270-04 to add additional ports. Check to be sure there are no folds or kinks in the wire before installing the seat.

   Note: Installation of heated seats on 2014-up FL Touring motorcycles requires use of Harley adaptor 69200722 or 69201599 depending on the year.

3. Engage the nose bracket into the frame.

4. A firm downward punch or chop to the nose of the seat will push the seat closer to the chrome dash. If there is a gap at the dash, the dash can be adjusted by loosening the 1/2" hex nut and Phillips screw on the dash, sliding the dash back and retightening.

5. The seat is spring-loaded so the rear mounting bracket will be approximately 1" to 1-1/2" above fender mount. Gently push seat down and secure to fender with stock screw.

6. Mustang Suggest that a rack-mounted backrest be set to the rearmost position. Fully loosen the four nuts under the outer rack channels and tap the backrest rearward to the end of the slots and retighten the nuts.

Using a backrest:

1. Using a backrest with seats with a split in the baseplate between the rider and passenger seat requires first mounting a Harley or Mustang frame-mounted backrest kit. The post on the Mustang kit is bent to account for the angle. It may be necessary to add washers as spacers to the front mount to refine the angle.

2. Seats without a split in the baseplate but with a split in the cover use a straight-post Mustang backrest. A bent-post backrest from a frame-mounted backrest kit will not work with these seats.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 8:30 - 5:00 Eastern or send an e-mail to tech@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 75646, 76025, 76030, 76031, 76032, 76033, 76034, 76036, 76037, 76038, 76039, 76614, 76712, 76860, 76861, 76862, 76863, 76864, 76865, 76981, 79006, 79007, 79538, 79539, 79546, 79547, 79556, 79558, 79579, 79586, 79603, 79604, 79606, 79608, 79609, 79640, 79641, 79642, 79643, 79644, 79645, 79646, 79647, 79648, 79700, 79701, 79702, 79703, 79704, 79705



Products made by Mustang Motorcycle Products, LLC are warranted for one year against defects in material and workmanship. Mustang must first be notified of any apparent defect. A return authorization will be issued. Carefully pack the product and return prepaid. Upon receipt, Mustang will make a fair, prompt decision regarding repair or replacement. Incidental and consequential damages arising from or in connection with the installation or use of a Mustang product are not covered by this warranty. An original purchase receipt must be provided to obtain a warranty repair or replacement.