



NOTES:

- 1. Dimensioning per ANSI Y14.5M-1982.
- 2. Refer to MO symbol list.
- A Tapers for nesting of carriers are allowed if the dimensional range is satisfied.
- 1 The third slot is used for polarization only.
- $\frac{1}{2}$ $\frac{1}{2}$ is the seating plane of the carrier.
 - 6. All dimensions in inches.

S	VARIATIONS (DIMENSIONS IN INCHES)											
M B C	AA				AB				AC			N
<u> </u>	MIN	NOM	MAX	X D T E	MIN	NOM	MAX	E	MIN	NOM	MAX	XOT E
Α	.555	.560	.565		.585	.590	.595		.620	.625	.630	
A1	.285	.290	.295		.355	.360	.365		.355	.360	.365	!
A2			.175				.175				.175	
b	.188	.190	.192		.188	.190	.192		.188	.190	.192	
D	1.995	2.000	2.005		2.745	2.750	2.755		3.490	3.500	3.510	
D2	1.758	1.760	1.762		2.377	2.380	2.383		3.145	3.150	3.155	
D3	1.695	1.720	1.745	3	2.295	2.320	2.345	3	2.975	3.050	3.125	3
D4	1.700	1.720	1.740	3	2.330	2.365	2.400	3	2.975	3.050	3.125	3
E	1.995	2.000	2.005		2.745	2.750	2.755		3.490	3.500	3.510	
E1	1.250 BASIC			4	2.000 BASIC			4	2.750 BASIC			4
E3	.375 BASIC				.375 BASIC				.375 BASIC			
h	.060	.075	.090		.060	.075	.090		.060	.075	.090	
k	.060	.075	.090		.060	.075	.090		.060	.075	.090	
NOTE	1, 2, 6				1, 2, 6				1, 2, 6			
REF	5-260				5-260				5-314			
ISSUE	SSUE A					A			8			

JEDEC	GENERIC	ISSUE	DATE	00 017	SHEET
SOLID STATE PRODUCT OUTLINE	CARRIER FAMILY	В	1/93	CO-013	3 OF 3