



NOTES:

1. REFER TO APPLICABLE SYMBOL LIST.
2. DIMENSIONING & TOLERANCEING PER ANSI Y14.5, 1982.
3. PACKAGE CONTOUR OPTIONAL BETWEEN TERM 1 & 3 AND WITHIN ϕD .
4. TERMINALS 2 & 3 ARE TAB TYPE.
5. TERMINAL 2 IS ROUND TYPE AND TERMINAL 3 IS TAB TYPE.
6. MINIMUM ELECTRICAL CREEPAGE LENGTH BETWEEN TERM 1 & 2 AND BETWEEN TERM 1 & 3.
7. MINIMUM ELECTRICAL STRIKE DISTANCE BETWEEN TERM 1 & 2 AND BETWEEN TERM 1 & 3.
8. TYPICAL TWO PLACES.
9. L_3 IS FOR CONNECTOR CLEARANCE. COUNTERBORE ϕD_2 IS OPTIONAL.
10. CONTROLLING DIMENSION: INCH.



SYMBOL	VARIATIONS (ALL DIMENSIONS SHOWN IN MILLIMETERS)												
	AE		NOTE	AF		NOTE			NOTE			NOTE	
	MIN.	MAX.		MIN.	MAX.		MIN.	MAX.		MIN.	MAX.		
b	4.73	7.92		4.73	7.92								
b ₁	4.725	4.851		4.73	4.85								
db	1.448	1.498	9	1.448	1.498	8							
c	.356	.482		.356	.812								
ØD	87.63	100.33	3	-	111.50	2							
ØD ₁	62.74	63.50	7	63.5	73.40								
ØD ₂	2.54	—	11	-	-								
EC	45.72	—	5	48.26	-	4							
ES	30.48	—	6	27.94	-	5							
H	25.40	27.94		33.02	38.1								
h	1.27	4.06	8	1.78	4.06	7							
Øj	3.13	3.68	8	3.31	3.68	7							
L	6.23	19.30		6.23	19.30								
L ₂	.64	1.65		-	-								
L ₃	2.54	—	11	-	-								
N	.77	2.79	8	.77	-	7							
Q ₁	.254	.508	9	-	-								
R	—	58.42		-	63.5								
S	2.93	3.55	9	2.93	3.55	8							
ØT	1.27	1.77		1.27	1.77								
B	15°	50°		15°	50°								
NOTE	1, 2, 9			1, 2, 10									
REF	ITEM 93-2												
ISSUE													
JEDEC SOLID STATE PRODUCT OUTLINES				TITLE DISC TYPE FAMILY				ISSUE J	DATE 7/14/85	TO-200			



NOTES:

1. REFER TO APPLICABLE SYMBOL LIST.
2. DIMENSIONING & TOLERANCING PER ANSI Y14.5, 1982.
3. PACKAGE CONTOUR OPTIONAL BETWEEN TERM 1 & 3 AND WITHIN ØD.
4. TERMINALS 2 & 3 ARE TAB TYPE.
5. TERMINAL 2 IS ROUND TYPE AND TERMINAL 3 IS TAB TYPE.
6. MINIMUM ELECTRICAL CREEPAGE LENGTH BETWEEN TERM 1 & 2 AND BETWEEN TERM 1 & 3.
7. MINIMUM ELECTRICAL STRIKE DISTANCE BETWEEN TERM 1 & 2 AND BETWEEN TERM 1 & 3.
8. TYPICAL TWO PLACES.
9. L₃ IS FOR CONNECTOR CLEARANCE. COUNTERBORE ØD₂ IS OPTIONAL.
10. CONTROLLING DIMENSION: INCH.

SYMBOL	VARIATIONS (ALL DIMENSIONS SHOWN IN INCHES)										
	AE		NOTE	AF		NOTE			NOTE		
	MIN.	MAX.		MIN.	MAX.		MIN.	MAX.		MIN.	MAX.
b	.186	.312		.186	.312						
b ₁	.186	.191		.186	.191						
Øb	.057	.059	9	.057	.059	8					
c	.014	.019		.014	.032						
ØD	3.450	3.950	3	-	4.390	2					
ØD ₁	2.470	2.500	7	2.500	2.890						
ØD ₂	.100	—	11	-	-						
EC	1.800	—	5	1.900	-						
ES	1.200	—	6	1.100	-						
H	1.000	1.400		1.300	1.500						
h	.050	.160	8	.070	.160						
Øj	.130	.160	8	.130	.145						
L	.245	.760		.245	.760						
L ₂	.025	.065		-	-						
L ₃	.100	—	11	-	-						
N	.030	.110	8	.030	-						
Q ₁	.010	.020	9	-	-						
R	—	2.300		-	2.500						
S	.115	.140	9	.115	.140						
ØT	.050	.070		.050	.070						
B	15°	50°		15°	50°						
NOTE	1, 2, 9			1, 2, 10							
REF	ITEM 93-2			ITEM 119							
ISSUE											
JEDEC SOLID STATE PRODUCT OUTLINES				TITLE DISC TYPE FAMILY			ISSUE J	DATE 7/10/87	TO-200		