

NOTES:

- 1. REFER TO APPLICABLE SYMBOL LIST.
- 2. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M-1982.
- 3. LEAD DIMENSION UNCONTROLLED IN ZONE L3.



 \triangle TAB CONTOUR OPTIONAL WITHIN DIMENSION b₂ & L₂.



DIMENSIONS b1 AND c1 APPLY TO BASE METAL ONLY. DIMENSIONS b & c APPLY TO PLATED LEAD.



LEAD TIP CONTOUR IS OPTIONAL AND SHALL EXTEND .080 INCHES MAX FROM LEAD TIP.



SECTION A-A DIMENSIONS APPLY BETWEEN .100 TO .150 INCHES FROM LEAD TIP.

- 8. DIMENSION "D" DOES NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED .005 INCHES PER SIDE.
- 9. ALL DIMENSIONS IN INCH.

		VARIATIONS						
	AA							
SYMBOL	MIN		NOM	MAX		NOTES		
A	.086		.090		.094			
A ₁	.034		.039	.045				
b	.025		-	.036		7		
b ₁	.025		.030	.035		5,7		
b ₂	.175		.185	.215		4		
b3	.035		.040 .045					
c	.018		-	024		7		
c 1	.018		.020	.023		5,7		
c 2	.018		.035	.040				
Ď	.235		.240	.250		8		
D ₁	.100		.150	.200		İ		
D ₂		.190 REF						
Ε .	.250		.258	.265		l		
E ₁	.1 7 0		-	-]		
е	.090 BSC							
L	.350		.365	.380		6		
L ₁	.072		.082	.092				
L2	.030		.040	.050		4		
Lз	-		-	.060		3		
NOTE	1,2,9	 						
REF.	10-322S		·					
ISSUE			*					
IEDEC		TITLE:R-PSFM-F3		ISSUE	DATE		SHEET 2	
JEDEC SOLID STATE PRODUCT		HEADER FAMILY INSERTION MOUNT		A	605	TC 000	OF	
OUTLINES		(PERIPHERAL TERMINALS)			6-95	TS-002	2	