

NOTES

- 1 FOR INDIVIDUAL DECK ASSEMBLY DETAILS, REFER TO MO-199.
- 2 DIMENSIONING AND TOLERANCING CONFORM TO ASME Y14.5M-1994.
- 3 ALL DIMENSIONS IN MILLIMETERS.
- 4 N IS THE MAXIMUM NUMBER OF LEADS.



TO BE DETERMINED AT SEATING PLANE C.



DIMENSION 64 DOES NOT INCLUDE DAMBAR PROTRUSION OR INTRUSION.
THE DAMBAR PROTRUSION(S) SHALL NOT CAUSE THE SHOULDER WIDTH
TO EXCEED 64 MAXIMUM BY MORE THAN X mm. THE DAMBAR INTRUSION(S)
SHALL NOT REDUCE THE SHOULDER WIDTH TO LESS THAN 0.03 mm
BELOW B4 MINIMUM.

1,27 0.13 0,80 0.08 0.65 0.08



THE LEAD 1 IDENTIFIER AND LEAD NUMBERING CONVENTION SHALL CONFORM TO JESD 95 SPP-012. DETAILS OF LEAD 1 IDENTIFIER ARE OPTIONAL, BUT MUST BE LOCATED WITHIN THE ZONE INDICATED. THE LEAD 1 IDENTIFIER MAY BE EITHER A MOLDED OR A MARKED FEATURE.



FOR TWO HIGH VARIATIONS (Ax), LEADS OF UPPER DEVICE MUST BE CENTRAL TO LEADS OF BOTTOM DEVICE WITHIN \pm 0.13 mm. FOR FOUR HIGH VARIATIONS (Bx), ADJOINING DEVICE LEADS MUST BE CENTRAL WITHIN \pm 0.13 mm, WITH THE TOTAL VARIATION WITHIN THE STACKED ASSEMBLY TO BE \pm 0.20 mm



DATUM A AND B ARE ESTABLISHED ON THE BOTTOM DECK OF THE 2 OR 4 HIGH ASSEMBLY.




DIMENSION E 1S MEASURED AT THE WIDEST POINT OF THE STACK ASSEMBLY AND INCLUDES ANY SOLDER FILLET PROTRUSION.


	STATE OUTLINE	Ċ
-KODOC I	OOTLINE	_

IEDEC

THIS *REGISTERED OUTLINE* HAS BEEN PREPARED BY THE JEDEC JC-11 COMMITTEE AND REFLECTS A PRODUCT WITH ANTICIPATED USAGE IN THE ELECTRONICS INDUSTRY; CHANGES ARE LIKELY TO OCCUR.

	·						
TITLE SMALL OUTLINE		ISSUE	DATE		1		
J-LEAD PACKAGE ASSEMBLY 2 HIGH/4 HIGH STACK	PRSO-J/LSOJ	В	6/99	M0-200	of 5		





5 Y	COMMON DIMENSIONS									
М В О	DIMENSIONS IN MILLIMETERS									
0 L	MIN	NOM	MAX	E						
E1		10.15 BASIC	,							
E2	9.90 BAS1C									
R	0.55	0.65	0.75							

	COMMON TOLERANCES	
ccc	0.40	5
ddd	0.15	
NOTE	2, 3	
DEF	11-481	

ISSUE

S Y	VARIATIONS											Ì	
M B O		AA		AB			ВА			BB			N 0 T
L	MIN	NOM	MAX	MIN	NOM	MAX	MIN	NOM	MAX	MIN	NOM	MAX	T E
А		=	3.20			3.20			5.50			5.50	
b	0.36		0.52	0.26		0.40	0.36		0.52	0.26		0.40	
b3	0.36	0.40	0.44	0.26	0.30	0.34	0.36	0.40	0.44	0.26	0.30	0.34	
b4	0.62	0.66	0.79	0.46	0.50	0.63	0.62	0.66	0.79	0.46	0.50	0.63	6
D	Ι.	95 BAS		4	40 BAS		1	95 BAS		ſ	40 BAS		
Е	11.15	11.40	11.65	11.15	11.40	11.65	11.15	11.40	11.65	11.15	11.40	11.65	
		İ	1							1 1			
е	1.27 BASIC		SIC	0.80 BASIC			1.27 BASIC			0.80 BASIC			
Ν	32 44				32 44						4		
aaa		0.20			0.20		0.20 0.20						
bbb		0.20			0.20		0.20 0.20						
					-								
NOTE	1,2,3				1.2.3			1,2,3			1, 2, 3		
REF.		1-481		1 1	11-481		11-481		11-481				
ISSUE		А			A		A A						L
	JEDE				L OUTI			ISSUE	DATE			_	4
	ILID ST IUCT OL			EAD PA HIGH/				В	6/99	3 ML)-200	J OF	5
1		- · - · · · · -	'I -						1	1		ı	i i

S	VARIATIONS												
\$ Y M B O	AC										—————————————————————————————————————		
L	MIN	NOM	MAX	MIN	NOM	MAX	MIN	NOM	MAX	MIN	NOM	MAX	E
А			3.20										
b	0.26		0.40										
b3 b4	0.26		0.40										6
D	i	ı 25 BAS	•					:					U
Е	11.15	11.40	11.65										
е	0.	 65 BAS	IC I										
N		66			•	'	i	,	•		•	,	4
aaa bbb		0.20											
DDD		0.20											
NOTE	1,2,	 7											
REF.		l-513			···								
ISSUE		В											
9) (A.D.	I O T I C	31.10		-			
S Y M						VAR	IATIO	JNS					N
B 0 L	MIN	NOM	MAX	MIN	NOM	MAX	MIN	NOM	MAX	MIN	NOM	MAX	N O T E
		ı						i 1	·			l	
			į										
NOTE											· · · · · · · · · · · · · · · · · · ·		
REF.													
ISSUE													
	JEDEC			SMAL	L OUTI	LINE ASSEM	DI V	ISSUE	DATE		200		5
	🖵												
S0 PROD	LID ST UCT OU	JTLINE	2	HIGH/	4 HIGI	H STAC	K K	В	6/99		-20	OF	5