





SHEET  
1 OF 4



SYMBOL	VARIATIONS							
	AA							
	MIN	NOM	MAX	NOTES				
A	4.50	5.00	5.50	2				
A1	1.45	1.80	2.15					
A2	1.65	2.00	2.35					
b	1.45	—	1.60					
b1	1.40	—	1.50					
b2	2.00	2.20	2.40					
b3	1.95	2.15	2.35					
b4	3.00	3.20	3.15					
b5	2.95	3.15	3.35					
c	1.10	1.20	1.30					
c1	0.90	—	1.10					
c2	0.65	0.75	0.85					
c3	0.50	0.60	0.70					
D	19.80	20.30	20.80					
D1	15.50	15.80	16.10					
D2	0.70	1.00	1.30					
D3	0.75	1.00	1.25					
E	15.10	15.60	16.10					
E1	13.30	13.60	13.90					
E2	2.25	2.45	2.70					
E3	1.20	1.45	1.70					
E4	2.00	2.50	3.00					
e	5.45 BASIC							
L	13.80	14.30	14.80					
L1	1.00	1.30	1.60					
L2	3.85	4.05	4.25					
R	2.00	—	3.00					
NOTE 1, 4								
REF. 10–401								
ISSUE A								
JEDEC SOLID STATE PRODUCT OUTLINE		TITLE PLASTIC CLIP MOUNTED PACKAGE, 3 LEADS			ISSUE A	DATE 3/00	TO–274	SHEET 3 OF 4

NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M–1994.



DIMENSIONS b1, b3, b5, c1 AND c3 APPLY TO BASE METAL ONLY.



DIMENSION D AND E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED 0.13 MILLIMETERS PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.

4. ALL DIMENSIONS SHOWN IN MILLIMETERS.

JEDEC SOLID STATE PRODUCT OUTLINE	TITLE PLASTIC CLIP MOUNTED PACKAGE, 3 LEADS	ISSUE A	DATE 3/00	TO-274	SHEET 4 OF 4
---	---	------------	--------------	--------	-----------------