


SECTION A-A 4 7



SECTION B-B

JEDEC	TITLE: R-PQFP	ISSUE	DATE:		SHEET
SOLID STATE PRODUCT OUTLINES	Quad Flat Pack Surface Mount Thermally Enhanced Pkg	Α	05 - 98	TO-271	2 OF 3

NOTES:

ALL DIMENSIONS IN MILLIMETER.

DIMENSIONING AND TOLERANCING PER ASME Y14.5M - 1994.

DIMENSION "D1" & "E1" DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH, PROTRUSIONS OR GATE BURRS SHALL NOT EXCEED 0.15 PER SIDE.



DIMENSIONS b2, b3 AND c1 APPLY TO BASE METAL ONLY. DIMENSIONS b & c APPLY TO LEADS WITH FINISH.



APPLIES TO METAL SURFACE ONLY.



DATUM A & B TO BE DETERMINED AT DATUM PLANE H.



SECTION A -A $\,\&\,B$ - B DIMENSIONS APPLY TO THE FLAT SECTION OF THE LEAD BETWEEN 0.10 TO 0.25 MILLIMETERS FROM THE LEAD TIP.



WRITE PROTECTED AREA, EXACT SIZE AND SHAPE OPTIONAL



DIMENSIONS "D2" AND "E2" TO BE DETERMINED AT DATUM PLANE H.



RESIN BLEED/FLASH INTRUSION ALLOWED AT TERMINAL BASE, (DEFINED BY SHADED AREA,) SHALL NOT EXCEED 0.45 MILLIMETERS. (per side)



RESIN BLEED/FLASH INTRUSION ALLOWED IN AREA DEFINED BY SHADED AREA, SHALL NOT EXCEED 0.25 MILLIMETERS. (per side)

	VADIATIONS							
		VARIATIONS AA						
SYMBOL	MIN	I	NOM	MAX		NOT	ΓES	
A	1.45		1.55	1	.65			
b	0.40)		0.60		4,7		
b 1	0.70)		0.85		4,7		
b 2	0.40)	0.47	0.55		4,7		
b 3	0.70)	0.75	0.80		4,7		
b 4	0.00)	0.10	0.20				
b 5	0.10)	0.25	0.40				
c	0.35			0.45		4,7		
c1	0.35		0.38	0.42		4,7	4,7	
D	6.40)	6.55	6.70				
D1	4.70)	4.85	4.95		3	3	
D2		4.80 REF				9		
D3	3.30)	3.45	3.60		11		
D4	1.65		1.75	1.90		10		
E	5.60)	5.75	5.85				
E1	4.45		4.60	4.70		3		
E2		4.60 REF			9			
E3	1.80)	1.85	1.95		11		
E4	0.40)	0.50	0.60				
E5	0.40)	0.50	0.60		10		
L	0.75		0.90	1.00				
L1	0.45		0.55	0.65				
L2	1.40)	1.55	1.70				
L3	1.25		1.35	1.50				
L4	2.25		2.35	2.50				
NOTE	1, 2, 7							
REF.	11.10-370							
ISSUE	A	Т	ITLE: R-PQFP	ICCLIE	DATE		CHEET	
JEDEC			Quad Flat Pack	ISSUE	DATE		SHEET 3	
SOLID STATE PRODUCT		5	Surface Mount		0	TO 071	OF	
OUTLINES		The	rmally Enhanced	Α	05 - 98	TO -271	Or	

DOCE						
JEDEC		TITLE: R-PQFP	ISSUE	DATE		SHEET
SOLID STATE PF	RODUCT	Quad Flat Pack Surface Mount				3
OUTLINE	ES	Thermally Enhanced	Α	05 - 98	TO -271	OF
		Pačkage	1.	00 00	10 201	3