


		VARIA	ATION	15		-		ALL DI	MENSI	ONS IN N	MILLIMET	ΓER	
S Y M B O	MIN	мах	2 0 t E s	MIN	мах	20+62	MIN	MAX	N O T E S	MIN	MAX	20 T E S	
5	A			AB			AC			AD			
A Al	1.27 .39	1.90 1.14		1.27 .39	1.90 1.14		1.27 .39	1.90 1.14		1.27 .39	1.90 1.14		
D D1	5.85 2.93	6.22 3.17	4	8.26 3.94	8.63 4.19	4	8.77 4.96	9.14 5.20	4	10.55 6.99	10.92 7.23	4	
D2 N S1	5.34 1	5.71 6 1.65	5	7.50 2 2.04	7.87 0 2.41	5	7.88 2 1.78	8.38 4 2.15	5	9.40 3: 1.66	2 2.03	5	
	: 1, 2, 7, 10 JC-11.3 ITEM 112			1, 2, 7, 10 ITEM 112			1, 2, 7, 10 ITEM 112			1, 2, 7, 10 ITEM 112			
	AE			AF			AG			АН			
A Al	1.27 .39	1.90 1.14		1.27 .39	2.03 1.14		1.27 .39	2.03 1.52		1.27 .64	2.03 1.52	·	
D D1	12.07 9.02	12.49 9.27	4	14.08 11.05	14.52 11.30	4	18.09 15.09	18.61 15.39	4	23.14 20.12	23.77 20.52	4	
D2	11.05	11.68		12.70	13.58		14.74	15.87		16.39	17.90		
N S1	40 5 1.40 1.77		48 1.40 1.77		5	64 1.40 1.77		5	84 1.40 1.77		5		
NOTES REF.:	: 1, 2, 7, 10 JC-11.3 ITEM 112			1, 2, 7, 10 ITEM 112			1, 2, 7, 10 ITEM 112			1, 2, 7, 10 ITEM 112			
	AJ												
A Al	1.27 .64	2.28 1.52											
D D1	26.19 23.14	26.79 23.59	4										
D2	16.39	17.90											
N S1		6 . 1.77	5										
	NOTES: 1,2,7,10 REF.: JC-11.3 ITEM 112												
SOL	JEDE ID STAT	E PROD	UCT	TITLE STANDARD ISSUE DATE Single Layer Chip Carrier Family 1.02 (.040") Termi- A 8/1/85 nal Spacing						-AJ			



	VARIATIONS ALL DIMENSIONS IN INCHES												
S Y M B O	MIN	MAX	70+Es	MIN	MAX	Z O H W S	MIN	MAX	Z 0 + E s	MIN	MAX	Z O ← W w	
S	L			АВ		AC			AD				
A Al	.050 .015	.075 .045		.050 .015	.075 .045		.050 .015	.075 .045		.050 .015	.075 .045		
D D1	.230 .115	.245 .125	4	.325 .155	.340 .165	4	.345 .195	.360 .205	4	.415 .275	.430 .295	4	
D2 N S1	.210 1	.225	5	.295 2 .080	.310 0 .095	5	.310 2	.330 4 .085	5	.065	.400 32 .080	5	
	: 1, 2, 7, 10 , JC-11.3 ITEM 112			1, 2, 7, 10 ITEM 112			1, 2, 7, 10 ITEM 112			1, 2, 7, 10 ITEM 112			
	AE			AF			AG			AH			
A A1	.050 .015	.075 .045		.050 .015	.080 .045		.050 .015	.080 .060		.050 .025	.080 .060		
D D1	.475 .355	.492 .365	4	.554 .435	.572 .445	4	.712 .594	.733 .606	4	.911 .792	.936 .808	4	
D2	.435	.460		.500	.535	٠	.580	.625		.645	.705		
N S1	.055	0 .70	5	.055	.070	5	.055	4 .070	5	.055	.070	5	
	NOTES: 1, 2, 7, 10 REF.: "JC-11.3 ITEM 112				1, 2, 7, 10 ITEM 112			1, 2, 7, 10 ITEM 112			1, 2, 70, 10 ITEM 112		
		AJ					-						
A A	.050 .025	.090 .060											
D D1	1.031 .911	1.055 .929	4										
D2	.645	.705											
N 51	.055	6 .070	5										
NOTES:		7, 10 3 ITEM 1	.12										
SOLID	JEDEC STATE OUTLINE	PRODU	СТ	TITLE STANDARD Single Layer Chip Carrier Family 1.02 (.040") Termi- nal Spacing DATE 8/1/85 MS-014 AA-AJ									