

## **NOTES:**

- 1. REFER TO APPLICABLE SYMBOL LIST.
- 2. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M-1982.
- DIMENSIONS b<sub>1</sub> AND c<sub>1</sub> APPLY TO BASE METAL ONLY. DIMENSIONS b & c APPLIES TO LEAD WIDTH FINISH.
- DIMENSIONS IN SECTION A-A APPLY BETWEEN 2.5 TO 4 mm FROM THE LEAD TIPS.
- THIS PACKAGE IS AVAILABLE AS 2 LEADED DEVICE, CENTER LEAD MAY BE OMITTED.
  - 6. ALL DIMENSIONS IN MILLIMETERS.

	I		VARIAT	IONS			
	AA						
SYMBOL	MIN		NOM		X	NOTES	
A A <sub>1</sub>	2.13	2.47 1.27 BSC		2.81			
A1 A2 b b1 c c1 D D1 E e L ØP	0.10 0.43 0.43 0.22 0.22 3.55 4.31 14.60 1.52		0.20 - 0.52 - 0.39 3.81 2.54 BSC 4.57 1.27 BSC 15.55 1.73	0.40 0.66 0.61 0.56 4.07 4.83 16.51 1.94		3 3 3 3	
NOTE REF.	1, 2, 5, 6 10-336						
ISSUE	A						
JEDEC SOLID STATE PRODUCT OUTLINES		TITLE: R-PSFM-F OPTO FAMILY INSERTION MOUNT (PERIPHERAL TERMINALS)		ISSUE A	4-94	TO-266	SHEET 2 OF 2