



FIGURE 2

ALL DIMENSIONS ARE IN INCHES



SECTION J-J


PGA XXX  
TRAY DESIGNATOR  
DETAIL - K




NOTE: SCALLOP IS CENTERED  
ON SIDE OF TRAY

DETAIL - C  
(ROTATED 90° CCW)

10  
XXX C° MAX  
TEMPERATURE RATING  
DETAIL - B



SECTION - H-H  
(ROTATED 90° CCW)



DETAIL - D  
(ROTATED 90° CCW)

TRAY STACKING DETAIL

JEDEC  
Solid State  
Product Outline

TITLE  
Tray for Handling  
and Shipping of  
PGA Packages

ISSUE  
E

DATE  
11/94

CD - 010

SHEET  
2 of 6

## NOTES:



THESE SURFACES TO BE FREE OF SEAMS.



CHAMFER DENOTES PACKAGE PIN 1 ORIENTATION.



THIS SCALLOP ALLOWS THE USE OF A PIN TO MECHANICALLY BIAS THE TRAY ORIENTATION.

4. THE SYMBOL N REFERS TO PGA PACKAGE PIN MATRIX SUPPORTED.

5. TOTAL USABLE CELLS  $N3 = N1 \times N2$ .

6. PACKAGE INTERFACE CONTROLLED BY PACKAGE CONFIGURATION.

7. NON-TABULATED DIMENSIONS HAVE A TOLERANCE OF  $.XX = \pm .01$ ,  $.XXX = \pm .005$ , ANGLES  $\pm 0.5^\circ$ .

8. CONTROLLING DIMENSIONS ARE IN INCHES.

9. INTERPRET DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH ANSI Y14.5M-1982.



XXX IS THE MAXIMUM OPERATING TEMPERATURE TO WHICH THE EMPTY TRAY CAN BE SUBJECTED FOR 48 CONTINUOUS HOURS WITHOUT VIOLATING THE DIMENSIONAL TOLERANCES OF THE TRAY.

11. DIMENSION M, M1, M2 AND M3 DEFINE THE CENTER LINES FOR THE CELL SITES.

DIMENSIONS IN INCHES

[illegible]

DIMENSIONS IN INCHES

[illegible]

NOTE: 7, 8, 9

REF: 5-258

ISSUE: A

JEDEC  
Solid State  
Production Outline

TITLE  
Tray for Handling  
and Shipping of  
PGA Packages

ISSUE

F

DATE  
11/94

C0-010

SHEET  
4 OF 6

DIMENSIONS IN INCHES

SHEET  
5  
OF  
6

SHEET  
6 OF 6