



NOTES:

1. REFER TO APPLICABLE SYMBOL LIST.
2. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M-1982.
3. ALL DIMENSIONS IN INCHES.
4. APPLIES BETWEEN LEADS 3 THROUGH 6, 11 THROUGH 14.
 APPLIES BETWEEN LEADS 1 THROUGH 3, 6 THROUGH 8, 9 THROUGH 11, 14 THROUGH 16.
5. SECTION A-A' APPLIES THROUGH LENGTH L.

JEDEC SOLID STATE PRODUCT OUTLINES	TITLE 16 LEAD FLANGE MOUNTED CERAMIC POWER PACKAGE (TYPE 1) R-CDFM-T16	ISSUE A	DATE JUNE 1993	M0-138
				SHEET 2 OF 3

SYMBOL	VARIATIONS (ALL DIMENSIONS SHOWN IN INCHES)											
	AA			NOTE				NOTE				NOTE
	MIN.	NOM.	MAX.		MIN.	NOM.	MAX.		MIN.	NOM.	MAX.	
A	.215	.245	.265									
A1	.055	.060	.065									
A2	.026	.032	.038									
b	.033	.035	.037									
b1	.033	.035	.036									
b2	.075	.080	.085									
c	.014	.015	.017									
c1	.014	.015	.016									
D	1.475	1.480	1.485									
D1	1.465	1.480	1.495									
D2	1.275	1.280	1.285									
D3	.195	.200	.205									
E	1.695	1.700	1.705									
E1	1.285	1.300	1.315									
E2	1.165	1.180	1.195									
E3	1.095	1.100	1.105									
e		.100BSC		4								
e1		.150BSC		4								
e2		.900BSC										
eA		1.500BSC										
L	.090	—	—	5								
L1	.090	.100	.110									
M	—	—	.002									
N	—	16	—									
øP	.116	.118	.120									
Q1	.100	.110	.120									
q		1.280BSC										
q1		1.500BSC										
NOTE	1.2.3.4.5											
REF	10-310											
ISSUE	A											
JEDEC SOLID STATE PRODUCT OUTLINES			TITLE 16 LEAD FLANGE MOUNTED CERAMIC POWER PACKAGE (TYPE 1) R-CDFM-T16				ISSUE A		DATE JUNE 1993		M0-138	
											SHEET 3 OF 3	