

AMPLIFIER SELECTION GUIDE

	MODEL NO.	FREQ. [MHz] f _L f _U	GAIN [dB] MIN.	MAX ⁽¹⁾ POWER [dBm]	N.F. [dB] TYP.	3rd ORDER I.P. [dBm]	VSWR ⁽²⁾		DC POWER		CASE STYLE	STD. CONN.	OPTION
							IN	OUT	V VOLT	I [mA]			
PIN	ERA-1	DC-8000	9.0	+12.0	4.3	+26.0	1.5:1	1.5:1	+3.4	40	VV105		
	ERA-2	DC-6000	13.0	+13.0	4.0	+26.0	1.3:1	1.2:1	+3.4	40	VV105		
	ERA-3	DC-3000	16.0	+12.5	3.5	+25.0	1.5:1	1.4:1	+3.2	35	VV105		
	ERA-4	DC-4000	11.0	+17.3	4.2	+34.0	1.2:1	1.3:1	+4.5	65	VV105		
	ERA-5	DC-4000	16.0	+18.4	4.3	+32.5	1.3:1	1.3:1	+4.9	65	VV105		
	ERA-6	DC-4000	10.5	+17.9	4.5	+36.0	1.3:1	1.6:1	+5.0	70	VV105		
MONOLITHIC • SURFACE MOUNT	ERA-1SM	DC-8000	9.0	+12.0	4.3	+26.0	1.5:1	1.5:1	+3.4	40	WW107		
	ERA-2SM	DC-6000	13.0	+13.0	4.0	+26.0	1.3:1	1.2:1	+3.4	40	WW107		
	ERA-21SM	DC-8000	11.2	+12.6	4.7	+26.0	1.1:1	1.3:1	+3.5	40	WW107		
	ERA-3SM	DC-3000	16.0	+12.5	3.5	+25.0	1.5:1	1.4:1	+3.2	35	WW107		
	ERA-33SM	DC-3000	15.0	+13.5	3.9	+28.5	1.6:1	1.25:1	+4.3	40	WW107		
	ERA-4SM	DC-4000	11.0	+17.3	4.2	+34.0	1.2:1	1.3:1	+4.5	65	WW107		
	ERA-4XSM	DC-4000	12.0	+15.0	4.2	+35.0	1.2:1	1.2:1	+4.5	65	WW107		
	ERA-5SM	DC-4000	16.0	+18.4	4.3	+32.5	1.3:1	1.2:1	+4.9	65	WW107		
	ERA-5XSM	DC-4000	16.0	+16.5	3.5	+33.0	1.2:1	1.2:1	+4.9	65	WW107		
	ERA-50SM	DC-1500	16.0	+17.2	3.5	+32.5	1.3:1	1.2:1	+4.4	60	WW107		
	ERA-51SM	DC-4000	14.0	+18.1	4.1	+33.0	1.1:1	1.2:1	+4.5	65	WW107		
	ERA-6SM	DC-4000	10.5	+17.9	4.5	+36.0	1.3:1	1.6:1	+5.0	70	WW107		
	ERA-8SM	DC-2000	17.0	+12.5	3.1	+25.0	1.4:1	1.8:1	+3.7	36	WW107		
	Gali-1	DC-8000	9.0	+10.5	4.5	+27.0	1.3:1	1.4:1	+3.4	40	DF782		
	Gali-19	DC-7000	9.6	+9.0	6.5	+23.7	1.6:1	1.5:1	+3.6	40	DF782		
	Gali-2	DC-8000	12.0	+11.0	4.6	+27.0	1.6:1	1.6:1	+3.5	40	DF782		
	Gali-21	DC-8000	11.5	+10.5	4.0	+27.0	1.1:1	1.3:1	+3.5	40	DF782		
	Gali-29	DC-7000	12.7	+10.0	6.0	+24.7	1.5:1	1.5:1	+3.6	40	DF782		
	Gali-3	DC-3000	17.5	+10.5	3.5	+25.0	1.5:1	1.2:1	+3.3	35	DF782		
	Gali-33	DC-4000	16.0	+11.4	3.9	+28.0	1.6:1	1.2:1	+4.3	40	DF782		
	Gali-39	DC-7000	17.7	+9.0	4.9	+22.9	1.6:1	1.5:1	+3.5	35	DF782		
	Gali-4	DC-4000	11.0	+16.0	4.0	+34.0	1.2:1	1.4:1	+4.6	65	DF782		
	Gali-4F	DC-4000	11.0	+13.8	4.0	+32.0	1.2:1	1.5:1	+4.4	50	DF782		
	Gali-49	DC-5000	11.5	+15.0	5.5	+33.3	1.7:1	1.5:1	+5.0	65	DF782		
	Gali-5	DC-4000	16.0	+16.0	3.5	+35.0	1.2:1	1.4:1	+4.4	65	DF782		
	Gali-5F	DC-4000	15.5	+14.2	3.5	+31.5	1.2:1	1.4:1	+4.3	50	DF782		
	Gali-51	DC-4000	14.0	+16.5	3.5	+35.0	1.3:1	1.5:1	+4.5	65	DF782		
	Gali-51F	DC-4000	14.0	+14.4	3.5	+32.0	1.2:1	1.5:1	+4.4	50	DF782		
	Gali-52	DC-2000	16.0	+13.5	2.7	+32.0	1.35:1	1.4:1	+4.4	50	DF782		
	Gali-55	DC-4000	17.0	+13.5	3.3	+28.5	1.25:1	1.3:1	+4.3	50	DF782		
	Gali-59	DC-5000	16.3	+16.5	4.3	+33.3	1.6:1	1.5:1	+4.8	65	DF782		
	Gali-6	DC-4000	10.0	+16.5	4.5	+35.5	1.5:1	1.8:1	+5.0	70	DF782		
	Gali-6F	DC-4000	10.0	+14.3	4.5	+35.5	1.5:1	1.9:1	+4.8	50	DF782		
	Gali-S66	DC-3000	15.0	+1.0	2.7	+18.0	1.25:1	1.7:1	+3.5	16	DF782		
	Gali-74	DC-1000	20.0	+17.3	2.7	+38.0	1.2:1	1.6:1	+4.8	80	DF782		
	HELA-10	50-1000	10.5	+30.0	3.5	+47.0	1.22:1	1.22:1	+12.0	525	CM624		
	LEE-19	DC-8000	9.6	+10.2	6.5	+24.5	1.5:1	1.4:1	+3.6	40	FG873		
	LEE-29	DC-8000	13.3	+10.9	5.5	+25.5	1.4:1	1.3:1	+3.6	40	FG873		
	LEE-39	DC-8000	18.5	+10.4	4.5	+23.4	1.3:1	1.3:1	+3.5	35	FG873		
	LEE-49	DC-5000	12.0	+16.4	5.5	+33.0	1.6:1	1.4:1	+4.9	65	FG873		
	LEE-59	DC-5000	17.8	+17.3	4.5	+33.0	1.5:1	1.5:1	+4.8	65	FG873		
	MAR-1SM	DC-1000	13.0	+1.5	5.5	+14.0	1.3:1	1.3:1	+5.0	17	WW107		
	MAR-2SM	DC-2000	8.5	+4.5	6.5	+17.0	1.3:1	1.4:1	+5.0	25	WW107		
	MAR-3SM▼	DC-2000	8.0	+10.0	6.0	+23.0	1.5:1	1.7:1	+5.0	35	WW107		
	MAR-4SM	DC-1000	7.0	+12.5	6.5	+25.5	1.6:1	2.0:1	+5.3	50	WW107		
	MAR-6SM▼	DC-2000	9.0	+2.0	3.0	+14.5	1.5:1	1.4:1	+3.5	16	WW107		
	MAR-7SM▼	DC-2000	8.5	+5.5	5.0	+19.0	1.4:1	1.5:1	+4.0	22	WW107		
	MAR-8SM	DC-1000	19.0	+12.5	3.3	+27.0	3.1:1	3.1:1	+7.8	36	WW107		
	MAR-8ASM	DC-1000	20.0	+12.5	3.1	+25.0	1.4:1	1.8:1	+3.7	36	WW107		
	MAV-11SM	50-1000	9.0	+17.5	3.6	+30.0	1.5:1	1.7:1	+5.5	60	RRR137		
	MAV-11A	50-2000	9.0	+18.5	4.8	+35.0	1.4:1	1.1:1	+5.5	60	DH820		
	MAV-11BSM	50-1000	9.5	+18.0	4.4	+34.0	1.2:1	1.2:1	+5.5	60	RRR137		
	MERA-533	DC-4000	16	+16.5	3.5	+35	1.4:1	1.5:1	+4.9	65	DL805		
	MERA-556	DC-2200	16.0	+16.5	3.5	+35	1.2:1	1.4:1	+4.9	65	DL1020		
	MERA-7433	DC-1000	20.0	+18.0	2.7	+36	1.25:1	1.8:1	+4.8	80	DL805		
	MERA-7456	DC-1000	20.0	+18.0	2.7	+36	1.3:1	2.0:1	+4.8	80	DL1020		
	MNA-2	500-2500	10.3	+17.7	5.4	+28.0	1.5:1	1.6:1	+5.0	76	DQ849		
	MNA-3	500-2500	13.0	+11.4	4.9	+21.3	1.9:1	1.5:1	+5.0	30	DQ849		
	MNA-4	500-2500	14.0	+19.0	4.8	+29.0	1.5:1	1.7:1	+5.0	75	DQ849		
	MNA-5	500-2500	17.0	+12.2	3.5	+21.0	1.6:1	1.9:1	+5.0	28	DQ849		
	MNA-6	500-2500	21.5	+18.0	2.9	+28.0	1.5:1	1.6:1	+5.0	81	DQ849		
	MNA-7	1500-5900	15.0	+15.9	6.9	+28.6	2.0:1	1.5:1	+5.0	73	DQ849		
	RAM-1	DC-1000	13.0	+1.5	5.5	+14.0	1.3:1	1.3:1	+5.0	17	AF190		
	RAM-2	DC-2000	8.5	+4.5	6.5	+17.0	1.2:1	1.4:1	+5.0	25	AF190		
	RAM-3	DC-2000	8.0	+10.0	6.0	+23.0	1.6:1	1.7:1	+5.0	35	AF190		
	RAM-4	DC-1000	7.0	+12.5	6.5	+25.5	1.4:1	1.9:1	+5.3	50	AF190		
	RAM-6	DC-2000	9.0	+2.0	2.8	+14.5	1.4:1	1.3:1	+3.5	16	AF190		
	RAM-7	DC-2000	8.5	+5.5	4.5	+19.0	2.0:1	1.8:1	+4.0	22	AF190		
	RAM-8	DC-1000	19.0	+12.5	3.0	+27.0	3.1:1	3.1:1	+7.8	36	AF190		
	VNA-21	500-2500	12.6	+8.5	6.4	+20.0	1.4:1	1.3:1	+5.0	31	XX211		
	VNA-22	500-2500	11.8	+17.0	6.7	+29.0	1.6:1	1.4:1	+5.0	80	XX211		
	VNA-23	500-2500	15.4	+10.0	4.7	+21.0	1.5:1	1.3:1	+5.0	32	XX211		
	VNA-25	500-2500	16.0	+18.2	5.5	+29.0	1.5:1*	1.6:1	+5.0	85	XX211		
	VNA-28	500-2500	19.7	+11.0	3.7	+22.0	1.6:1	1.5:1	+5.0	33	XX211		

		MODEL NO.	FREQ. [MHz] f _L f _U	GAIN [dB] MIN.	MAX ⁽¹⁾ POWER [dBm]	N.F. [dB] TYP.	3rd ORDER I.P. [dBm]	VSWR ⁽²⁾		DC POWER V I VOLT [mA]		CASE STYLE	STD. CONN.	OPTION				
VAR. GAIN	CON	ZFL-1000G ZFL-1000GH	10-1000 10-1200	17.0 24.0	+3.0 +13.0	12.0 15.0	+13.0 +25.0	2.0:1 2.2:1	2.0:1 2.0:1	+15.0 +15.0	100 170	Y39 Y39	SMA SMA	— —				
LOW NOISE (N.F. <4.0 dB)	PIN	AMP-76 AMP-77 AMP-75 AMP-15	5-500 5-500 5-500 5-1000	26.0 15.0 19.0 13.0	+13.5 +16.0 +12.0 +8.0	3.1 3.3 2.4 2.8	+28.0 +32.0 +28.0 +22.0	2.0:1 2.0:1 2.0:1 2.0:1	2.0:1 2.0:1 2.0:1 2.0:1	+15.0 +15.0 +15.0 +15.0	71 56 31 29	PP120 PP120 PP120 PP120						
		MAN-1HLN MAN-1LN	10-500 0.5-500	10.0 28.0	+15.0 +8.0	3.7 2.8	+30.0 +18.0	1.8:1 1.8:1	1.8:1 1.8:1	+12.0 +12.0	70 60	A06 A05						
		TO-0812LN TO-1217LN TO-1724LN	800-1200 1200-1700 1700-2400	20.0 20.0 20.0	+8.0 +10.0 +10.0	1.2 1.6 1.6	+22.5 +25.0 +22.0	2.5:1 2.5:1 2.5:1	2.5:1 2.5:1 2.5:1	+15.0 +15.0 +15.0	70 70 70	QQ96 QQ96 QQ96						
		CON	ZFL-500LN ZFL-1000LN ZFL-500HLN	0.1-500 0.1-1000 10-500	24.0 20.0 19.0	+5.0 +3.0 +16.0	2.9 2.9 3.8	+14.0 +14.0 +30.0	1.5:1 1.5:1 1.5:1	1.6:1 2.0:1 1.5:1	+15.0 +15.0 +15.0	60 60 110	Y39 Y39 Y39	SMA SMA SMA	BNC — —			
			ZEL-0812LN ZHL-0812HLN ZHL-0812MLN	800-1200 800-1200 800-1200	20.0 30.0 28.0	+8.0 +26.0 +20.0	1.5 1.5 1.3	+18.0 +36.0 +33.0	2.5:1 2.4:1 1.5:1	2.5:1 2.4:1 1.6:1	+15.0 +15.0 +15.0	70 725 300	EEE132 NN92 S32	SMA SMA SMA	— — —			
			ZEL-1217LN ZHL-1217HLN ZHL-1217MLN	1200-1700 1200-1700 1200-1700	20.0 30.0 30.0	+10.0 +26.0 +20.0	1.5 1.5 1.2	+25.0 +36.0 +34.0	2.5:1 2.4:1 1.5:1	2.5:1 2.4:1 1.6:1	+15.0 +15.0 +15.0	70 725 300	EEE132 NN92 S32	SMA SMA SMA	— — —			
			ZEL-1724LN ZHL-1724HLN ZHL-1724MLN	1700-2400 1700-2400 1700-2400	20.0 30.0 28.0	+10.0 +26.0 +20.0	1.5 1.5 1.2	+22.0 +36.0 +32.0	2.5:1 2.4:1 1.5:1	2.5:1 2.4:1 1.6:1	+15.0 +15.0 +15.0	70 725 300	EEE132 NN92 S32	SMA SMA SMA	— — —			
			ZQL-900LNW ZQL-900MLNW ZQL-900LN ZQL-900MLN	800-900 800-900 824-849 824-849	13.0 22.0 15.0 25.5	+21.0 +23.0 +21.0 +24.5	1.0 1.2 1.0 1.0	+35.0 +41.0 +35.0 +41.0	1.2:1 1.3:1 1.2:1 1.3:1	1.1:1 1.4:1 1.1:1 1.4:1	+15.0 +15.0 +15.0 +15.0	160 230 160 230	CW686 CW686 CW686 CW686	SMA SMA SMA SMA	— — — —			
	ZQL-1900LNW ZQL-1900MLNW ZQL-1900LN ZQL-1900MLN		1700-2000 1800-2000 1850-1910 1850-1910	14.0 23.0 15.0 25.0	+18.5 +25.0 +19.0 +26.0	0.9 1.1 0.9 1.1	+37.0 +41.0 +37.0 +41.0	1.15:1 1.4:1 1.15:1 1.25:1	1.25:1 1.25:1 1.25:1 1.20:1	+15.0 +15.0 +15.0 +15.0	160 310 160 310	CW686 CW686 CW686 CW686	SMA SMA SMA SMA	— — — —				
	ZQL-2700MLNW ZQLSC-1100 ZQLSC-2400 ZX60-3011 ZX60-1215LN ZX60-1614LN		2200-2700 600-1100 1400-2400 400-3000 800-1400 1217-1620	25.0 19.0 12.0 10.0 13.0 11.0	+25.0 +16.0 +17.0 +19.0 +12.5 +13.5	1.0 0.6 0.9 1.6 0.4 0.5	+38.0 +34.0 +35.0 +31.0 +27.0 +30.0	1.25:1 1.8:1 1.6:1 1.7:1 1.7:1 1.3:1	1.15:1 1.8:1 1.7:1 1.6:1 1.4:0 1.3:1	+15.0 +24.0 +24.0 +12.0 +12.0 +12.0	325 185 185 120 42 42	CW686 GZ1067 GZ1067 GC957 GA955 GA955	SMA SMA SMA SMA SMA SMA	— — — — — —				
	HIGH ISOLATION		PIN	MAN-2AD MAN-11AD MAN-1AD	2-1000 2-2000 5-500	9.0 8.0 16.0	-3.5 -3.5 +7.0	6.5 6.5 7.2	+14.0 +14.0 +20.0	2.0:1 3.0:1 1.6:1	2.0:1 2.0:1 1.7:1	+15.0 +15.0 +12.0	22 22 85	A05 A05 A05				
				CON	ZFL-2AD ZFL-11AD	2-1000 2-2000	9.0 8.0	-3.5 -3.5	6.5 6.5	+14.0 +14.0	2.0:1 2.5:1	2.0:1 2.0:1	+15.0 +15.0	22 22	Y39 Y39	SMA SMA	— —	
					ZFL-1HAD ZFL-2HAD ZHL-1HLD	10-500 50-1000 225-400	10.0 11.0 23.0	+20.0 +20.0 +27.0	7.5 5.0 2.5	+30.0 +33.0 +40.0	1.3:1 2.0:1 2.0:1	1.35:1 2.0:1 2.0:1	+15.0 +15.0 +24.0	115 110 525	SS98 SS98 T34	SMA SMA SMA	— — —	
			LOW POWER		CON	ZX60-2510M ZX60-2514M ZX60-2522M ZX60-2531M ZX60-2534M ZX60-3018G ZX60-4016E ZX60-6013E ZX60-8008E ZX60-5916M	500-2500 500-2500 500-2500 500-2500 500-2500 20-3000 20-4000 20-6000 20-8000 1500-5900	10.4 14.0 21.5 31.0 34.0 18.0 15.7 13.0 8.4 15.5	+17.1 +18.3 +19.2 +18.2 +18.0 +12.8 +17.4 +13.4 +10.8 +14.5	5.4 4.8 3.0 3.5 3.1 2.7 3.9 3.3 4.1 6.4	+28.8 +30.3 +30.6 +28.4 +30.0 +25.0 +30.0 +28.7 +24.0 +28.3	1.5:1 1.5:1 1.5:1 1.3:1 1.3:1 1.3:1 1.25:1 1.4:1 1.3:1 2.2:1	1.6:1 1.7:1 1.7:1 1.5:1 1.5:1 1.4:1 1.3:1 1.2:1 1.6:1 1.2:1	+5.0 +5.0 +5.0 +5.0 +5.0 +12.0 +12.0 +12.0 +12.0 +5.0	95 90 95 102 153 34 64 39 39 96	GC957 GC957 GC957 GA955 GA955 GC957 GC957 GC957 GC957 GC957	SMA SMA SMA SMA SMA SMA SMA SMA SMA SMA	— — — — — — — — — —
				PIN		AMP-25G MAN-1 MAN-2 AMP-3G	10-2500 0.5-500 0.5-1000 30-3000	16.0 28.0 18.0 8.0	+12.0 +8.0 +9.0 +9.5	3.5 4.5 6.0 3.5	+24.0 +18.0 +19.0 +20.0	1.6:1 1.8:1 1.8:1 2.6:1	1.2:1 1.8:1 1.8:1 2.5:1	+15.0 +12.0 +12.0 +15.0	55 60 85 55	PP120 A05 A05 PP230		
						CON	ZFL-500 ZFL-1000 ZFL-750 ZJL-7G ZJL-6G ZJL-3G ZX60-14012L	0.05-500 0.1-1000 0.2-750 20-7000 20-6000 20-3000 0.3-14000	20.0 17.0 18.0 7.5 10.0 14.0 9.0	+9.0 +9.0 +9.0 +9.0 +10.0 +8.0 +9.0	5.3 6.0 6.0 5.0 4.5 3.8 5.5	+18.0 +18.0 +18.0 +24.0 +24.0 +22.0 +20.0	1.9:1 1.5:1 1.5:1 1.5:1 1.5:1 1.4:1 1.3:1	1.9:1 2.0:1 2.0:1 1.5:1 1.4:1 1.6:1 1.7:1	+15.0 +15.0 +15.0 +12.0 +12.0 +12.0 +12.0	60 105 90 50 50 45 62	Y460 Y460 Y460 BW459 BW459 BW459 GC957	SMA SMA SMA SMA SMA SMA SMA

⁽¹⁾ Minimum output power at 1 dB gain compression. For LEE, MNA, VNA, ZX60-M models, typical.

⁽²⁾ For ERA, Gali, LEE, VAM-77 models, VSWR given as DC-3GHz; ERA-50SM DC-1.5 GHz; ERA-8SM DC-1GHz. For MNA and VNA models, VSWR given as 750-2500 MHz, except MNA-7 which is 2.5-5.9 GHz.

• Surface Mount.

▼ Alternate package style SOT 143, see VAM series.

* Increase below 1500 MHz.

Using the Selection Guide:

Locate the Mini-Circuits' amplifier best suited for your particular application quickly with this convenient Selection Guide. Amplifiers are grouped into ten major categories and then listed in the sequence of frequency span. If your amplifier requirements are not met by the catalog models listed, we encourage you to contact our Application Engineering Department. You will find them courteous and eager to support your needs with their depth of knowledge coupled with our extensive database on engineering and catalog models.

AMPLIFIER SELECTION GUIDE

		MODEL NO.	FREQ. [MHz] f _L f _U	GAIN [dB] MIN.	MAX ^[1] POWER [dBm]	N.F. [dB] TYP.	3rd ORDER I.P. [dBm]	VSWR ^[2] IN OUT		DC POWER V I VOLT [mA]		CASE STYLE	STD. CONN.	OPTION
MEDIUM POWER	PIN	AMP-2000	10-2000	20.0	+15.0	5.0	+25.0	2.0:1	2.0:1	+150.0	100	QQ96		
	CON	ZHL-6A	.0025-500	21.0	+23.0	9.5	+34.0	1.8:1	2.0:1	+24.0	350	S32	BNC	—
		ZFL-1000H	10-1000	28.0	+20.0	5.0	+33.0	2.0:1	2.0:1	+15.0	150	SS98	SMA	—
		ZFL-1000VH	10-1000	20.0	+25.0	4.5	+38.0	2.0:1	2.5:1	+15.0	320	SS98	SMA	—
		ZFL-1000VH2	10-1000	26.0	+25.0	5.0	+38.0	2.0:1	2.5:1	+15.0	320	SS98	SMA	—
		ZFL-2000	10-2000	20.0	+16.0	7.0	+25.0	2.0:1	2.0:1	+15.0	120	SS98	SMA	—
		ZFL-2500	500-2500	28.0	+15.0	8.0	+27.0	2.5:1	2.5:1	+5.0	220	Y460	SMA	—
		ZFL-2500VH	10-2500	20.0	+24.0	5.5	+35.0	1.7:1	2.0:1	+15.0	300	SS98	SMA	—
		ZHL-1042J	10-4200	25.0	+20.0	4.5	+30.0	2.5:1	2.5:1	+15.0	300	NN92	SMA	—
		ZJL-4G	20-4000	10.0	+11.0	5.5	+30.5	1.4:1	1.6:1	+12.0	75	BW459	SMA	—
		ZJL-4HG	20-4000	13.0	+12.0	4.5	+30.5	1.5:1	1.4:1	+12.0	75	BW459	SMA	—
		ZJL-5G	20-5000	7.0	+9.5	8.5	+32.0	1.6:1	1.3:1	+12.0	80	BW459	SMA	—
		ZKL-2R7	10-2000	20.0	+11.0	5.0	+30.0	1.3:1	1.4:1	+12.0	120	BY493	SMA	—
		ZKL-2R5	10-2000	26.0	+15.0	5.0	+31.0	1.4:1	1.4:1	+12.0	120	BY493	SMA	—
		ZKL-2	10-2000	30.0	+15.0	4.0	+31.0	1.4:1	1.4:1	+12.0	120	BY493	SMA	—
		ZKL-1R5	10-1500	36.0	+15.0	3.0	+31.0	1.4:1	1.6:1	+12.0	115	BY493	SMA	—
		ZRON-8G	2000-8000	20.0	+20.0	6.0	+30.0	2.0:1	2.0:1	+15.0	310	AV243	SMA	—
MEDIUM HIGH POWER	CON	ZHL-32A	.05-130	25.0	+29.0	10.0	+38.0	2.0:1	2.0:1	+24.0	600	S32	BNC	SMA,N
		ZHL-3A	.4-150	24.0	+29.5	11.0	+38.0	2.0:1	2.0:1	+24.0	600	S32	BNC	SMA,N
		ZHL-1A	2-500	16.0	+28.0	11.0	+38.0	2.0:1	2.0:1	+24.0	600	S32	BNC	SMA,N
		ZHL-450-75	5-450	9.3	+26.0	3.5	+48.0	2.5:1	1.6:1	+12.0	525	S32	BNC	—
		ZHL-1010-75	50-1000	9.5	+26.0	3.5	+47.0	1.5:1	1.5:1	+12.0	525	S32	BNC	—
		ZHL-2	10-1000	16.0	+29.0	9.0	+38.0	2.0:1	2.0:1	+24.0	600	T34	BNC	SMA,N
		ZHL-2-8	10-1000	27.0	+29.0	10.0	+38.0	2.0:1	2.0:1	+24.0	600	T34	BNC	SMA,N
		ZHL-2-12	10-1200	24.0	+29.0	4.0	+38.0	2.0:1	2.0:1	+24.0	750	T34	SMA	—
		ZHL-1010	50-1000	9.5	+26.0	3.5	+46.0	1.5:1	1.5:1	+12.0	525	S32	SMA	—
		ZHL-2010	50-1000	20.0	+26.0	3.7	+46.0	1.5:1	1.5:1	+12.0	900	S32	SMA	—
		ZHL-3010	50-1000	30.0	+26.0	5.5	+46.0	2.0:1	1.6:1	+12.0	1000	S32	SMA	—
		ZHL-42W	10-4200	30.0	+28.0	8.0	+38.0	2.5:1	2.5:1	+15.0	880	U36	SMA	—
		ZHL-4240W	10-4200	40.0	+28.0	8.0	+38.0	2.5:1	2.5:1	+15.0	900	U36	SMA	—
		ZHL-42	700-4200	30.0	+28.0	10.0	+38.0	2.5:1	2.5:1	+15.0	880	U36	SMA	—
		ZHL-211	800-950	20.0	+29.0	8.0	+38.0	1.8:1	1.8:1	+24.0	600	T34	BNC	SMA
		ZHL-4240	700-4200	40.0	+28.0	8.0	+38.0	2.5:1	2.5:1	+15.0	900	U36	SMA	—
		ZRL-400	150-400	27.0	+23.5	2.5	+42.0	1.25:1	1.35:1	+12.0	575	FJ893	SMA	—
		ZRL-700	250-700	27.0	+23.5	2.0	+46.0	1.20:1	1.30:1	+12.0	575	FJ893	SMA	—
		ZRL-1150LN	500-1400	25.0	+22.0	1.0	+40.0	1.25:1	1.25:1	+12.0	500	FJ893	SMA	—
		ZRL-1200	850-1200	25.0	+23.5	2.0	+46.0	1.2:1	1.25:1	+12.0	575	FJ893	SMA	—
		ZRL-2150	950-2150	22.5	+17.5	1.5	+33.0	1.3:1	1.2:1	+12.0	300	FJ893	SMA	—
		ZRL-2300	1400-2300	21.0	+23.0	2.5	+46.0	1.2:1	1.16:1	+12.0	575	FJ893	SMA	—
		ZRL-2400N	1000-2400	23.0	+21.0	1.0	+45.0	1.25:1	1.3:1	+12.0	500	FJ893	SMA	—
		ZRL-3500	700-3500	11.0	+21.0	2.6	+45.0	1.4:1	1.3:1	+12.0	575	FJ893	SMA	—
		ZVE-8G	2000-8000	30.0	+30.0	4.0	+40.0	2.0:1	2.0:1	+12.0	1200	BN333	SMA	—
HIGH POWER	CON	ZHL-03-5WF	60-300	30.0	+36.0	4.0	+47.0	1.4:1	1.5:1	+24.0	2800	CP641	SMA	—
		ZHL-5W-1	5-500	40.0	+37.0	4.0	+49.0	2.0:1	2.5:1	+24.0	3300	DDD131	SMA	—
		ZHL-1-2W	5-500	29.0	+33.0	12.0	+44.0	2.0:1	2.0:1	+24.0	900	T35	BNC	SMA,N
		ZHL-900-10W	480-900	19.0	+38.0	10.0	+50.0	2.0:1	2.0:1	+24.0	5500	DDD131	SMA	—
		ZHL-1000-3W	500-1000	38.0	+35.0	9.0	+45.0	2.0:1	2.5:1	+24.0	2250	DDD131	SMA	—
VERY HIGH POWER	CON	LZY-1	20-512	39.0	+44.0	8.6	+54.0	2.0:1	9.0:1	+26.0	7300	BT412	SMA	—
		LZY-2	500-1000	40.0	+43.0	8.0	+54.0	2.0:1	3.5:1	+28.0	8000	BT451	SMA	—

^[1] Minimum output power at 1 dB gain compression.
^[2] VSWR for ZRL model is typical.

Using the Selection Guide:
 Locate the Mini-Circuits' amplifier best suited for your particular application quickly with this convenient Selection Guide. Amplifiers are grouped into ten major categories and then listed in the sequence of frequency span. If your amplifier requirements are not met by the catalog models listed, we encourage you to contact our Application Engineering Department. You will find them courteous and eager to support your needs with their depth of knowledge coupled with our extensive database on engineering and catalog models.