


MODEL 64

1/4" Square

Multiturn

Cermet Trimming

Potentiometer



ELECTRICAL

Standard Resistance Range, Ohms	10 to 1Meg
Standard Resistance Tolerance	±10%
Input Voltage, Maximum	200Vdc or rms not to exceed power rating
Slider Current, Maximum	100mA or within rated power, whichever is less
Power Rating, Watts	0.25 at 85°C derating to 0 at 150°C
End Resistance, Maximum	2 Ohms
Actual Electrical Travel, Turns, Nominal	12
Dielectric Strength	900Vrms
Insulation Resistance, Minimum	1,000 Megohms
Resolution	Essentially infinite
Contact Resistance Variation, Maximum	1% or 1 Ohms, whichever is greater

ENVIRONMENTAL

Seal	85°C Fluorinert® (No Leaks)
Temperature Coefficient, Maximum	±100ppm/°C
Operating Temperature Range	-65°C to +150°C
Thermal Shock	5 cycles, -65°C to +150°C (1% ΔRT, 1% ΔVR)
Moisture Resistance	Ten 24 hour cycles (1% ΔRT, IR 1,000 Megohms Min.)
Shock, 6ms Sawtooth	100G's (1% ΔRT, 1% ΔVR)
Vibration	20G's, 10 to 2,000 Hz (1% ΔRT, 1% ΔVR)
High Temperature Exposure	250 hours at 125°C (2% ΔRT, 2% ΔVR)
Rotational Life	200 cycles (2% ΔRT)
Load Life at 0.5 Watts	1,000 hours at 85°C (2% ΔRT)
Resistance to Solder Heat	260°C for 10 sec. (1% ΔRT)

MECHANICAL

Mechanical Stops	Clutch action, both ends
Torque, Starting Maximum	3 oz.-in. (0.021 N-m)
Weight, Nominal	.014 oz. (0.40 grams)

Fluorinert® is a registered trademark of 3M Company.
Specifications subject to change without notice.

TOP ADJUSTMENT (Inch/mm)

Model 64W and 64Y

Technical drawing showing the dimensions and features of the Model 64W and 64Y components.

Top View Dimensions:

- Overall Width: 1.27
- Overall Height: 1.02
- Top Edge Feature: $.050$
- Left Edge Feature: $.040$
- Right Edge Feature: $.165 \pm .020$
- Bottom Edge Feature: $.250 \pm .020$
- Bottom Edge Feature: $6.35 \pm .051$

Side View Dimensions:

- Overall Height: 1.02
- Top Edge Feature: $.040$
- Right Edge Feature: $.270 \pm .020$
- Right Edge Feature: $6.86 \pm .051$
- Bottom Edge Feature: $.020$ Min.
- Bottom Edge Feature: $.172$
- Bottom Edge Feature: 4.37 Min.



Labels and Features:

- Metal Adjustment Screw
- Standard Marking On This Surface
- Terminal Pins (3)
- Solderable

Dimensions:

- $.070 \pm .005$ Dia. With Slot
- 1.78 ± 0.13
- $.020$ Min. Wide x $.020$ Min. Deep
- 0.51
- 0.51
- $0.018 \pm .002$
- $0.46 \pm .05$

Note: Model 64W dimensions applicable to all models except as noted




STANDARD RESISTANCE VALUES, OHMS

10	100	1K	10K	50K	250K
20	200	2K	20K	100K	500K
50	500	5K	25K	200K	1Meg


SIDE ADJUSTMENT (Inch/mm)

1


Model 64X and 64Z




Model 64Z



Model 64X



Model 64P



PACKAGING

Standard: Tubes
All units oriented with #1 pin to same side.

	Pin Style		P,W,Y	X,Z
Magazine	Width	=	0.38" (9.65 mm)	0.38" (9.65 mm)
	Height	=	0.62" (15.75mm)	0.62" (15.75mm)
	Length	=	14.5" (368 mm)	16.9" (429 mm)
	Capacity	=	50 Units	50 Units

Option: Tape & Reel, Ammo Pack (Available only for 64Y and 64Z)
All units oriented with #1 pin to the right of the direction of feed.

Tape	Seat Plane to Centerline of Sprocket Hole	=	.71" (18 mm)
	Width	=	18 mm
	Sprocket	=	Single Hole .50" spacing
	Capacity	=	1,000 Units
Reel	Diameter	=	14" (363 mm)
Ammo	Tape Fold	=	12"
	Box	=	1.8" x 13" x 10" (46mm x 330mm x 254mm)

ORDERING INFORMATION

Standard:

64

P

R

10K

Model Series

Pin Style

Resistance Value

Resistance Prefix

Option:

64

Y

F

R

10K

XX

Pin Style

Pin Style Suffix

Packaging Option

AP = Ammo pack


TR = Tape & Reel

(No code used for tubes)

(Used with AP & TR packaging options.

"F" designates 0.6" min. lead length.)

CIRCUIT DIAGRAM



NOTES

Metric equivalents, based on 1 inch = 25.4mm are rounded to the same number of significant figures as in the original. English units and are provided for general information only.

Tolerances unless otherwise specified:
Linear = ± .01 inches (.25mm)
Angular = ± 2 degrees

DIMENSIONS

INCH
mm

THIRD ANGLE PROJECTION