

C Programming

[INDEX](#)
[◀ Previous](#)
[Next ▶](#)

ARITHMETIC OPERATORS

The symbols of the arithmetic operators are:-

Operation	Operator	Comment	Value of Sum before	Value of sum after
Multiply	*	sum = sum * 2;	4	8
Divide	/	sum = sum / 2;	4	2
Addition	+	sum = sum + 2;	4	6
Subtraction	-	sum = sum - 2;	4	2
Increment	++	++sum;	4	5
Decrement	--	--sum;	4	3
Modulus	%	sum = sum % 3;	4	1

The following code fragment adds the variables *loop* and *count* together, leaving the result in the variable *sum*

```
sum = loop + count;
```

Note: If the modulus % sign is needed to be displayed as part of a text string, use two, ie %%

```
#include <stdio.h>

main()
{
    int sum = 50;
    float modulus;

    modulus = sum % 10;
    printf("The %% of %d by 10 is %f\n", sum, modulus);
}
```

Sample Program Output

```
The % of 50 by 10 is 0.000000
```

CLASS EXERCISE C5

What does the following change do to the printed output of the previous program?

```
printf("The %% of %d by 10 is %.2f\n", sum, modulus);
```

[Answers](#)

©Copyright B Brown. 1984-1999. All rights reserved.

