

C Programming

[INDEX](#)
[◀ Previous](#)
[Next ▶](#)

FORMATTERS FOR STRINGS/CHARACTERS

Consider the following program.

```
#include <stdio.h>

main()      /* FORMATS.C */
{
    char      c = '#';
    static char s[] = "helloandwelcometoclanguage";

    printf("Characters:\n");
    printf("%c\n", c);
    printf("%3c%3c\n", c, c);
    printf("%-3c%-3c\n", c, c);
    printf("Strings:\n");
    printf("%s\n", s);
    printf("%.5s\n", s);
    printf("%30s\n", s);
    printf("%20.5s\n", s);
    printf("%-20.5s\n", s);
}
```

The output of the above program will be,

```
Characters:
#
# #
# #
Strings:
helloandwelcometoclanguage
hello
    helloandwelcometoclanguage
                hello
hello
```

The statement `printf("%.5s\n",s)` means print the first five characters of the array `s`. The statement `printf("%30s\n", s)` means that the array `s` is printed right justified, with leading spaces, to a field width of thirty characters.

The statement `printf("%20.5s\n", s)` means that the first five characters are printed in a field size of twenty which is right justified and filled with leading spaces.

The final `printf` statement uses a left justified field of twenty characters, trailing spaces, and the `.5` indicating to print the first five characters of the array `s`.

©Copyright B Brown. 1984-1999. All rights reserved.

[INDEX](#)
[◀ Previous](#)
[Next ▶](#)