



US006867443B2

(12) **United States Patent**  
**Liu et al.**

(10) **Patent No.:** **US 6,867,443 B2**  
(45) **Date of Patent:** **Mar. 15, 2005**

(54) **PARALLEL, INDIVIDUALLY ADDRESSABLE PROBES FOR NANOLITHOGRAPHY**

(75) Inventors: **Chang Liu**, Champaign, IL (US); **Ming Zhang**, Urbana, IL (US); **David Andrew Bullen**, Urbana, IL (US)

(73) Assignee: **The Board of Trustees of the University of Illinois**, Urbana, IL (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/647,724**

(22) Filed: **Aug. 25, 2003**

(65) **Prior Publication Data**

US 2004/0119490 A1 Jun. 24, 2004

#### **Related U.S. Application Data**

(63) Continuation of application No. 10/008,719, filed on Dec. 7, 2001, now Pat. No. 6,642,129.

(60) Provisional application No. 60/307,976, filed on Jul. 26, 2001.

(51) **Int. Cl.**<sup>7</sup> ..... **H01L 27/148**; H01L 29/768

(52) **U.S. Cl.** ..... **257/226**; 257/444

(58) **Field of Search** ..... 257/226, 234, 257/235, 431, 440, 443, 444

(56) **References Cited**

#### **U.S. PATENT DOCUMENTS**

5,363,697 A	11/1994	Nakagawa
5,372,930 A	12/1994	Colton et al.
5,666,190 A	9/1997	Quate et al.
5,696,491 A	12/1997	White et al.
5,835,477 A	11/1998	Binnig et al.
5,866,807 A	2/1999	Elings et al.
6,136,208 A	10/2000	Chou et al.
6,189,374 B1	2/2001	Addertin et al.
6,218,086 B1	4/2001	Binnig et al.
6,279,389 B1 *	8/2001	Adderton et al. .... 73/105

6,416,476 B1	7/2002	Ogasawara et al.
6,507,478 B1	1/2003	Sameshima
6,574,499 B1 *	6/2003	Dines et al. .... 600/427
6,590,208 B2 *	7/2003	Massie ..... 250/306
6,635,311 B1 *	10/2003	Mirkin et al. .... 427/256
2001/0038598 A1	11/2001	Despont et al.

#### **OTHER PUBLICATIONS**

David Rotman, "Nanotech Goes to Work (Technology Information)", Technology Review (Cambridge, Mass.), vol. 104, No. 1, pp. 62-68, Jan. 1, 2001.

Ming Zhang, David Bullen, Kee S. Ryu, Chang Liu, (University of Illinois at Urbana-Champaign), Seunghun Hong, Sung-Wook Chung, and Chad A. Mirkin (Northwestern University), "Passive and Active Probe Arrays for Dip-Pen Nanolithography".

N.A. Amro, S. Xu; Gang-Yu Liu, "Patterning surfaces using tip-directed displacement and self-assembly", Langmuir, vol. 16, No. 7, pp. 3006-3009, Apr. 4, 2000.

Seunghun Hong, C.A. Mirkin, "A nanoplottter with both parallel and serial writing capabilities", Science, vol. 288, No. 5472, pp. 1808-1811, Jun. 9, 2000.

Jin Zhu, "Chemical and physical methods for the modification of high-temperature superconductors, nanoparticles and other inorganic substrates (Abstract)", The Sciences and Engineering, vol. 60-12B, pp. 6102, 1999.

(List continued on next page.)


*Primary Examiner*—Phuc T. Dang

(74) *Attorney, Agent, or Firm*—Greer, Burns & Crain, Ltd

(57) **ABSTRACT**

A microfabricated probe array for nanolithography and process for designing and fabricating the probe array. The probe array consists of individual probes that can be moved independently using thermal bimetallic actuation or electrostatic actuation methods. The probe array can be used to produce traces of diffusively transferred chemicals on the substrate with sub-1 micrometer resolution, and can function as an arrayed scanning probe microscope for subsequent reading and variation of transferred patterns.

**14 Claims, 8 Drawing Sheets**



**OTHER PUBLICATIONS**

Dana A. Weinberger, Seunghun Hong, Chad A. Mirkin, B.W. Wessels, Thomas B. Higgins, "Combinatorial generation and analysis of nanometer-and micrometer-scale silicon features via 'dip-pen' nanolithography and wet chemical etching", *Advanced Materials*, vol. 12, No. 21, pp. 1600-1603, Nov. 2000.

R.D. Piner, Jin Zhu, Feng Xu, Seunghun Hong, C.A. Mirkin, "Dip-Pen" nanolithography", *Science*, vol. 283, No. 5402, pp. 661-663, Jan. 29, 1999.

Chad A. Mirkin, "DNA-based Methodology for Preparing Nanocluster Circuits, Arrays, and Diagnostic Materials", *MRS Bulletin*, vol. 25, No. 1, pp. 43-54, 2000.

Michael Gross, "Incredible nanoplotter", *Chemistry in Britain*, vol. 36, No. 10, p. 25, Oct. 2000.

S. Hong, J. Zhu, C.A. Mirkin, "Multiple ink nanolithography toward a multiple-pen nano-plotter", *Science*, vol. 286, No. 5439, pp. 523-525, Oct. 15, 1999.

\* cited by examiner




FIG. 1  
PRIOR ART




FIG. 2




FIG. 3A

FIG. 3B




FIG. 4A

FIG. 4B

FIG. 5A



FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 6A




FIG. 6B




FIG. 6C





FIG. 6D






FIG. 7




FIG. 8






FIG. 9




FIG. 10A




FIG. 10D




FIG. 10B




FIG. 10E




FIG. 10C




FIG. 10F




FIG. 11

## PARALLEL, INDIVIDUALLY ADDRESSABLE PROBES FOR NANOLITHOGRAPHY

### RELATED APPLICATIONS

This is a continuation of application Ser. No. 10/008,719, filed Dec. 7, 2001 now U.S. Pat. No. 6,642,129, which claims priority of U.S. Provisional Application Ser. No. 60/307,976, filed Jul. 26, 2001.

### STATEMENT OF GOVERNMENT INTEREST

This invention was made with United States Government assistance through Defense Advanced Research Projects Agency (DARPA) Contract No. NW 0650 300 F 245. The Government has certain rights in this invention.

### FIELD OF THE INVENTION

The present invention relates generally to the art of efficient and high-speed generation of fine surface patterns made of chemical resist or biological substances using micromachined or microfabricated probes.

### BACKGROUND OF THE INVENTION

High-throughput lithography and surface patterning with extremely fine linewidths (e.g., on the order of 10–100 nm) are very important for the future growth of the microelectronics industry and nanotechnology. Next-generation integrated circuit technology will inevitably call for efficient and low-cost generation of features with a sub-100-nm linewidth. The emerging field of nanotechnology also requires patterning and functionalization of surfaces with a spatial resolution that is comparable with the scale of the molecules and cells that need to be manipulated and modified.

The resolution of conventional projection optical lithographic systems, still the most widely used in the microelectronics industry, is limited by optical diffraction. The resolution can be improved by using beam-based direct-writing tools with high energy and short wavelengths. High-energy beam lines, including ones that rely on electron beams and X-rays, are being used. However, such direct-write lithography systems suffer from several drawbacks. First, such systems are invariably complex and expensive. Second, these lithographic tools operate with a single beam and produce patterns in a serial manner, resulting in low throughput. Third, conventional high resolution lithography systems are not capable of depositing patterns made of biological molecules or chemical compounds. Only special chemical resists may be used.

Dip-pen Nanolithography (DPN) is a new and recently introduced method of scanning probe nanolithography. A description of DPN is contained in PCT/US00/00319, the entirety of which is incorporated herein by reference. It functions by depositing nanoscale patterns on surfaces using the diffusion of a chemical species from a scanning probe tip to the surface, sometimes via a water meniscus that naturally forms between tip and sample under ambient conditions. As a DPN tip is scanned across the surface of a substrate, molecules on the surface of the tip are transported through the water meniscus that forms between the tip and the substrate surface. Once on the surface, the molecules chemically anchor themselves to the substrate, forming robust patterns. Features in the 10 nm to many micrometer range can be fabricated with commercially available silicon nitride tips. One factor that influences the linewidth of DPN writing is the linear speed of the tip. Smaller linewidths are achieved with faster tip speeds. Other factors that influence the

linewidth include the sharpness of the DPN tip and the diffusion constants of the molecules used as inks.

DPN offers a number of unique benefits, including direct writing capability, high resolution (~10 nm linewidth resolution, ultimate ~5 nm spatial resolution), ultrahigh nanostructure registration capabilities, the flexibility to employ a variety of molecules for writing compounds (including biomolecules) and writing substrates (such as Au, SiO<sub>2</sub>, and GaAs), the ability to integrate multiple chemical or biochemical functionalities on a single “nano-chip”, a one-layer process for patterning, and the ability to automate patterning using customized software.

DPN technology can be implemented using a low-cost commercial scanning probe microscope (SPM) instrument. In a typical setup, the DPN probe chip is mounted on an SPM scanner tube in a manner similar to commercially available SPM tips. Precise horizontal and vertical movement of the probes is attained by using the internal laser signal feedback control system of the SPM machine.

### SUMMARY OF THE INVENTION

The present invention provides nanolithography, such as Dip Pen Nanolithography, as well as nanoscale imaging, with individually addressable probes in dip pen arrays. A probe array having a plurality of active probes is provided, which allows greater functionality than in conventional, single-pen DPN by allowing independent actuation of individual probes through supplying current or voltage to an actuator coupled with the probe. A plurality of independently addressable probes produces a plurality of traces of same or different chemicals.

An apparatus is provided for applying at least one patterning compound to a substrate for nanolithography. The apparatus includes an array of parallel probes, each probe including a cantilever, a tip at a distal end of the cantilever for applying one of the at least one patterning compound to the substrate, and an actuator operatively coupled to the cantilever. The probes may be configured for Dip Pen Nanolithography. The actuator is designed to be responsive to an applied current or voltage to move the cantilever, and thus move the tip away from the substrate. The contact state between individual probe tips and the writing substrate can thus be independently controlled. In the case of DPN writing, the patterning process is suspended when the probe tip leaves the substrate. A number of preferred types of embodiments are disclosed. Methods are also provided for fabricating active probe arrays.

In one preferred type of embodiment of the invention, the actuator deflects the cantilever in response to applied electrical current to move the tip relative to the substrate. The actuator may be thermally operated.

According to a preferred embodiment, a thermal actuator includes a resistive heater connected to the cantilever and a wire connecting the resistive heater to a current source. When a current is applied through the resistive heater, heat is generated due to ohmic heating, thus raising the temperature of the resistor as well as the cantilever. Due to difference in the thermal expansion coefficient of the materials for the cantilever and for the metal resistor, the cantilever will be bent selectively in response to the applied current. A patch of thin metal film can be connected to the cantilever for enhancing the extent of thermal bending.

In a second type of preferred embodiment of the invention, the actuator deflects the cantilever in response to applied voltage. The actuator may be electrostatically operated. Preferred displacement is created by applying a voltage

3

differential between two electrodes, at least one of them being not stationary.

A preferred embodiment of an electrostatic actuator includes a paddle electrode formed at an inner end of the cantilever opposite to the tip and a counter electrode. The paddle electrode faces the counter electrode with a gap having a predefined gap spacing. When a differential electrical voltage is applied across the top electrode and the counter electrode, the resultant electrostatic attraction force bends the cantilever beam and therefore moves the tip positions.

A preferred type of method of the current invention provides a method for applying at least one patterning compound to a substrate for high-speed probe-based nanolithography. The method includes the steps of: providing an array of individually addressable probes, each probe having a tip on a distal end; coating tips with same or different chemical substances; positioning the tips of the array of individually addressable probes over the substrate so that the tips are in contact with the substrate; raster-scanning the probes over the substrate surface; and selectively actuating at least one selected probe from the array of probes to move the tip of the selected probe away from the substrate. Accordingly, the selected probe does not apply patterning compound to the substrate when selected, while the non-selected probes apply at least one patterning compound to the substrate. Arbitrary two-dimensional patterns can be produced by raster-scanning the chip that contains the arrayed probes while controlling the position of individual probes during the scanning process. The probes may be configured for Dip Pen Nanolithography. The probes can also be generally applied to other nanolithography techniques where the interaction between a tip and a substrate alters the electrical, chemical, or molecular state of the surface, and may be used for imaging.

According to a preferred method of the present invention, the step of selectively actuating at least one selected probe includes the step of applying a current to a resistive heater connected to the cantilever, so that the cantilever beam is flexed. The deflection of the cantilever moves the tip away from the substrate to suspend writing on the substrate.

According to another preferred method of the present invention, the step of selectively actuating an individual probe includes applying a differential electrical voltage across a counter electrode and a moving electrode connected to an end of the selected probe. In this way, the moving and counter electrodes are moved towards one another, preferably to deflect the cantilever of the probe and move the tip away from the substrate.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic representation of the DPN process, showing a single tip coated with chemical compounds passing over a substrate (writing surface);

FIG. 2 is a schematic diagram of a parallel nanolithography writing system having a probe array according to one type of embodiment of the present invention, interfaced with an auxiliary control unit;

FIGS. 3a–3b are schematics of an array of bimetallic thermally actuated probes before and after deflection of selected probes, respectively, according to a preferred type of embodiment of the present invention;

FIGS. 4a–4b are schematics of a bimetallic thermally actuated probe before and after deflection of the probe, respectively;

FIGS. 5a–5e are schematic drawings showing major steps in the fabrication process of a thermally actuated probe according to a preferred aspect of the invention;

4

FIGS. 6a–6d are schematic drawings showing a top view of the fabrication steps shown in FIGS. 5b–5e, respectively;

FIG. 7 is a schematic drawing of an electrostatically actuated probe according to a preferred type of embodiment of the invention;

FIG. 8 is a schematic drawing of an array of electrostatically actuated probes according to a preferred type of embodiment of the invention;

FIG. 9 is a schematic showing a top view of an electrostatic actuator probe;

FIGS. 10a–10f are schematics taken along a section of FIG. 9 and in the direction indicated, showing fabrication steps for an electrostatically actuated probe according to a preferred method of the invention; and

FIG. 11 is a schematic drawing of a two-dimensional array DPN nanoplotted according to another preferred embodiment of the invention.

### DETAILED DESCRIPTION OF THE INVENTION

Generally speaking, the present invention provides active probes and active probe arrays, which are designed to achieve direct-write nanolithography, such as DPN. Devices according to the present invention can generate sub-100 nm patterns in a high speed, parallel, and controllable fashion. The active probe arrays offer greater functionality by allowing actuation of individual probes through supplying current or voltage to an actuator of the probe. The present invention is primarily directed to methods and devices for parallel DPN using active probe arrays, and methods for fabricating active probes and active probe arrays.

The active probe array can also be used for other existing or future surface patterning and lithography methods based on the scanning probe microscope (SPM) instrument family. An atomic force microscope (AFM) is considered a member of the SPM instrument family. Examples of such lithography systems include local thermal oxidation and displacement lithography.

Referring now to FIG. 1, an example of a conventional DPN process is shown. DPN employs a tip 20 on a distal end of a cantilever of an AFM probe 22 (or other SPM probe) to deposit, or “write”, nanoscale patterns onto a solid writing substrate 24, such as gold. The tip 20 applies a patterning compound 26 coated on the tip 20 to the writing substrate 24. The patterning compound 26 may be a hydrophobic patterning compound with a chemical affinity for the writing substrate 24, such as, but not limited to, 1-octadecanethiol (ODT) or mercaptohexadecanoic acid (MHA).

Similar to traditional macroscopic “dip pens” (e.g., quill, fountain, or ball-point pens, or multi-pen plotters), DPN employs molecular (capillary) transport to transfer the patterning compound 26 from the tip 20 to the writing substrate 24, forming a pattern 28 of the patterning compound. A water meniscus 30 forms between the tip 20 and the writing substrate 24 due to relative humidity in a work area, and carries the patterning compound 26 from the tip to the writing substrate as the tip is moved relatively to the writing substrate in the direction of the writing W, as indicated on FIG. 1.

Initial DPN processes involved a single probe 22 (pen). Parallel patterns also have been realized using an array of up to eight commercial probes 22 with an inter-probe spacing of 1.4 mm to write a plurality of patterns 28 on the writing substrate 24. This technique also allows application of multiple patterns 28, where each pattern contains a different

patterning compound, such as a biocompound. Parallel writing is also useful, for example, to form patterns **28** during integrated circuit formation. Examples of parallel probe structures can be found in R. Piner et al., "Dip-Pen" Nanolithography, *Science*, 1999, v. 283, pp. 661-663; S. Hong et al., Multiple Ink Nanolithography: Toward a Multiple-Pen Nano-Plotter, 1999, v. 286, pp. 523-525; S. Hong et al., A Nanoplotter with Both Parallel and Serial Writing Capabilities, *Science*, v. 288, pp. 1808-1811.

Conventional parallel probe DPN processes are performed using commercially available AFM probes **22**. Individual probes **22** cannot be moved independently from one another. Hence, all probes **22** must move simultaneously. Also, the inter-probe spacing of current parallel DPN arrays is too large for certain DPN applications and cannot fully satisfy the needs for a high-throughput and high-density arrayed DPN writing system. The present invention provides a nanoplotter with an array of independently active, microfabricated, closely spaced DPN probes.

FIG. 2 shows a schematic view of an active multi-pen, parallel DPN writing system **32** according to one type of embodiment of the current invention. A DPN probe chip **34** having a probe array including a plurality of active probes **38** is mounted on an AFM scanner tube **40** in a manner similar to standard single-tip AFM probes. AFM feedback electronics **42**, typically piezo tube electronics, control horizontal and vertical movement of the probe chip **34**.

As the tips **20** of the active probes **38** are in contact with the writing substrate **24**, an integrated actuator **46** controlled by a connected auxiliary control circuit **48** directs individual movement of the tips, preferably while the probe chip **34** is raster-scanned along the substrate **24** for patterning. The location of the integrated actuator **46** indicated in FIG. 2 is illustrative, and other actuator locations are contemplated. The term "in contact" is intended to refer to a sufficient proximity between the tips **20** and the substrate **24** to allow patterning of the patterning compound **26**. When supplied with current or voltage from the control unit **48** via the probe chip **34**, the actuator **46** moves a cantilever **50** of the active probe **38** to lift the tip **20** at an end of the cantilever off the writing substrate **24**. This suspends the chemical deposition process. In this way, the active probe **38** can be individually controlled through selective application of current or voltage to create arbitrary patterns with high throughput.

FIGS. **3a** and **3b** show an array **56** of thermally actuated probes **54** according to a preferred type of embodiment of the present invention, before and after actuation of selected probes, respectively. In FIG. **3a**, the array **56** is shown having five thermally actuated probes **54**, none of which is actuated. In response to an applied current, and as shown in FIG. **3b**, the second and fourth thermally actuated probes (indicated by arrows) are flexed upwardly (in FIGS. **3a** and **3b**, into the paper), thus moving their tips **20** away from the writing substrate **24**, and suspending chemical deposition. It will be appreciated by those skilled in the art that the selective distribution of current to form the patterns **28** may be controlled by programming the control circuit **48**.

The material of the cantilever beam **50** in the thermally actuated probes **54** preferably is silicon nitride thin film formed by low pressure chemical vapor deposition methods (LPCVD). According to a preferred type of method of the present invention, the thermally actuated probes **54** are formed by creating silicon nitride probes that include a thermal actuator having at least a resistive heater **66**.

FIGS. **4a** and **4b** show one of the thermally actuated probes **54** in non-flexed and flexed (actuated) positions,

respectively. The resistive heater **66**, patterned onto the silicon nitride cantilever **50** of the thermally actuated probe **54**, is coupled to a bonding wire **70** for carrying current to the resistive heater. The bonding wire **70** is in turn coupled to the control circuit **48** for selectively distributing current to the bonding wire **70** and thus actuating the thermally actuated probes **54**. Preferably, a metal film patch **68** is connected to the cantilever **50** to increase the deflection of the probe **54**.

FIGS. **5a-5e** and **6a-6d** show formation steps for the thermally actuated probe array **56**, forming a single thermally actuated probe **54** and a pair of thermally actuated probes, respectively. Referring to FIG. **5a**, a silicon dioxide thin film **60** is grown on a front side of a silicon substrate **62**, preferably a <100>-oriented silicon wafer, to form a protective mask for creating the tip **20**. The oxide layer **60** is patterned photolithographically to realize the mask for forming the tip **20**. In FIG. **5b** (also in FIG. **6a**), a portion of the silicon substrate **62** defining the pyramidal shape of the tip **20** is formed by using anisotropic wet etching in ethylene diamine pyrocatechol (EDP). Next, as shown in FIGS. **5c** (**6b**), a layer of LPCVD silicon nitride **64** is deposited and patterned onto the etched silicon substrate **62** to define the shape of the thermally active probe **54**, including the cantilever **50**. As shown in FIGS. **5d** (**6c**), the resistive (ohmic) heater **66** and the (optional) metal patch **68** are formed on the thermally active probe **54** by depositing and patterning, for example, Cr/Au onto the layer of silicon nitride **64**, creating an integrated bimetallic thermal actuator. The thermally actuated probes **54** are then released by using EDP etching to undercut the support substrate **62**. A portion of a silicon substrate **62** provides a handle for the thermally actuated probes **54**, as shown in FIGS. **4a** and **4b**.

In operation, the thermally actuated probes **54**, in response to an applied current, bend along their length to move the tip **20** as shown in FIG. **4b**, due to differential thermal expansion of the metal for resistive heater **66** and optional patch **68** and the cantilever **50** of the thermally actuated probe. In a preferred method of operation, the control circuit **48** sends a current through the bonding wire **70** to the resistive heater **66** to bend the thermally actuated probe **54** into a circular arc of radius R due to differential thermal expansion of the silicon nitride cantilever **50** and the gold patch **68**.

The expression for R under a given temperature change of  $\Delta T$  is approximately

$$R = - \frac{(w_1 E_1 t_1^2)^2 + (w_2 E_2 t_2^2)^2 + 2w_1 w_2 E_1 E_2 t_1 t_2 (2t_1^2 + 3t_1 t_2 + 2t_2^2)}{6w_1 w_2 E_1 E_2 t_1 t_2 (t_1 + t_2)(\alpha_1 - \alpha_2)\Delta T}.$$

The parameters w, t, E and  $\alpha$ , respectively, are the width, thickness, Young's modulus of elasticity, and the coefficient of thermal expansion of two constituent materials, denoted as materials 1 and 2. The subscripts correspond to these two materials. The temperature of a thermal actuator is dictated by the heat balance of the beam. Heat is generated by ohmic heating and lost through conduction and convection.

In the thermally actuated probe **54**, the bending of the cantilever beam **50** results in a deflection of the tip **20** of  $\delta$ :

$$\delta = R \left( 1 - \cos\left(\frac{L}{R}\right) \right)$$

Accordingly, application of current I through selected bonding wires **70** causes the cantilever **50** of the thermally actuated probes **54** connected to the bonding wires to deflect upwardly and thus move the tip **20**, as shown in FIG. **4b**.

The throughput of probe-based nanolithography can be made very high when a large number of active probes **38** in parallel are integrated on the probe chip **34**. The thermally actuated probe array **36**, manufactured according to the preferred type of embodiment of the present invention described above, results in a compact nanoplotter with high probe densities (spaced 100  $\mu\text{m}$  on center) and integrated sharp tips, and may be used for nanolithography and AFM imaging.

According to another preferred type of embodiment of the present invention, an electrostatically actuated probe **72**, shown in a preferred type embodiment in FIG. 7, is provided. Preferably, the probe **72** is formed as a unit of an electrostatic probe array **74**, shown in a preferred embodiment in FIG. 8 in combination with the probe chip **34**.

As shown in FIGS. 7 and 8, the electrostatically actuated probe **72** includes an electrostatic actuator **76**, which may include a paddle-shaped plate **78** at the inner longitudinal end of the cantilever **50**, longitudinally opposite to the tip **20**. The paddle-shaped plate **78** is preferably integrally formed with the electrostatically actuated probe **72**. The electrostatic actuator **76** further includes a counter electrode **81**, which is preferably stationary, and may be formed on the probe chip **34**, for electrostatically interacting with the paddle-shaped plate **78**. The counter electrode **81** may be formed as part of a parallel array of electrodes electrically connected to a number of bonding pads **85** longitudinally opposed to the counter electrodes, and both are patterned, adhered, or otherwise formed or attached to a glass substrate **94** which, in the completed embodiment, covers the array of counter electrodes and connecting bonding pads. The bonding pads **85** are preferably electrically connected to the control circuit **48** for selectively applying a voltage to one or more of the bonding pads. Methods for manufacturing the glass layer **94** including the counter electrodes **81** and the bonding pads **85** will be apparent to those in the art.

It is preferred that the electrostatically actuated probe **72** is also supported at or near the midpoint of the cantilever **50** by a compact, soft spring **80**, for providing torsion support to the electrostatically actuated probe, allowing deflection and thus angular motion of the probes, for moving the tips **20** of the probes. As shown in FIG. 8, the spring **80** for each of the array **74** of electrostatically actuated probes **72** is preferably a section of a unitary piece (such as a twist beam) laterally extending through each individual probe. It is further preferred that each section of the spring **80** have a relatively small cross section along the longitudinal direction of the cantilever **50**. As one in the art will appreciate, dimensions of the spring **80** such as the cross-sectional area can be varied depending on boundary conditions to control the angular flexibility of the cantilever **50**.

FIG. 9 is a top view of a preferred embodiment of the electrostatically actuated probe **72**. It is preferred, though not required, that the cantilever **50**, paddle-shaped plate **78**, and soft spring **80** be formed integrally from boron-doped silicon. This material is preferred both for its low etch rate in EDP solutions and for its relatively high electrical conductivity.

A preferred method of fabrication of the electrostatically actuated probe **72** is shown in FIGS. 10a–10f. Referring first to FIG. 10a, a silicon dioxide layer **82** is grown on a front side of a three-layered wafer containing a heavily boron-doped silicon layer **84** sandwiched between a <100>-oriented silicon wafer **86** and an epitaxial <100>-oriented silicon layer **88**. Alternatively, the silicon layer **84** may be doped by phosphorous. The silicon dioxide layer **82** defines boundaries of a mask for forming the tip **20**. Furthermore,

the silicon dioxide layer **82** can define boundaries for forming a spacer **90**, which vertically separates the electrostatically actuated probe **72** from the counter electrode **81**, which is patterned on a separate glass substrate **94**. In FIG. 10b, the silicon tip **20** and the spacer **90** are formed from the epitaxial silicon wafer **88** by EDP etching. Next, as shown in FIG. 10c, a thermal oxide layer **92** is grown over the epitaxial silicon wafer **88**, including the tip **20**, the spacer **90**, and the boron-doped silicon layer **84** to protect the front side during the final release. As shown in FIG. 10d, the silicon wafer **86** is then etched by EDP to remove material underneath the boron-doped silicon layer **84**, and release the boron-doped silicon cantilever **50**.

Next, as shown in FIG. 10e, the thermal oxide layer **92** is removed, and the electrostatically actuated probes **84** are formed from the boron-doped silicon layer **84**, including, preferably integrally, the cantilever **50**, the soft spring **80**, and the paddle-shaped plate **78**, for each probe in the array. As shown in FIG. 8, the portion of the cantilever **50** longitudinally disposed between the paddle-shaped plate **78** and the soft spring **80** is preferably wider in cross-sectional area along the lateral direction, i.e. in the direction of the length of the soft spring, than the distal portion of the cantilever. In this way, the deflection of the tip **20** is greater because the bending torque is fully transferred to the support spring **80**. The electrostatically actuated probe **72** is released.

Finally, as shown in FIG. 10f, the layer of glass **94** and the connected counter electrode **81** are formed or placed over the spacer **90**.

The preferred fabrication method results in electrostatically actuated probes **72** having a sharp tip **20** (preferably, <100 nm radius of curvature) and spaced approximately 620  $\mu\text{m}$  on center. Accordingly, electrostatically actuated probes **72** according to a preferred embodiment of the present invention can be used for both DPN writing and AFM imaging.

Bonding wires **70** (not shown in FIGS. 10a–10f) preferably connect the paddle-shaped plate **78** to ground potential, while the counter electrode **81** is preferably electrically coupled to the control circuit **48** via bonding pads **85** for applying voltage to the counter electrode. It will be appreciated that the electric potentials of the paddle-shaped plate **78** and the counter electrode **81** may alternatively be reversed; i.e. the paddle-shaped plate may be coupled to a voltage source, while the counter electrode may be grounded. The modifications necessary for such an alternative embodiment will be understood by those in the art.

In a preferred method of operation, voltage is applied to the paddle-shaped plate **78** to apply potential to the paddle-shaped plate **78**, while the conductive counter electrode **81** is grounded. Again, alternatively, the voltage application and grounding functions could be reversed between the top electrode **81** and the paddle-shaped plate **78**. Either operation applies a differential electrical voltage across the top electrode **81** and the paddle-shaped plate **78**, which are preferably separated by the spacer **90**. An attractive force develops between the plates of the counter electrode **81** and the paddle-shaped plate **78** that pulls them toward each other, thus tilting the cantilever **50**, and preferably angularly deflecting the cantilever **50** about the soft spring **80**, to move the tip **20** away from the substrate **24**. As in the thermally actuated probes **54**, the tip **20** can thus be selectively lifted to suspend the writing (or imaging) process.

A number of preferred embodiments have been described for active, one-dimensional arrays. However, arrays are possible in two dimensions as well. FIG. 12 shows a

two-dimensional array **100** according to another preferred embodiment of the present invention. The two-dimensional array **100** shown in FIG. **11** includes six rows and five columns of downwardly-angled probes **102**. The downwardly-angled probes **102** may be produced by, for example, modifying the formation process for the thermally actuated probe array **56** to extend cantilevers of individual, thermally actuated probes **54** from cavities (replicated cells) that are preferably evenly disposed along the two-dimensional array **100**. The thermally actuated probes **54** are preferably integrated into the two-dimensional array **100** due to a shorter required length for each cantilever **50**. The methods for modifying steps of fabrication and operation for the thermally actuated probes **54** in the two-dimensional array **100** will be understood by those in the art.

One skilled in the art can appreciate that several inventive devices and methods for DPN arrays have been shown and described, which have various attributes and advantages. By configuring each probe to be individually addressed and actuated by application of current or voltage, either thermally or electrostatically, the active probe arrays according to embodiments of the present invention allow the formation of arbitrary patterns with added resolution, at throughput comparable to conventional methods.

While various embodiments of the present invention have been shown and described, it should be understood that other modifications, substitutions and alternatives are apparent to one of ordinary skill in the art. Such modifications, substitutions and alternatives can be made without departing from the spirit and scope of the invention, which should be determined from the appended claims.

Various features of the invention are set forth in the appended claims.

What is claimed is:

**1.** An apparatus for forming a pattern on surface of a substrate comprising:

- a probe chip, said probe chip comprising a plurality of probes arranged in an array along said probe chip, the array being one of one-dimensional and two-dimensional, each of said plurality of probes having a tip;
- a first actuator for moving the probe chip parallel to the surface of the substrate;
- said probe chip further comprising a plurality of second actuators operatively connected to each of the plurality of probes, for selectively raising or lowering the tip of each of the probes in a direction substantially perpendicular to the surface of the substrate;
- a source connected to each of the plurality of second actuators for selectively actuating the plurality of second actuators.

**2.** The apparatus of claim **1** wherein each of said second actuators is configured to move the tip of a selected probe away from the substrate upon actuation of a selected second actuator.

**3.** A substrate having a pattern of a patterning compound on its surface, said pattern being produced by a method comprising the steps of:

moving a chip over the substrate to position a plurality of probes over said substrate simultaneously;

selectively actuating at least one of the plurality of probes to place the probes in one of in contact and out of contact of the substrate, while at least another of the plurality of probes remains in contact with the substrate; at least the plurality of probes placed in contact with the substrate having a tip and the patterning compound on the tip;

wherein the pattern is formed by application of the patterning compound from the tip to the substrate.

**4.** The substrate of claim **3** wherein the patterning compound comprises a biological compound.

**5.** The substrate of claim **3** wherein, when the at least one of the probes is placed in contact with the substrate, the tip of each of the in-contact probes is within a sufficient distance of the substrate to permit patterning of the patterning compound.

**6.** The substrate of claim **3** wherein the patterning compound comprises at least two different types of patterning compounds.

**7.** The substrate of claim **3** wherein the substrate is a patterned integrated circuit.

**8.** The substrate of claim **3** wherein the patterning compound comprises at least one of octadecanethiol (ODT) and mercaptohexadecanoic acid (MHA).

**9.** The substrate of claim **3** wherein lines are formed by selected probes in contact with the substrate, the lines being less than 100 in width.

**10.** The substrate of claim **3**, wherein the substrate comprises gold.

**11.** An apparatus for applying a patterning compound to a substrate for nanolithography, the apparatus comprising:

- a plurality of scanning probe microscope (SPM) instrument probes arranged in an array;
- an actuator operatively connected to each of the plurality of atomic force microscope (AFM) probes for selectively actuating each of the probes, us placing a tip of each of the selectively actuated probes in sufficient proximity to the substrate to allow application of the patterning compound thereto.

**12.** The apparatus of claim **11** wherein the plurality of SPM probes are disposed on a probe chip.

**13.** The apparatus of claim **12** further comprising:

a scanner tube for moving the probe chip.

**14.** The apparatus of claim **13** wherein the scanner tube uses piezo-actuation.

\* \* \* \* \*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 6,867,443 B2  
DATED : March 15, 2005  
INVENTOR(S) : Liu et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 1,

Line 14, delete "NW 0650 300 F 245" and insert -- DAAD19-00-1-0414 --.

Line 20, delete "resist" and insert -- resists --.

Column 9,


Line 3, delete "FIG. 11" and insert -- FIG. 12 --.

Column 10,

Line 33, between "100" and "in width" insert -- nm --.

Signed and Sealed this

Twenty-third Day of August, 2005

A handwritten signature in black ink, reading "Jon W. Dudas". The signature is written in a cursive style with a large, stylized "J" and "D".

JON W. DUDAS

*Director of the United States Patent and Trademark Office*