



Spiking Neural Networks for Control

Max Schaufelberger

February 8, 2024 — KTH Royal Institute of Technology



Table of Contents

Introduction

Simulation

Control

Learning

Combined Learning

BackupSlides

Control

Learning

Learned Control


Conclusion




Introduction

What are we talking about

Control a Linear system



Use Spiking neural networks



What are we talking about

Control a Linear system

- Tracking of reference trajectory

$$\begin{aligned}\dot{x} &= Ax + Bu \\ y &= Cx\end{aligned}\quad (1)$$

Only stable systems

Use Spiking neural networks

- Third Generation of NN
- Working with discrete spikes
- Inherently fit for temporal data

Goal / Motivation

Artificial SNN can already solve various cognitive task such as

- Memorization
- Basic Logic
- Simulation of Dynamic Systems
- Control

Although with varying levels of biologic plausibility. We set out to build a controlled dynamic system based on SNN using learning and biologic plausibility

- Allow for black-box deployment without manual parameter tuning
- "Limit ourselves to use the brains capabilities to design a controller"

Method

1. Simulate

Use a spiking network to simulate a dynamic system

2. Control

Devise a control scheme to control the network output

3. Learn


Apply biologically plausible learning rules to our network

4. Combine


Integrate all three steps into a single controller



Simulation





Simulation of Linear systems



- Build NN that outputs \hat{x} from the system $\dot{x} = Ax + c$ given c
- Group of LIF neurons with intrinsic Voltage, tracking the projected error $V_i = F(x - \hat{x}) + \mu r_i$
- Network decoding $\hat{x} = F^T r$

$$\dot{V} = -\lambda_V V + Fc + W^f o(t) + W^s r(t) + \sigma_V \eta(t)$$

Geometric





100

150

200

250

300

350

400

450

500

550

600

650

700

100

150

200

250


300

350

400

Control

Control Concept



[HC19]

(Almost) identical network architecture

- Network output is external input into (previous) simulating network \longleftrightarrow Network state contains control signal
- Governed by PD-control as $c = \dot{x} - Ax$
- In presence of output matrix $C \neq I \leftrightarrow \text{rank}(B^T C^T) = \text{rank}(B^T)$

fix the layouting of this page

Examples

150

Insert Picture

Insert Picture

200

250

300

350



100

150

200

250

300

350

400

450

500

550

600

650

700

150


200

250

300 Learning

350

400



$$V_i = F_i(x - \hat{x}) - \mu r_i$$

Learning rules

Slow Learning rule $W^s = F(A + \lambda_d I)F^T$

- Online Learning of Student teacher dynamics $\dot{\hat{x}} = M\hat{x} + c$
- Error Feedback Ke during Training
- $\delta M \propto e\hat{x}^T \rightarrow \delta W^s \propto F(e\hat{x}^T)F^T \approx F e r^T$
- Error alignment?
- Supervised Learning rule

Fast Learning rule $W^f = FF^T + \mu I$

- Voltage measures system error
- Minimize average Voltage outside of Neuron Threshold
- Biologically plausible pre-post locally
- Unsupervised Learning Rule

Examples

150

Insert Picture

Insert Picture

200

250

300

350



100

150

200

250

300

350

400

450

500

550

600

650

700

150

200

250


300

350

400


Combined Learning

Control Concept




[HC19]

Control Concept






[HC19]

Control Concept



[HC19]


Control Concept II



Problems

In conjunction, problems can arise:

- Divergence in Learning
- Control with Noise
- Reliance on analytic results
- Biologically implausible Learning



Dual network approach I

No Learning rule for control network available

Open loop control

Incapable of noise detection or correction

No compensation of training error

Highly dependent on governing dynamics from $c_{\text{cont}} = \dot{x} - Ax$

Dual network approach II


No Learning rule for control network available

Open-loop controller

Incapable of noise detection or correction

No compensation of training error

Highly dependent on governing dynamics from $C_{\text{contr}} = \dot{x}_{\text{ref}} - Ax_{\text{ref}}$





Single network approach I

No Learning rule for control network available

Open loop controller

Incapable of noise detection or correction

No compensation of training error

Highly dependent on governing dynamics from $C_{\text{contr}} = \dot{x}_{\text{ref}} - Ax_{\text{ref}}$

Nonnormality restriction on Input Matrix $B | B^T B = I$



Single network approach II

No Learning rule for control network available

Open loop controller

Incapable of noise detection or correction

No compensation of training error




Highly dependent on governing dynamics from $C_{\text{contr}} = \dot{x}_{\text{ref}} - Ax_{\text{ref}}$

Nonnormality restriction on Input Matrix $B \in \mathbb{B} := \{M \mid M^T M = \mathbb{I}\}$ Write this with such that I dont have 5 versions i need to keep track of

100 Zeit hier meine versuche mit 2 netzten, 2 netze mit feedback, 1 netz, 1 netz mit feedback etc und was/warum es nicht geklappt hat


350 BackupSlides

Autoencoder



$$\begin{aligned}\hat{x} &= Do(t) \\ \dot{r} &= -\lambda r + o(t)\end{aligned}\tag{2}$$

Autoencoder II





$$\begin{aligned}\dot{x} &= -\lambda x + c \\ \hat{x} &= Dr\end{aligned}\quad (3)$$

$$\dot{r} = -\lambda r + o(t)$$

$$\dot{x} = Dr$$


Autoencoder III



Geometric



Geometric



Minimize the cost J (Greedy)

$$J = \int_0^T \|x - \hat{x}\|_2^2 + C(r) dt \quad (6)$$

$$\begin{aligned} V_i &= \Gamma_i^T (x - \hat{x}) - \mu r_i \\ \dot{V}_i &= -\lambda_V V_i + \Gamma_i^T c(t) \\ &\quad + W^f o(t) + W^s r(t) + \sigma_V \eta(t) \end{aligned} \quad (7)$$

$$W^f = \Gamma^T \Gamma + \mu I$$

$$W^s = \Gamma^T (A + \lambda_d I) \Gamma$$

Example Simple

content...



Example Big

content...



Conclusion

content...



100

150

200

250

300

350

400

450

500

550

600

650

700

100

150

200

250


300

350

400

Control

Control Concept




[HC19]

Add a separator here

Control Concept

150

200




[HC19]

Add a separator here

250

300

350



Control with SNN

It is necessary on $B \in \mathbb{R}^{n \times p}$

$$u = \Gamma r + \Omega o(t) \quad (8)$$

$$\text{rank}(B^T C^T) = p \quad (11)$$

Slow and Instantaneous decoding

$$\begin{aligned} \dot{V}(t) = & -\lambda_V V(t) + \Omega^T B^T A e(t) + \Omega^T B^T c(t) \\ & + W^s r(t) + W^f o(t) + \sigma_V \eta(t) \end{aligned} \quad (9)$$

Requires full state information on x
and \hat{x}

$$c = \dot{x} - Ax \quad (10)$$

Example in Ideal Conditions

works fine+ add plot

150

200

250

300

350

Example with 2 networks

works bad+ add plot

150

200

250

300

350



Control

150

200

250

300

350

400

450

500

550

600

650

700

Conclusion

150

200

250

300

350

Conclusion

- Acceptable results in ideal conditions

Conclusion

- Acceptable results in ideal conditions
- Rank condition is limiting factor

150

200

250

300

350

Conclusion

- Acceptable results in ideal conditions
- Rank condition is limiting factor
- Network noise is invisible to the control

Conclusion

- Acceptable results in ideal conditions
- Rank condition is limiting factor
- Network noise is invisible to the control
- Simple open loop controller in the definition of c



Learning

Fast Learning rule

Slow Learning rule

Online Teacher-Student Scheme

Fast Learning rule

content...

200

250



300

350

$$\dot{\hat{x}} = (M - K\Gamma)\hat{x} + c + Kx$$

$$W^s = \Gamma^T (A + \lambda_d I) \Gamma$$

Slow Learning rule



Online Teacher-Student Scheme for M under $\dot{x} = Mx + c$

Matrix update under squared loss

$$\delta M \propto e \hat{x}^T \longrightarrow \delta W^s \propto \Gamma (e \hat{x}^T) \Gamma^T \approx \Gamma e r \quad (12)$$

replace the F with Γ in the picture!



Learned Control

100

150

200

250

300

350

400

450

500

550

600

650

700

100

150

200

250

300

350

400

Conclusion

Conclusion

- Very limited applicability
- Open loop + rank condition limiting factor
- Too inaccurate learning of slow weights W^s
- Too dependent on initial conditions in learning
- In ideal conditions useable results achievable
- Only of theoretical interest
- Impressive accuracy
- Results are somewhat translatable to NEF and LSMs



Conclusion

Future Work

Future Work

- Enable non-linear dynamics

Future Work

- Enable non-linear dynamics
- Obey Dale's Law for neuron excitation and inhibition

Future Work

- Enable non-linear dynamics
- Obey Dale's Law for neuron excitation and inhibition
- Optimize Control

Future Work

- Enable non-linear dynamics
- Obey Dale's Law for neuron excitation and inhibition
- Optimize Control
- Learning of En- and Decoder Γ

Future Work

- Enable non-linear dynamics
- Obey Dale's Law for neuron excitation and inhibition
- Optimize Control
- Learning of En- and Decoder Γ
- Allow for synaptic delays



Frame title

Block

Lorem ipsum!

Bibliography

- [BD15] Ralph Bourdoukan and Sophie Denève. “Enforcing balance allows local supervised learning in spiking recurrent networks”. In: **Advances in Neural Information Processing Systems**. Ed. by C. Cortes, N. Lawrence, D. Lee, M. Sugiyama, and R. Garnett. Vol. 28. Curran Associates, Inc., 2015. URL: https://proceedings.neurips.cc/paper_files/paper/2015/file/3871bd64012152bfb53fdf04b401193f-Paper.pdf.
- [HC19] Fuqiang Huang and ShiNung Ching. “Spiking networks as efficient distributed controllers”. In: **Biological Cybernetics** 113.1 (Apr. 2019), pp. 179–190. ISSN: 0340-1200, 1432-0770. DOI: [10.1007/s00422-018-0769-7](https://doi.org/10.1007/s00422-018-0769-7). URL: <http://link.springer.com/10.1007/s00422-018-0769-7> (visited on 10/23/2022).

pt

100

150

200

250

300

350

400

450

500

550

600

650

700

100

150

200

250

300

350

400

